

Bootstrap estimation of overall median and 90%ile

Sasha D. Hafner

August 2020

Bootstrap settings

Number of samples and one-tailed probability

```
nsamp <- 10000  
p <- 0.9
```

Sampling

```
r1md <- r3md <- vector()  
r1v <- acid.pars$man.ph.r1  
r3v <- acid.pars$man.ph.r3  
  
for (i in 1:nsamp) {  
  s1 <- sample(r1v, replace = TRUE)  
  s3 <- sample(r3v, replace = TRUE)  
  
  r1md <- c(r1md, median(s1))  
  r3md <- c(r3md, median(s3))  
}
```

Check

```
median(r1v)
```

```
## [1] 0.6648668
```

```
median(r3v)
```

```
## [1] 0.23819
```

```
median(r1md)
```

```
## [1] 0.6648668
```

```
median(r3md)
```

```
## [1] 0.23819
```

```
quantile(r1md, 1:9/10)
```

```
##          10%          20%          30%          40%          50%          60%          70%          80%          90%  
## 0.6084847 0.6089017 0.6626218 0.6626218 0.6648668 0.6651733 0.6651733 0.6784625 0.7039975
```

```
quantile(r3md, 1:9/10)
```

```
##          10%          20%          30%          40%          50%          60%          70%          80%          90%  
## 0.1661837 0.1685484 0.1949507 0.1949507 0.2381900 0.2393360 0.2393360 0.2793163 0.3097139
```