

jumbled demonstrations

Sasha D. Hafner

03 April, 2024

Overview

This document demonstrates usage of some of the function in the jumbled repo, available from github.com/sashahafner/jumbled.

Load functions

```
ff <- list.files(pattern = '\\.R$')
for(i in ff) source(i)
```

aggregate2

A wrapper for `aggregate` that accepts multiple functions and simpler arguments. Does not accept formula notation.

Example from `aggregate` help file:

```
aggregate(breaks ~ wool + tension, data = warpbreaks, mean)
```

```
##   wool tension   breaks
## 1    A      L 44.55556
## 2    B      L 28.22222
## 3    A      M 24.00000
## 4    B      M 28.77778
## 5    A      H 24.55556
## 6    B      H 18.77778
```

To include `sd` and `n`, use `aggregate2`:

```
aggregate2(warpbreaks, x = 'breaks', by = c('wool', 'tension'),
            FUN = list(mean = mean, sd = sd, n = length))
```

```
##   wool tension breaks.mean breaks.sd breaks.n
## 1    A      L  44.55556 18.097729         9
## 2    B      L  28.22222  9.858724         9
## 3    A      M  24.00000  8.660254         9
## 4    B      M  28.77778  9.431036         9
## 5    A      H  24.55556 10.272671         9
## 6    B      H  18.77778  4.893306         9
```

Accepts multiple variables (as in `aggregate`).

```
aggregate2(na.omit(airquality), x = c('Ozone', 'Temp'), by = 'Month',
            FUN = list(mean = mean, sd = sd, n = length))
```

```
##   Month Ozone.mean Temp.mean Ozone.sd Temp.sd Ozone.n Temp.n
## 1     5   24.12500  66.45833 22.88594 6.633113     24    24
## 2     6   29.44444  78.22222 18.20790 7.838651     9     9
## 3     7   59.11538  83.88462 31.63584 4.439161    26    26
## 4     8   60.00000  83.69565 41.76776 7.054559    23    23
## 5     9   31.44828  76.89655 24.14182 8.503549    29    29
```

aggregate3

Similar, but uses formula notation. Example from aggregate help file:

```
aggregate(breaks ~ wool + tension, data = warpbreaks, mean)
```

```
##   wool tension  breaks
## 1    A        L 44.55556
## 2    B        L 28.22222
## 3    A        M 24.00000
## 4    B        M 28.77778
## 5    A        H 24.55556
## 6    B        H 18.77778
```

To include sd and n, use aggregate3:

```
aggregate3(warpbreaks, breaks ~ wool + tension,
            FUN = list(mean = mean, sd = sd, n = length))
```

```
##   wool tension breaks.mean breaks.sd breaks.n
## 1    A        L   44.55556 18.097729        9
## 2    B        L   28.22222  9.858724        9
## 3    A        M   24.00000  8.660254        9
## 4    B        M   28.77778  9.431036        9
## 5    A        H   24.55556 10.272671        9
## 6    B        H   18.77778  4.893306        9
```

For multiple response variables, use cbind().

```
aggregate3(airquality, cbind(Ozone, Temp) ~ Month,
            FUN = list(mean = mean, sd = sd, n = length))
```

```
##   Month Ozone.mean Temp.mean Ozone.sd Temp.sd Ozone.n Temp.n
## 1     5   23.61538  66.73077 22.22445 6.533346    26    26
## 2     6   29.44444  78.22222 18.20790 7.838651     9     9
## 3     7   59.11538  83.88462 31.63584 4.439161    26    26
## 4     8   59.96154  83.96154 39.68121 6.666218    26    26
## 5     9   31.44828  76.89655 24.14182 8.503549    29    29
```

So `Ozone + Temp ~ Month` doesn't work, because `aggregate()` can't handle it properly. It would be nice to address this limitation in the future.

dfcombos

Something like `expand.grid` for data frames. Can accept vectors too, but resulting name is poor.

```
d1 <- data.frame(name = letters[1:5], x = 1.1)
d2 <- data.frame(b = 1:3)
dfcombos(d1, d2)
```

```
##      name    x b
## 1      a 1.1 1
## 2      b 1.1 1
## 3      c 1.1 1
## 4      d 1.1 1
## 5      e 1.1 1
## 6      a 1.1 2
## 7      b 1.1 2
## 8      c 1.1 2
## 9      d 1.1 2
## 10     e 1.1 2
## 11     a 1.1 3
## 12     b 1.1 3
## 13     c 1.1 3
## 14     d 1.1 3
## 15     e 1.1 3
```

```
v1 <- c(TRUE, FALSE)
dfcombos(d1, d2, v1)
```

```
##      name    x b X[[i]]
## 1      a 1.1 1  TRUE
## 2      b 1.1 1  TRUE
## 3      c 1.1 1  TRUE
## 4      d 1.1 1  TRUE
## 5      e 1.1 1  TRUE
## 6      a 1.1 2  TRUE
## 7      b 1.1 2  TRUE
## 8      c 1.1 2  TRUE
## 9      d 1.1 2  TRUE
## 10     e 1.1 2  TRUE
## 11     a 1.1 3  TRUE
## 12     b 1.1 3  TRUE
## 13     c 1.1 3  TRUE
## 14     d 1.1 3  TRUE
## 15     e 1.1 3  TRUE
## 16     a 1.1 1 FALSE
## 17     b 1.1 1 FALSE
## 18     c 1.1 1 FALSE
## 19     d 1.1 1 FALSE
## 20     e 1.1 1 FALSE
## 21     a 1.1 2 FALSE
## 22     b 1.1 2 FALSE
## 23     c 1.1 2 FALSE
## 24     d 1.1 2 FALSE
## 25     e 1.1 2 FALSE
## 26     a 1.1 3 FALSE
## 27     b 1.1 3 FALSE
## 28     c 1.1 3 FALSE
## 29     d 1.1 3 FALSE
```

```
## 30      e 1.1 3 FALSE
```

dfsumm

Generate a data frame summary more detailed and compact than `summary` output.

```
dfsumm(attenu)
```

```
##
## 182 rows and 6 columns
## 182 unique rows
##           event      mag station      dist      accel      date.time
## Class      numeric numeric  factor numeric numeric  POSIXct, POSIXt
## Minimum           1         5   1008      0.5    0.003 2024-04-03 10:55:45
## Maximum          23        7.7   c266      370    0.81 2024-04-03 10:55:45
## Mean            14.7        6.08    262     45.6    0.154 2024-04-03 10:55:45
## Unique (excl. NA)   23        17    117     153     120           1
## Missing values      0         0     16       0       0           0
## Sorted             TRUE      FALSE    FALSE    FALSE    FALSE          TRUE
##
```

Add date to check R v4.3 problem.

```
attenu$date.time <- Sys.time()
```

```
dfsumm(attenu)
```

```
##
## 182 rows and 6 columns
## 182 unique rows
##           event      mag station      dist      accel      date.time
## Class      numeric numeric  factor numeric numeric  POSIXct, POSIXt
## Minimum           1         5   1008      0.5    0.003 2024-04-03 10:57:55
## Maximum          23        7.7   c266      370    0.81 2024-04-03 10:57:55
## Mean            14.7        6.08    262     45.6    0.154 2024-04-03 10:57:55
## Unique (excl. NA)   23        17    117     153     120           1
## Missing values      0         0     16       0       0           0
## Sorted             TRUE      FALSE    FALSE    FALSE    FALSE          TRUE
##
```

Compare to `summary`.

```
summary(attenu)
```

```
##           event      mag      station      dist
## Min.   : 1.00   Min.   :5.000   117   : 5   Min.   : 0.50
## 1st Qu.: 9.00   1st Qu.:5.300   1028  : 4   1st Qu.: 11.32
## Median :18.00   Median :6.100   113   : 4   Median : 23.40
## Mean   :14.74   Mean   :6.084   112   : 3   Mean   : 45.60
## 3rd Qu.:20.00   3rd Qu.:6.600   135   : 3   3rd Qu.: 47.55
## Max.   :23.00   Max.   :7.700   (Other):147   Max.   :370.00
##                                     NA's   : 16
##           accel      date.time
## Min.   :0.00300   Min.   :2024-04-03 10:57:55.69
## 1st Qu.:0.04425   1st Qu.:2024-04-03 10:57:55.69
## Median :0.11300   Median :2024-04-03 10:57:55.69
## Mean   :0.15422   Mean   :2024-04-03 10:57:55.69
```

```
## 3rd Qu.:0.21925    3rd Qu.:2024-04-03 10:57:55.69
## Max.      :0.81000    Max.      :2024-04-03 10:57:55.69
##
```

interp

Fill in missing observations for multiple columns via interpolation. `interp` calls `approx`.

```
args(interp)
```

```
## function (dat, x, ys, by = NA, ...)
## NULL
```

```
dat <- data.frame(time = 1:30, a = rnorm(30), b = rnorm(30), c = rnorm(30))
dat[5:10, -1] <- NA
dat[20:22, 'a'] <- NA
```

```
dat
```

```
##      time      a      b      c
## 1      1 0.31833673 -0.26774095 -0.46288318
## 2      2 -1.42379885  1.58585916 -0.88455498
## 3      3 -0.40509086  0.04690059 -1.63092757
## 4      4  0.99538657  0.35649678  0.56223059
## 5      5          NA          NA          NA
## 6      6          NA          NA          NA
## 7      7          NA          NA          NA
## 8      8          NA          NA          NA
## 9      9          NA          NA          NA
## 10     10         NA         NA         NA
## 11     11 -1.10363778 -0.46205239 -0.09514776
## 12     12  0.44418506 -0.22509928  1.13878050
## 13     13 -0.20495061 -0.84644780  0.50231463
## 14     14  1.67563243  0.07304632 -0.51541405
## 15     15 -0.13132225 -0.27503642 -2.46839047
## 16     16 -0.19988298 -0.38642636 -0.87255274
## 17     17  0.05491242 -0.04620314  0.96408808
## 18     18 -0.68216549 -0.82589372  0.91079625
## 19     19 -0.72770415 -0.85403424  1.92580884
## 20     20          NA  0.11873681 -0.30290695
## 21     21          NA  0.28359691 -1.05470705
## 22     22          NA  1.93008647  0.41811609
## 23     23  0.17716660 -1.14052762  0.70127282
## 24     24 -0.01250080 -1.32211824  0.24675828
## 25     25 -0.39431713  1.22883161  0.46429516
## 26     26  0.35156293 -0.54845603 -0.39546819
## 27     27  0.87876756 -0.12600749  0.71307031
## 28     28  0.20465408  0.68771872  1.18501256
## 29     29 -0.88738071  0.70520038 -1.91114929
## 30     30 -0.47721606  0.80147843  1.11493056
```


```
dat2 <- interp(dat, 'time', c('a', 'b', 'c'))
```

```
dat2
```

```
##      time      a      b      c
```

```
## 1      1  0.31833673 -0.267740953 -0.46288318
## 2      2 -1.42379885  1.585859163 -0.88455498
## 3      3 -0.40509086  0.046900595 -1.63092757
## 4      4  0.99538657  0.356496777  0.56223059
## 5      5  0.69552594  0.239561182  0.46831939
## 6      6  0.39566532  0.122625586  0.37440820
## 7      7  0.09580470  0.005689991  0.28049701
## 8      8 -0.20405592 -0.111245605  0.18658582
## 9      9 -0.50391654 -0.228181200  0.09267462
## 10     10 -0.80377716 -0.345116796 -0.00123657
## 11     11 -1.10363778 -0.462052391 -0.09514776
## 12     12  0.44418506 -0.225099283  1.13878050
## 13     13 -0.20495061 -0.846447800  0.50231463
## 14     14  1.67563243  0.073046319 -0.51541405
## 15     15 -0.13132225 -0.275036420 -2.46839047
## 16     16 -0.19988298 -0.386426357 -0.87255274
## 17     17  0.05491242 -0.046203141  0.96408808
## 18     18 -0.68216549 -0.825893722  0.91079625
## 19     19 -0.72770415 -0.854034238  1.92580884
## 20     20 -0.50148646  0.118736809 -0.30290695
## 21     21 -0.27526878  0.283596906 -1.05470705
## 22     22 -0.04905109  1.930086466  0.41811609
## 23     23  0.17716660 -1.140527618  0.70127282
## 24     24 -0.01250080 -1.322118243  0.24675828
## 25     25 -0.39431713  1.228831605  0.46429516
## 26     26  0.35156293 -0.548456032 -0.39546819
## 27     27  0.87876756 -0.126007492  0.71307031
## 28     28  0.20465408  0.687718722  1.18501256
## 29     29 -0.88738071  0.705200376 -1.91114929
## 30     30 -0.47721606  0.801478429  1.11493056
```

```
plot(a ~ time, data = dat)
points(a ~ time, data = dat2, cex = 0.5, col = 'blue')
```



Now works for data.tables too.

```
dat <- data.table::as.data.table(dat)
dat2 <- interpm(dat, 'time', c('a', 'b', 'c'))
```

```
dat <- data.frame(time = rep(1:10, 3), group = rep(c('a', 'b', 'c'), each = 10), a = rnorm(30), b = rnorm(30), c = rnorm(30))
dat[5:9, -1:-2] <- NA
dat[c(20, 22), 'a'] <- NA
```

dat

##	time	group	a	b	c
## 1	1	a	-0.46930021	1.3491063	-0.49751241
## 2	2	a	-1.14800275	-1.6350828	0.76558578
## 3	3	a	1.10399796	-0.7155327	0.50139307
## 4	4	a	-0.28924992	-0.9164943	0.33191117
## 5	5	a	NA	NA	NA
## 6	6	a	NA	NA	NA
## 7	7	a	NA	NA	NA
## 8	8	a	NA	NA	NA
## 9	9	a	NA	NA	NA
## 10	10	a	-0.12892591	0.4598761	0.62192056
## 11	1	b	0.29911231	0.1677058	-1.47180517
## 12	2	b	0.01829921	-0.2750030	0.79819546
## 13	3	b	-1.15006133	0.4923226	0.27946251
## 14	4	b	-0.42939635	1.3397546	0.65787426
## 15	5	b	0.85000298	-0.4767442	0.59372632
## 16	6	b	-0.21482949	-1.4967955	-0.57792651
## 17	7	b	-0.61741402	-1.2014240	0.47606273
## 18	8	b	0.10942738	-0.4074610	-1.18763362
## 19	9	b	-0.70651106	-0.9477481	0.71768805
## 20	10	b	NA	0.8516664	0.13469724
## 21	1	c	0.35080172	-0.5884310	1.42208034
## 22	2	c	NA	-1.3624731	0.04073091
## 23	3	c	-0.03337353	-0.4496379	-0.33840975
## 24	4	c	0.36144400	-0.6433250	-0.55811539
## 25	5	c	1.04557564	-0.5107456	1.02781348
## 26	6	c	0.10321239	0.2572020	-0.22547048
## 27	7	c	0.33179556	-0.4195554	-1.23163005
## 28	8	c	-1.56855881	-0.9522277	-0.75824474
## 29	9	c	0.44026994	0.5123934	1.08551815
## 30	10	c	1.88187132	-1.7442677	-1.04909888

```
interpm(dat, 'time', c('a', 'b', 'c'), by = 'group')
```

##	time	group	a	b	c
## 1	1	a	-0.46930021	1.34910627	-0.49751241
## 2	2	a	-1.14800275	-1.63508277	0.76558578
## 3	3	a	1.10399796	-0.71553273	0.50139307
## 4	4	a	-0.28924992	-0.91649432	0.33191117
## 5	5	a	-0.26252925	-0.68709924	0.38024607
## 6	6	a	-0.23580858	-0.45770417	0.42858097
## 7	7	a	-0.20908791	-0.22830909	0.47691586
## 8	8	a	-0.18236724	0.00108599	0.52525076
## 9	9	a	-0.15564657	0.23048107	0.57358566
## 10	10	a	-0.12892591	0.45987615	0.62192056

```
## 11 1 b 0.29911231 0.16770583 -1.47180517
## 12 2 b 0.01829921 -0.27500302 0.79819546
## 13 3 b -1.15006133 0.49232262 0.27946251
## 14 4 b -0.42939635 1.33975457 0.65787426
## 15 5 b 0.85000298 -0.47674422 0.59372632
## 16 6 b -0.21482949 -1.49679554 -0.57792651
## 17 7 b -0.61741402 -1.20142397 0.47606273
## 18 8 b 0.10942738 -0.40746103 -1.18763362
## 19 9 b -0.70651106 -0.94774810 0.71768805
## 20 10 b NA 0.85166640 0.13469724
## 21 1 c 0.35080172 -0.58843101 1.42208034
## 22 2 c 0.15871409 -1.36247310 0.04073091
## 23 3 c -0.03337353 -0.44963794 -0.33840975
## 24 4 c 0.36144400 -0.64332503 -0.55811539
## 25 5 c 1.04557564 -0.51074555 1.02781348
## 26 6 c 0.10321239 0.25720201 -0.22547048
## 27 7 c 0.33179556 -0.41955545 -1.23163005
## 28 8 c -1.56855881 -0.95222766 -0.75824474
## 29 9 c 0.44026994 0.51239341 1.08551815
## 30 10 c 1.88187132 -1.74426769 -1.04909888
```

```
interpm(dat, 'time', c('a', 'b', 'c'), by = 'group', rule = 2)
```

```
##   time group      a      b      c
## 1    1    a -0.46930021 1.34910627 -0.49751241
## 2    2    a -1.14800275 -1.63508277 0.76558578
## 3    3    a 1.10399796 -0.71553273 0.50139307
## 4    4    a -0.28924992 -0.91649432 0.33191117
## 5    5    a -0.26252925 -0.68709924 0.38024607
## 6    6    a -0.23580858 -0.45770417 0.42858097
## 7    7    a -0.20908791 -0.22830909 0.47691586
## 8    8    a -0.18236724 0.00108599 0.52525076
## 9    9    a -0.15564657 0.23048107 0.57358566
## 10  10    a -0.12892591 0.45987615 0.62192056
## 11   1    b 0.29911231 0.16770583 -1.47180517
## 12   2    b 0.01829921 -0.27500302 0.79819546
## 13   3    b -1.15006133 0.49232262 0.27946251
## 14   4    b -0.42939635 1.33975457 0.65787426
## 15   5    b 0.85000298 -0.47674422 0.59372632
## 16   6    b -0.21482949 -1.49679554 -0.57792651
## 17   7    b -0.61741402 -1.20142397 0.47606273
## 18   8    b 0.10942738 -0.40746103 -1.18763362
## 19   9    b -0.70651106 -0.94774810 0.71768805
## 20  10    b -0.70651106 0.85166640 0.13469724
## 21   1    c 0.35080172 -0.58843101 1.42208034
## 22   2    c 0.15871409 -1.36247310 0.04073091
## 23   3    c -0.03337353 -0.44963794 -0.33840975
## 24   4    c 0.36144400 -0.64332503 -0.55811539
## 25   5    c 1.04557564 -0.51074555 1.02781348
## 26   6    c 0.10321239 0.25720201 -0.22547048
## 27   7    c 0.33179556 -0.41955545 -1.23163005
## 28   8    c -1.56855881 -0.95222766 -0.75824474
## 29   9    c 0.44026994 0.51239341 1.08551815
## 30  10    c 1.88187132 -1.74426769 -1.04909888
```



```
dat <- data.table::as.data.table(dat)
dat
```

##	time	group	a	b	c
##	<int>	<char>	<num>	<num>	<num>
## 1:	1	a	-0.46930021	1.3491063	-0.49751241
## 2:	2	a	-1.14800275	-1.6350828	0.76558578
## 3:	3	a	1.10399796	-0.7155327	0.50139307
## 4:	4	a	-0.28924992	-0.9164943	0.33191117
## 5:	5	a	NA	NA	NA
## 6:	6	a	NA	NA	NA
## 7:	7	a	NA	NA	NA
## 8:	8	a	NA	NA	NA
## 9:	9	a	NA	NA	NA
## 10:	10	a	-0.12892591	0.4598761	0.62192056
## 11:	1	b	0.29911231	0.1677058	-1.47180517
## 12:	2	b	0.01829921	-0.2750030	0.79819546
## 13:	3	b	-1.15006133	0.4923226	0.27946251
## 14:	4	b	-0.42939635	1.3397546	0.65787426
## 15:	5	b	0.85000298	-0.4767442	0.59372632
## 16:	6	b	-0.21482949	-1.4967955	-0.57792651
## 17:	7	b	-0.61741402	-1.2014240	0.47606273
## 18:	8	b	0.10942738	-0.4074610	-1.18763362
## 19:	9	b	-0.70651106	-0.9477481	0.71768805
## 20:	10	b	NA	0.8516664	0.13469724
## 21:	1	c	0.35080172	-0.5884310	1.42208034
## 22:	2	c	NA	-1.3624731	0.04073091
## 23:	3	c	-0.03337353	-0.4496379	-0.33840975
## 24:	4	c	0.36144400	-0.6433250	-0.55811539
## 25:	5	c	1.04557564	-0.5107456	1.02781348
## 26:	6	c	0.10321239	0.2572020	-0.22547048
## 27:	7	c	0.33179556	-0.4195554	-1.23163005
## 28:	8	c	-1.56855881	-0.9522277	-0.75824474
## 29:	9	c	0.44026994	0.5123934	1.08551815
## 30:	10	c	1.88187132	-1.7442677	-1.04909888

```
interpm(dat, 'time', c('a', 'b', 'c'), by = 'group')
```

##	time	group	a	b	c
##	<int>	<char>	<num>	<num>	<num>
## 1:	1	a	-0.46930021	1.34910627	-0.49751241
## 2:	2	a	-1.14800275	-1.63508277	0.76558578
## 3:	3	a	1.10399796	-0.71553273	0.50139307
## 4:	4	a	-0.28924992	-0.91649432	0.33191117
## 5:	5	a	-0.26252925	-0.68709924	0.38024607
## 6:	6	a	-0.23580858	-0.45770417	0.42858097
## 7:	7	a	-0.20908791	-0.22830909	0.47691586
## 8:	8	a	-0.18236724	0.00108599	0.52525076
## 9:	9	a	-0.15564657	0.23048107	0.57358566
## 10:	10	a	-0.12892591	0.45987615	0.62192056
## 11:	1	b	0.29911231	0.16770583	-1.47180517
## 12:	2	b	0.01829921	-0.27500302	0.79819546
## 13:	3	b	-1.15006133	0.49232262	0.27946251
## 14:	4	b	-0.42939635	1.33975457	0.65787426

```
## 15:      5      b  0.85000298 -0.47674422  0.59372632
## 16:      6      b -0.21482949 -1.49679554 -0.57792651
## 17:      7      b -0.61741402 -1.20142397  0.47606273
## 18:      8      b  0.10942738 -0.40746103 -1.18763362
## 19:      9      b -0.70651106 -0.94774810  0.71768805
## 20:     10      b      NA  0.85166640  0.13469724
## 21:      1      c  0.35080172 -0.58843101  1.42208034
## 22:      2      c  0.15871409 -1.36247310  0.04073091
## 23:      3      c -0.03337353 -0.44963794 -0.33840975
## 24:      4      c  0.36144400 -0.64332503 -0.55811539
## 25:      5      c  1.04557564 -0.51074555  1.02781348
## 26:      6      c  0.10321239  0.25720201 -0.22547048
## 27:      7      c  0.33179556 -0.41955545 -1.23163005
## 28:      8      c -1.56855881 -0.95222766 -0.75824474
## 29:      9      c  0.44026994  0.51239341  1.08551815
## 30:     10      c  1.88187132 -1.74426769 -1.04909888
##      time  group      a      b      c
```

```
interpm(dat, 'time', c('a', 'b', 'c'), by = 'group', rule = 2)
```

```
##      time  group      a      b      c
##      <int> <char>      <num>      <num>      <num>
## 1:      1      a -0.46930021  1.34910627 -0.49751241
## 2:      2      a -1.14800275 -1.63508277  0.76558578
## 3:      3      a  1.10399796 -0.71553273  0.50139307
## 4:      4      a -0.28924992 -0.91649432  0.33191117
## 5:      5      a -0.26252925 -0.68709924  0.38024607
## 6:      6      a -0.23580858 -0.45770417  0.42858097
## 7:      7      a -0.20908791 -0.22830909  0.47691586
## 8:      8      a -0.18236724  0.00108599  0.52525076
## 9:      9      a -0.15564657  0.23048107  0.57358566
## 10:     10      a -0.12892591  0.45987615  0.62192056
## 11:      1      b  0.29911231  0.16770583 -1.47180517
## 12:      2      b  0.01829921 -0.27500302  0.79819546
## 13:      3      b -1.15006133  0.49232262  0.27946251
## 14:      4      b -0.42939635  1.33975457  0.65787426
## 15:      5      b  0.85000298 -0.47674422  0.59372632
## 16:      6      b -0.21482949 -1.49679554 -0.57792651
## 17:      7      b -0.61741402 -1.20142397  0.47606273
## 18:      8      b  0.10942738 -0.40746103 -1.18763362
## 19:      9      b -0.70651106 -0.94774810  0.71768805
## 20:     10      b -0.70651106  0.85166640  0.13469724
## 21:      1      c  0.35080172 -0.58843101  1.42208034
## 22:      2      c  0.15871409 -1.36247310  0.04073091
## 23:      3      c -0.03337353 -0.44963794 -0.33840975
## 24:      4      c  0.36144400 -0.64332503 -0.55811539
## 25:      5      c  1.04557564 -0.51074555  1.02781348
## 26:      6      c  0.10321239  0.25720201 -0.22547048
## 27:      7      c  0.33179556 -0.41955545 -1.23163005
## 28:      8      c -1.56855881 -0.95222766 -0.75824474
## 29:      9      c  0.44026994  0.51239341  1.08551815
## 30:     10      c  1.88187132 -1.74426769 -1.04909888
##      time  group      a      b      c
```

logaxis

Add log axis to base R plots.

logistic

The logistic function for transformations.

rbindf

Like `rbind` but data frame columns do not need to match. From `monitoR` package.

rounddf

Round complete data frames.

```
dat <- data.frame(a = 1:10, b = rnorm(10), c = letters[1:10])
dat
```

```
##      a          b c
## 1    1  0.29039955 a
## 2    2 -0.44757343 b
## 3    3 -0.21886077 c
## 4    4 -1.60544351 d
## 5    5  0.07483969 e
## 6    6 -0.52191870 f
## 7    7 -0.06490237 g
## 8    8  1.05136997 h
## 9    9 -1.74215826 i
## 10  10  1.73254803 j
```

```
rounddf(dat)
```

```
##      a      b c
## 1    1  0.29 a
## 2    2 -0.45 b
## 3    3 -0.22 c
## 4    4 -1.61 d
## 5    5  0.07 e
## 6    6 -0.52 f
## 7    7 -0.06 g
## 8    8  1.05 h
## 9    9 -1.74 i
## 10  10  1.73 j
```

```
rounddf(dat, digits = c(0, 4))
```

```
## Warning in rounddf(dat, digits = c(0, 4)): First value in digits repeated to
## match length.
```

```
##      a      b c
## 1    1  0.2904 a
## 2    2 -0.4476 b
## 3    3 -0.2189 c
## 4    4 -1.6054 d
```

```
## 5 5 0.0748 e
## 6 6 -0.5219 f
## 7 7 -0.0649 g
## 8 8 1.0514 h
## 9 9 -1.7422 i
## 10 10 1.7325 j
```

```
rounddf(dat, digits = c(0, 4), func = signif)
```

```
## Warning in rounddf(dat, digits = c(0, 4), func = signif): First value in digits
## repeated to match length.
```

```
##      a      b c
## 1 1 0.29040 a
## 2 2 -0.44760 b
## 3 3 -0.21890 c
## 4 4 -1.60500 d
## 5 5 0.07484 e
## 6 6 -0.52190 f
## 7 7 -0.06490 g
## 8 8 1.05100 h
## 9 9 -1.74200 i
## 10 10 1.73300 j
```

```
rounddf(dat, digits = c(2, 2), func = signif)
```

```
## Warning in rounddf(dat, digits = c(2, 2), func = signif): First value in digits
## repeated to match length.
```

```
##      a      b c
## 1 1 0.290 a
## 2 2 -0.450 b
## 3 3 -0.220 c
## 4 4 -1.600 d
## 5 5 0.075 e
## 6 6 -0.520 f
## 7 7 -0.065 g
## 8 8 1.100 h
## 9 9 -1.700 i
## 10 10 1.700 j
```

Trailing zeroes are dropped when written out (although this does not show up in R console). Avoid with `pad = TRUE`, which converts adds trailing zeroes and converts column to character.

```
set.seed(124)
```

```
dat <- data.frame(a = 1:10, b = rnorm(10), c = letters[1:10])
dat
```

```
##      a      b c
## 1 1 -1.38507062 a
## 2 2 0.03832318 b
## 3 3 -0.76303016 c
## 4 4 0.21230614 d
## 5 5 1.42553797 e
## 6 6 0.74447982 f
## 7 7 0.70022940 g
## 8 8 -0.22935461 h
## 9 9 0.19709386 i
```

```
## 10 10 1.20715377 j
```

```
summary(dat)
```

```
##           a           b           c
## Min.      : 1.00   Min.   :-1.3851   Length:10
## 1st Qu.: 3.25   1st Qu.: -0.1624   Class :character
## Median : 5.50   Median : 0.2047   Mode  :character
## Mean      : 5.50   Mean    : 0.2148
## 3rd Qu.: 7.75   3rd Qu.: 0.7334
## Max.     :10.00   Max.    : 1.4255
```

```
roundddf(dat)
```

```
##      a      b c
## 1    1 -1.39 a
## 2    2  0.04 b
## 3    3 -0.76 c
## 4    4  0.21 d
## 5    5  1.43 e
## 6    6  0.74 f
## 7    7  0.70 g
## 8    8 -0.23 h
## 9    9  0.20 i
## 10 10  1.21 j
```

```
roundddf(dat, pad = TRUE)
```

```
##      a      b c
## 1    1 -1.39 a
## 2    2  0.04 b
## 3    3 -0.76 c
## 4    4  0.21 d
## 5    5  1.43 e
## 6    6  0.74 f
## 7    7  0.70 g
## 8    8 -0.23 h
## 9    9  0.20 i
## 10 10  1.21 j
```

```
dat <- roundddf(dat, pad = TRUE)
```


```
summary(dat)
```

```
##           a           b           c
## Min.      : 1.00   Length:10       Length:10
## 1st Qu.: 3.25   Class :character   Class :character
## Median : 5.50   Mode  :character   Mode  :character
## Mean      : 5.50
## 3rd Qu.: 7.75
## Max.     :10.00
```

ggsave2x

Save a ggplot2 figure in more than one format in a single call.

```
library(ggplot2)
ggplot(economics, aes(date, unemployment)) +
  geom_line(colour = "red")
```



```
ggsave2x('economics', width = 5, height = 5)
```

Saves png and pdf by default, add more with **type** argument. Use ... optional arguments for more flexibility.


mintegrate

Integrate flux measurements for emission.

```
source('mintegrate.R')
```

1. Linear

```
x <- 0:10  
y <- 0:10  
plot(x, y)
```



Exact integral is $10 * 10 / 2 = 50$.

```
mintegrate(x, y, 'midpoint')
```

```
## [1] 0.0 0.5 2.0 4.5 8.0 12.5 18.0 24.5 32.0 40.5 50.0
```

```
mintegrate(x, y, 'left')
```

```
## [1] 0 1 3 6 10 15 21 28 36 45 55
```

```
mintegrate(x, y, 'right')
```


```
## [1] 0 1 3 6 10 15 21 28 36 45 45
```

```
mintegrate(x, y, 'trap')
```

```
## [1] 0.0 0.5 2.0 4.5 8.0 12.5 18.0 24.5 32.0 40.5 50.0
```


Note differences on the way up.

```
plot(0:10, x * y / 2, ylim = c(0, 60))
lines(0:10, mintegrate(x, y, 'midpoint'), col = 'orange')
lines(0:10, mintegrate(x, y, 'left'), col = 'red')
lines(0:10, mintegrate(x, y, 'right'), col = 'blue')
lines(0:10, mintegrate(x, y, 'trap'), col = 'green', lty = 2)
```



Leave out 0 (say first measurement is at time = 1).

```
x <- 1:10
y <- 1:10
plot(x, y)
```



Exact integral depends on what occurred before $t = 1$.

```
mintegrate(x, y, 'midpoint')
```

```
## [1] 0.0 1.5 4.0 7.5 12.0 17.5 24.0 31.5 40.0 49.5
```



```
mintegrate(x, y, 'left')
```

```
## [1] 0 2 5 9 14 20 27 35 44 54
```

```
mintegrate(x, y, 'right')
```

```
## [1] 1 3 6 10 15 21 28 36 45 45
```

```
mintegrate(x, y, 'trap')
```

```
## [1] 0.0 1.5 4.0 7.5 12.0 17.5 24.0 31.5 40.0 49.5
```

Can incorporate assumptions.

```
mintegrate(x, y, 'midpoint', lwr = 0)
```

```
## [1] 0.5 2.0 4.5 8.0 12.5 18.0 24.5 32.0 40.5 50.0
```

```
mintegrate(x, y, 'left', lwr = 0)
```

```
## [1] 1 3 6 10 15 21 28 36 45 55
```

```
mintegrate(x, y, 'right', lwr = 0)
```


```
## [1] 1 3 6 10 15 21 28 36 45 45
```

```
mintegrate(x, y, 'trap', lwr = 0, ylw = 0)
```

```
## [1] 0.5 2.0 4.5 8.0 12.5 18.0 24.5 32.0 40.5 50.0
```

Nonlinear

```
x <- 1:10  
y <- exp(-x)  
plot(x, y, type = 'l')
```



Exact integral from 1:10 is $\exp(-10) - \exp(-1) = 0.3678$. From 0 it is 1.0.

```

mintegrate(x, y, 'midpoint', value = 'total')


## [1] 0.3979879
mintegrate(x, y, 'left', value = 'total')

## [1] 0.2140708
mintegrate(x, y, 'right', value = 'total')

## [1] 0.5819049
mintegrate(x, y, 'trap', value = 'total')

## [1] 0.3979879
plot(0:10, -exp(-(0:10)) + exp(-min(0:10)), col = 'red')
points(x, -exp(-x) + exp(-min(x)), ylim = c(0, 0.7))
lines(x, mintegrate(x, y, 'midpoint'), col = 'orange')
lines(x, mintegrate(x, y, 'left'), col = 'red')
lines(x, mintegrate(x, y, 'right'), col = 'blue')
lines(x, mintegrate(x, y, 'trap'), col = 'green', lty = 2)

```




None is perfect, but midpoint and trapezoid (identical in this implementation) are the best, only slightly overestimating. Note that they all do poorly compared to a true integral that starts at 0 (red points). This cannot really be helped—how could we infer the true high values of y close to 0 from these limited measurements?

```


x <- 0:10
plot(x, exp(-x))

```




The `lwr` argument can extend the first rate back to 0 or any arbitrary starting point, which helps a bit.

```
x <- 1:10
plot(0:10, -exp(-(0:10)) + exp(-min(0:10)), col = 'red')
points(x, -exp(-x) + exp(-min(x)), ylim = c(0, 0.7))
lines(x, mintegrate(x, y, 'midpoint', lwr = 0), col = 'orange')
```



But measurements are needed at or closer to 0 to do really well with this function. Start at 0.

```
x <- 0:10
y <- exp(-x)
plot(x, y, type = 'l')
```



```
mintegrate(x, y, 'midpoint', value = 'total')
```

```
## [1] 1.081928
```

```
mintegrate(x, y, 'left', value = 'total')
```

```
## [1] 0.5819503
```


```
mintegrate(x, y, 'right', value = 'total')
```

```
## [1] 1.581905
```

```
mintegrate(x, y, 'trap', value = 'total')
```


```
## [1] 1.081928
```

```
plot(x, -exp(-x) + exp(-min(x)), ylim = c(0, 1.5))
lines(x, mintegrate(x, y, 'midpoint'), col = 'orange')
lines(x, mintegrate(x, y, 'left'), col = 'red')
lines(x, mintegrate(x, y, 'right'), col = 'blue')
lines(x, mintegrate(x, y, 'trap'), col = 'green', lty = 2)
```



We can prove that all methods become accurate with very high resolution.

```
x <- 0:100 / 10
y <- exp(-x)
plot(x, y, type = 'l')
```



```
mintegrate(x, y, 'midpoint', value = 'total')
```

```
## [1] 1.000788
```

```
mintegrate(x, y, 'left', value = 'total')
```

```
## [1] 0.95079
```

```
mintegrate(x, y, 'right', value = 'total')
```

```
## [1] 1.050785
```


```
mintegrate(x, y, 'trap', value = 'total')
```

```
## [1] 1.000788
```

```
x <- 0:10000 / 1000
```

```
y <- exp(-x)
```

```
plot(x, y, type = 'l')
```



```
mintegrate(x, y, 'midpoint', value = 'total')
```

```
## [1] 0.9999547
```

```
mintegrate(x, y, 'left', value = 'total')
```

```
## [1] 0.9994547
```

```
mintegrate(x, y, 'right', value = 'total')
```

```
## [1] 1.000455
```

```
mintegrate(x, y, 'trap', value = 'total')
```

```
## [1] 0.9999547
```


```
plot(x, -exp(-x) + exp(-min(x)), col = 'gray')
```

```
lines(x, mintegrate(x, y, 'midpoint'), col = 'orange')
```

```
lines(x, mintegrate(x, y, 'left'), col = 'red')
```

```
lines(x, mintegrate(x, y, 'right'), col = 'blue')
```

```
lines(x, mintegrate(x, y, 'trap'), col = 'green', lty = 2)
```



Note that data need not be sorted by x.


```
x <- 0:10
y <- exp(-x)

mintegrate(x, y, 'midpoint')

## [1] 0.0000000 0.6839397 0.9355471 1.0281083 1.0621596 1.0746864 1.0792948
## [8] 1.0809901 1.0816137 1.0818432 1.0819276

x[1] <- 4
x[5] <- 0
y <- exp(-x)

int <- mintegrate(x, y, 'midpoint')
plot(x, int)
```




difftime

```
now <- Sys.time()
x <- difftime(now, now - 1:10)
y <- exp(-as.numeric(x))
```

```
int <- mintegrate(x, y)
```

```
## Warning in mintegrate(x, y): Converting x to numeric. Check values with value =
## "xy".
```

```
plot(x, int)
```

```
mintegrate(x, y, value = 'xy')
```

```
## Warning in mintegrate(x, y, value = "xy"): Converting x to numeric. Check
## values with value = "xy".
```

```
##      [,1]      [,2]
## [1,]    1 0.0000000
## [2,]    2 0.2516074
## [3,]    3 0.3441685
## [4,]    4 0.3782199
## [5,]    5 0.3907467
## [6,]    6 0.3953550
## [7,]    7 0.3970504
## [8,]    8 0.3976740
## [9,]    9 0.3979035
## [10,]   10 0.3979879
```

With different units, result will differ. It is up to the user to make sure y and x have same time unit!

```
x <- difftime(now, now - 1:10, units = 'hours')
y <- exp(-as.numeric(x * 3600))
```

```
mintegrate(x, y, value = 'xy')
```

```
## Warning in mintegrate(x, y, value = "xy"): Converting x to numeric. Check
## values with value = "xy".
```

```
##      [,1]      [,2]
## [1,] 0.0002777778 0.000000e+00
## [2,] 0.0005555556 6.989093e-05
## [3,] 0.0008333333 9.560237e-05
## [4,] 0.0011111111 1.050611e-04
## [5,] 0.0013888889 1.085407e-04
## [6,] 0.0016666667 1.098208e-04
## [7,] 0.0019444444 1.102918e-04
```


```
## [8,] 0.0022222222 1.104650e-04
## [9,] 0.0025000000 1.105287e-04
## [10,] 0.0027777778 1.105522e-04
```

Grouped

```
x <- 0:10
y <- exp(-x)
```

```
x <- c(x, x)
y <- c(y, y + 0.2)
g <- rep(c('a', 'b'), each = 11)
```

```
int <- mintegrate(x, y, by = g)
plot(x, int, pch = g)
```



consec

```
source('consec.R')
```

```
x <- data.frame(a = 1:20, b = c(1, 1, 1, 2, 2, 2, 4, 4, 5, 10, 10, 10, 10, 0, 0, 0, 0, 1, 1, 2))
```

```
x$group <- consec(x$b)
x
```

```
##      a  b group
## 1    1  1     1
## 2    2  1     1
## 3    3  1     1
## 4    4  2     2
## 5    5  2     2
## 6    6  2     2
```

```
## 7 7 4 3
## 8 8 4 3
## 9 9 5 4
## 10 10 10 5
## 11 11 10 5
## 12 12 10 5
## 13 13 10 5
## 14 14 0 6
## 15 15 0 6
## 16 16 0 6
## 17 17 0 6
## 18 18 1 7
## 19 19 1 7
## 20 20 2 8
```

```
x$group
```

```
## [1] 1 1 1 2 2 2 3 3 4 5 5 5 5 6 6 6 6 7 7 8
```

```
x$group <- consec(x$b, value = 'f')
```

```
x
```

```
## a b group
## 1 1 1 1
## 2 2 1 1
## 3 3 1 1
## 4 4 2 2
## 5 5 2 2
## 6 6 2 2
## 7 7 4 3
## 8 8 4 3
## 9 9 5 4
## 10 10 10 5
## 11 11 10 5
## 12 12 10 5
## 13 13 10 5
## 14 14 0 6
## 15 15 0 6
## 16 16 0 6
## 17 17 0 6
## 18 18 1 7
## 19 19 1 7
## 20 20 2 8
```

```
x$group
```

```
## [1] 1 1 1 2 2 2 3 3 4 5 5 5 5 6 6 6 6 7 7 8
```

```
## Levels: 1 2 3 4 5 6 7 8
```

With character variable.

```
x <- data.frame(a = 1:20, b = letters[c(1, 1, 1, 2, 2, 2, 4, 4, 5, 10, 10, 10, 10, 9, 9, 9, 9, 1, 1, 2)])
```

```
x$group <- consec(x$b)
```

```
x
```

```
## a b group
## 1 1 a 1
```

```
## 2 2 a 1
## 3 3 a 1
## 4 4 b 2
## 5 5 b 2
## 6 6 b 2
## 7 7 d 3
## 8 8 d 3
## 9 9 e 4
## 10 10 j 5
## 11 11 j 5
## 12 12 j 5
## 13 13 j 5
## 14 14 i 6
## 15 15 i 6
## 16 16 i 6
## 17 17 i 6
## 18 18 a 7
## 19 19 a 7
## 20 20 b 8
```

```
x$group
```

```
## [1] 1 1 1 2 2 2 3 3 4 5 5 5 5 6 6 6 6 7 7 8
```

```
x$group <- consec(x$b, value = 'f')
x
```

```
##      a b group
## 1 1 a 1
## 2 2 a 1
## 3 3 a 1
## 4 4 b 2
## 5 5 b 2
## 6 6 b 2
## 7 7 d 3
## 8 8 d 3
## 9 9 e 4
## 10 10 j 5
## 11 11 j 5
## 12 12 j 5
## 13 13 j 5
## 14 14 i 6
## 15 15 i 6
## 16 16 i 6
## 17 17 i 6
## 18 18 a 7
## 19 19 a 7
## 20 20 b 8
```

```
x$group
```

```
## [1] 1 1 1 2 2 2 3 3 4 5 5 5 5 6 6 6 6 7 7 8
## Levels: 1 2 3 4 5 6 7 8
```