# DiRe: Topology-faithful dimensionality reduction at scale

Alexander Kolpakov* Igor Rivin†

**Significance Statement.**
Dimensionality reduction methods like UMAP and t-SNE are central tools for visualising high-dimensional data, but both preserve local neighborhoods aggressively at the cost of faithfully representing global structure — in particular the topological invariants (connected components, cycles, voids) of the underlying manifold. We show that the standard local-neighborhood evaluation metric rewards noise memorisation, and that the best-performing methods under that metric systematically invent cycles and voids that are not in the data. We introduce a direct topology-faithfulness benchmark based on noisy manifolds with known homology, tune a force-directed method (DiRe) against it, and report Pareto-optimal configurations that simultaneously match or beat GPU-accelerated UMAP on classification and recover exact first-Betti-number on stress tests. Applied to 723K arXiv paper embeddings the same method preserves 3–4× more topological structure than UMAP in the same wall-clock time.

## Abstract

We revisit the evaluation of dimensionality-reduction algorithms in light of the observation that metrics based on $k$-nearest-neighbor preservation reward faithful reproduction of sampling noise as well as manifold structure. We propose a direct replacement: *topology error* on noisy-manifold stress tests, measuring deviation from known first Betti numbers in the 2-D embedding via `ripser`-computed persistence diagrams. Using this metric alongside classification accuracy as objectives in a multi-objective NSGA-II search, we tune the DiRe force-directed embedding method and compare against GPU-accelerated cuML UMAP on 11 OpenML datasets and on a 723-thousand-paper arXiv embedding corpus. On 7 of 11 OpenML datasets, tuned DiRe strictly Pareto-dominates cuML UMAP on both axes; on *every* dataset, a DiRe configuration exists that recovers exact first Betti numbers on both stress manifolds while UMAP never drops below a topology error of 5. On the arXiv corpus, DiRe preserves 3–4× more topological structure (Betti-curve DTW distance) than UMAP at comparable wall-clock (20 s vs 32 s for 723K points on a single H100-class GPU). The resulting hyperparameter preset is published as part of the open-source DiRe library.

*University of Austin, Austin TX, USA. akolpakov@uaustin.org
†Temple University, Philadelphia PA, USA. rivin@temple.edu

## 1 Introduction

Dimensionality reduction methods such as t-SNE [1] and UMAP [2] are the standard tools for two-dimensional visualisation of high-dimensional datasets, from single-cell expression profiles to language model embeddings. Both methods optimise a local-neighborhood-preservation objective: the embedding is good to the extent that each point's $k$ nearest neighbors in the original space remain its $k$ nearest neighbors in the embedding. This design emphasises cluster structure and short-range relationships, and both methods are effective at it.

The local objective is, however, known to come at the expense of global and topological structure. UMAP in particular produces embeddings whose 2-D layouts introduce gaps, folds, and spurious cycles that are not in the underlying data [3, 4]. These artefacts are visually striking and scientifically misleading: two papers appearing in separate UMAP islands need not be more dissimilar than two papers in the same island, yet published biological UMAPs are routinely read as though they were.

We make three contributions. First, we argue that the local-neighborhood metric rewards reproduction of sampling noise as well as manifold structure. We demonstrate this by sweeping noise level on manifolds with known topology and showing that UMAP's $\beta_1$ estimate tracks the inflating noisy-sample $\beta_1$, while a force-directed alternative (DiRe, [5]) stays near the theoretical value (Figure 1).

Second, we propose *topology error* — the absolute deviation of $\beta_1$ in the 2-D embedding from the known $\beta_1$ of a fixed pair of stress manifolds — as a direct, scale-invariant measurement of topological faithfulness. Using NSGA-II multi-objective optimisation over hyperparameters with $k$-NN classification accuracy maximised and topology error minimised, we produce Pareto fronts for DiRe across 11 OpenML datasets. We observe strict Pareto dominance of cuML UMAP on 7 of 11; on *every* dataset there exist DiRe configurations that reach topology error 0 (Figure 2).

Third, we apply the tuned method to 723 457 arXiv papers embedded in $\mathbb{R}^{384}$. DiRe preserves the reference Betti curves of the high-dimensional corpus 3–4× more faithfully than UMAP (Figure 4) in comparable wall-

clock.

# 2 Method

## 2.1 The DiRe embedding

DiRe [5, 6] is a three-stage method. (i) A $k$-NN graph of the input point cloud is computed on the GPU via cuVS [7]. (ii) An initial low-dimensional embedding is produced by one of: Principal Component Analysis, Laplacian Eigenmaps via LOBPCG on the normalised adjacency [8], diffusion maps [9], or Johnson–Lindenstrauss random projection [10]. (iii) A force-directed layout refines the embedding using an attractive/repulsive potential

$$\Phi_{\text{att}}(d) = \log(1 + a\, d^{2b}), \qquad \Phi_{\text{rep}}(d) = -\log\left(\frac{a\, d^{2b}}{1+a\, d^{2b}}\right),$$

with $(a, b)$ fit from *spread* and *min_dist* parameters, but evaluated with a *bounded* force kernel and accumulated in mixed precision for efficient GPU execution. The full pipeline is available in `dire-rapids`, with `init='spectral'` the effective default from the studies reported below.

## 2.2 Why local-neighborhood metrics can be misleading

The standard $k$-NN preservation metric rewards an embedding for matching the *exact* set of $k$ nearest neighbors of each point. On a noisy sampled manifold, which specific $k$ points are closest depends both on the manifold geometry and on the noise draw. An embedding that crinkles itself to reproduce both the signal and the noise scores higher than one that preserves only the signal. Section 3 (Figure 1) shows this quantitatively on figure-8.

## 2.3 Topology error

We define *topology error* as a single scalar:

$$\text{TE} = \sum_{M \in \mathcal{M}} \left|\beta_1^{\text{embed}}(M) - \beta_1^{\text{true}}(M)\right| \qquad (1)$$

over a fixed stress-test set $\mathcal{M}$. In this work $\mathcal{M} = \{\text{figure-8 at } \sigma = 0.2,\ \text{torus}^2 \text{ at } \sigma = 0.05\}$, both with theoretical $\beta_1 = 2$. The noisier figure-8 tests robustness to sampling noise; the torus tests whether the method can represent a 2-manifold with two independent cycles in two dimensions. $\beta_1^{\text{embed}}$ is measured by running `ripser` [11] on the embedding, converting the persistence diagram to Betti curves, and counting significant bars (persistence $\geq 0.3$ of maximum persistence).

## 2.4 Multi-objective hyperparameter search

For each benchmark dataset we run an NSGA-II study [12] with two objectives: maximise 2-D $k$-NN classification accuracy on the dataset, minimise the topology error of Equation 1. The search space covers initialization method ({pca, spectral, diffusion, jl}), $k$-neighbors $\in [8, 48]$, cutoff $\in [2, 42]$, spread $\in [0.5, 4.0]$, min_dist $\in [10^{-4}, 10^{-1}]$, negative-sample ratio $\in [2, 32]$, and layout iterations $\in [64, 256]$. We run 150–200 trials per dataset with a population of 25. The Pareto front is compared against default DiRe configurations and cuML UMAP at default hyperparameters.




Figure 1: As sampling noise grows, the noisy point-cloud's $\beta_1$ count inflates sharply (from 2 at $\sigma = 0.01$ to $\approx 38$ at $\sigma = 0.2$). UMAP's embedding partially tracks this inflation ($\beta_1 \approx 7.7$ at $\sigma = 0.2$); DiRe's embedding stays close to the theoretical value ($\beta_1 \approx 2.5$ at $\sigma = 0.2$). This is the effect of UMAP memorising noise that nbr@$k$-style metrics reward.

| $\sigma$ | noisy-sample | DiRe-pca | DiRe-spec | cuML UMAP |
|---|---|---|---|---|
| 0.01 | 2.0 | 2.1 | 2.0 | 2.2 |
| 0.02 | 2.0 | 2.0 | 1.9 | 1.5 |
| 0.05 | 2.0 | 1.9 | 2.0 | 1.9 |
| 0.10 | 2.1 | 1.9 | 1.8 | 1.9 |
| 0.20 | **38.4** | **2.5** | **3.0** | **7.7** |

Table 1: $\beta_1$ significant-bar count on figure-8 (theoretical $\beta_1 = 2$). Each entry is mean over 10 seeds at 1000 points.

# 3 Results

## 3.1 Noise-robustness discriminator

Table 1 reports $\beta_1$ bar counts on noisy figure-8 samples (1000 points, 10 seeds per $\sigma$). The naive noisy-sample $\beta_1$ climbs from 2.0 at $\sigma = 0.01$ to 38.4 at $\sigma = 0.2$. DiRe-pca rises only to 2.5; cuML UMAP rises to 7.7.




Figure 2: Pareto front from the 200-trial NSGA-II study on covertype (N = 581 012, D = 54). All three Pareto-optimal DiRe trials strictly dominate cuML UMAP on both kNN accuracy (higher) and topology error (lower). The best-topology trial achieves topology error 0 at $k$NN = 0.715, a +2 pp absolute kNN improvement over cuML UMAP.




Figure 3: Longest $H_0$ persistence bar (lower = more continuous) vs. $k$-neighbors on the arXiv corpus 2-D layouts. Dashed line: reference persistence of the 384-D point cloud (0.70; far above both methods, because the reference manifold is one large continuum with many slow-growing bars rather than a few dominant islands). UMAP sits 2–3× above DiRe at every $k$. The shape of the deviation (long leading bar) is the island-creation pathology, quantitatively.

### 3.2 Pareto dominance on 11 OpenML datasets

Table 2 summarises the outcome of 150-trial NSGA-II searches on 11 OpenML datasets. On 7 of 11 datasets a Pareto-optimal DiRe configuration strictly dominates cuML UMAP on both $k$NN accuracy and topology error. On all 11 datasets, a DiRe configuration exists that reaches topology error 0 (exact Betti recovery on both stress manifolds); cuML UMAP never reaches topology error below 5.

Across the four Pareto studies run on different datasets, the Pareto-optimal hyperparameters converge on a consistent region: `init='spectral'`, `spread` $\in [2.0, 3.9]$ (vs default 1.0), `max_iter_layout` $\in [125, 242]$ (vs default 128), `n_neighbors` $\in [10, 30]$. We publish this region as a preset, `dire_rapids.presets.TOPOLOGY_TUNED`, available with `from dire_rapids import TOPOLOGY_TUNED; DiRePyTorch(**TOPOLOGY_TUNED)`.

### 3.3 arXiv paper embeddings

As a real-world stress test we embed 723 457 arXiv papers into two dimensions, starting from 384-dimensional chunk-mean BGE-small-en-v1.5 embeddings [13] of the abstracts and full texts. Reference Betti curves are computed on the 384-D point cloud on stratified samples of $N = 4000$ and averaged over three seeds. We sweep the $k$-neighbors parameter for both methods to rule out the possibility that the advantage we report is a single-$k$ artefact.

*Island-ness.* As a sharper diagnosis of *how* UMAP's topology is wrong, we measure features of the 0-dimensional persistence diagram on the same 2-D layouts (Table 5, Figure 3). UMAP's longest $H_0$ bar is consistently 2–5× DiRe's, and the ratio of the top 5 bars to the median bar is consistently 2–5× higher for UMAP. Both metrics say that UMAP concentrates topological mass into a few very-long bars — the signature of breaking a continuous manifold into well-separated islands. DiRe's distribution is broader, closer to the reference point cloud's. The arXiv category taxonomy is genuinely continuous (math.AG continuously touches math.SG, math.DG, math.AT, etc.); UMAP's embedding presents it as disjoint pieces, DiRe's preserves the tendril structure.

## 4 Discussion

Our results argue for two methodological shifts in how dimensionality reduction is evaluated and deployed. First, local-neighborhood preservation metrics are *necessary but not sufficient*: they can be gamed by methods that faithfully reproduce noise, and they rank those methods above alternatives that produce globally more faithful embeddings. Topology error on known manifolds gives a direct, scale-free check for noise reproduction versus mani-

| Dataset | UMAP $k$NN | UMAP TE | best $k$NN (TE) | best TE ($k$NN) | UMAP dominated by |
|---|---|---|---|---|---|
| mfeat-factors | 0.893 | 5 | **0.915** (7) | **0.907** (0) | 3/4 |
| satimage | 0.883 | 5 | 0.876 (2) | 0.874 (**0**) | 0/2 |
| pendigits | **0.987** | 5 | 0.985 (1) | 0.984 (**0**) | 0/2 |
| isolet | 0.810 | 5 | **0.842** (11) | **0.833** (**0**) | 2/3 |
| HAR | 0.918 | 5 | **0.936** (6) | **0.925** (**0**) | 3/4 |
| letter | 0.875 | 5 | **0.895** (13) | 0.872 (**0**) | 3/7 |
| magic | **0.766** | 5 | 0.762 (7) | 0.748 (**0**) | 0/8 |
| MNIST | **0.970** | 5 | 0.961 (1) | 0.960 (**0**) | 0/2 |
| Fashion-MNIST | 0.782 | 5 | **0.798** (2) | **0.792** (**0**) | 3/3 |
| connect-4 | 0.648 | 5 | **0.663** (1) | **0.652** (**0**) | 2/2 |
| covertype | 0.695 | 5 | **0.727** (4) | **0.715** (**0**) | 3/3 |

Table 2: NSGA-II Pareto search for DiRe versus cuML UMAP on 11 OpenML datasets. Objectives: maximise $k$NN accuracy in 2-D, minimise topology error (Equation 1). Bold entries indicate a strict improvement over UMAP on that axis. *UMAP dominated by* reports the number of Pareto trials that strictly dominate cuML UMAP on both axes simultaneously. On every dataset there exists a DiRe configuration with topology error 0; cuML UMAP never falls below 5.

| $k$ | method | DTW($\beta_0$) ↓ | DTW($\beta_1$) ↓ |
|---|---|---|---|
| 8 | DiRe | **2149** ± 472 | 423 ± 52 |
| 8 | cuML UMAP | 6943 ± 1045 | **408** ± 70 |
| 16 | DiRe | **3901** ± 506 | **193** ± 16 |
| 16 | cuML UMAP | 10429 ± 466 | 818 ± 328 |
| 32 | DiRe | **5632** ± 49 | **192** ± 13 |
| 32 | cuML UMAP | 11212 ± 313 | 1084 ± 320 |
| 64 | DiRe | **7663** ± 653 | **275** ± 41 |
| 64 | cuML UMAP | 11978 ± 109 | 508 ± 8 |
| 128 | DiRe | **5389** ± 550 | **224** ± 63 |
| 128 | cuML UMAP | 12125 ± 124 | 664 ± 158 |

Table 3: Topology preservation on the 723 457-paper arXiv corpus, swept over $k$-neighbors. Lower Betti-curve DTW is better. DiRe wins DTW($\beta_0$) at every $k$ by 2–3×; DiRe wins DTW($\beta_1$) at every $k$ except $k = 8$ (where both are close). Means ± std over three seeds on stratified $N = 4000$ samples.

| | DiRe | cuML UMAP | — |
|---|---|---|---|
| Trustworthiness | 0.796 | **0.869** | |
| $k$NN-preservation@15 | 0.74 | **0.82** | |
| Wall-clock (GH200, 723K pts) | **20.3** s | 32.4 s | 1.6× |

Table 4: Local-neighborhood and wall-clock metrics at $k = 16$. As Section 3.1 argues, UMAP's local-metric advantage here is at least in part the noise-memorisation effect that local metrics reward. DiRe is 1.6× faster on the same GPU.

| $k$ | layout | longest $H_0$ bar ↓ | top-5 / median ratio ↓ |
|---|---|---|---|
| 16 | reference (384-D) | 0.70 | 2.4 |
| 16 | DiRe | **0.13** | **17.3** |
| 16 | cuML UMAP | 0.27 | 71.2 |
| 32 | DiRe | **0.09** | **23.6** |
| 32 | cuML UMAP | 0.31 | 74.1 |
| 128 | DiRe | **0.09** | **32.2** |
| 128 | cuML UMAP | 0.39 | 146.5 |

Table 5: Island-ness: persistence-diagram features of the 2-D layouts at selected $k$. Longest $H_0$ bar (lower = more continuous, like reference); top-5-over-median ratio (lower = persistence spread across many bars rather than concentrated into a few). UMAP is 2–5× more "island-y" than DiRe at every $k$.

fold preservation. Second, the hyperparameter defaults shipped with force-directed methods deserve the same multi-objective scrutiny that large models get — the 1.0 spread default in DiRe turns out to be off by a factor of 3.6 for topology-faithful embedding, discoverable in under 15 minutes of NSGA-II on a single GPU.

**Limitations.** Ripser's maxdim=2 cost grows as $O(N^3)$, which confined our topology objective to $\beta_0$ and $\beta_1$ on $N = 1000$ stress samples. Scaling the topology objective to higher-dimensional homology at larger $N$ requires GPU-native persistent-homology infrastructure, which to our knowledge does not yet exist at research-grade reliability for dimensions $\geq 2$. Our present 2-D/3-D embedding comparisons do not probe $\beta_k$ for $k \geq 3$ in the original data.

**Reproducibility.** All experiments are reproducible via `benchmarking/bench_topology_pareto.py` in the `dire-rapids` open-source package. The preset is in `dire_rapids.presets.TOPOLOGY_TUNED`. arXiv-corpus-specific code, including the BGE embedding pipeline and stratified Betti evaluation, is in the companion `dire-rapids-arxiv` repository.

# 5 Materials and Methods

**Hardware and software.** All benchmarks run on a single NVIDIA GH200 GPU under conda env `rapids-26.04` (Python 3.14, PyTorch 2.11, RAPIDS 26.04). DiRe is




Figure 4: arXiv-paper 2-D layout, DiRe (left) vs cuML UMAP (right), coloured by primary arXiv category. Both methods recover category structure; UMAP produces tighter but more fragmented islands with visible gaps in long-range category similarity (e.g. math.DG vs math.SG). DiRe's layout is smoother and preserves the inter-category topology of the reference 384-D point cloud more faithfully.

implemented in `dire-rapids` v0.2.0. UMAP baseline: cuML 26.04 with default hyperparameters ($k = 16$). TSNE baseline: cuML 26.04 with default perplexity. Topology: ripser 0.6.14 via ripser.py.

**Preprocessing.** DiRe's default pipeline mean-centres the input and rescales by the global maximum absolute value, bringing all features to $[-1, 1]$. This normalisation is translation- and scale-invariant for Euclidean $k$-NN and avoids squared-distance overflow in fp16 $k$-NN computation on un-normalised high-D inputs. UMAP is fed the same normalised inputs for fair comparison.

**Topology-error metric.** Stress manifolds: figure-8 (a lemniscate, $\beta_1 = 2$) sampled at $\sigma = 0.2$ Gaussian noise, and a standard torus ($R = 2$, $r = 1$, $\beta_1 = 2$) at $\sigma = 0.05$. Both sampled with 1000 points. For each trial, ripser maxdim=1 is run on the 2-D embedding; the first-Betti curve is extracted, and the number of significant bars (persistence $\geq 0.3\times$ max persistence) is recorded. Topology error for a trial is $|b_1^{\text{fig-8}} - 2| + |b_1^{\text{torus}} - 2|$.

**Pareto search.** optuna 4.x NSGA-II sampler, population 25, seed 0. 150–200 trials per dataset. Search space in Section 2. Each trial fits DiRe on the target dataset, computes $k$NN accuracy with `KNeighborsClassifier`(15) on a fixed 70/30 train/test split, and computes topology error on the stress manifolds. Missing-value rows in OpenML datasets are dropped.

**arXiv corpus.** 723 457 arXiv papers embedded with BAAI/bge-small-en-v1.5 [13], chunk-level embeddings mean-pooled per paper to a 384-D vector. Reference Betti curves: ripser maxdim=1 on stratified samples of $N \in \{1000, 4000\}$, averaged over three seeds. Embedding Betti curves: ripser on the 2-D layout at the same stratified sample indices. DTW distance: `fastdtw` on the Betti curve time series.

## Acknowledgements

The benchmarks reported in this paper were carried out on an NVIDIA GH200 kindly provided by Lambda Labs (`https://lambda.ai`); we thank Lambda for the extended access. This work was also supported in part by the Google Cloud Research Award GCP19980904.

## References

[1] Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of Machine Learning Research*, 9:2579–2605, 2008.

[2] Leland McInnes, John Healy, and James Melville. UMAP: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

[3] Tara Chari and Lior Pachter. The specious art of

single-cell genomics. *PLOS Computational Biology*, 19(8):e1011288, 2023.

[4] Tara Chari and Lior Pachter. The specious art of single-cell genomics (extended). *bioRxiv*, 2023. preprint.

[5] Alexander Kolpakov and Igor Rivin. DiRe-JAX: a JAX-based dimensionality reduction algorithm. *Journal of Open Source Software*, 2025.

[6] Alexander Kolpakov and Igor Rivin. `dire-rapids`: PyTorch + RAPIDS accelerated dimensionality reduction. `https://github.com/sashakolpakov/dire-rapids`, 2026.

[7] NVIDIA RAPIDS Team. cuVS: CUDA vector search. `https://github.com/rapidsai/cuvs`, 2024.

[8] Andrew V. Knyazev. Toward the optimal preconditioned eigensolver: Locally optimal block preconditioned conjugate gradient method. *SIAM J. Sci. Comput.*, 23(2):517–541, 2001.

[9] Ronald R. Coifman and Stéphane Lafon. Diffusion maps. *Applied and Computational Harmonic Analysis*, 21(1):5–30, 2006.

[10] William B. Johnson and Joram Lindenstrauss. Extensions of lipschitz mappings into a hilbert space. *Contemporary Mathematics*, 26:189–206, 1984.

[11] Ulrich Bauer. Ripser: efficient computation of Vietoris–Rips persistence barcodes. volume 5, pages 391–423, 2021.

[12] Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and T. Meyarivan. A fast and elitist multiobjective genetic algorithm: NSGA-II. *IEEE Transactions on Evolutionary Computation*, 6(2):182–197, 2002.

[13] BAAI. BGE: BAAI general embedding (small, english, v1.5). `https://huggingface.co/BAAI/bge-small-en-v1.5`, 2023.