

Pushout Attachments and Conditional Complexity of Executable Models

Alexander Kolpakov

August 13, 2026

Abstract

We represent the modular enlargement of an executable model by a pushout of finite typed presentations. Adhesivity preserves the original model and recovers the shared interface, while chosen pushouts make linking functorial and coproducts describe parallel attachments. A semantic comparison gives a precise criterion for behavioral persistence. Effective linking also bounds conditional prefix complexity; under the stated canonicalization and invariance assumptions, attachment and extension codes yield the same profiles of loss against complexity, up to additive constants, and share an exact scalar envelope. The result separates syntax, semantics, ideal complexity, and concrete coding cost, and shows that a preference for modularity can arise only through restrictions on the permitted attachments.

Keywords. Adhesive category; cofibration; executable model; Kolmogorov complexity; minimum description length; pushout.

Mathematics Subject Classification (2020).

Primary 18B50; Secondary 18A30, 18A40, 68Q30, 68Q55.

1 Introduction

One often enlarges a finite executable presentation by joining a new module to it along a typed interface. We write this operation as the span

$$X \xleftarrow{u} A \xrightarrow{i} B$$

and take its pushout $P = X \sqcup_A B$. The object X is the presentation already in hand, A is the interface, and B is the incoming module. If the boundary map i is monic, then the induced map $X \rightarrow P$ retains the base as a subpresentation.

We place raw typed presentations in the presheaf slice $\mathbf{Syn} = \mathbf{Set}^{C^{\text{op}}}/T$, and denote its pointwise finite objects by $\mathbf{Syn}_f$. We call monomorphisms cofibrations. The name merely marks the maps along which modules may be attached; it carries no claim about weak equivalences, lifting axioms, or a model structure. Presheaf slices are adhesive, so a pushout along such a map is also a pullback and carries monomorphisms to monomorphisms [3, 4]. The old syntax therefore survives, and the overlap is exact. None of this is new category theory. Its purpose here is to say, without metaphor, what survives when a program grows by modules.

Yet the survival of syntax says nothing by itself about execution. A checker for a particular language may reject an ambient pushout, which is why we impose admissibility separately. Nor

does successful compilation guarantee that old behavior remains. Given a semantics functor $\text{Run} : \mathbf{Exec} \rightarrow \mathbf{Beh}$, applying Run to an admissible attachment produces a canonical comparison

$$\text{Run}(X) \sqcup_{\text{Run}(A)} \text{Run}(B) \longrightarrow \text{Run}(P).$$

We call the attachment semantically exact when this map is invertible. If monomorphisms in $\mathbf{Beh}$ are stable under pushout and $\text{Run}(i)$ is monic, semantic exactness makes $\text{Run}(X) \rightarrow \text{Run}(P)$ monic as well. The comparison map thus locates the proof that each application must supply, rather than smuggling a semantic conclusion into a fact about syntax.

Fixing the base X , we arrange attachment spans and pointed cofibration extensions into two categories. Chosen pushouts define a linking functor. It is left adjoint to the fully faithful functor that views an extension as an attachment with no new interface. Extensions are therefore reflective among attachments. The two effective constructions behind this reflection also give the translations between codes used later. After canonicalization, and provided loss is unchanged by the relevant isomorphisms, the translations shift the complexity profiles by at most constants. If the grammar forbids degenerate cells, however, the reflection may leave the grammar. Only then can the syntax of attachment express a real modular preference.

The point is the chain joining these observations. An admissible attachment along a monic boundary preserves the old syntax. Under the stated hypotheses, semantic exactness carries that persistence into behavior. Effective linking then turns a description of the attachment into a conditional description of the extension. The categorical ingredients and the scalar envelope are familiar in isolation. By placing the reflection and its coding consequence side by side, we can use them without pretending that admissibility, semantic preservation, ideal Kolmogorov complexity, and the length of a practical code are interchangeable notions.

Gluing by pushouts connects the construction to adhesive graph transformation [3, 4] and to categorical accounts of open systems based on structured cospans [1]. Structured cospans compose open systems along their boundaries. Here the base is fixed, an interface span is itself an object, and the reflector forgets all but the linked pointed extension. Our selection problem is a conditional restriction of algorithmic loss–complexity and individual rate–distortion profiles [10, 11], with minimum description length supplying the interpretation in terms of actual codes [6]. Formalisms for executable world models motivate the discipline of Section 2 [7, 8, 9], though the categorical construction itself is not drawn from those works.

2 Executable model presentations

2.1 The operational criterion

Definition 2.1 (Executable presentation). *Fix effective alphabets of actions $\mathcal{A}$, observations $\mathcal{O}$, rewards $\mathcal{W}$, patterns, values, and guards, together with a decidable checker for types and interfaces and a single effective interpreter I . An executable presentation is a finite hierarchy M of guarded rules that the checker accepts; its spaces of configurations and goals must also have effective encodings. The interpreter induces a computably enumerable backward relation*

$$R_M^- \subseteq \text{Goal}_M \times \text{Goal}_M^*$$

and an effective relation for forward inference. When actions are supplied as conditions, the latter takes the form of the partial computable map

$$F_M : \text{Conf}_M \times \mathcal{A} \rightharpoonup \text{Conf}_M \times \mathcal{O} \times \mathcal{W}$$

which may be iterated on each predicted configuration to produce a rollout. The backward relation reads a consequent as a goal and its antecedents as subgoals. A rule body may call other named rules through typed references.

Passing the checker certifies only syntactic executability. It promises neither termination nor usefulness. An ill-posed input or a computation that never halts has no output, and a semantic loss introduced later may assign it infinite cost.

2.2 A typed presheaf category

Let $\mathcal{C}$ be a finite, computably presented category. Its objects stand for syntactic sorts—rule nodes, antecedent and consequent ports, guards, state slots, or references within a hierarchy—and its arrows record incidence. Fix a presheaf T of types and attributes. We require effective codes for every attribute that occurs in a finite object, so that equality, typing, incidence, and naturality can all be decided from finite codes. Raw typed presentations then form the slice

$$\mathbf{Syn} = \mathbf{Set}^{\mathcal{C}^{\text{op}}} / T.$$

Write $\mathbf{Syn}_f$ for the full subcategory whose underlying presheaves are pointwise finite. Literal names and attributes that must be preserved are encoded in the map to T , rather than left as informal decorations.

A presentation discipline selects a subcategory $\mathbf{Exec} \subseteq \mathbf{Syn}_f$ of well-formed finite open and closed executable presentations; this subcategory need not be full. Write $\iota : \mathbf{Exec} \hookrightarrow \mathbf{Syn}_f$ for its inclusion. Its morphisms preserve types, the structure of guarded rules, ports, and references within the hierarchy. The discipline also specifies a semantics functor

$$\text{Run} : \mathbf{Exec} \longrightarrow \mathbf{Beh},$$

where $\mathbf{Beh}$ may consist of transition systems, trace presentations, or any other explicitly chosen kind of behavior.

The distinction matters. Raw syntax has every finite colimit we shall need, whereas a particular grammar, checker, compiler, or scheduler may not be closed under arbitrary pushouts. We therefore form all pushouts in $\mathbf{Syn}_f$. Such a pushout is *admissible* when the four objects and four arrows of its square all belong to $\mathbf{Exec}$. Since $\mathbf{Exec}$ need not be full, admissibility does not say that the same square is a pushout there.

3 Pushout attachments along cofibrations

3.1 Interface spans

An attachment has the shape of a span

$$X \xleftarrow{u} A \xrightarrow{i} B.$$

Its colimit identifies the two appearances of the interface A ; this colimit is the pushout $X \sqcup_A B$.

Throughout the paper, a *cofibration* means a morphism of $\mathbf{Syn}_f$ that is monic in $\mathbf{Syn}$. Isomorphisms are cofibrations; composites and pushouts of cofibrations are again cofibrations. The term has no further model-categorical force here.

Lemma 3.1 (Finite typed pushouts). *The category $\mathbf{Syn}$ is adhesive. The subcategory $\mathbf{Syn}_f$ is closed under finite colimits. The class of its morphisms that are monomorphisms in $\mathbf{Syn}$ contains the isomorphisms, is closed under composition, and is stable under pushout.*

Proof. Every presheaf category is a topos, every slice of a topos is a topos, and every topos is adhesive [3, 4]. Hence a pushout along a monomorphism is also a pullback, and the corresponding cobase change remains monic. Colimits in a presheaf category, and in its slices, are assembled component by component from coproducts and quotients. Since $\mathcal{C}$ has only finitely many objects, a finite colimit of pointwise finite presheaves is still pointwise finite. Closure under isomorphism and composition is general; stability under pushout is the adhesive part of the argument. $\square$

Definition 3.2 (Cofibration attachment). *Let $X, A, B \in \mathbf{Syn}_f$. A cofibration attachment consists of a binding $u : A \rightarrow X$ and a boundary inclusion $i : A \hookrightarrow B$ that is a cofibration. Its linked presentation is*

$$P = X \sqcup_A B.$$

The attachment is executable when this ambient pushout is admissible.

In this picture, A records the typed dependencies of the new module, B contains the module itself, and u binds the exposed ports to X . It is i , not u , that must be monic: this is precisely what makes the cobase change preserve the base.

Proposition 3.3 (Persistence and exact overlap). *For a cofibration attachment, the canonical map $j_X : X \rightarrow P$ is a fibration, and the canonical comparison*

$$A \longrightarrow X \times_P B$$

is an isomorphism. If the binding u is also a cofibration, then the canonical map $j_B : B \rightarrow P$ is a cofibration as well.

Proof. The map j_X is obtained by changing the base of i along u , and is therefore a cofibration. In the ambient adhesive category, a pushout along a monomorphism is a pullback. Thus $A \rightarrow X \times_P B$ is invertible. If u is itself a cofibration, the same argument applied on the other side makes j_B a cofibration. $\square$

The base is therefore still embedded, component by component, and the original interface can be recovered as $X \times_P B$. When u is monic as well, both pieces embed and meet in exactly A . Notice what the proposition does not say. It does not place P in **Exec**; that is the separate work of admissibility. Even after admissibility is known, the universal property still lives in the ambient category unless the inclusion creates this pushout. And nothing so far guarantees that executions which once succeeded will continue to do so.

3.2 The category of attachments

Fix $X \in \mathbf{Syn}_f$. Let $\mathbf{Ext}_X$ be the full subcategory of the coslice $X \downarrow \mathbf{Syn}_f$ whose objects are cofibrations $e : X \hookrightarrow Y$. Let $\mathbf{Att}_X$ have objects

$$c = (X \xleftarrow{u} A \xrightarrow{i} B)$$

with i a cofibration. For $c' = (X \xleftarrow{u'} A' \xrightarrow{i'} B')$, a morphism $(a, b) : c \rightarrow c'$ consists of maps $a : A \rightarrow A'$ and $b : B \rightarrow B'$ satisfying $u = u'a$ and $bi = i'a$.

Theorem 3.4 (Attachment reflection). *After choosing pushouts, linking defines a functor*

$$L_X : \mathbf{Att}_X \longrightarrow \mathbf{Ext}_X, \quad (X \xleftarrow{u} A \xrightarrow{i} B) \longmapsto (X \hookrightarrow X \sqcup_A B).$$

The functor

$$D_X : \mathbf{Ext}_X \longrightarrow \mathbf{Att}_X, \quad (j : X \hookrightarrow Y) \longmapsto (X \xleftarrow{\text{id}_X} X \xrightarrow{j} Y)$$

is fully faithful and $L_X \dashv D_X$. In particular, the counit $L_X D_X \Rightarrow \text{Id}_{\mathbf{Ext}_X}$ is an isomorphism, so $\mathbf{Ext}_X$ is reflective in $\mathbf{Att}_X$.

Proof. A morphism $(a, b) : c \rightarrow c'$ induces a unique map $L_X c \rightarrow L_X c'$ under X , by the universal property of the pushout. Uniqueness gives functoriality, and Proposition 3.3 says that the source map of every linked extension is a cofibration. For $e = (j : X \hookrightarrow Y)$, pushout universality gives natural bijections

$$\mathbf{Ext}_X(L_X c, e) \cong \{b : B \rightarrow Y \mid bi = ju\} \cong \mathbf{Att}_X(c, D_X e).$$

Thus $L_X \dashv D_X$. For a morphism between degenerate attachments, the map on interfaces can only be id_X . It follows that D_X is fully faithful; more explicitly, it sends a morphism h in the coslice to (id_X, h) . Finally, the pushout of $X \xleftarrow{\text{id}_X} X \xrightarrow{j} Y$ is canonically Y . This is the counit isomorphism. $\square$

The reflection belongs, for now, to the ambient syntax category. It descends to attachments inside $\mathbf{Exec}$ only if the chosen pushouts, together with all their induced mediating maps, remain within the presentation discipline.

Proposition 3.5 (Parallel composition). *The category $\mathbf{Ext}_X$ has finite coproducts, created by the coslice. For $e_s : X \hookrightarrow Y_s$, their coproduct has apex the iterated pushout $Y_1 \sqcup_X \cdots \sqcup_X Y_m$. If each $e_s = L_X c_s$, this apex is canonically the colimit of the corresponding finite star of attachment spans. Thus parallel attachments are independent of ordering up to the canonical coproduct isomorphisms.*

Proof. The identity on X is initial in $\mathbf{Ext}_X$, while binary coproducts in the coslice are pushouts over X . Their common base map factors as $X \hookrightarrow Y_1 \hookrightarrow Y_1 \sqcup_X Y_2$; the second map is a base change of $X \hookrightarrow Y_2$. Since both factors are cofibrations, the coproduct again lies in $\mathbf{Ext}_X$; fullness means that the coslice coproduct is created there. Iterating gives all finite coproducts. The last assertion follows because the iterated pushout and the star colimit have the same universal property. $\square$

An incoming cell may, of course, depend on cells already attached. Given

$$X_{k-1} \xleftarrow{u_k} A_k \xrightarrow{i_k} B_k, \quad X_k = X_{k-1} \sqcup_{A_k} B_k,$$

with each i_k a cofibration, Proposition 3.3, applied at every stage, gives the filtration

$$X_0 \hookrightarrow X_1 \hookrightarrow \cdots \hookrightarrow X_n.$$

Every arrow in this filtration is a cofibration, and every finite stage remains in $\mathbf{Syn}_f$.

4 Execution semantics

4.1 The comparison map

Take an executable attachment, and suppose that the following pushout of behaviors exists:

$$Q = \text{Run}(X) \sqcup_{\text{Run}(A)} \text{Run}(B).$$

The syntactic pushout cocone, after applying Run , gives compatible maps from $\text{Run}(X)$ and $\text{Run}(B)$ into $\text{Run}(P)$. The universal property of Q therefore supplies a canonical comparison

$$\chi : Q \longrightarrow \text{Run}(P).$$

Definition 4.1 (Semantically exact attachment). *An executable attachment is semantically exact when χ is an isomorphism.*

Exactness is one sufficient compatibility condition for a language and its linker. The syntactic pushout does not imply it, nor need it be necessary for every other reasonable notion of preserving behavior.

Theorem 4.2 (Semantic monicity criterion). *Assume that the displayed behavioral pushout exists, monomorphisms in **Beh** are stable under pushout, $\text{Run}(i) : \text{Run}(A) \rightarrow \text{Run}(B)$ is monic, and the attachment is semantically exact. Then*

$$\text{Run}(j_X) : \text{Run}(X) \longrightarrow \text{Run}(P)$$

is monic.

Proof. The canonical map $\text{Run}(X) \rightarrow Q$ is obtained by pushing out $\text{Run}(i)$, so it is monic. Composing it with the isomorphism $\chi : Q \rightarrow \text{Run}(P)$ gives $\text{Run}(j_X)$, which is therefore monic. $\square$

The conclusion is internal to the chosen category **Beh**. It says that old traces or transitions are literally preserved only if morphisms in that category also reflect traces or transitions. Along any finite chain of attachments satisfying the theorem, $\text{Run}(X_0) \rightarrow \text{Run}(X_n)$ is monic because monomorphisms are closed under composition.

The assumptions separate two ways the construction can fail. First, a guard or a clash of names may cause the compiler to reject the raw pushout. Second, even a program that compiles may acquire interactions absent from the pushout of its component behaviors, in which case χ is not invertible. Suppose, for example, that a global scheduler always chooses the first matching rule. Attaching a new rule of higher priority can then suppress an output formerly chosen from X , even though the pushout of rule graphs is admissible. On the proposed syntax morphisms, such a scheduler may not define a functor at all. Passing to a coarser category of behaviors can restore functoriality, but the comparison map may still fail to be invertible. This elementary example is enough to show why syntax alone cannot preserve behavior. Enumerating traces proves exactness only when the declared semantics is finite, effectively presented, and exhaustively checkable. A finite sample never proves global equivalence of programs.

5 Conditional complexity of linking

Fix a universal prefix machine U , together with effective self-delimiting codes for finite presentations, morphisms, and tuples. We write $K_U(z \mid w)$ for conditional prefix Kolmogorov complexity. A candidate is encoded as a pointed extension (X, j, Y) , not merely as a labeled object in isolation, and the base X is given a fixed canonical code. To canonicalize an extension in the coslice $X \downarrow \mathbf{Syn}_f$, first represent j as a literal inclusion and keep the labels on its image. At each sort, rename the remaining elements by a standard finite set, and choose the least among the finitely many incidence codes that result. Renaming must preserve both the map to T and the marked arrow. Our decidability assumptions on finite attributes make this procedure effective. The resulting complexity still depends, as it must, on the chosen representation and universal machine, but not on pointless changes of names outside the base.

For an attachment to X , let

$$c = (A, B, u, i)$$

be its complete attachment code. Componentwise finite coproducts, quotienting by the interface identifications, and canonical relabeling give a fixed computable linker Link , total on valid finite span codes, with literal domain X and

$$\text{Link}(X, c) = (j_X : X \hookrightarrow P), \quad P = X \sqcup_A B,$$

after canonicalization. The linker constructs raw syntax; it is not asked to decide whether the result belongs to **Exec**. The following bounds concern those outputs that are admissible.

Proposition 5.1 (Complexity bound for effective linking). *There is a constant b , depending only on the encodings, universal machine, and linker, such that every admissible attachment satisfies*

$$K_U((j_X : X \hookrightarrow X \sqcup_A B) \mid X) \leq K_U(A, B, u, i \mid X) + b.$$

If the cell B is already available as conditional information, then

$$K_U((j_X : X \hookrightarrow X \sqcup_A B) \mid X, B) \leq K_U(A, u, i \mid X, B) + b.$$

Proof. A fixed program first runs a shortest conditional description of the attachment and then calls Link . Its own length is constant. For the second inequality, the same program receives B on its conditional tape. $\square$

This is the usual monotonicity of prefix complexity under a fixed partial computable map, here applied to the linker. In the first inequality the cell B is not free information; in the second it is, because both sides receive it as a condition. The same care is needed with libraries. If every candidate may call one fixed library R , then every code and every complexity must be conditioned on the same pair (X, R) . Giving each candidate its own uncharged library destroys the comparison. Finally, these statements are upper bounds, not additive identities: shared algorithmic information can make a joint description shorter than the sum of its parts.

For a finite sequence of attachment codes $c_{1:n}$, iterated linking is also a fixed partial computable operation. Writing $j_{0,n} : X_0 \hookrightarrow X_n$ for the composite pointed extension, one has

$$K_U((j_{0,n} : X_0 \hookrightarrow X_n) \mid X_0) \leq K_U(c_{1:n} \mid X_0) + O(1).$$

If $\ell(c_{1:n} \mid X_0)$ is the length of a declared self-delimiting code with a fixed uniform effective decoder, then

$$K_U((j_{0,n} : X_0 \hookrightarrow X_n) \mid X_0) \leq \ell(c_{1:n} \mid X_0) + O(1).$$

The last inequality is a rule for practical bookkeeping, not an exact calculation of K_U . Once the self-delimiting decoder for tuples has been fixed, its $O(1)$ term is uniform in n .

6 Choosing extensions by Kolmogorov complexity

6.1 Conditional profiles of loss and complexity

Once a universal machine has been fixed, Kolmogorov complexity [2] becomes a coordinate measuring description. For finite data x , the classical structure function is

$$h_x(\alpha) = \min\{\log_2 |S| : x \in S, S \text{ finite}, K_U(S) \leq \alpha\},$$

with value $+\infty$ when the constraint set is empty [10, 5]. Algorithmic rate-distortion functions generalize this expression by replacing $\log |S|$ with a distortion criterion [11].

We now consider only candidates that extend a given base. Fix a presentation $X \in \mathbf{Exec}$, finite data D , and a countable, effectively presented class $\mathcal{E}_X$ of morphisms $e = (j : X \hookrightarrow Y)$ in $\mathbf{Exec}$ whose underlying maps are cofibrations. The marked arrow belongs to the candidate, since one target may extend X in several different ways. Let

$$L_D(e) \in [0, +\infty]$$

be the chosen loss under execution. We allow infinite loss when execution does not terminate or a semantic obligation fails, and write $k_X(e) = K_U(e \mid X)$.

Definition 6.1 (Profiles). *For $\alpha \in \mathbb{N}$ and finite $r \geq 0$, the two conditional profiles are*

$$H_{D,X}(\alpha) = \min\{L_D(e) : e \in \mathcal{E}_X, k_X(e) \leq \alpha\}$$

and

$$C_{D,X}(r) = \min\{k_X(e) : e \in \mathcal{E}_X, L_D(e) \leq r\},$$

Each minimum is understood to be $+\infty$ if its constraint set is empty.

For fixed α , only finitely many candidate codes have a prefix description of length at most α . Thus the first minimum, if finite, is attained. The second is attained whenever finite because complexity takes integer values. Consequently, for $\alpha \in \mathbb{N}$ and finite r ,

$$H_{D,X}(\alpha) \leq r \iff C_{D,X}(r) \leq \alpha.$$

In general these profiles are ideal, uncomputable objects. They reduce to the classical structure function when X is empty or fixed, the candidates are finite sets S containing D , and $L_D(S) = \log_2 |S|$, apart from the fixed convention used to encode candidates.

6.2 The scalar envelope and MDL specialization

For $\lambda > 0$, define

$$\Phi_{D,X}(\lambda) = \inf_{e \in \mathcal{E}_X} (L_D(e) + \lambda k_X(e)).$$

As usual, an infimum over the empty set is $+\infty$.

Proposition 6.2 (Exact scalar envelope). *For every $\lambda > 0$,*

$$\Phi_{D,X}(\lambda) = \inf_{\alpha \in \mathbb{N}} (H_{D,X}(\alpha) + \lambda \alpha) = \inf_{r \geq 0} (r + \lambda C_{D,X}(r)).$$

If at least one candidate has finite loss, the infimum defining $\Phi_{D,X}(\lambda)$ is attained, and every minimizer is Pareto-optimal in the two coordinates (L_D, k_X) .

Proof. For any candidate e , set $\alpha = k_X(e)$. Then $H_{D,X}(\alpha) \leq L_D(e)$, so the first right-hand infimum is at most $\Phi_{D,X}(\lambda)$. Conversely, a finite value of $H_{D,X}(\alpha)$ is realized by some e_α , and

$$\Phi_{D,X}(\lambda) \leq L_D(e_\alpha) + \lambda k_X(e_\alpha) \leq H_{D,X}(\alpha) + \lambda \alpha.$$

Taking infima proves the first equality. The second is the same argument with the coordinates exchanged: take $r = L_D(e)$ in one direction, and in the other choose a candidate that realizes $C_{D,X}(r)$.

To prove attainment, choose a candidate whose objective has some finite value M . Any candidate doing at least as well must satisfy $k_X(e) \leq M/\lambda$, and there are only finitely many such candidates. One of them therefore minimizes the objective. If another candidate improved both coordinates weakly and one of them strictly, it would strictly lower the scalar objective. Every minimizer is consequently Pareto optimal. $\square$

For a probabilistic instance, suppose $\{P_e(\cdot | X) : e \in \mathcal{E}_X\}$ is a family of conditional semimeasures that is uniformly lower semicomputable from (e, X) , and set $-\log_2 0 = +\infty$. The coding inequality gives

$$K_U(D | e, X) \leq -\log_2 P_e(D | X) + O(1),$$

and a self-delimiting concatenation therefore gives

$$K_U(D | X) \leq K_U(e | X) - \log_2 P_e(D | X) + O(1),$$

where the constant is uniform in D, e, X and depends only on the decoder for the family. Taking $L_D(e) = -\log_2 P_e(D | X)$, we find that $\Phi_{D,X}(1)$ is the ideal conditional optimum for two-part MDL. It is finite precisely when at least one candidate gives D positive mass [6, 5]. The conclusion depends on the uniform coding hypothesis just stated; it does not follow for an arbitrary real-valued loss.

6.3 Extension codes versus attachment codes

Let $\mathcal{C}_X$ be the valid codes $c = (A, B, u, i)$ of admissible cofibration attachments for which $e_c = \text{Link}(X, c)$ lies in $\mathcal{E}_X$. Assume that $\mathcal{E}_X$ remains closed when we apply the fixed canonicalization that preserves X , and that pointed isomorphisms fixing X do not change the loss. Define the ideal profile and scalar objective for attachment codes by

$$H_{D,X}^{\text{att}}(\alpha) = \min\{L_D(e_c) : c \in \mathcal{C}_X, K_U(c | X) \leq \alpha\}$$

and

$$\Phi_{D,X}^{\text{att}}(\lambda) = \inf_{c \in \mathcal{C}_X} (L_D(e_c) + \lambda K_U(c | X)).$$

For this comparison, the object map of L_X is the one canonical computable linker already fixed above, used uniformly for every X . The construction $(X, e) \mapsto D_X e$ is uniform and computable as well.

Theorem 6.3 (Comparing attachment and extension codes). *There are nonnegative integer constants b_1, b_2 , depending only on the fixed machine, encodings, linker, and canonicalizer and independent of D, X, α, λ , such that*

$$H_{D,X}(\alpha + b_1) \leq H_{D,X}^{\text{att}}(\alpha), \quad \Phi_{D,X}(\lambda) \leq \Phi_{D,X}^{\text{att}}(\lambda) + \lambda b_1,$$

and

$$H_{D,X}^{\text{att}}(\alpha + b_2) \leq H_{D,X}(\alpha), \quad \Phi_{D,X}^{\text{att}}(\lambda) \leq \Phi_{D,X}(\lambda) + \lambda b_2.$$

Proof. For $e = (j : X \hookrightarrow Y) \in \mathcal{E}_X$, the degenerate attachment $D_X e = (X \xleftarrow{\text{id}_X} X \xrightarrow{j} Y)$ is admissible: its pushout square has maps $\text{id}_X, j, j, \text{id}_Y$ in **Exec**. Its canonical link is isomorphic to e as a pointed extension. Closure under canonicalization therefore places the link in $\mathcal{E}_X$, and the code in $\mathcal{C}_X$. The fixed effective object maps of L_X and D_X give constants

$$K_U(L_X c | X) \leq K_U(c | X) + b_1, \quad K_U(D_X e | X) \leq K_U(e | X) + b_2.$$

The first inequality is Proposition 5.1; the second comes from the fixed construction of a degenerate attachment. By Theorem 3.4, $L_X D_X e \cong e$ under X , and invariance under pointed isomorphism preserves its loss. Apply the two complexity bounds to the feasible sets and then to the scalar objectives. The four claimed inequalities follow. $\square$

The converse is allowed to use degenerate cells, and this is essential. It says that an unrestricted attachment language has no more inductive bias than the extension class itself, except for constants introduced by coding. A restricted grammar of primitive cells can express a genuine preference for modularity. In that case the converse inequalities may fail, though the forward bounds supplied by the linker survive.

6.4 Machine dependence and computable proxies

Proposition 6.4 (Invariance). *Hold $\mathcal{E}_X$ and L_D fixed, and let U and V be optimal universal prefix machines. There is a nonnegative integer c such that, for all $D, X, \alpha \in \mathbb{N}$, finite $r \geq 0$, and $\lambda > 0$,*

$$\begin{aligned} H_{D,X}^U(\alpha + c) &\leq H_{D,X}^V(\alpha), & H_{D,X}^V(\alpha + c) &\leq H_{D,X}^U(\alpha), \\ C_{D,X}^U(r) &\leq C_{D,X}^V(r) + c, & C_{D,X}^V(r) &\leq C_{D,X}^U(r) + c, \end{aligned}$$

and, whenever the scalar optima are finite,

$$|\Phi_{D,X}^U(\lambda) - \Phi_{D,X}^V(\lambda)| \leq \lambda c.$$

Proof. The invariance theorem supplies a constant c for which $|K_U(e \mid X) - K_V(e \mid X)| \leq c$, uniformly in e and X . Insert this bound into the constraints defining the two profiles to obtain the first four inequalities. Insert it into the scalar objectives and take infima to obtain the last. $\square$

The invariance constant does not make a choice from finite data canonical. A selector that can actually be run must still fix a machine, or at least a computable prefix code. Let $\mathcal{C}_X^{\text{code}}$ be a declared family of valid codes with one uniform prefix decoder, and let $\ell(c \mid X)$ be the explicit code length. It may minimize

$$L_D(\text{Link}(X, c)) + \lambda \ell(c \mid X), \quad c \in \mathcal{C}_X^{\text{code}}.$$

If the list of codes is explicit and finite, the linker is total, and the loss is total and rational valued, exhaustive evaluation decides the minimum. For general computable reals one may obtain only certified intervals, unless a gap separating the candidates is known. With an enumerable family or partial execution, a search that may be stopped at any time cannot in general certify that its current answer is globally best.

An explicit code length bounds the prefix complexity of the linked extension, up to the constant cost of its decoder. But it scores derivations, not isomorphism classes. Several distinct codes may produce the same extension, and their multiplicity changes the induced prior. Without further assumptions, one therefore gets no general guarantee of approximation to the ideal Kolmogorov frontier.

7 Conclusion

An admissible pushout along a monic boundary keeps the base intact and recovers the interface as the exact place where old and new syntax meet. The attachment reflection organizes these pushouts into a functor: pointed cofibration extensions sit reflectively inside attachment spans, and finite coproducts describe modules linked in parallel. Semantic exactness is the extra condition that carries monicity from syntax into behavior. Effective linking and the fully faithful construction of degenerate attachments translate codes in both directions. Unrestricted attachment codes and

extension codes thus trace the same profiles of loss against complexity, up to uniform additive constants, while the scalar envelope turns those profiles into a regularized choice.

The construction is deliberately conditional. For a concrete executable language, one must still prove that the chosen pushouts are admissible and that the semantics is exact, or at least conservative in the required sense. A meaningful preference for modularity also demands a restricted grammar of primitive cells, one that excludes the degenerate attachments in the image of D_X . Those two tasks are where the character of a particular language, and the substance of a particular model-selection argument, finally enter.

References

- [1] John C. Baez and Kenny Courser. Structured cospans. *Theory and Applications of Categories*, 35(48):1771–1822, 2020. <https://www.tac.mta.ca/tac/volumes/35/48/35-48abs.html>.
- [2] Andrey N. Kolmogorov. Three approaches to the quantitative definition of information. *Problems of Information Transmission*, 1:1–7, 1965.
- [3] Stephen Lack and Paweł Sobociński. Adhesive and quasiadhesive categories. *RAIRO—Theoretical Informatics and Applications*, 39:511–545, 2005. <https://doi.org/10.1051/ita:2005028>.
- [4] Stephen Lack and Paweł Sobociński. Toposes are adhesive. In *Graph Transformations*, volume 4178 of *Lecture Notes in Computer Science*, pages 184–198. Springer, 2006. https://doi.org/10.1007/11841883_14.
- [5] Ming Li and Paul Vitányi. *An Introduction to Kolmogorov Complexity and Its Applications*. Springer, 3 edition, 2008.
- [6] Jorma Rissanen. Modeling by shortest data description. *Automatica*, 14:465–471, 1978. [https://doi.org/10.1016/0005-1098\(78\)90005-5](https://doi.org/10.1016/0005-1098(78)90005-5).
- [7] Jürgen Schmidhuber. Curious model-building control systems. In *Proceedings of the International Joint Conference on Neural Networks*, volume 2, pages 1458–1463, 1991. <https://doi.org/10.1109/IJCNN.1991.170605>.
- [8] Jürgen Schmidhuber. Optimal ordered problem solver. *Machine Learning*, 54:211–254, 2004. <https://doi.org/10.1023/B:MACH.0000015880.99707.b2>.
- [9] Bas R. Steunebrink, Jan Koutník, Kristinn R. Thórisson, Eric Nivel, and Jürgen Schmidhuber. Resource-bounded machines are motivated to be effective, efficient, and curious. In *Artificial General Intelligence*, volume 7999 of *Lecture Notes in Computer Science*, pages 119–129. Springer, 2013. https://doi.org/10.1007/978-3-642-39521-5_13.
- [10] Nikolai K. Vereshchagin and Paul M. B. Vitányi. Kolmogorov’s structure functions and model selection. *IEEE Transactions on Information Theory*, 50:3265–3290, 2004. <https://doi.org/10.1109/TIT.2004.838346>.
- [11] Nikolai K. Vereshchagin and Paul M. B. Vitányi. Rate distortion and denoising of individual data using Kolmogorov complexity. *IEEE Transactions on Information Theory*, 56:3438–3454, 2010. <https://doi.org/10.1109/TIT.2010.2048491>.