Adding L121 to the complete A input boundary

Full manuscripts and complete file inventories

The primary coordinate remains calibrated selected PDF text, NFC, characters excluding whitespace. This document records inputs; it calculates no factor. All five units, both Unicode normalizations and the raw complete, raw selected and calibrated selected variants remain available.

The boundary contains nine complete sources (131 pages), the whole unchanged common paper (23 pages), all nine complete applications (56 pages), and the three old program appendices (30 pages): 22 PDFs and 240 physical pages. Title, abstract, proof text, references, addresses and extractable figure labels are included. Selected text removes only exact running furniture.

Source	Pages	Characters	Application	Pages	Characters
L032	8	16,558	A1	4	8,228
L034	11	21,433	A2	3	5,801
F016	19	43,983	A3	6	15,436
F013	11	25,562	A4	3	6,241
L035	22	51,019	A5	6	14,514
N009	22	36,824	A6	11	28,130
L128	9	18,424	A7	3	8,825
L012	17	32,767	A8	9	23,401
L121	12	27,367	A9	11	25,549
Whole common paper, U				23	66,140

All 600 earlier PDF cells and 300 earlier raw-file cells are preserved exactly. The two new PDFs add 60 cells and fifteen complete files add 150 cells, giving 660 PDF cells and 450 raw-file cells. A cell is one metric, normalization and selection coordinate; these are not counts of papers or results.

Any later whole written comparison pays all of U and all nine applications. Any later individual comparison assumes the whole common paper and the declared required computational/data and retained mathematical premises have already been acquired. L121 uses no sibling application as a premise. These acquisition conditions do not make the program or external-proof cost zero.

Complete raw inventory	Files	Exact bytes
Required programs/data	20	105,850
Old auxiliaries	3	18,741
Operational runners	6	28,439
Partial formal files	16	100,644

The nine new required files are eight complete programs and `model_data.json`; `cubic_relation/check.py` is a required coordinate calculation. Four other new runners are operational. All 45 contents differ, so there is no within-topic duplicate-content discount.

The old appendices represent only the eleven old computational files. No printed appendix represents the entire enlarged required collection. There is no complete printed-code factor and no software-inclusive factor. Historical source software, including L121's Magma work, remains unpriced.

The two new PDF sensitivities

PDF	Selection	Norm.	Tokens	Alphanum.	Nonspace	Collapsed	UTF-8
L121	raw, complete	NFC	5,990	6,745	27,911	33,900	35,689
L121	raw, complete	NFKC	5,998	6,745	27,991	33,988	35,627
L121	raw, selected	NFC	5,893	6,643	27,367	33,259	35,048
L121	raw, selected	NFKC	5,901	6,643	27,447	33,347	34,986
L121	calibrated	NFC	5,893	6,643	27,367	33,259	35,052
L121	calibrated	NFKC	5,901	6,643	27,447	33,347	34,986
A9	raw, complete	NFC	4,902	5,472	25,562	30,463	30,976
A9	raw, complete	NFKC	4,905	5,472	25,562	30,466	30,979
A9	raw, selected	NFC	4,891	5,461	25,549	30,439	30,952
A9	raw, selected	NFKC	4,894	5,461	25,549	30,442	30,955
A9	calibrated	NFC	4,891	5,455	25,549	30,439	31,032
A9	calibrated	NFKC	4,894	5,455	25,549	30,442	30,971

"Tokens" counts whitespace-separated tokens. "Alphanum." counts maximal Unicode letter/number runs. "Nonspace" counts characters excluding whitespace. The last two columns count characters and UTF-8 bytes after whitespace collapse. Full exact text hashes accompany the numerical vectors.

The new source is the retained twelve-page author PDF of *Two families of locally toroidal regular 4-hypertopes arising from toroids*, by Fernandes, Leemans, Piedade and Ivić Weiss. Its complete eleven-page application is *Period lattices and locally toroidal hypertopes*. Both entire PDFs were freshly inspected for running furniture, formula extraction and executable listings. Neither contains an executable listing; no new code mask is applied. Mathematical algorithm prose, presentation relators and software references remain.

The actual-font audit reconciles 36 Type1 font dictionaries and 871 encoded glyph classes. Eighty-eight exceptional classes were viewed as embedded outlines. There are 18 source and 51 application repair occurrences, in 17 classes. Each binds its exact dictionary, encoding, byte, text event, page and context. Six source private-use bracket pieces become their visible Unicode bracket components. Printable sum, brace, script-letter and blackboard-letter aliases are repaired locally. The mapsto tail remains a separate component from its adjacent arrow. Ordinary ligatures and printed line hyphens are preserved; NFKC is a separate sensitivity.

The source's vector diagrams on pages 5–7 retain extracted labels. Their edges, layout and geometric content are not priced. All earlier limitations, including L035's raster material, remain explicit. This is extracted text, not a complete visible-text or graphic-cost claim. No source PDF, primary body text, font stream or raster is distributed in the input packet.

The accepted corrected L121 contract has 27 source dispositions; the previous 102 dispositions remain unchanged. They do not create extra originals or question credit. The six new Lean declarations establish countermodel relations and two nonconsequences only; they do not formalize the group orders, infinite families or geometry. Earlier partial-formal scopes are unchanged.

The scientific acceptance chain and fixed precount protocol are bound separately from the completed input report. Independent input acceptance is a separate step before numerical comparison. The preserved precount policy records that no new counts had been evaluated at its earlier freeze; the additive completion receipt records the present count stage.