PCA_Day01

March 3, 2026

1 Name : H.K. Sashika Chamindi

2 Day : Monday

3 Date : 2026.03.02

4 Topic : PCA (Principal Component Analysis) for Visualization

5 How to Convert 2D Array to 1D

[1]:
```
# import necerssary libraries
%matplotlib inline
import numpy as np
import matplotlib.pyplot as plt
```

[2]:
```
# Create dataset as a NumPy array
# Each row represents a student
# Column 1 = Maths Marks
# Column 2 = Science Marks
data = np.array([[40, 20],
                 [55, 30],
                 [70, 60],
                 [50, 35],
                 [45, 40],
                 [62, 75],
                 [45, 30],
                 [68, 80],
                 [80, 70],
                 [75, 90]])
```

[3]:
```
# Plot the original data points
# X-axis = Maths Marks
# Y-axis = Science Marks
from matplotlib.pyplot import figure
figure(figsize=(8, 6), dpi=80)
plt.scatter(data[:, 0], data[:, 1])
plt.xlabel("Maths Marks")
```

```
plt.ylabel("Science Marks")
plt.title("Original Data")
plt.show()
```



[4]:
```
# ----------------------------------
# STANDARDIZATION (Feature Scaling)
# ----------------------------------

from sklearn.preprocessing import StandardScaler

# Create scaler object
scaler = StandardScaler()

# Fit and transform the data
# This converts data to mean = 0 and standard deviation = 1
scaled_data = scaler.fit_transform(data)

# Print scaled data
print(scaled_data)
```

```
[[-1.43299332 -1.39951173]
 [-0.3016828  -0.97541727]
 [ 0.82962771  0.29686613]
 [-0.67878631 -0.76337004]
 [-1.05588981 -0.5513228 ]
 [ 0.2262621   0.93300782]
 [-1.05588981 -0.97541727]
 [ 0.67878631  1.14505506]
 [ 1.58383472  0.72096059]
 [ 1.20673122  1.56914952]]
```

[5]:
```
# Plot scaled data
plt.scatter(scaled_data[:, 0], scaled_data[:, 1])
plt.xlabel("Scaled Maths Marks")
plt.ylabel("Scaled Science Marks")
plt.title("Scaled Data")
plt.show()
```



[6]:
```
# ------------------------------------
# PCA (Principal Component Analysis)
```

```
# -----------------------------------

from sklearn.decomposition import PCA
```

[11]:
```
# Create PCA object with 2 components
# (Same as original dimension, just to check variance)
pca = PCA(n_components=2)
```

[12]:
```
# Fit PCA on scaled data
pca.fit(scaled_data)
```

[12]:
```
PCA(n_components=2)
```

[13]:
```
# Check variance captured by each principal component
print("Explained Variance:", pca.explained_variance_)
print("Explained Variance Ratio:", pca.explained_variance_ratio_)
```

```
Explained Variance: [2.07778406 0.14443817]
Explained Variance Ratio: [0.93500282 0.06499718]
```

[14]:
```
# Here we can see that first component captures ~94% variance
```

[20]:
```
# Now reduce dimension from 2D → 1D
pca = PCA(n_components=1)
pca.fit(scaled_data)
```

[20]:
```
PCA(n_components=1)
```

[22]:
```
# Check variance captured by principal component
print("Explained Variance:", pca.explained_variance_)
print("Explained Variance Ratio:", pca.explained_variance_ratio_)
```

```
Explained Variance: [2.07778406]
Explained Variance Ratio: [0.93500282]
```

[23]:
```
# Transform data into 1 principal component
pca_scaled_data = pca.transform(scaled_data)
```

[27]:
```
# Dimensions of the scaled data (rows,columns)
scaled_data.shape
```

[27]:
```
(10, 2)
```

[28]:
```
# Dimensions of scaled data after using PCA (rows,columns)
pca_scaled_data.shape
```

[28]:
```
(10, 1)
```

[31]:
```
# ------------------------------------
# Reconstructing Data
# ------------------------------------

# Convert 1D data back to 2D approximation
# (This is an approximate reconstruction)
pca_scaled_data = pca.inverse_transform(pca_scaled_data)
```

[32]:
```
# scaled data (light color)
plt.scatter(scaled_data[:, 0], scaled_data[:, 1], alpha=0.2)

# Reconstructed data (after PCA)
plt.scatter(pca_scaled_data[:, 0], pca_scaled_data[:, 1])
```

[32]:
```
<matplotlib.collections.PathCollection at 0x27365d8d950>
```



5.1 Visualizing and Reducing the Number of Dimensions in a High-Dimensional Dataset Using PCA

[35]:
```
# Import the digits dataset from scikit-learn
from sklearn.datasets import load_digits

# Load the digits dataset
digits = load_digits()
```

[36]:
```
# Check the shape of the data
print(digits.data.shape)
```

```
(1797, 64)
```

[37]:
```
# Import matplotlib for plotting
import matplotlib.pyplot as plt

# Visualize the second digit image (index 1)
plt.matshow(digits.images[1])  # Show as a matrix/image
plt.show()  # Display the plot
```



[38]:
```
# Check the actual label of the second image
print(digits.target[1])  # Output: 1
```

1

[40]:
```
# Import matplotlib for plotting
import matplotlib.pyplot as plt

# Visualize the 34th digit image (index 33)
plt.matshow(digits.images[33])  # Show as a matrix/image
plt.show()  # Display the plot
```



[41]:
```
# Check the actual label of the 34th image
print(digits.target[33])  # Output: 5
```

5

[42]:
```
# Import PCA (Principal Component Analysis) from scikit-learn
from sklearn.decomposition import PCA

# Initialize PCA to reduce data from 64 dimensions to 2 dimensions
# This is useful for visualization
```

```python
pca = PCA(n_components=2)

# Fit PCA on the digits data and transform it into 2D
# digits.data has shape (1797, 64), new_data will have shape (1797, 2)
new_data = pca.fit_transform(digits.data)

# Print the original data shape (number of samples, number of features)
print(digits.data.shape)  # Output: (1797, 64)

# Print the transformed data shape (number of samples, 2 principal components)
print(new_data.shape)     # Output: (1797, 2)
```

```
(1797, 64)
(1797, 2)
```

[43]:
```python
# Import matplotlib for plotting
import matplotlib.pyplot as plt

# Create a scatter plot of the 2D PCA-transformed data
# new_data[:, 0] -> x-axis (Principal Component 1)
# new_data[:, 1] -> y-axis (Principal Component 2)
# c=digits.target -> color points based on their actual digit labels (0-9)
plt.scatter(new_data[:, 0], new_data[:, 1], c=digits.target, cmap='tab10',␣
 ↪alpha=0.7)

# Label the x-axis as 'PC 1' (Principal Component 1)
plt.xlabel('PC 1')

# Label the y-axis as 'PC 2' (Principal Component 2)
plt.ylabel('PC 2')

# Add a colorbar to show which color corresponds to which digit
plt.colorbar(label='Digit Label')

# Display the plot
plt.show()
```



5.2 PCA for speedup models

[44]:
```
from sklearn.datasets import load_digits
import numpy as np
```

[45]:
```
digits = load_digits()
digits.data.shape
```

[45]: (1797, 64)

[46]:
```
# Import StandardScaler for feature scaling
from sklearn.preprocessing import StandardScaler

# Initialize the scaler
sc = StandardScaler()

# Scale the data: mean = 0, variance = 1
new_data = sc.fit_transform(digits.data)
```

[48]:
```
# divide dataset into training and testing set
from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(new_data, digits.target,␣
↪test_size=0.2, random_state=42)
```

[49]:
```
x_train.shape
```

[49]: (1437, 64)

[50]:
```
x_test.shape
```

[50]: (360, 64)

[56]:
```
# Import Logistic Regression from scikit-learn
from sklearn.linear_model import LogisticRegression

# Initialize the model
# solver='lbfgs' is good for small datasets, max_iter=1000 ensures convergence
model = LogisticRegression(solver='lbfgs', max_iter=1000)

# Import time module to measure training time
import time

# Record start time
start = time.time()

# Train the model on training data
model.fit(x_train, y_train)

# Record end time
end = time.time()

# Print the training time in milliseconds
print('Time: ' + str((end - start)*1000) + ' ms')
```

```
Time: 62.317848205566406 ms
```

[57]:
```
from sklearn.metrics import accuracy_score
y_pred = model.predict(x_test)
accuracy_score(y_test, y_pred)
```

[57]: 0.9722222222222222

[58]:
```
from sklearn.decomposition import PCA
pca = PCA(n_components=10)
new_data_pca = pca.fit_transform(new_data)
```

[59]:
```
new_data_pca.shape
```

[59]: (1797, 10)

[60]:
```
from sklearn.model_selection import train_test_split
x_train, x_test, y_train, y_test = train_test_split(new_data_pca, digits.
↪target, test_size=0.2, random_state=42)
```

[61]:
```
x_train.shape
```

[61]: (1437, 10)

[62]:
```
x_test.shape
```

[62]: (360, 10)

[64]:
```
# import logistic regression to train the model
from sklearn.linear_model import LogisticRegression
model = LogisticRegression(solver='lbfgs', max_iter=1000)
```

[84]:
```
# calculate time
import time
start = time.time()
model.fit(x_train, y_train)
end = time.time()

print('Time: ' + str((end - start)*1000) + ' ms')
```

```
Time: 43.21026802062988 ms
```

[85]:
```
from sklearn.metrics import accuracy_score
y_pred = model.predict(x_test)
accuracy_score(y_test, y_pred)
```

[85]: 0.8972222222222223

[ ]:
```

```