

# Mockito

**“Code with Passion!”**



# Topics

- What is & Why Mockito?
- How to use mocking?
- Mockito APIs

# What is & Why Mockito?

# What is & Why Mockito?

- Mockito is a mocking framework
  - > It lets you write tests with clean & simple API
  - > Mockito tests are very readable and they produce clean verification errors
- Use Mockito to get "smart" fake implementations of classes or interfaces out of your reach
- "We decided during the main conference that we should use JUnit and Mockito because we think they are the future of TDD and mocking in Java"
  - > - Dan North, the originator of BDD



# How to use Mocking?

# Classical 3A Test

```
@Test  
public void test() throws Exception {  
  
    // Arrange  
  
    // Act  
  
    // Assert  
  
}
```

# Classical 3A Test without Dependency

```
@Test
public void test() throws Exception {

    // Arrange
    Testee testee = new Testee();

    // Act
    actualResult = testee.doSomething();

    // Assert
    assertTrue(expectedResult, actualResult);

}
```

## 3A Test with a Dependency (using Mockito)

@Test

public void test() throws Exception {

// Arrange, prepare behaviour

Testee testee = new Testee();

Dependency aMock = mock(Dependency.class); // Or use @Mock

when(aMock.someMethod()).thenReturn(someObject);

// Act

actualResult = testee.doSomething();

// Assert – verify result and mock object behavior

assertTrue(expectedResult, actualResult);

verify(aMock).someMethod(someObject);

}

1. Create a mock

2. Train a mock

3. Verify a mock



# How to Use Mockito?

# Mocking API

- For creating Mock object
  - > @Mock or mock(Dependency.class)
  - > @Spy
- For injecting Mock object to the target class
  - > @InjectMocks
- For extending
  - > @ExtendWith(MockitoExtension.class)
- > For training Mocks
  - > when(methodCall).thenReturn(returnValue);
  - > when(methodCall).thenThrow(Throwable)
- For verification
  - > verify(mock, times(1)).methodCall();

# Example

```
@ExtendWith(MockitoExtension.class)
public class PersonTest {

    @Mock
    private Address address;

    @InjectMocks
    private Person person;

    @Before
    public void setup() throws Exception {
        person = new Person();
        MockitoAnnotations.initMocks(this);
    }

    @Test public void
    should_return_complete_info_including_address() throws Exception {
        when(address.retrieveAddressInfo()).thenReturn("USA Cambridge");
        assertThat(person.retrievePersonInfo(), is("Sang Shin USA Cambridge"));
        verify(address, times(1)).retrieveAddressInfo();
    }
}
```

# Lab:

**Exercise 1: Mockito**  
**1653\_tdd\_mockito.zip**



**Code with Passion!**

