Ajax Support in Spring MVC

"Code with Passion!"




Ajax Support in Spring 3

- Ajax remoting with JSON is provided as part of Spring MVC 3
 - > Generating JSON responses
 - > Binding JSON requests using the Spring MVC @Controller programming model.
- Use of jQuery or Dojo JavaScript libraries

Sending Ajax Request to the Server

```
$(document).ready(function() {
     // check name availability on focus lost
     $('#name').blur(function() {
          if ($('#name').val()) {
                checkAvailability();
     });
});
// Ask the server using Ajax call if the name you just entered is available.
// If it is not, an error message will be displayed and the form will
// remain disabled until you enter a name that is available.
function checkAvailability() {
   // Ask for data from the server in the JSON format
  $.getJSON("account/availability", // URL
        { name: $('#name').val() }, // data to be sent
        function(availability) { // callback function
           if (availability.available) {
                fieldValidated("name", { valid : true });
           } else {
                fieldValidated("name", { valid : false,
            message: $('#name').val() + " is not available, try " + availability.suggestions });
```

Http Request



Server-side Code that generates JSON Response

```
// Handle "/account/availability" Ajax request.
@RequestMapping(value="/availability", method=RequestMethod.GET)
// The "@ResponseBody" annotation instructs Spring MVC to serialize the
// "AvailabilityStatus" to the client. Spring MVC automatically serializes
// to JSON because that is the format client requested through .getJSON(..)
// jQuery method.
public @ResponseBody AvailabilityStatus getAvailability(@RequestParam String name) {
    for (Account a : accounts.values()) {
        if (a.getName().equals(name)) {
            return AvailabilityStatus.notAvailable(name);
        }
    }
    return AvailabilityStatus.available();
}
```

Sending JSON Ajax Request to Server

```
$(document).ready(function() {
  // check name availability on focus lost
  $('#name').blur(function() {
     if ($('#name').val()) {
    checkAvailability();
  // submit the form data in JSON format
  $("#account").submit(function() {
     var account = $(this).serializeObject();
     $.postJSON("account",
                                                     // URL
          account.
                                                                // data
          function(data) {
                                                     // callback function
             // set the "#assignedId" field with the "data.id"
             $("#assignedId").val(data.id);
             showPopup();
     return false:
```

Server-side Code that Handles POST

```
// @RequestBody annotation instructs Spring MVC to map the body of the HTTP request
// to an Account object. Spring MVC knows to map from JSON because the client set
// the request Content Type to application/json through .getJSON(..) jQuery method.
@RequestMapping(method=RequestMethod.POST)
public @ResponseBody Map<String, ? extends Object> create(@RequestBody Account account,
HttpServletResponse response) {
     // Validates the Account object. If there are validation errors,
     // a HTTP 400 is returned with the error messages, otherwise a HTTP
     // 200 is returned with the assigned account ID.
     Set<ConstraintViolation<Account>> failures = validator.validate(account);
     // If there are validation error, send HTTP 400 along with
     // validation error messages.
     if (!failures.isEmpty()) {
          response.setStatus(HttpServletResponse.SC_BAD_REQUEST);
          return validationMessages(failures);
     // If no validation error, add the account the accounts map
     // and send an account id back to the client.
     else {
          accounts.put(account.assignId(), account);
          return Collections.singletonMap("id", account.getId());
```



Code with Passion!

