



Day 8: Dictionaries and Maps ☆

by Shafaet

[Problem](#)[Submissions](#)[Leaderboard](#)[Discussions](#)[Editorial](#)[Tutorial](#)

Objective

Today, we're learning about Key-Value pair mappings using a *Map* or *Dictionary* data structure. Check out the [Tutorial](#) tab for learning materials and an instructional video!

Task

Given n names and phone numbers, assemble a phone book that maps friends' names to their respective phone numbers. You will then be given an unknown number of names to query your phone book for. For each *name* queried, print the associated entry from your phone book on a new line in the form `name=phoneNumber`; if an entry for *name* is not found, print `Not found` instead.

Note: Your phone book should be a Dictionary/Map/HashMap data structure.

Input Format

The first line contains an integer, n , denoting the number of entries in the phone book.

Each of the n subsequent lines describes an entry in the form of 2 space-separated values on a single line. The first value is a friend's name, and the second value is an 8-digit phone number.

After the n lines of phone book entries, there are *an unknown number of lines of queries*. Each line (query) contains a *name* to look up, and you must continue reading lines until there is no more input.

Note: Names consist of lowercase English alphabetic letters and are *first names* only.

Constraints

- $1 \leq n \leq 10^5$
- $1 \leq \text{queries} \leq 10^5$

Output Format

On a new line for each query, print `Not found` if the name has no corresponding entry in the phone book; otherwise, print the full *name* and *phoneNumber* in the format `name=phoneNumber`.

Sample Input

```
3
sam 99912222
tom 11122222
harry 12299933
sam
edward
harry
```

Sample Output

```
sam=99912222
Not found
harry=12299933
```

Explanation

We add the following $n = 3$ (Key,Value) pairs to our map so it looks like this:

phoneBook = {(sam, 99912222), (tom, 11122222), (harry, 12299933)}

We then process each query and print key=value if the queried **key** is found in the map; otherwise, we print Not found.

Query 0: sam

Sam is one of the keys in our dictionary, so we print sam=99912222.

Query 1: edward

Edward is not one of the keys in our dictionary, so we print Not found.

Query 2: harry

Harry is one of the keys in our dictionary, so we print harry=12299933.

Easy

Submitted 110085 times
Max Score **30**

Need Help?

[View Tutorial](#)[View Discussions](#)[View Editorial Solution](#)[View Top Submissions](#)

Rate This Challenge:

[Download problem statement](#)[Download sample test cases](#)[Suggest Edits](#)

Current Buffer (saved locally, editable)

Java 8



```
1 //Complete this code or write your own from scratch
2 import java.util.*;
3 import java.io.*;
4
5 class Solution {
6     public static void main(String[] argh) {
7         Scanner in = new Scanner(System.in);
8         int n = in.nextInt();
9         Map<String, Integer> fonebook = new HashMap<>();
10        for (int i = 0; i < n; i++) {
11            String name = in.next();
12            int phone = in.nextInt();
13            // Write code here
14            fonebook.put(name, phone);
15        }
16        while (in.hasNext()) {
17            String s = in.next();
18            // Write code here
19            if (fonebook.get(s) != null) {
```