AI SIGN LANGUAGE TRANSLATOR

A Project Report submitted

Partial Fulfilment of the Requirements

For the Degree of

Bachelor of Technology

In

Artificial Intelligence and Data Sciences

By

Sarnala Sasidhar (2303031241478)

Adabala Likitha Naidu (2303031240173)

Mamidi Jaya Prakash (2303031240621)

Mudavath Charan Tej (2303031240659)

Under the Guidance of

Ms. Binisha Makwana



to

Artificial Intelligence and Data Science Department

Parul University , Vadodara

April 2026

UNDERTAKING

We declare that the work presented in this project report, entitled "**Ai Sing Language Translator**", submitted to the Artificial Intelligence and Data Sciences Department, Parul University, Vadodara, for the award of the Bachelor of Technology degree in Artificial Intelligence and Data Sciences, is our original work. We have not plagiarised or submitted the same work for the award of any other degree. In case this undertaking is found incorrect, we accept that our degree may be unconditionally withdrawn.

April, 2026

Vadodara

Sarnala Sasidhar (2303031241478): ----------

Adabala Likitha Naidu (2303031240173): ----------

Mamidi Jaya Prakash (2303031240621): ----------

Mudavath Charan Tej (2303031240659)**: ----------**



CERTIFICATE

This is to certify that the work contained in this project report entitled "**Ai Sign Language Translator**", by the following students bearing the respective Enrollment numbers.

Sarnala Sasidhar (2303031241478)

Adabala Likitha Naidu (2303031240173)

Mamidi Jaya Prakash (2303031240621)

Mudavath Charan Tej (2303031240659)

This is also certified that this work is submitted for partial fulfilment of the degree of Bachelor of Technology in Artificial Intelligence and Data Sciences from Parul University, Vadodara, under my supervision from January 2026 to April 2026, and to the best of my knowledge, has not been submitted elsewhere for any degree.

Therefore, I deem this work fit and recommend it for submission for the award of the aforesaid degree.

April, 2026

Vadodara

Lect. Binisha Makwana,

Professor and Project Guide,

AIDS Department, Parul University, Vadodara,

Synopsis

The **"AI Sign Language Translator"** is an intelligent system designed to convert hand gestures used in sign language into readable text or audible speech. This project aims to bridge the communication gap between people with hearing or speech impairments and those who do not understand sign language.

The system is built using **"Python"** as the core programming language due to its simplicity and strong support for AI and computer vision libraries. It uses **"MediaPipe"**, a powerful framework developed by Google, to detect and track hand landmarks in real-time through a webcam. MediaPipe identifies key points on the hand such as fingers and joints, enabling accurate gesture recognition.

For the learning and prediction part, the project uses **"TensorFlow",** a widely used deep learning framework. TensorFlow helps in training a model using a dataset of different hand gestures corresponding to alphabets or words. Once trained, the model can classify new gestures captured by the camera.

The workflow involves capturing hand gestures via a webcam, extracting features using MediaPipe, and passing them into a TensorFlow model for classification. The output is then displayed as text or converted into speech, enabling real-time communication.

This system is efficient, cost-effective, and can be expanded to support multiple sign languages. It demonstrates the practical application of artificial intelligence in accessibility and inclusive communication.

To ensure easy deployment and consistency across different systems, the entire application is containerized using **"Docker"**. Docker packages the application along with all its dependencies, such as Python libraries, TensorFlow, and MediaPipe, into a single container. This eliminates issues related to environment setup and allows the project to run on any system that supports Docker. It also simplifies sharing, testing, and scaling the application.

Acknowledgements

We would like to express our gratitude to our supervisor, **Lect. Binisha Makwana**, who is a Professor in the Artificial Intelligence and Data Science Department at Parul University, Vadodara, for his advice, encouragement, enduring patience and constant support to me.

We are greatly indebted to all the faculty members of the Artificial Intelligence and Data Science Department of Parul University for their valuable input and for helping us understand theories and models along the bachelor's program.

We would like to express our sincere appreciation and gratitude to all our classmates for their encouragement, consistent support and invaluable suggestions at the time when needed. We remain grateful to all who directly or indirectly helped us at different stages of our project work.

With deep appreciation, we recognise the invaluable contributions of all individuals and entities mentioned above, without whom the successful completion of this project would not have been possible.

Sarnala Sasidhar (2303031241478)

Adabala Likitha Naidu (2303031240173)

Mamidi Jaya Prakash (2303031240621)

Mudavath Charan Tej (2303031240659)

Contents

Chapter 1: Introduction…….8

Brief about the domain…….. 8

Problem Statement…… 9

Project motivation and relevance…….. 10

Scope……. 11

Objective(s)……... 13

Key features and expected outcomes…… 14

Chapter 2: Literature Survey……15

Review of Recent Ai Sign Language Translator…….15

LSTM-Based Gesture Recognizer……...17

YOLOv5+Media Pipe Real-Time Translator…….18

Chapter 3: Analysis / SRS……..21

- Purpose of the project……21
- Intended users and product scope……..23
- Functional and non-functional requirements……. 24
- User interface and hardware/software requirements…….25
- List of references used in analysis…… 26

Chapter 4: System Design……...31

- System architecture (client-server, etc.) ……31
- Design diagrams: Use Case, Class, Sequence (as required) ……..36
- User interface design approach……...37
- Security, performance, and integration aspects……..39

Chapter 5: Methodology…….43

- Development approach (Agile, Waterfall, etc.) ……43
- Design thinking or user-centric principles…….44
- Technology stack selection……44
- Quality assurance and testing strategies……46
- Tools for collaboration (Trello, GitHub, etc.) ……..47
- Include a Gantt Chart for project timeline…….48

Chapter 6: Implementation……49

- Backend and frontend implementation summary……..49
- Tools, APIs, and platforms used……51
- Code snippets (optional)……52
- Screenshots of UI, features like BMI calculation, chat interface……..57
- Flowcharts for logic implementation…….63

Chapter 7: Testing……64

- Unit testing (frontend/backend logic) ……64
- Test cases used for validation…….65
- External validation comparison (e.g., BMI calculators) ……68
- Performance/load testing…….69
- Screenshots and outcome discussion……...70

Chapter 8: Conclusion and Future Work……72

- Summary of what has been achieved…….72
- Limitations…….73
- How objectives were fulfilled……73
- Overview Table (project goals vs. accomplishments) ……77
- Enhancements and additional modules……...79
- Possible integration with other tools……...80

Reference……..…81-82

Chapter 1

Introduction

❖ Background and Domain Overview

The **"AI Sign Language Translator"** project belongs to the domain of "Artificial Intelligence (AI)", specifically combining "Computer Vision" and "Machine Learning". This domain focuses on enabling machines to interpret human gestures and visual inputs, making it highly relevant for accessibility and assistive technology applications.

In this project, computer vision techniques are used to capture and analyze hand gestures through a webcam. Tools like "MediaPipe" help in detecting hand landmarks such as finger positions and movements in real time. These visual features are then processed using machine learning models built with "TensorFlow", which classify gestures into meaningful outputs like alphabets, words, or sentences.

The project also falls under the "Human-Computer Interaction (HCI)" domain, as it creates an interface that allows humans to communicate with computers using natural hand gestures. Additionally, it contributes to the "Assistive Technology" domain by providing solutions that support individuals with hearing or speech impairments.

To enhance portability and deployment, the project is showcased using "Docker". Docker ensures that the entire application—including code, libraries, and dependencies—runs consistently across different environments without setup issues. This makes the project easy to deploy, demonstrate, and scale.

❖ Problem Statement

Communication between individuals who use sign language and those who do not understand it remains a significant challenge in daily life. People with hearing or speech impairments often face difficulties in expressing their thoughts, needs, and emotions, especially in environments where interpreters are not available. This communication gap can lead to social isolation, limited access to education, healthcare, and employment opportunities.

Traditional methods of communication, such as written text or human interpreters, are not always efficient, accessible, or available in real time. There is a need for an automated, accurate, and real-time system that can recognize sign language gestures and translate them into understandable text or speech.

The problem is to design and develop an intelligent system using **"MediaPipe"** and **"TensorFlow"** that can detect hand gestures through a camera, process them using machine learning algorithms, and convert them into meaningful output. Additionally, the system should be easy to deploy and run across different platforms, which can be achieved using **"Docker".**

Therefore, the core problem is to create a reliable, real-time, and portable AI-based solution that bridges the communication gap between sign language users and non-sign language users, improving accessibility and inclusivity in society.

❖ Project Motivation and Relevance

“Project Motivation”

The motivation behind the **“AI Sign Language Translator”** project arises from the real-world communication challenges faced by individuals with hearing and speech impairments. Millions of people rely on sign language as their primary mode of communication, yet a large portion of society does not understand it. This creates a barrier in everyday interactions such as education, healthcare, workplaces, and social environments.

There is a strong need for a system that can interpret sign language in real time without requiring a human interpreter. With advancements in artificial intelligence and computer vision, technologies like **“MediaPipe”** enable accurate hand tracking, while **“TensorFlow”** allows machines to learn and recognize gesture patterns effectively. The motivation is to leverage these technologies to build a smart, automated, and accessible communication tool.

Additionally, deploying the system using **“Docker”** ensures that the application can be easily run on different systems without complex setup, making it practical for real-world use and demonstrations.

“Relevance of the Project”

This project is highly relevant in today’s world as it addresses the growing need for inclusive and assistive technologies. It aligns with the goals of digital accessibility by providing a solution that helps bridge the communication gap between sign language users and non-users.

The project is also relevant in the fields of “Artificial Intelligence, Computer Vision, and Human-Computer Interaction”, showcasing how modern technologies can solve social problems. It can be applied in various domains such as:

- **Education** :– helping students communicate with teachers and peers
- **Healthcare** :– enabling better patient-doctor communication
- **Public Services** :– improving accessibility in offices and institutions

Moreover, with the increasing adoption of containerization tools like Docker, the project demonstrates modern software deployment practices, making it scalable, portable, and industry-relevant.

❖ Scope

The AI Sign Language Translator project has a broad and impactful scope in the fields of “Artificial Intelligence”, “Computer Vision”, and “Human-Computer Interaction”. The system is designed to recognize hand gestures and convert them into understandable text or speech, enabling seamless communication between deaf/mute individuals and others.

1. Real-Time Gesture Recognition

The system can process live video input using a webcam and identify hand gestures instantly. This allows real-time translation of sign language into text or voice output, making conversations faster and more natural.

2. Multi-Language Support

The project can be expanded to support different sign languages such as American Sign Language (ASL), Indian Sign Language (ISL), and others. This increases its usability across different regions and cultures.

3. Integration with Applications

The translator can be integrated into:

- Mobile applications
- Web applications
- Smart devices

This enables accessibility in daily communication platforms like messaging apps and virtual assistants.

4. Assistive Technology

The project serves as an assistive tool for people with hearing or speech impairments, promoting inclusivity in:

- Education systems
- Workplaces
- Public services

5. Use of Advanced Technologies

The system leverages tools and frameworks like:

- TensorFlow for model training
- MediaPipe for hand tracking
- Python for implementation

This allows scalability and continuous improvement using machine learning models.

6. Deployment Using Containerization

Using Docker, the project can be easily deployed across different systems without compatibility issues. This ensures:

- Portability
- Easy installation
- Consistent performance

7. Future Enhancements Scope

The project can be further extended to include:

- Full sentence recognition instead of single gestures
- Voice output with natural speech
- AI-based emotion detection
- Integration with wearable devices

❖ Objectives

The main objective of this project is to develop an intelligent system using “Artificial Intelligence” and “Computer Vision” that can recognize sign language gestures and convert them into readable text or audible speech.

1. Real-Time Gesture Recognition

To design a system that can capture and recognize hand gestures in real time using a webcam and process them efficiently.

2. Accurate Translation

To achieve high accuracy in translating sign language gestures into text or speech using machine learning models trained with tools like TensorFlow.

3. Hand Tracking and Detection

To implement precise hand detection and tracking using frameworks such as MediaPipe for better gesture recognition.

4. Communication Enhancement

To bridge the communication gap between deaf/mute individuals and people who do not understand sign language.

5. User-Friendly Interface

To create a simple and interactive interface that allows users to easily interact with the system without technical knowledge.

6. Multi-Platform Deployment

To develop a system that can be deployed on multiple platforms (web, mobile, desktop) using technologies like Docker.

7. Scalability and Improvement

To build a scalable model that can be improved over time by adding more gestures, languages, and features.

8. Promote Inclusivity

To support inclusive communication and accessibility in education, workplaces, and daily life.

❖ Key Features and Expected Outcomes

Key Features	Expected Outcomes
Real-Time Gesture Recognition	Improved Communication
Hand Tracking & Detection (MediaPipe)	High Accuracy
Machine Learning Model (TensorFlow)	Real-Time Performance
Text & Speech Output	Increased Accessibility
User-Friendly Interface	Practical Application of *Machine Learning*
Multi-Language Support	Easy Deployment
Docker Deployment	Future Expansion
Scalability	

Chapter 2

Literature survey

❖ Review Of Recent Ai Sign Language Translator

➢ Transformer-based Sign2Text (Maia et al., 2025; Neurocomputing)

• **Citation**: Wesley F. Maia, António M. Lopes, Sergio A. David (2025). Automatic sign language to text translation using MediaPipe and transformer architectures. Neurocomputing.

• **Problem:** End-to-end sign-language translation (continuous video → natural language text). The goal is a sign-language-to-text (SLT) system, bridging deaf-hearing communication by translating videos of sign language into spoken-language sentences.

▪ **DATASETS**

• **PHOENIX14T (2014):** German sign language weather reports with gloss annotations. Contains ≈7.1k training, 519 dev, 642 test sequences (German sign glosses aligned to German and English text). Each gloss sequence averages ~38 signs.

• **How2Sign (2021):** English sign-language interpretations of How2 (video lecture) data. ≈47k segments (29k train, 5k dev, 5k test) without gloss annotations (only video + English subtitles).

• **Input**: RGB video preprocessed by MediaPipe Holistic/Hands/BodyPose. They extract 2D body-keypoints and hand-landmarks per frame (Normalized 3D coordinates of ~55 joints covering hands, body, face). Each frame becomes a vector of keypoint coordinates.

• **Preprocessing:** Normalization of keypoints (e.g. scale/translation invariance), plus data augmentation (random rotations, scaling, noise) on keypoints to improve robustness. They also use a convolutional embedding layer that treats the sequence of keypoints as a "channel" for convolution before the Transformer.

• **Model (Architecture):** A multi-stage Transformer.

• **Sign2Gloss:** A Transformer encoder–decoder takes the keypoint embeddings sequence and predicts a sequence of gloss tokens (sign labels). Key points are combined with positional encodings, and the model is trained with a Connectionist Temporal Classification (CTC) loss on gloss output to handle variable-length alignment.

• **Gloss2Text**: A fine-tuned BART (Bidirectional and Auto-Regressive Transformer) converts the gloss sequence into a grammatical target-language sentence (German or English). This uses standard cross-entropy loss on the text.

• **Sign2Gloss2Text (integrated):** End-to-end pipeline passing keypoints through Sign2Gloss then Gloss2Text. They also experimented with a direct Sign2Text bypass (no gloss), which performed poorly on How2Sign.

graph LR

Video[Video frames] -->|MediaPipe| Keypoints[Keypoint Sequence]

Keypoints -->|Transformer Encoder-Decoder + CTC| Gloss[Gloss Sequence]

Gloss -->|BART Transformer| Text[Translated Text]

Hyperparameters: The Transformer used ≈6–12 layers, multi-head attention (unspecified heads), hidden size ~512. BART was pretrained (400M tokens) then fine-tuned. Training used Adam optimizer; details are not public.

- Evaluation Metrics: Perplexity, Word Error Rate (WER), BLEU-4 score. They report BLEU-4 for text translation.

- **Results:**

- PHOENIX14T: Their Sign2Gloss2Text BLEU-4 is comparable to pixel-based baselines (~25–30 BLEU). (Exact numbers not given in preview, but said "competitive with marginal differences" to baselines.)

- How2Sign: Direct Sign2Text (no gloss) BLEU-4 was significantly lower, underscoring the need for gloss labels.

- **E.g.** glossary-based SLT of PHOENIX14T can reach BLEU-4 ≈30–35, whereas gloss-free How2Sign was much lower (difficult task).

- Strengths: First to use body/hand keypoints (MediaPipe) in SLT; avoids large video models. Gloss-based pipeline yields natural output. Competitive with state-of-the-art on PHOENIX14T

- **Limitations**

- Gloss dependency: Requires gloss annotations or dictionary (not available for all data). How2Sign (no gloss) results were poor.

- Domain: PHOENIX is a narrow domain (weather reports); model may not generalize to daily signs.

- Unidirectional: Only sign→text (no text→sign).

- Complexity: Transformers and BART are heavyweight (high compute, large models). Not real-time on typical hardware.

- Reproducibility: No public code or models provided. Implementation likely PyTorch/TensorFlow; compute needs are high (Transformer+BART). Data (PHOENIX14T, How2Sign) are publicly available.

Key Citation: "We employ fine-tuning of BART, a state-of-the-art transformer model… Evaluation on the PHOENIX14T dataset demonstrates … competitive performance, with BLEU-4 scores… On the How2Sign dataset… lower BLEU-4 scores, highlighting the limitations of gloss-free approaches.

❖ LSTM-based Gesture Recognizer (Utomo et al., 2025;JIWE)

- **Citation:** Wargijono Utomo et al. (2025). Indonesian Language Sign Detection using Mediapipe with LSTM Algorithm. Journal of Informatics and Web Engineering . DOI: 10.33093/jiwe.2025.

- **Problem:** Recognize isolated alphabetic/numeric signs in Indonesian Sign Language (ISL). Aimed to improve communication by converting sign gestures to text. This is a gesture recognition (not full sentence translation) system.

- **Datasets:** Custom collected.

- **36 classes:** 26 letters (A–Z) + 10 digits (0–9).

- **Data collection:** For each gesture, 25 video sequences (i.e. 25 separate recordings) were captured. Each sequence yields a series of frames.

- **Data split:** 80% training, 10% validation, 10% testing. (Exact numbers not given, but e.g. 25 sequences × 36 classes = 900 sequences total.)

- **Input:** RGB video frames. They use MediaPipe Hands to extract 21 hand-landmark coordinates per frame. (No full-body or face; just one or two hands.) Each frame yields a 42-dimensional vector (x,y) per landmark if 2D, or 63D if using 3D coords; this is fed sequentially to the model.

- **Preprocessing**: Probably normalization of landmark coordinates (centering, scaling). Sequences may be padded or truncated to fixed length for the LSTM. Not explicitly detailed in the abstract. Data augmentation was not mentioned (they suggest it for future work).

- **Model (Architecture):** A stacked LSTM network for sequential classification. The exact number of layers/units is not reported. Likely a few LSTM layers (e.g. 1–2 layers of 128–256 units) followed by a dense softmax. The model processes each sequence of hand-keypoint vectors and outputs one of 36 classes.

  - **Training:**

- **Loss:** Categorical Cross-Entropy.

- **Optimizer:** (Not specified; likely Adam).

- **Epochs/Batch:** (Not specified).

- **Hardware:** Not mentioned; dataset and model are small, so a single-GPU or even CPU would suffice.

- **Evaluation Metrics:** Accuracy, Precision, Recall, F1-score (macro and weighted). These are standard for classification.

  - **Results:**

- **Accuracy:** 97.1% on test set.

- **Precision/Recall/F1:** Macro-precision 97.0%, macro-recall 96.6%, macro-F1 96.4%; weighted-F1 97.0%.

- **Confusion:** All letters and digits were well recognized (matrix not shown here).
- This shows the LSTM+MediaPipe approach yields very high accuracy on isolated letters/digits.
    - **Strengths:**

• **Real-time capable:** Lightweight LSTM runs fast on live input (no mention of latency but such models typically process >30 FPS on modern CPU/GPU).

- **High accuracy:** Nearly 97%.
- **End-to-end pipeline:** From webcam to text (digit/letter) with no extra sensors.
- **Open datasets:** While they used own data, similar letter datasets exist (ASL alphabets, etc.).
    - **Limitations:**
- **Limited vocabulary:** Only 36 classes (letters/numbers); not words or sentences.
- **Static gestures:** Each sign is a static pose or short motion; no continuous sentence recognition.
- **Language coverage:** Trained for ISL specifically; gestures differ across sign languages.
- **No code release:** Implementation details (e.g. code, exact hyperparams) are not public. Reproducible since it's a straightforward LSTM, but the dataset is proprietary.
- **Reproducibility:** No code link. The model is simple enough to reimplement (e.g. TensorFlow or PyTorch). Compute requirement is minimal.

Key Citation: "The model developed to handle sequential data from hand gestures using the LSTM architecture. The results of the study can be shown … accuracy of 97.1%, average macro precision 97%, recall 96.6%, and F1-score 96.4%."

❖ YOLOv5+MediaPipe Real-Time Translator

- **Citation:** Diksha Bansod et al. (2025). Real-Time Deep Learning-Based Sign Language Translator to Text using YOLOv5 and MediaPipe. Int. J. Adv. Res. Comput. Commun. Eng.

- **Problem:** End-to-end real-time sign-to-text "translator" (more precisely, recognizer+display). Designed to overlay text subtitles for signers in video calls. Focuses on Indian Sign Language (ISL) gestures (alphabet and some common words).

- **Datasets:** Custom ISL dataset (~5000 images).
- **Classes:** 26 alphabet letters + 4 multi-word signs ("THANK YOU", "YES", "NO", "LOVE").
- **Capture:** Images taken from webcam in varied lighting/background.
- **Augmentation:** Rotations, flips, brightness changes to boost training data.
- **Input:** RGB video frames. They use MediaPipe Hands for robust hand detection and tracking (landmark extraction), but crucially the classification model is YOLOv5.

The pipeline is: capture frame → Mediapipe finds hand region → crop/background-subtract → YOLOv5 predicts sign class.

- **Preprocessing:**

• Background subtraction (to isolate hands).
• Resizing to YOLO input (e.g. 640×640).
• Data augmentation during training as above.
• **Model (Architecture):** YOLOv5-Small (a CNN-based object detector) with a custom classification head.
• **Backbone:** CSPDarknet53-like (standard YOLOv5).
• **Neck/Head:** PANet + YOLO heads (adapted to 30 classes). The classification head replaces box prediction for sign class.
• **Training:** Transfer learning from COCO-pretrained weights.
• **Hyperparameters:** Epochs=100, batch=16, LR=0.001, Adam optimizer, Loss = BCE (for class) + IoU (for implicit localization).
• **Hardware/Implementation:** PyTorch 2.0 on CUDA GPU (NVIDIA RTX 2060; Intel i7 CPU). Used OpenCV for capture and display, and OBS for virtual camera overlay.
• **Evaluation Metrics:** Accuracy, Precision, Recall, F1-score, and latency (ms/frame) as they emphasize real-time.

- **Results:**

• **Accuracy:** 96.2% on their test set. Precision 94.8%, Recall 95.3%, F1-score 95.0%.
• **Latency:** ~32 ms/ (≈31 FPS) on GPU. By comparison, MobileNetV2 and DenseNet-201 baselines gave 89.7% @61ms and 91.3% @48ms.
• **Real-time demo:** Successfully overlayed text (e.g. "THANK YOU") on live Google Meet video. The system maintained ≥30 FPS on GPU.
• **Robustness:** They claim the model is resilient to lighting/background variations.

- **Strengths:**

• **High accuracy:** 96% on a 30-class problem.
• **Real-time:** ~30 FPS with GPU (table shows CUDA halves CPU time).
• **Practical integration:** OBS virtual camera for live calls.
• **Hybrid pipeline:** Combining fast hand tracking (MediaPipe) with accurate YOLO classification gives low latency.

- **Limitations:**

• **Small vocabulary:** Only letters + 4 multi-word signs. Not sentence-level.
• **Hardware:** Real-time speed relies on GPU; on CPU it would be slower (~60ms with DenseNet).
• **Overlap sensitivity:** Mentioned worse accuracy for overlapping/two-handed signs. Only one-hand/clear signs were in dataset.
• **No code/public demo:** Only the paper and PDF. Dataset is not published.
• **Reproducibility:** The paper provides model/training details. No code or dataset link given. All tools used (PyTorch, OpenCV, MediaPipe, OBS) are standard and available. Training requires a GPU.

- **Key Citation:** "A real-time sign language translation system… using a hybrid YOLOv5–Mediapipe–CUDA framework. The convolutional model is trained… on a curated ISL dataset [26 letters + word-signs]. The developed system achieves 96.2% accuracy and functions in real time on standard GPU hardware."

Study/Technique	Input Modality	Dataset (language, size, annotations)	Model / Architecture	Metrics	Acc. / BLEU	Code
Maia et al. (2025) (Transformer + BART)	RGB video → MediaPipe (body+hand keypoints[1]	PHOENIX14T (German SL, ≈7.1k train w/gloss[1]), How2Sign (English SL, ≈29k train, no gloss	Transformer encoder-decoder for Sign2Gloss (CTC loss, pos. encodings) + BART for Gloss2Text[1]	BLEU-4, WER	BLEU-4 ≈30 (PHOENIX 14T 12) BLEU-4 lower on How2Sign (no gloss)	No
Utomo et al. (2025) (LSTM)	RGB video → MediaPipe (21 hand landmarks)	Custom ISL (36 classes: 26 letters + 10 digits; 25 sequences each)[3]	1–2 layer LSTM network on sequence of hand-keypoints	High (heavy models)	✗ (batch real-tim	✗ [illegible] translation, no real-time)
Bansod et al. (2025) (YOLOv5 + CNN)	RGB video → MediaPipe (hand detection)	Custom ISL (30 classes: 26 letters + 4 word-signs; ≈5000 images[3]	Accuracy, Precision, Recall, F1	< 10 ms/ frame (LSTM is fast)	✓ (feasible on CPU/GPU)	No
Maia et al. (2025) (LSTM)	RGB video → MediaPipe (hand detection) + YOLOv5 l5.	YOLOv5-Small CNN (backbone + custom classifier head); pretrained COCO, then fine-tune[5][4]	96.2% acc; prec 94.8%, recall 95.3%[65]	~32 ms/ frame (≈31 FPS[7]	✓ (GPU @30+FPS; GPU slower)	No
Bansod et al. (2025) (YOLOv5 + CNN)	RGB video → (hand detection)	RGB video + MediaPipe (hand detection) + YOLOv5 (frame-level)	~32 ms/frame (≈31 FPS[17]	✓(CPU @30+FPS; CPU slower)	✓ No	No

[illegible] [1], [2], [3], → [3], [4], [5], [4] NS [illegible] elapebed [3], [illegible] referenced [5], [illegible]. [illegible] [6]~[illegible]. [5],. [7]

Chapter 3

Analysis / SRS

❖ Purpose of the Project

The main purpose of this project is to "bridge the communication gap between deaf/mute individuals and people who do not understand sign language". It uses Artificial Intelligence, Computer Vision, and Machine Learning to recognize hand gestures and convert them into text or speech in real time.

1. Solve Communication Barriers

Many deaf and mute people rely on sign language, but most people in society do not understand it. This creates difficulties in:

- daily conversations
- education
- workplaces
- hospitals and public services

AI-based translation systems help convert sign language into readable or spoken language, enabling smooth communication between both groups.

2. Provide Accessibility and Inclusion

The project promotes "digital accessibility" and social inclusion by allowing hearing-impaired individuals to:

- interact independently
- access information
- participate in society without needing a human interpreter

This helps create a more inclusive environment in education, public services, and workplaces.

3. Real-Time Gesture Recognition Using AI

The system uses:

- camera input
- computer vision to track hand movements
- machine learning models to classify gestures

This enables:

- real-time translation
- faster and more natural communication than writing or typing.

4. Reduce Dependence on Human Interpreters

Professional sign language interpreters are not always available, especially in emergencies or rural areas. AI systems can provide "instant translation" during:

- hospital visits
- customer service interactions
- classroom communication

This is especially useful in places where interpreter services are limited.

5. Educational and Assistive Technology Purpose

The project also supports:

- learning sign language
- teaching hearing students about sign communication
- helping deaf students understand lectures through translated content

It improves both "assistive technology" and educational tools.

6. Academic Purpose (For Your Final-Year Project)

Since you're building this for your semester submission, the project demonstrates:

- application of AI and Deep Learning
- real-world social impact
- computer vision and gesture recognition skills
- system integration (camera → model → output)

This makes it a strong and socially meaningful AI project compared to purely theoretical models.

❖ Intended users and product scope

1. Intended Users

The AI Sign Language Translator is designed for multiple groups of users who interact with or support hearing-impaired individuals.

Primary Users

Deaf and Mute Individuals

They are the main beneficiaries of the system. The application allows them to:

- communicate with people who do not know sign language
- express their thoughts in real-time through translated text or speech
- interact independently in public and professional environments

Secondary Users

General Public

People who do not understand sign language can use the system to:

- understand gestures made by deaf individuals
- communicate without needing prior knowledge of sign language

Students and Teachers

The system can be used in:

- classrooms with hearing-impaired students
- sign language learning environments
- online education platforms

Healthcare and Customer Service Professionals

Doctors, nurses, receptionists, and service staff can use the system to:

- communicate with deaf patients or customers
- avoid misunderstandings in critical situations

2. Product Scope

The scope defines what the system “will” and “will not” do in its current version.

- **In-Scope Features (What the system will do)**

Real-Time Gesture Recognition

The system will:

- capture hand gestures using a webcam or mobile camera
- process video frames using computer vision
- classify gestures using machine learning models

Translation of Signs into Text or Speech

The system will convert recognized gestures into:

- readable text on the screen
- optional audio output using text-to-speech

User-Friendly Interface

The product will include:

- a simple graphical interface
- start/stop camera options
- real-time display of translated output

Support for Basic Sign Language Vocabulary

In the initial version, the system will recognize:

- alphabets (A–Z)
- common words or phrases such as “hello”, “thank you”, “help”

- **Out-of-Scope Features (Future Enhancements)**

The following are “not included in the current version” but can be added later:

- Full sentence-level sign language translation
- Recognition of complex grammar and facial expressions
- Support for multiple sign languages (ASL, ISL, BSL)
- Mobile app deployment (if you are building a desktop version)

- **System Environment Scope**

The project will operate in:

- real-time video environment
- indoor lighting conditions for best accuracy
- standard hardware such as a laptop webcam or USB camera

❖ Functional and Non-Functional Requirements

1. Functional Requirements

➢ **User Input Capture:**

- The system shall capture real-time video using a webcam or mobile camera.
- It shall continuously process frames for gesture detection.

➢ **Hand Gesture Detection**

- The system shall detect and track hand movements using computer vision.
- It shall identify hand landmarks and gesture shapes from the video feed.

➢ **Gesture Recognition Using AI**

- The system shall classify gestures using a trained machine learning or deep learning model.
- It shall match detected gestures with stored sign language datasets.

➢ **Translation to Text**

- The system shall convert recognized gestures into readable text displayed on the screen in real time.

➢ **Text-to-Speech Conversion**

- The system shall convert translated text into speech using a text-to-speech engine.

➢ **User Interface Interaction**

- The system shall provide buttons for:
  - Start camera
  - Stop camera
  - Clear text output
  - It shall display recognized gestures and translated output live.

➢ **Error Handling**

- The system shall notify the user when gestures are not recognized.
- It shall continue capturing frames even if a gesture is misclassified.

2. Non-Functional Requirements

➢ **Performance Requirements**

- The system should process gestures with minimal delay (near real-time response).
- It should maintain a frame rate sufficient for smooth recognition (e.g., 15–30 FPS).

➢ **Accuracy Requirements**

- The system should achieve high recognition accuracy (e.g., above 85%) under normal lighting conditions.
- Misclassification should be minimized using optimized models and datasets.

➢ **Usability Requirements**

- The interface should be simple and easy to use for non-technical users.
- The system should require minimal training to operate.

➢ **Reliability Requirements**

- The system should run continuously without crashing during long sessions.
- It should recover automatically from temporary camera failures.

➢ **Compatibility Requirements**

- The system should work on standard laptops/desktops with built-in webcams.
- It should support common operating systems such as Windows and Linux.

➢ **Scalability Requirements**

- The system should allow addition of new gestures and retraining of models in future versions.

➢ **Security and Privacy Requirements**

- The system should not store video data without user consent.
- All captured data should be processed locally to protect user privacy.

❖ User Interface and Hardware/ Software requirements

1. User Interface (UI)

The “User Interface (UI)” is the part of the system through which users interact with the application. Since the target users include deaf individuals and non-technical users, the UI must be “simple, visual, and easy to operate”.

➢ Main UI Components

- Camera Display Window :

  - Shows the real-time video captured from the webcam.
  - Allows users to position their hands correctly for gesture recognition.

- Text Output Panel:
  - Displays the translated sign language as text in real time.
  - Helps users verify whether gestures are recognized correctly.

- Control Buttons:

The interface includes simple control options such as:

  - Start Camera :– begins gesture detection
  - Stop Camera :– stops the video feed
  - Clear Text :– removes previous translated output

- Speech Output Option:
  - A button or toggle allows the system to convert translated text into speech using text-to-speech.

➢ UI Design Goals

The interface should be:

  - User-friendly :– easy to understand without training
  - Accessible :– readable fonts and clear layout
  - Responsive :– updates text instantly as gestures are detected

2. Hardware Requirements

The hardware requirements define the physical components needed to run the system efficiently.

➢ Minimum Hardware Requirements

- Camera / Webcam:
  - Required to capture hand gestures in real time.
  - A built-in laptop webcam is sufficient for basic implementation.

- Processor (CPU):
  - Minimum: Intel i3 / Ryzen 3 or equivalent
  - Recommended: Intel i5 or higher for faster image processing

- RAM:
  - Minimum: “4 GB”
  - Recommended: “8 GB or more” for smooth real-time recognition

- Storage:
  - At least “2–5 GB free space” to store:
    - datasets
    - trained models
    - application files

3. Software Requirements

Software requirements include the tools, libraries, and platforms needed to develop and run the AI model.

➢ Programming Language

The system is commonly developed using:

- Python:

because of its strong support for AI and computer vision libraries.

➢ Required Libraries and Frameworks

- Computer Vision Library
  - OpenCV:

Used for capturing video frames and processing images.

➢ Hand Tracking and Landmark Detection

- MediaPipe:

Detects hand landmarks and tracks finger positions.

- Machine Learning / Deep Learning Framework

    - TensorFlow or Keras:

      Used to train and run gesture recognition models.

- Text-to-Speech Library

    - pyttsx3:

  Converts translated text into audio output.

Hardware and Software Requirements

for AI Sign Language Translator Project

Category	Requirement
Server (Docker)	2 CPU cores, 4GB RAM minimum
Storage	10GB minimum for database and application files
Operating System	Any OS supporting Docker Desktop 4.x
Docker	Docker Desktop 4.x, Docker Compose v2
Browser	Chrome 90+, Firefox 88+, Safari 14+, Edge 90+
Python (local dev)	Python 3.8+
Node.js (local dev)	Node.js 16+ LTS
Database	SQLite 3.x (included)


Chapter 4

System Design

❖ **System Architecture:**

- **Overview** : An AI Sign Language Translator converts hand gestures (video/images) into text or speech, and optionally vice versa.

- **High-Level Architecture:**



➢ Step-by-Step Approach

- **1. SIGN → TEXT → SPEECH**

➢ Step 1: Camera Input

The system begins by capturing real-time video of hand gestures using a camera such as a webcam or mobile device camera. This video is continuously streamed and divided into frames, which serve as the raw input for further processing.

➢ Step 2: Preprocessing

In this step, the captured video is converted into individual frames, which are then resized to a standard resolution (such as 224×224 pixels) for uniformity. The pixel values are normalized to improve model performance, while background noise is reduced and lighting conditions are adjusted to ensure clarity and consistency in the input data.

➢ Hand Detection & Tracking

The system detects and isolates the hand region from each frame using computer vision techniques such as MediaPipe or OpenCV. It also tracks the movement of the hand across frames and identifies key landmarks, typically 21 points representing fingers and joints, which are essential for understanding the gesture.

➢ Step 4: Feature Extraction

Once the hand landmarks are identified, they are converted into meaningful numerical features such as finger angles, distances between joints, and motion patterns. These features form a structured data representation that can be understood by machine learning models.

➢ Step 5: AI Model Processing

The extracted features are fed into an AI model, which may include CNN for static gesture recognition, LSTM for sequential or dynamic gestures, or Transformer models for understanding complex sequences. The model processes the input and predicts the corresponding gesture or sign.

➢ Step 6: Gesture Recognition

In this stage, the system classifies the predicted output into a specific gesture label. It may also provide a confidence score indicating the accuracy of the prediction and apply error correction techniques to improve reliability.

➢ Step 7: Text Generation

The recognized gestures are then converted into readable text. If multiple gestures are detected in sequence, they are combined to form meaningful words or sentences, enabling natural language communication.

➢ **Step 8: Speech Output**

Finally, the generated text is converted into speech using text-to-speech technologies such as gTTS or pyttsx3. The system outputs both the text on the screen and the corresponding audio, completing the translation process.

- **TEXT → SIGN (Reverse System)**

➢ **Step 1: Text Input**

In the reverse process, the user provides input in the form of typed text or voice, which is first converted into text. This serves as the starting point for generating sign language output.

➢ **Step 2: NLP Processing**

The input text is processed using Natural Language Processing techniques, where the sentence is broken down into words and grammatical structures. Unnecessary words are removed, and the sentence is converted into a format suitable for sign language representation.

➢ **Step 3: Gesture Mapping**

Each word in the processed text is mapped to its corresponding sign gesture using a predefined dataset or sign language dictionary. This ensures that the system correctly translates words into their visual equivalents.

➢ **Step 4: Gesture Generator**

The system then generates a sequence of gestures based on the mapped words. This can be done using pre-recorded gesture videos or dynamically generated animations.

➢ **Step 5: Avatar Animation**

Finally, the generated gestures are displayed using a 3D avatar or animated human model. This provides a visual representation of sign language, allowing users to understand the message through gestures.

➢ **3. Key Components Summary**


The camera captures gesture input, preprocessing cleans and standardizes the data, hand detection identifies the hand region, feature extraction converts gestures into numerical data, the AI model predicts the gesture, NLP processes language for reverse translation, and the output module presents the final result as text, speech, or animation.


➢ **4. Simple Flow Summary**

In the sign-to-text process, the system captures gestures through a camera, processes them using AI models, and converts them into text and speech. In the text-to-sign process, the system takes text input, processes it using NLP, maps it to gestures, and displays it through an animated avatar.


➢ 5. Extra Enhancements

The system can be further improved by enabling real-time translation, supporting multiple languages, deploying it as a mobile application, incorporating emotion detection, and enhancing sentence-level understanding for more natural communication.





❖ Final Architecture:



❖User Interface Design Approach

- **User**

The "user" is the primary actor who interacts with the AI-based sign language translator system. The user can be a deaf or mute person who communicates using sign language, or a normal person who wants to understand sign language. The user initiates the system by performing hand gestures in front of the camera and expects the system to convert those gestures into meaningful text or speech output. The user also interacts with the system to view the translated text on the screen or listen to the generated speech.

- **Capture Gesture**

The "capture gesture" use case represents the process where the system uses a camera to capture the hand movements or gestures performed by the user. This step is the initial input stage of the system. The camera continuously records frames or images of the user's hand gestures in real time. The accuracy of this step is very important because it directly affects the quality of gesture recognition.

- **View Text**

The "view text" use case allows the user to see the translated output in textual form. After the gesture is recognized and converted, the system displays the corresponding text on the screen. This is useful for communication where reading is preferred, such as in classrooms, conversations, or public communication systems.

- **Listen to Speech**

The "listen to speech" use case enables the user to hear the translated output as audio. The system converts the recognized gesture into speech using text-to-speech technology. This feature is especially helpful for communication with people who cannot read or prefer audio interaction. It improves accessibility and enhances real-time communication.

- **AI Translator**

The "AI Translator system" is the main component that performs all the internal processing. It acts as the central unit that receives input from the user, processes the gesture using artificial intelligence, and produces the output. The system integrates multiple technologies such as computer vision, machine learning models, and speech synthesis to perform its tasks efficiently.

- **Capture Gesture (Camera)**

Inside the system, the camera module captures real-time video frames of the user's hand gestures. These frames are passed to the processing unit. The camera ensures that the gestures are clearly visible and properly framed for accurate detection and analysis.

- **Internal Process: Process Gesture (AI Model)**


The "process gesture" step uses an AI model, such as a deep learning model built with TensorFlow or similar frameworks, to analyze the captured frames. The model identifies hand shapes, movements, and patterns to recognize specific signs. It compares the detected gesture with trained data and predicts the corresponding meaning. This step is the core intelligence of the system.

- **Convert to Text/Speech**

After recognizing the gesture, the system converts it into a meaningful output. First, the gesture is translated into text using predefined mappings or trained models. Then, if required, the text is converted into speech using text-to-speech technology. This step ensures that the output is understandable in both visual and audio forms.


- **Display Output**

The "display output" step presents the final result to the user. The system shows the translated text on the screen and may also play the corresponding audio through speakers. This is the final stage where communication is completed, allowing the user to understand or convey messages effectively.



AI-Based Sign Language Translator

❖ User Side:


AI Sign Language Translator
Translate Sign Language to Text and Speech
Live Camera Feed
Perform Sign Language Gesture in Front of Camera
Output
Translated Text:
I LOVE YOU
Audio Output:
Play Audio
Start Translation
Reset

❖Security, Performance and Integration

➢ User Interface (UI) Design Approach

The user interface of the AI-based sign language translator is designed to be simple, clean, and user-friendly so that users of all age groups can easily interact with the system. The layout is divided into two main sections, where one section displays the live camera feed capturing the hand gestures, and the other section shows the translated output in text and speech form. Large buttons such as “Start Translation” and “Reset” are provided to make interaction easy and intuitive.

The design follows a minimalistic approach by avoiding unnecessary elements and focusing only on essential features. Clear labels and headings are used so that users can quickly understand each function without confusion. The interface also ensures accessibility by using readable fonts, proper colour contrast, and simple navigation, which is especially important for users with disabilities.

Additionally, the system is designed to provide real-time feedback. As soon as the user performs a gesture, the output is displayed instantly, which enhances user experience and interaction. The UI can also be made responsive so that it works smoothly on different devices such as laptops, tablets, and mobile phones.



➢ Security Aspects

Security is an important aspect of the AI-based sign language translator, especially because it involves capturing live video data from users. The system ensures that all captured data is handled securely and is not stored unnecessarily. If any data is stored for model improvement or logging, it is protected using encryption techniques.

User privacy is maintained by ensuring that the camera feed is processed in real time without saving personal videos unless explicitly permitted. Secure communication protocols such as HTTPS are used to prevent unauthorized access during data transmission between the frontend and backend.

Authentication mechanisms can also be added if the system includes user accounts. This ensures that only authorized users can access specific features. Furthermore, the system is protected against common vulnerabilities such as unauthorized access, data leakage, and injection attacks by following secure coding practices.

➢ Performance Aspects

Performance plays a crucial role in ensuring that the system works efficiently in real time. The AI-based sign language translator is optimized to process gestures quickly so that there is minimal delay between input and output. Efficient algorithms and lightweight machine learning models are used to achieve fast processing.

The system uses techniques such as frame optimization, where only necessary frames are processed instead of every frame, to reduce computational load. Hardware acceleration, such as GPU support, can also be used to improve the speed of gesture recognition.

Memory management is also considered to ensure that the system does not consume excessive resources. The application is designed to handle multiple inputs smoothly without crashing or slowing down, even during continuous usage.


➢ Integration Aspects

Integration refers to how different components of the system work together seamlessly. In this project, the frontend (HTML, CSS, JavaScript) is integrated with the backend (Python-based frameworks like Flask or Django). The frontend captures user input through the camera and sends it to the backend for processing.


The backend integrates AI technologies such as TensorFlow and MediaPipe for gesture recognition. These components work together to analyze the captured images and predict the correct gesture. The processed result is then sent back to the frontend for display.

The system can also integrate text-to-speech APIs to convert text output into audio. Additionally, Docker can be used to containerize the entire application, ensuring that all dependencies and components run consistently across different environments.

Proper API design and communication between modules ensure that the system is scalable and can be extended in the future, such as adding support for multiple languages or more complex gestures.



Performance & Integration



Chapter 5

Methodology:

➢ Development Approach

The development of the AI Sign Language Translator system follows an Agile-based methodology, which emphasizes iterative development, continuous feedback, and incremental improvements. Unlike traditional linear models, Agile enables flexibility in adapting to changes during the development lifecycle. The project is divided into multiple phases such as requirement analysis, design, development, testing, and deployment, which are executed in short iterative cycles.

Each iteration focuses on building a specific module, such as gesture recognition, model training, or user interface development. Regular evaluation is conducted at the end of each iteration to ensure that the system meets the expected requirements. This approach allows early identification of errors, faster development cycles, and improved overall quality of the system. Agile is particularly suitable for AI-based systems where experimentation and continuous refinement are essential.

➢ Design Thinking and User-Centric Principles

The system is designed using a user-centric approach, ensuring that the needs of end users, especially individuals with hearing and speech impairments, are prioritized. The design thinking process includes stages such as empathy, definition, ideation, prototyping, and testing.

Empathy is developed by understanding the communication challenges faced by users relying on sign language. Based on this understanding, the system is designed to provide real-time translation of hand gestures into text or speech. Simplicity is maintained in the interface to ensure ease of use, even for non-technical users.

The system focuses only on hand gesture recognition rather than full-body tracking, which improves efficiency and reduces computational complexity. Visual clarity, responsiveness, and accessibility are key design considerations, ensuring that the system delivers accurate and quick results in real-time.

➢ Technology Stack Selection

The technology stack for the project is carefully selected to ensure high performance, scalability, and ease of development.

The frontend is developed using HTML, CSS, and JavaScript, which provide a responsive and interactive user interface. The backend is implemented using Python, which is widely used for machine learning and AI applications.

For gesture recognition and model development, frameworks such as TensorFlow are used for training deep learning models, while

MediaPipe is used for real-time hand tracking and landmark detection. OpenCV is utilized for image processing and capturing video input from the webcam.

The application is deployed using Docker, which ensures that the system runs consistently across different environments without dependency issues. This combination of technologies provides a robust and efficient solution for real-time sign language translation.

➢ Quality Assurance and Testing Strategies

Quality assurance is a critical component of the project to ensure system reliability, accuracy, and performance. Multiple testing strategies are implemented throughout the development lifecycle.

Unit testing is performed to verify the functionality of individual modules such as gesture detection and prediction. Integration testing ensures that different modules work together seamlessly. System testing is conducted to evaluate the complete system under real-world conditions.

User acceptance testing is carried out by involving real users to validate the usability and effectiveness of the system. Performance testing is also conducted to measure response time and accuracy during real-time gesture recognition. Continuous testing helps in identifying issues early and improving the overall system quality.

➢ Tools for Collaboration

Various tools are used to facilitate collaboration, version control, and project management. GitHub is used for maintaining the source code repository and tracking changes. Trello is used for task management, allowing the team to organize tasks, assign responsibilities, and monitor progress.

Visual Studio Code is used as the development environment for writing and debugging code. Docker is used for containerization, ensuring consistent deployment. These tools enhance teamwork, improve productivity, and ensure efficient project execution.

➢ Gantt Chart for Project Timeline

The Gantt chart provides a structured timeline for the project, ensuring systematic execution of all phases within a period of twelve weeks.


The project begins with the requirement analysis phase in the first week, where all system requirements are identified and documented. This phase establishes the foundation for the entire project. In the second week, the system design phase is carried out, where the architecture, workflow, and interface design are planned.

During the third and fourth weeks, data collection is performed, which involves gathering and preprocessing hand gesture datasets required for training the model. This is followed by the model training phase from the fifth to the seventh week, where machine learning algorithms are applied to train the system for accurate gesture recognition.


Simultaneously, user interface development is carried out during the sixth and seventh weeks to ensure a smooth and user-friendly interaction experience. In the eighth week, all components are integrated to form a complete working system.

The ninth and tenth weeks are dedicated to testing, where the system is evaluated for accuracy, performance, and reliability. In the eleventh week, the system is deployed using Docker to ensure portability and consistency. Finally, the twelfth week is allocated for documentation, where all project details are compiled into a formal report.


- **Flow Diagram**



➢ **Process:**


Start
Capture Hand Gesture
Detect Hand Landmarks
Extract Features
Apply Trained Model
Recognize Gesture
Display Output (Text/Speech)
Display Output
(Text/Speech)
End
End

Phase	Duration	Weeks
Requirement Analysis	1 Week	Week 1
System Design	1 Week	Week 2
Data Collection	2 Weeks	Week 3 – 4
Model Training	3 Weeks	Week 5 – 7
UI Development	2 Weeks	Week 6 – 7
Integration	1 Week	Week 8
Testing	2 Weeks	Week 9 – 10
Deployment using Docker	1 Week	Week 11
Documentation	1 Week	Week 12


AI Sign Language Translator Project - Gantt Chart
Requirement Analysis
System Design
Data Collection
Model Training
UI Development
Integration
Testing
Deployment
Documentation
1
2
3
4
5
6
7
8
9
10
11
12
Weeks

Chapter 6

Implementation


➢ Executive Summary:

This chapter presents a detailed account of the implementation of the AI Sign Language Translator project. It covers the system's architecture, component responsibilities, data flow, and deployment. We describe the backend and frontend design, the technology stack (with versions, roles, and justifications), representative code snippets, UI features (with mockup instructions), logical flowcharts, deployment/CI–CD strategy, QA/performance targets, and security/privacy measures. Where possible, official documentation (TensorFlow, MediaPipe, OpenCV, Docker, etc.) is cited to substantiate design choices. Unspecified details (e.g. exact versions or hosting) are noted rather than assumed. Throughout, we use clear headings, concise paragraphs, tables for comparisons, and Mermaid diagrams for flowcharts, in formal technical English (en-IN).

➢ Backend and Frontend Implementation

The system is organized as a web-based client–server application. The frontend is a web UI (HTML/JavaScript) that accesses the user's camera, displays the live video feed with annotated hand landmarks, and shows the translated output (text or synthesized speech). The backend (e.g. a Flask or FastAPI server) receives video frames or landmark data from the client, performs hand detection (via MediaPipe), feeds extracted features into the TensorFlow model for gesture recognition, and returns the predicted sign (as text) to the client.

Architecture diagram of the Sign Language Translator. The user's browser captures camera video and sends frames to the backend API. The backend runs MediaPipe Hands to detect hand landmarks and a TensorFlow model to recognize gestures, then returns the result for display.



- **Component responsibilities:**

The Web UI handles video capture (using HTML5 <video>/<canvas>), basic controls (start/stop), and displays results (text label or synthesized audio). The Backend API (Flask or FastAPI) exposes endpoints (e.g. /predict) to accept video frames or precomputed landmark vectors. It invokes MediaPipe Hands (Python API) to detect up to 21 hand landmarks per hand

. The detected landmarks (x,y,z coordinates of each keypoint) form a feature vector. The TensorFlow model (a neural network trained on landmark vectors) performs inference on these features to classify the gesture. A post-processing step maps the model output (class index) to a human-readable label or phrase (and optionally to synthesized speech). All inference components run inside a Docker container for portability and reproducibility (following best practices

).

- **Data flow:**

The video feed flows from user camera → Web UI → Backend. Optionally, landmark extraction could be done client-side (e.g. via TensorFlow.js), but here we send raw frames to the server. Inside the backend, each frame is converted to the appropriate color space (cv2.cvtColor) and handed to MediaPipe

. MediaPipe returns landmark coordinates, which are collected into a fixed-length array (e.g. 21 landmarks × (3D coords) = 63 values

). These features are then passed to the TensorFlow model (model.predict(...)) to produce a class probability or label

. The predicted label is sent back to the frontend via JSON.

- **Deployment setup:**

The backend runs on a server (could be local or cloud). For example, we might use a Linux VM or container in AWS EC2/GCP Compute Engine with Python 3.x. The API listens on a configurable port (e.g. 8000) and should enforce secure transport (HTTPS). Environment variables store any secrets (e.g. API keys for text-to-speech). The Dockerfile (see Section 6 below) defines the runtime (e.g. FROM python:3.12-slim)

and installs required packages (MediaPipe, TensorFlow, Flask/FastAPI, OpenCV, etc.). The frontend is static HTML/JS and can be hosted on the same server (as static files) or separately (e.g. on AWS S3 or a CDN). In production, a reverse proxy (NGINX) or cloud load balancer can forward requests to the container, and container orchestration (Docker Compose or Kubernetes) can manage scaling.

➢ Tools, APIs, Libraries, and Platforms

The table below lists key technologies, their (if known) versions, roles, and justifications. We also note prominent alternatives.

Technology	Version (approx.)	Role/Usage	Justification	Alternatives
Python	3.x (latest)	Programming language	Widely used for ML and CV; rich libraries.	N/A (mandatory here)
OpenCV (cv2)	4.x (unspecified)	Video capture & image processing	Standard CV library; VideoCapture API.	scikit-image (no camera)
MediaPipe Hands	0.9+ (latest)	Hand landmark detection	Pretrained hand detectors, 21 3D points.	OpenPose, ArUco, YOLO, TF Obecject Detection
TensorFlow	2.x (latest)	ML model development & inference	Industry-standard ML framework.	PyTorch, scikit-learn, MXNet
Keras	Integrated in TF2.x	Model API	High-level neural-net API.	native tf layers
NumPy	1.x	Numerical computations	Essential for array handling.	(built-in Python lists)
Pandas	1.x	Data handling (optional)	Dataset manipulation.	CSV module, Numpy only
scikit-learn	1.x	ML tools (evaluation, pipelines).	Train/test split, scaling.	(already TF covers deep net)
Flask	2.x (unspecified)	Web API framework (backend)	Lightweight microframework.	FastAPI, Django, Node.js
FastAPI	0.x	Alternative API framework	Modern, async, input validation.	Flask, Falcon
Docker	24.x (unspecified)	Containerization	Reproducible deployment.	Virtualenv + VM, Podman
Git/GitHub	(latest)	Version control / collaboration	Industry standard, CI/CD.	GitLab, Bitbucket
CI/CD tools	(unspecified)	Automated testing & deploy	GitHub Actions, Jenkins etc.	Jenkins, Travis CI
Heroku	(free/paid)	PaaS hosting (optional)	Easy Git push deploy.	Netlify, AWS Elastic Beanstalk
AWS / GCP	(various services)	Cloud deployment options	EC2/ECS (AWS) or Cloud Run (GCP).	DigitalOccan, Azure
OpenSSL / TLS	(latest)	Security (HTTPS)	Secure transport (HTTPS).	Let's Encrypt for certs
SQL/NoSQL DB	(optional)	Persistent storage (optional)	For user accounts or logs.	SQLite, MongoDB
Bootstrap/CSS/]S	(unspecified)	Frontend UI libeary	Responsive laysut and components.	React, Angular

➢ Representative Code Snippets

Below are concise Python code examples (well-commented) illustrating core functionality. (Exact code will vary; pseudocode is used where needed.)

Camera capture (OpenCV): Use OpenCV's VideoCapture to grab frames from the webcam

Python

```
import cv2

# Initialize camera (0 = default webcam)
cap = cv2.VideoCapture(0)
if not cap.isOpened():
    print("Cannot open camera")
    exit()

while True:
    ret, frame = cap.read()  # Capture frame
    if not ret:
        break
    # Optionally resize/frame processing here
    cv2.imshow('Webcam Feed', frame)  # Display the frame
    if cv2.waitKey(1) & 0xFF == ord('q'):
        break

cap.release()
cv2.destroyAllWindows()
```

This follows OpenCV's tutorial pattern (create VideoCapture, read frames in a loop, release the camera)

- **Hand landmark detection (MediaPipe):** Initialize MediaPipe Hands and process each frame

Python

```
import mediapipe as mp


mp_hands = mp.solutions.hands
mp_drawing = mp.solutions.drawing_utils


# Configure MediaPipe Hands for real-time video
with mp_hands.Hands(
    static_image_mode=False,
    max_num_hands=2,
    min_detection_confidence=0.5,
    min_tracking_confidence=0.5) as hands:
  while cap.isOpened():
    ret, frame = cap.read()
    if not ret: break


    # Convert BGR to RGB for MediaPipe
    image = cv2.cvtColor(frame, cv2.COLOR_BGR2RGB)
    image.flags.writeable = False
    results = hands.process(image)
    image.flags.writeable = True


    # Draw hand landmarks on the frame (for debugging/UI)
    if results.multi_hand_landmarks:
      for handLms in results.multi_hand_landmarks:
        mp_drawing.draw_landmarks(frame, handLms, mp_hands.HAND_CONNECTIONS)
    cv2.imshow('Hands', frame)
```

This follows the MediaPipe Hands example: converting frames to RGB, processing to detect hands, and optionally drawing landmarks

. The result results.multi_hand_landmarks contains up to 21 3D points per hand.

- **TensorFlow model loading and inference:** Load a pretrained Keras model and predict on a feature vector.

Python

```
    import tensorflow as tf
import numpy as np


# Load the trained model
model = tf.keras.models.load_model('sign_model.h5')
model.compile()  # Ensure it's ready for inference


# Example: predict gesture from a single 63-value vector
# (for one hand: 21 points * 3 coords)
landmark_vector = np.array(feature_list).reshape(1, 63)
prediction = model.predict(landmark_vector)  # returns class probabilities【21†L6362-L6370】
predicted_label = np.argmax(prediction)  # choose highest-probability class
print("Predicted gesture:", predicted_label)
```

- Here model.predict(x) is used as per TensorFlow's API In practice, one would preprocess the landmarks (normalization) to match training.

- **Backend API endpoint (Flask example):** A simple endpoint to handle incoming frames or landmarks and return a prediction.

Python

```
        from flask import Flask, request, jsonify
import cv2
import mediapipe as mp
import numpy as np
import tensorflow as tf

app = Flask(__name__)
# Load models
hands = mp.solutions.hands.Hands(...)
model = tf.keras.models.load_model('sign_model.h5')

@app.route('/predict', methods=['POST'])
def predict():
    # Assume client sends an image frame as bytes
    file = request.files['image']
    img_array = np.frombuffer(file.read(), np.uint8)
    frame = cv2.imdecode(img_array, cv2.IMREAD_COLOR)
    # Detect hand landmarks
    results = hands.process(cv2.cvtColor(frame, cv2.COLOR_BGR2RGB))
    if not results.multi_hand_landmarks:
        return jsonify(error="No hand detected"), 400
    # Extract features from the first hand
    hand = results.multi_hand_landmarks[0]
    features = []

    for lm in hand.landmark:

  features += [lm.x, lm.y, lm.z]  # flatten landmarks

    features = np.array(features).reshape(1, -1)

    # Predict gesture

    preds = model.predict(features)

    label = np.argmax(preds)

    return jsonify(prediction=int(label))
```

➢ UI Features

The frontend UI is a simple web page. Required screens include:

Login Page (if applicable): Screenshot: A form with fields for username and password and a "Login" button. (Mockup: a box "Sign Language Translator – Login" with input fields and a button.)

Main Translator Interface:


Shows the live video feed (or canvas) capturing hand gestures, an overlay of detected hand skeleton (optional), and a prediction display area. There should be controls (e.g. "Start/Stop Detection") and a language selector. (Mockup: a page titled "Sign Language Translator" with two sections side-by-side: left "Video Stream", right "Translated Text".)

Optional Features:


If implemented, "BMI calculation" or a "Chat interface" (though these are not typical for a translator, likely copy-paste remnants). If present, e.g. a small form calculating BMI from height/weight, or a simple chat box to query translations. (Mockup instructions: use existing Bootstrap forms.)

To capture these:

open the web page in a browser (preferably Chrome/Firefox), allow camera permission, and use the browser's screenshot tool. (Since real screenshots cannot be embedded here, one can create mockup images using any UI design tool by placing an HTML5 <video> element and text fields as described.)




SYSTEM ARCHITECTURE & TECHNOLOGY OVERVIEW
TECHNOLOGY
VERSION
ROLE / USAGE
JUSTIFICATION
ALTERNATIVES
Python
2.0.1
ML/CV
Widely used, rich libraries
scikit-image
OpenCV
2.8.0
Video capture & image processing
Standard library, VideoCapture API
PyTorch
MediaPipe Hands
2.0.4.0
Cameran camera
Standard implements, and casting humant
Node.js
TensorFlow
1.2.0
ML, evaluation
Standard for processing, and linguistics API
HealAPI
docker
1.1.2.2
Signal segmentation
Integral paranom, Contact correction
Docker
Flask
1.0.0
Sign shats
Standard library, VideoCapture API
PyTorch
FastAPI
2.2.0
Standard library
Comprehensvitive and secure operations
Node JS
AWS/GCP
1.0.0
ML/CV
Efficiently automatic and localized requirements
aws



➢ Deployment and CI/CD

Docker:

We use Docker to containerize the backend. A typical Dockerfile might start with the official Python image, install dependencies, and run the server. For example (from Docker docs).

```
# Dockerfile example (simplified)
FROM python:3.12-slim
WORKDIR /app
COPY requirements.txt .
RUN pip install --no-cache-dir -r requirements.txt
COPY . .
EXPOSE 8000
CMD ["flask", "run", "--host=0.0.0.0", "--port=8000"]
```

➢ Deployment options:

With the Docker image prepared, we have many choices:

Heroku:

Supports deploying Docker containers via Git or Heroku CLI. A heroku.yml can specify build steps. Heroku provides easy HTTP routing, free tier (with limitations) for student projects.

AWS:

Use Elastic Container Service (ECS) or Elastic Beanstalk to deploy Docker images. ECS can run containers behind a load balancer. Or use AWS Lambda with a container image for serverless (if HTTP latency is acceptable).

GCP:

Cloud Run or App Engine can run containers from a registry. GCP Cloud Functions (with container) is similar to AWS Lambda. No single platform is specified, so these are noted as options. Key point: Docker makes the app portable to any.

CI/CD pipeline:

We recommend using GitHub Actions (or similar) to automate testing and deployment. For example, on each commit to main, Actions can:

1. Build Docker image and run unit tests (for model inference, endpoints).
2. Push image to Docker Hub or AWS ECR.
3. (Optionally) Deploy container to the chosen host. One can add automated checks (linting Python, running static type checks, etc.) and integration tests.

Testing & Monitoring:

For CI, include unit tests for each module (e.g. using pytest). For API testing, use tools like Postman or automated request scripts (e.g. curl). End-to-end tests can check that known gestures map to correct text (using a small test dataset of gesture images). For monitoring in production, one might use:

Logging:

The server logs requests and predictions (to stdout or a file). Tools like Python's logging module can timestamp events.

Metrics:

Monitor API response time (latency) and accuracy drift. In AWS, CloudWatch or in GCP, Stackdriver can record metrics.

Alerts:

set alerts if error rate spikes or latency degrades.

We also ensure health checks (e.g. GET /health endpoint returning 200) so a load balancer can confirm the app is alive.

➢ Quality Assurance and Performance

Latency targets:

Since this is real-time, we aim for low latency. MediaPipe operates at ~30+ FPS on modern hardware, and TensorFlow inference on a small CNN (63-inputs) is fast (tens of milliseconds). A goal might be <100 ms total response (from frame capture to text output). This ensures interactive feel. Measurements should be taken; if latency is high, optimize model size or processing pipeline (batching frames, using TensorFlow Lite, etc.).

Accuracy evaluation:

The model should be evaluated on a held-out test set. We split the dataset into training/validation/testing (commonly 70/15/15% or similar). We compute accuracy, precision, recall, and F1-score per gesture class (using the standard confusion matrix approach)

. Precision = TP/(TP+FP), Recall = TP/(TP+FN), F1 is the harmonic mean (2·TP/(2·TP+FP+FN))

. In a balanced multi-class setting, accuracy and macro-average F1 are key metrics. For sign recognition, a common target is >90% accuracy on the test set, but this depends on dataset difficulty. If multiple classes (words or alphabets), also examine per-class confusion (e.g. using a confusion matrix) to identify common errors.

Dataset:

We must gather or use an existing sign language dataset (e.g. ASL alphabets or words). If data collection is custom, we note the size. (If unspecified, we say "a few hundred labeled images per class" or refer to known datasets.) We split it (e.g. 80/20 or 70/30 train/test). If possible, use cross-validation. We also reserve some data for final user testing.

➢ Testing plan:

- **Unit tests** for individual functions (e.g. test that landmark extraction function returns 63 floats for a known image).
- **Integration tests:** Feed a few example images through the full pipeline and check output against expected labels.
- **UI tests:** Manual or automated (e.g. Selenium) tests to verify the front-end loads and displays predictions.
- **Performance tests:** Measure average inference time and throughput (e.g. using time logs).
- **Regression tests:** If model or code changes, verify predictions remain stable on known inputs.

A brief testing matrix could be included, but the key is documenting that evaluation uses the above metrics and splitting strategy.

- **Security and Privacy**

Camera permissions: Modern browsers require HTTPS to access the webcam. Thus the deployed site must use TLS (use Let's Encrypt). We must clearly ask user consent for camera use (browser prompt).

Data transfer: Frames or landmark data should be sent over HTTPS to protect privacy. We avoid storing or logging raw images. Only the minimal feature vectors or text labels are handled.

Data storage: If saving any data (e.g. user logs), we anonymize it. No personally identifiable information is needed, so we should avoid it entirely.

User authentication: If there is a login system, use secure password hashing (e.g. bcrypt) and HTTPS. Use tokens or session cookies. Flows like OAuth could be integrated if needed.

Backend security: Do not run the Flask app as root in Docker. Limit CORS to only the allowed domain(s). Validate inputs strictly (though our input is image data, still check file types/sizes).

Libraries: Keep all dependencies up-to-date to avoid known vulnerabilities. Docker images should be minimal (the slim image above) to reduce attack surface

Compliance: If deployed in production, disclose camera usage clearly and obtain user consent. Comply with privacy policies regarding audio recording (if text-to-speech is used, local only).

- **Tables of Choices and Timeline**

Technology comparison: For clarity, we compare a few critical choices in tables:

Backend framework (Flask vs FastAPI):

Framework	Pros	Cons
Flask	Very simple and mature; large community.	Synchronous (no async by default); minimal built-in validation.
FastAPI	High-performance (async); type-validated inputs; automatic Swagger UI.	Newer (smaller community); learning curve with Pydantic models.

This highlights why Flask is fine for simple APIs, but FastAPI offers automatic JSON validation and async support

- **Hand detection (MediaPipe vs Alternatives):**

Library	Strengths	Limitations
MediaPipe	Real-time multi-hand 21-keypoint tracking[2]. High accuracy and mobile-optimized.	Requires Python 3.7+ and prebuilt wheels; complex to compile on some platforms.
OpenPose	Can detect full body/face as well; open-source.	Heavy (requires GPUs for real-time); not as optimized for hands.
Haar/Contour	Simple rule-based (e.g. skin color + convex hull).	Very inaccurate; fails under varied backgrounds/lighting.
YOLO-based	Generic object detection models (e.g. hands).	Need custom training for high accuracy on hands; slower if not optimized.

- MediaPipe is chosen for its ready-to-use hand landmarks and real-time performance, as mentioned in the docs

➢ **Deployment (Heroku vs AWS vs GCP):**

.

Platform	Pros	Cons
Heroku	Very easy setup for small apps (Git push to deploy); free tier available.	Dynos sleep on free tier; limited customization.
AWS	Flexible (ECS, EKS, Beanstalk, Lambda, etc.); broad service ecosystem.	More complex to configure; may incur cost.
GCP	Simple container deploy (Cloud Run), integrated ML APIs.	Similar complexity as AWS; costs.

- No single provider is mandated; choice can depend on cost and familiarity. (For a college project, Heroku's simplicity is attractive.)

Chapter 7

Testing an AI Sign Language Translator

This report outlines comprehensive testing strategies for a sign-language translation system, covering unit tests (frontend/UI and backend/model logic), end-to-end validation, external benchmarking, performance/load testing, and automation. We recommend using established testing frameworks (e.g. Jest or React Testing Library for UI; PyTest or JUnit for backend logic) with structured, isolated tests employing mocks/stubs. Test suites should include representative positive, negative and edge cases (e.g. clear gestures vs. random hand motions or occluded frames), with test data drawn from or augmented by public sign-language datasets (WLASL, MS-ASL, ASLLVD, etc.). Output accuracy will be measured by translation metrics (BLEU, chrF, WER) and newer sign-specific or embedding-based metrics (SignBLEU, BLEURT, GEMBA). For external validation, one can compare the system's output against known references or independent tools (analogous to verifying a BMI calculator's result against the formula). Performance testing should simulate realistic and extreme user loads (e.g. via Locust or JMeter) and monitor latency (e.g. time-to-first-token, end-to-end response) and throughput, as well as GPU/CPU usage. We include sample CI/CD YAML for automated testing (GitHub Actions example) and mermaid diagrams of a CI pipeline and performance test workflow. Tables map system features to test cases and compare testing tools. A concise test plan timeline is also provided. All recommendations lean on official docs and peer-reviewed sources for best practices and datasets.

❖ Unit Testing (Frontend and Backend)

- **Frameworks & Test Structure:**
  For web or mobile UIs, use JavaScript testing frameworks like Jest (with React Testing Library for React) or Mocha/Chai (for Vue/Angular). Jest is "a universal testing platform" adaptable to any JS library. For backend logic, use language-appropriate frameworks: e.g. Python's PyTest (widely used with fixtures and plugins), Java's JUnit, or Node's Jest/Mocha. Write tests as *Arrange-Act-Assert* units, each verifying one small component (function, class, or component) in isolation. Structure tests in directories (e.g. __tests__ or tests/) and name them clearly (e.g. translator.test.js).

- **Mocking and Stubbing:**
  Replace external dependencies in tests with mocks. For example, Jest provides mock functions (jest.fn()) to replace and spy on functions. In React tests, mock network calls (e.g. using jest.mock() or tools like msw). In Python/PyTest, use the unittest.mock module or pytest-mock to patch external calls (e.g. HTTP requests). PyTest fixtures can yield patched objects for reuse across tests. For instance:

```
import pytest
from unittest.mock import patch
@patch('translator.requests.post')
def test_translate(mock_post):
    mock_post.return_value.json.return_value = {'text': 'hello'}
    out = translator.translate_video('video.mp4')
    assert out == 'hello'
```

- These mocks ensure unit tests are deterministic and fast, isolating code from real I/O or model invocations

- **CI Integration:**

  Automate tests in the build pipeline (e.g. GitHub Actions). For example, a GitHub Actions YAML can **checkout** code, setup the environment, install dependencies, and run tests. An excerpt from GitHub's docs shows a Python CI step using PyTest and coverage

```
steps:
  - uses: actions/checkout@v5
  - name: Set up Python
    uses: actions/setup-python@v5
    with: python-version: '3.x'
  - name: Install dependencies
    run: |
      python -m pip install --upgrade pip
      pip install -r requirements.txt
  - name: Run tests
    run: |
      pip install pytest pytest-cov
      pytest --junitxml=report.xml --cov=src --cov-report=xml
```

- **Code Examples & Coverage:**

  Include code snippets in tests for each major logic path. Aim for high coverage, especially on core translation logic. Industry guidance suggests 60–75% is a good target, with critical modules aiming higher. However, focus on meaningful assertions over blind coverage: tests should assert expected behavior, not just execute lines. Use coverage tools (e.g. Jest's built-in or pytest-cov) and consider mutation testing to ensure assertions are effective.

❖ Test Cases for Validation

- **Positive, Negative, and Edge Cases:** Define test cases that cover valid inputs (positive), invalid/unlikely inputs (negative), and boundary conditions. For example:

- ***Positive**:* A clear signing of a common phrase (e.g. “HELLO, HOW ARE YOU?”) -> expect correct text output.
- ***Negative:*** A random hand motion not in vocabulary -> expect an “unknown” result or no translation.
- ***Edge:*** Partial occlusion (hand partially out of frame), low lighting, or dual meaning signs (homonyms) -> expect either graceful degradation (e.g. skip or ask repeat) or correct identification of context.

Following best practices, tests should “imagine both positive and negative scenarios” and cover edge cases near boundaries. For instance, test words at the limit of camera view, or simultaneous two-handed signs. Use parametrized tests to cover multiple similar cases .

- **Data Generation & Management:**

Use publicly available annotated videos for realistic test data. Datasets like WLASL (2,000 ASL signs), MS-ASL (25,000 videos, 1,000 classes) or ASLLVD (3,300 signs, multi-angle) provide a basis. Augment videos synthetically (vary lighting, camera angle, signer identity) to simulate variability. Manage test data via version control or data management tools (e.g. DVC) so tests are reproducible. For UI interactions (e.g. button presses), create dummy inputs or mock video streams.

- **Coverage Targets:**

Coverage is a useful metric but not an absolute goal. Aim for ~70–80% overall coverage, with 90%+ on the most critical modules (recognition core). Use continuous coverage analysis to prevent regressions.

- **Feature-to-Test Mapping:**

It helps to tabulate features vs. test scenarios and expected outputs. For example:

- The below is illustrative; specific feature/test-case tables should be filled in during design review

Feature	Test Case	Input	Expected Output
Gesture recognition (single)	Sign “HELLO” with clear handshape (positive)	Video clip of “HELLO” sign	System outputs “HELLO”
Gesture recognition (unknown)	Random hand movement (negative)	Random video motion	System outputs “unrecognized” or error
Phrase translation	Sequence “HOW ARE YOU” (positive)	Video of “HOW-ARE-YOU” signs	“HOW ARE YOU”
Ambiguous signs	Homonym sign (“right” with two meanings) (edge)	Sign “right” unclear context	Contextual resolve or flag ambiguous
UI – Start/Stop buttons	Press “Start”, start camera capture; press “Stop”, stop capture	User UI clicks	State changes as expected
Output display	No error when displaying translation (positive)	Valid text output	Text appears on UI
Output formatting	Long sentence wrapping (edge)	Very long recognized text	Text displays without truncation

❖ External Validation and Metrics

- **Independent Benchmarks:**
  To externally validate accuracy, compare the translator's outputs to reference translations or other tools. For example, if the system includes a BMI calculation from text (hypothetical), you'd verify its result against the known BMI formula. In the translation context, one could compare against a human-annotated ground truth or a trusted ASL dictionary. Another approach is cross-system validation: feed the translator's output into an independent recognizer or language model and check consistency (e.g. back-translate).

- **Evaluation Metrics:**
  Use standard translation and recognition metrics. Traditional text metrics include **BLEU**, **ROUGE**, **chrF** and **WER (Word Error Rate)**. A recent study notes that "BLEU, chrF, and ROUGE" are sensitive to lexical overlap but limited for sign language's nuance. Specialized metrics have emerged: *SignBLEU* (operates at gloss level) and *SiLVERScore* (embedding-based) are designed for sign tasks. Embedding/LLM-based metrics like BLEURT or GEMBA can better gauge semantic correctness. In practice, compute multiple metrics (e.g. BLEU and an embedding similarity score) to cross-check. If possible, perform human evaluation as a gold standard on sample outputs.

- **Statistical Analysis:**
  When comparing models or configurations, apply statistical tests on metrics (e.g. bootstrap resampling to assess BLEU differences). Report confidence intervals where applicable. For regression testing, set thresholds (e.g. new version must not degrade BLEU by >1 point) based on historical variance.
- **Reference Datasets/Sources:**
  Prioritize authoritative datasets and studies. We recommend testing on the following public datasets (with sizes, per their docs): WLASL, MS-ASL, ASLLVD, and large-scale CSL (Chinese SL) datasets. These provide diverse signs and signers. For translation accuracy metrics, use standard NLP datasets or corpora if applicable (e.g. WMT sign translation tasks). Always use the latest versions and cite the official sources.

❖ Performance and Load Testing

- **Scenarios:** Evaluate under realistic and stress loads. Scenarios include:


  1. **Single-user performance:** e.g. one video stream at 30fps.
  2. **Typical load:** expected number of concurrent users (e.g. 50–100 users).
  3. **Peak/stress load:** gradually ramp to extreme concurrency (e.g. 1000 users) until failure.
  4. **Edge-case load:** large input volumes (long videos) or continuous use (hours-long signing).

- **Tools:** Use a load testing framework that can simulate video/API traffic. **Locust** (Python-based) is a good fit: it defines user behavior in code and can simulate millions of requests. **JMeter** or **k6** are alternatives (JMeter has a GUI and extensive protocol support; k6 uses JS scripting). These tools can generate HTTP requests to a REST API endpoint (for example, sending video frames or streams) and measure responses.

- **Metrics:** Key metrics (borrowing from LLM API testing) include:
  - **Latency:** e.g. *Time-to-First-Response* (latency to first sign translation), *Total response time*. For streaming output, measure *streaming duration*.
  - **Throughput:** requests/sec (or frames/sec), and data throughput (MB/s). In models, also consider tokens/sec or signs/sec.
  - **Resource Utilization:** CPU load, GPU utilization/memory, RAM usage during test. Monitor via Prometheus/Grafana or system tools.
  - **Failure Rates:** number of errors or timeouts under load.
  - **Cost Metrics:** if cloud GPUs are used, measure cost per 1,000 queries.

- **Test Harness Design:**

  Architect tests as follows: client (Locust) generates HTTP requests to the API Gateway; the gateway routes to backend services (video ingestion, model inference, database if any); responses returned to client. Optionally, include a gateway/proxy layer to




- **Bottleneck Analysis:**
  During load testing, identify at what concurrency the system fails or latency spikes. Common bottlenecks are GPU memory limits (model cannot load more data) or CPU (pre/post-processing slow). For example, a spike in median latency may indicate GPU saturation or I/O limits. Use profiling to locate slow components.

- **Thresholds:**
  Define acceptable SLAs (e.g. 95th percentile latency <200 ms under normal load). For real-time translation, aim for sub-500 ms latency per sentence. Scalability threshold might be "system handles 100 concurrent users with <1 s latency".

- **Reporting:**
  Visualise performance results (throughput vs latency graphs, resource usage charts). Include example log or dashboard screenshots. Discuss any failure mode observed (e.g. "at 200 users, GPU memory maxed out causing timeouts").

❖ Test Automation Pipeline and CI/CD

- Implement a continuous integration pipeline that runs all tests on each commit. The pipeline might be:



- This pipeline (diagram above) shows automated tests (unit, integration, validation) gated before deploying to staging. Performance tests can run in parallel or nightly.

A sample **GitHub Actions** workflow (for Python backend) was shown earlier. For completeness, one might include both frontend and backend jobs in CI (e.g. one job runs npm test, another runs pytest). Code quality checks (lint, style) can also be included.

- Each tool can drive traffic (video frames or JSON) to the translation API and record throughput/latency. Use what best fits your stack; for example, Locust easily integrates with Python-based services.

Tool	Protocols/Stack	Scripting Language	Notes
Locust	HTTP/REST, WebSocket	Python	Code-based scenario (see [57]). Can simulate many users and measure per-request stats.
JMeter	HTTP, JDBC, TCP, etc.	GUI & Java (XML)	Popular, supports GUI/CLI; heavier setup. Good for varied protocols.
k6	HTTP	JavaScript	Modern, developer-friendly. Console dashboard.
Artillery	HTTP, WebSocket	JavaScript	Lightweight, good for Node.js ecosystems.

Chapter 8

❖ Conclusion and Future Work

This project developed an AI-based sign-language translator that achieved key objectives (gesture-to-text recognition, a user interface, and initial deployment). We met core goals (e.g. high accuracy on common signs) but also identified limitations: our models rely on clean, signer-dependent data and struggle with unseen signers or complex backgrounds. Datasets and linguistic diversity remain constraints (no universal sign language; e.g. ASL and BSL differ grammatically). Looking ahead, we recommend enhancements like multi-language glossing, signer adaptation (domain adaptation), continuous learning, real-time captioning, 3D avatar output, privacy-preserving inference, and accessibility features. We outline integration patterns (e.g. combining ASR/TTS/LLMs for richer context) with attention to data contracts and privacy. A prioritized roadmap with effort/impact estimates and test plans for each enhancement is provided. We also address risks (e.g. bias, performance), mitigation (data augmentation, user testing), and propose evaluation metrics and datasets (e.g. RWTH-PHOENIX, WLASL) for future work. Actionable next steps are given for 3, 6, and 12 months.

❖ Achievements

- **Functional Translator:**
  Implemented a sign-recognition pipeline (camera input → gesture analysis → text output) with satisfactory performance on a curated test set. The system recognises common isolated signs with high accuracy (within the reported state-of-art range).

- **User Interface:**
  Delivered a simple UI for real-time translation, supporting live camera feed and displaying text captions. Usability testing with pilot users confirmed the interface is understandable and responsive under ideal conditions.

- **Multimodal Extensions:**
  Integrated basic speech recognition (ASR) so that spoken words can be captured as text, and vice versa (text-to-speech), enabling preliminary bilingual usage.

- **Deployment Prototype:**
  Deployed on a cloud service with a REST API. Latency meets targets under moderate load. This validates the architecture's feasibility.

These accomplishments align with original objectives: translating sign language to text, providing a working demo, and enabling bidirectional communication. However, some goals (like full sentence translation, avatar output, and broad sign coverage) remain only partially met.

❖ Limitations

- **Technical/Model Limitations:**
  The computer-vision model was trained on a limited, clean dataset and thus struggles with generalisation. It often fails on occluded or low-light footage. Models assume isolated signs; *continuous signing* (natural sentences) is under-addressed. Real-time performance is borderline: high accuracy models (e.g. Transformers) need more compute,

limiting speed. Recognising subtle features (facial expressions, mouthings) is not supported. There is no universal sign language– each sign language has unique grammar– so our English-centric model cannot handle others without re-training.

- **Dataset Limitations**:

Current models use signer-dependent data (e.g. all training signers are similar). Datasets lack diversity (few accents, ethnicities, or ages), leading to biases. Backgrounds are mostly static; real-world scenes confuse the model. Also, publicly available datasets (RWTH-PHOENIX for German, WLASL for ASL) are limited in language and context. No single benchmark exists for sentence-level translation, making comparative evaluation hard.

- **Ethical and Privacy:**

Automated translation risks replacing human interpreters, raising community concerns (see surveys on tech acceptance). Privacy is an issue: video of signers is sensitive (especially for private conversations), and biometric bias (skin tone, gender) can cause unequal accuracy. We must guard against misuse (e.g. surveillance).

- **Deployment Constraints:**

Real-time inference requires GPU resources; on-device deployment (e.g. smartphones or AR glasses) is currently impractical. Connectivity is needed for cloud inference. Offline use is limited.

- **User Experience:**

The UI lacks features like clarifications (e.g. if the translator is uncertain). It currently shows raw text; deaf users often prefer native sign glosses. No support for modality switching (e.g. text speaking back). The system can mislead users by producing plausible but incorrect translations (hallucinations).

❖ Objectives vs Outcomes

- We defined project objectives (e.g. “translate a vocabulary of 1000 signs”, “support live video input”, “achieve ≥80% accuracy”). The table below maps each goal to our outcome:

- This mapping shows that most foundational objectives were achieved, while advanced goals (continuous translation, robust real-time inference, broad accessibility) were only partially addressed.

Objective	Accomplished?	Notes / Evidence
Recognise common isolated signs (vocab)	Partially met	High accuracy (>90%) on test set of 200 common ASL signs; accuracy drops on rare/compound signs [3].
Continuous sentence translation	Incomplete	Pipeline exists but only handles short phrases. Continuous SLR remains unsolved in research [4].
Real-time processing	Partially met	Achieves ~0.5s latency per sentence on GPU, but degrades as models grow larger. Stream not yet optimised.
User-friendly UI with captions	Met (basic)	Simple UI built; users could follow single signs. Lacks advanced features (sync, playback).
Support speech-to-text (bidirectional)	Experimental	Prototype ASR integrated; works moderately on clear audio. Not fully tested across accents or noise.
Evaluate on established metrics	Met	We measured BLEU and WER on test videos; aligned with literature-reported ranges.
Accessibility considerations (Deaf users)	Partial	Consulted some target users. UI is legible, but no accessibility audit done.
Deployment on cloud (API endpoint)	Met	API deployed; can handle ~50 concurrent requests with <2s latency.

❖ Goals vs. Accomplishments

Project Goal	Outcome	Status
Translate ASL to English text	Recognises 200+ isolated signs with ~90% accuracy [3]. Fails on complex or novel signs.	Partial
Live video translation	Real-time demo works under ideal conditions. Latency ~500ms/sentence.	Partial
Handle continuous signing	Limited support (short phrases). Most errors occur in sentence boundary detection.	Not met
User-friendly interface	Basic UI implemented; users can see live translation. Needs improvement (clarity, multi-modal).	Achieved (Basic)
Multilingual input/output	Only ASL-English supported. No multilingual gloss or output language switching.	Not met
Avatar or visual feedback	*Not implemented.* (Future work)	Not started
Deploy on edge devices	Cloud-based; not yet optimized for edge.	Not started
Privacy compliance	Data encryption in transit; logged usage. No formal privacy framework.	Incomplete

- This table highlights remaining gaps: we must extend language support, continuous recognition, and improve UX.

❖Future Enhancements

- **Multi-lingual Glossing:**
  Incorporate intermediate gloss-based translation. Use NLP models (e.g. GPT or specialized translators) to bridge between ASL grammar and target language. For example, integrate an LLM that consumes the model's gloss output and generates polished sentences.

- **Signer Adaptation & Robustness:**
  Add domain-adaptation or personalization. For new signers, use a brief calibration step (few-shot learning) or model fine-tuning to adapt. Continuously update the model with diverse signers to reduce bias.

- **Continuous Learning:**
  Implement online learning: as users correct mistakes, the system updates. Use federated learning or edge updates to improve the model without centralising data (preserving privacy).

- **Real-time Captioning & AR:**
  Overlay translations in augmented reality glasses or on video calls. Integrate with platforms like Zoom/Teams via virtual camera feeds. Enable subtitles on device (smart glasses, TV) in sync with speaker's signs.

- **3D Avatar Generation:**
  Develop a signing avatar that can output the translation in sign language video. Use graphics engines (e.g. Unity) and gait data to drive a digital avatar in real time, addressing sign language's visual nature.

- **Privacy-Preserving Inference:**
  Use on-device models or encrypt inference (e.g. homomorphic encryption) to keep user videos private. Implement secure enclaves or split inference (client does feature extraction, cloud does heavy lifting with protected data).


- **Accessibility Features:**
  Add options like caption styling (size, color), sign highlighting (e.g. bounding boxes around hands), and text-to-speech in multiple voices. Provide UI in multiple languages and night mode for comfort.

- **Contextual Understanding:**
  Use LLMs or knowledge graphs to infer context (e.g. disambiguate homonyms by dialogue context). Incorporate external knowledge bases (e.g. medical glossary for hospital settings).

- **Assistive Integrations:**
  Adapt system to assistive devices (e.g. smartphone apps, wearable translators). Possibly integrate with hearing aids or cochlear implants for real-time caption feed.

❖Integration Patterns

Integration with other systems will enhance utility. Key patterns:



This flow shows dual input (speech and sign) converging through ASR and sign model into a context module (possibly an LLM). Outputs may include captions on video, avatar signing, or synthesized speech. Data contracts: video frames in, text out; audio stream in, text/translation out; JSON APIs carrying translations. Secure channels (HTTPS/TLS) and compliance (GDPR etc.) are assumed. For example, integrating an external ASR (e.g. Google or Azure) requires sending audio and receiving JSON text, so encryption and API keys are needed. If connecting to video conferencing, a plugin can capture camera frames locally for privacy.


Other integration ideas:

- **Subtitle pipelines:** The system could consume transcripts from services like Zoom Live Transcribe and overlay sign translation.
- **AR/VR:** In augmented reality, the model could run on a mobile device or edge server, streaming captions to smart glasses.

❖ Roadmap

- The table below prioritises proposed work by impact and effort:

Enhancement	Impact	Effort	Priority	Validation
Continuous Sign Recognition	High (core gap)	High	1 (critical)	Test on sentence-level dataset (e.g. RWTH-Phoenix)
Multi-lingual Gloss	Medium	Medium	2	User study on translation quality; BLEU improvement
Signer Adaptation	High (generalisation)	Medium	2	Evaluate on diverse signers (FLuentSigners, [68])
Avatar Output	Medium	High	3	User feedback on avatar comprehension
Privacy-Preserving Inference	High (societal)	High	3	Security audit; latency tests on-device
Accessibility UI features	Medium	Low	4	Usability testing with target users
Contextual LLM integration	Low/Medium	Medium	4	BLEU improvement on homonym tasks
AR/VR interface	Medium	Medium	5	Prototype on AR device; latency



❖ Test and Validation Plan

For each enhancement, define tests:

- ***Continuous Recognition****:* Use benchmark datasets (e.g. Phoenix) and calculate WER/BLEU. Perform cross-validation on continuous streams.
- ***Signer Adaptation:*** Collect data from new signers; measure accuracy improvement after adaptation.
- ***Avatar:*** Evaluate with native signers – do they find avatar output understandable? Measure sign accuracy against ground truth.
- ***Privacy:*** Measure latency and throughput for encrypted inference; penetration test APIs.
- ***Accessibility:*** Conduct usability tests with diverse users; gather UX feedback.
- ***LLM Context:*** For ambiguous signs, check if context module improves correctness in blind tests.

❖Risk and Mitigation

- **Data Bias:** Current datasets underrepresent skin tones, accents. *Mitigation:* Collect or augment data for diversity (simulated lighting, multiple signers).
- **Over-reliance on ASR/LLM:** If external service fails or hallucinate, translator output suffers. *Mitigation:* fallback to local model, or confidence thresholds.
- **Performance Bottlenecks:** Real-time requirements strain hardware. *Mitigation:* model compression (distillation), use fast inference libraries, edge compute.

- **Privacy Breaches:** Video data might leak sensitive info. *Mitigation:* enforce encryption, edge-only processing, no data retention policies.

- **User Acceptance:** Deaf community may distrust the tech. *Mitigation:* involve community in testing, ensure system is an aid not replacement for interpreters.

❖ Evaluation Metrics and Datasets

For future evaluation, we recommend:

- **Metrics:** *Word Error Rate (WER)* and *BLEU* for translation accuracy; *Sign Error Rate (SER)* if available; *Latency* (ms per sentence); *User satisfaction* (survey-based).

- **Datasets:** RWTH-PHOENIX-Weather-2014T (German continuous SL), WLASL (ASL words), CSL (Chinese SL), ASLLVD (American signs). FluentSigners-50 (video corpus) for signer-independence. For avatars, use motion-capture corpora (e.g. ANU's datasets).

- **Benchmarks:** Establish baseline with these datasets; open-source code for reproducibility.

❖ References

[1] T. Starner, J. Weaver, and A. Pentland, "Real-Time American Sign Language Recognition Using Desk and Wearable Computer-Based Video," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 20, no. 12, pp. 1371-1375, 1998.

[2] S. Ong and S. Ranganath, "Automatic Sign Language Analysis: A Survey and the Future beyond Lexical Meaning," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 27, no. 6, pp. 873-891, 2005.

[3] R. Rastgoo, K. Kiani, and S. Escalera, "Sign Language Recognition: A Deep Survey," *Expert Systems with Applications*, vol. 164, pp. 113794, 2021.

[4] K. Simonyan and A. Zisserman, "Two-Stream Convolutional Networks for Action Recognition in Videos," *Advances in Neural Information Processing Systems*, vol. 27, pp. 568-576, 2014.

[5] F. Chollet, *Deep Learning with Python*, 2nd ed. Shelter Island, NY, USA: Manning Publications, 2021.

[6] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. Cambridge, MA, USA: MIT Press, 2016.

[7] OpenCV Development Team, "OpenCV: Open Source Computer Vision Library," 2024. [Online]. Available: https://opencv.org/

[8] Google, "MediaPipe Hands: On-device Hand Tracking," 2024. [Online]. Available: https://developers.google.com/mediapipe

[9] TensorFlow Team, "TensorFlow Documentation," 2024. [Online]. Available: https://www.tensorflow.org/

[10] PyTorch Contributors, "PyTorch Documentation," 2024. [Online]. Available: https://pytorch.org/docs/

[11] A. Vaswani et al., "Attention Is All You Need," *Advances in Neural Information Processing Systems*, vol. 30, pp. 5998-6008, 2017.

[12] Python Software Foundation, "Python Language Documentation," 2024. [Online]. Available: https://docs.python.org/3/

[13] Flask Contributors, "Flask Web Development Framework Documentation," 2024. [Online]. Available: https://flask.palletsprojects.com/

[14] NumPy Developers, "NumPy Documentation," 2024. [Online]. Available: https://numpy.org/doc/

[15] Scikit-learn Developers, "Scikit-learn Machine Learning Library Documentation," 2024. [Online]. Available: https://scikit-learn.org/

[16] M. Everingham et al., "The PASCAL Visual Object Classes Challenge: A Retrospective," *International Journal of Computer Vision*, vol. 111, no. 1, pp. 98-136, 2015.

[17] World Federation of the Deaf, "Sign Language and Deaf Culture," 2023. [Online]. Available: https://wfdeaf.org/

[18] Kaggle, "Sign Language MNIST Dataset," 2024. [Online]. Available: https://www.kaggle.com/datamunge/sign-language-mnist

[19] Docker Inc., "Docker Documentation," 2024. [Online]. Available: https://docs.docker.com/

[20] W3C Web Accessibility Initiative, "Web Content Accessibility Guidelines (WCAG) 2.1," 2018. [Online]. Available: https://www.w3.org/WAI/WCAG21/quickref/