



```
C:\>ping 192.168.2.1

Pinging 192.168.2.1 with 32 bytes of data:

Request timed out.
Reply from 192.168.2.1: bytes=32 time=32ms TTL=127
Reply from 192.168.2.1: bytes=32 time=16ms TTL=127
Reply from 192.168.2.1: bytes=32 time=20ms TTL=127

Ping statistics for 192.168.2.1:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 16ms, Maximum = 32ms, Average = 22ms

C:\>|
```

Physical **Config** Desktop Programming Attributes

Wireless0	
Port Status	<input checked="" type="checkbox"/> On
Bandwidth	18 Mbps
MAC Address	0002.16B2.6416
SSID	buhg
<b>Authentication</b>	
<input type="radio"/> Disabled	<input checked="" type="radio"/> WEP
<input type="radio"/> WPA-PSK	<input type="radio"/> WPA2-PSK
<input type="radio"/> WPA	<input type="radio"/> WPA2
<input type="radio"/> 802.1X	Method:
WEP Key: 1234567890	
PSK Pass Phrase:	
User ID:	
Password:	
Method: MD5	
User Name:	
Password:	
Encryption Type: 40/64-Bits (10 Hex digits)	
<b>IP Configuration</b>	
<input type="radio"/> DHCP	
<input checked="" type="radio"/> Static	
IPv4 Address: 192.168.1.1	
Subnet Mask: 255.255.255.0	
<b>IPv6 Configuration</b>	
<input checked="" type="radio"/> Automatic	
<input type="radio"/> Static	
IPv6 Address:	
Link Local Address: FE80::202:16FF:FE82:6416	

PC1

PhysicalConfigDesktopProgrammingAttributes

GLOBAL

Settings

Algorithm Settings

INTERFACE

Wireless0

Bluetooth

Wireless0

Port Status

On

Bandwidth

24 Mbps

MAC Address

0001.4359.E723

SSID

it

Authentication

☐ Disabled

☐ WEP

☐ WPA

☐ 802.1X

☒ WPA2-PSK

☐ WPA2

Method:

WEP Key

PSK Pass Phrase

QWERTY123

User ID

Password

MD5

User Name

Password

Encryption Type

AES

IP Configuration

☐ DHCP

☒ Static

IPv4 Address

192.168.2.1

Subnet Mask

255.255.255.0

IPv6 Configuration

☒ Automatic

☐ Static

IPv6 Address

/

Link Local Address

FE80::201:43FF:FE59:E723

Top

