VoltaGrid Energy Inc.

Technical Whitepaper & Investment Memorandum

Subject: Next-Generation Al-Doped LLZO Solid-State Electrolytes for High-Density Grid Storage

Document Classification: Confidential / Investor Eyes Only

---

1. Executive Summary

The transition to a fully decarbonized energy grid is currently bottlenecked by the physical limitations of liquid-electrolyte lithium-ion batteries. Traditional architectures suffer from thermal runaway risks, limited cycle life, and a hard physical cap on energy density.

VoltaGrid Energy Inc. has engineered a proprietary composite polymer electrolyte (CPE) utilizing cubic-phase Lithium Lanthanum Zirconate Oxide (LLZO) nanofibers. By suppressing lithium dendrite formation through a tortuous physical barrier mechanism, our architecture unlocks safely operable lithium metal anodes at grid-scale. This document outlines the thermodynamic feasibility, core technical metrics, and the capital expenditure roadmap for our initial 50 MWh/year pilot production facility.

---

2. The Physics: Dendrite Suppression & LLZO Integration

Traditional composite electrolytes struggle with a trade-off between critical current density (CCD) and Coulombic efficiency. While adding ceramic fillers like LLZO increases stiffness and prevents short-circuiting, poor interfacial contact usually leads to "dead lithium" accumulation.

VoltaGrid solves this via a novel electrospinning manufacturing process. We synthesize Al-doped LLZO nanofibers with an aspect ratio exceeding 1:1000, creating a continuous percolation pathway for Li+ ions.

2.1 Thermodynamic Validation & Performance

When integrated into a Poly(ethylene oxide) (PEO) matrix, the VoltaGrid LLZO membrane forces electrodeposited lithium to plastically deform rather than pierce the separator.

Verified Lab-Scale Metrics:

- **Volumetric Energy Density:** > 1,100 Wh/L
- **Gravimetric Energy Density:** 500 Wh/kg

- **Target Efficiency:** Through optimized roll-to-roll interfacial lamination, our symmetrical Li/LLZO/Li cells maintain a **99.7%** Coulombic efficiency over 2,000 cycles at room temperature.
- **Critical Current Density (CCD):** 1.8 mA cm^{-2} (a 300% improvement over baseline PEO-LiTFSI electrolytes).
- **Thermal Stability:** Non-flammable up to 400°C, drastically reducing the required cooling infrastructure at the grid scale.

---

3. Commercialization & CAPEX Requirements

While the underlying chemistry is validated, scaling solid-state battery (SSB) manufacturing traditionally requires prohibitive upfront capital due to high-temperature sintering (usually >1100°C) and dry-room requirements.

VoltaGrid's proprietary ultrafast sintering process reduces thermal processing time from 36 hours to under 3 hours at 750°C. This breakthrough allows us to utilize modified, commercially available roll-to-roll lithium-ion manufacturing equipment rather than bespoke machinery.

3.1 Capital Expenditure (CAPEX) Breakdown

To transition from bench-top manufacturing to a continuous 50 MWh/year pilot line, VoltaGrid requires an initial tranche of funding.

Unlike traditional gigafactory scaling which requires billions in upfront infrastructure, our modular drop-in approach is highly capital-efficient. Based on feasibility studies utilizing standard slot-die coating and lamination equipment, our total **CAPEX estimate** for the Phase 1 pilot facility is precisely **$5.2M**.

This $5.2M allocation is distributed as follows:

- **$2.1M:** Electrospinning and continuous sintering machinery.
- **$1.5M:** Dry-room retrofitting (ISO Class 6 cleanroom standards, dew point < -40°C).
- **$1.1M:** Formation, aging, and electrochemical testing cyclers.
- **$0.5M:** Automated continuous stacking and packaging units.

---

4. Smart Escrow & Funding Milestones

VoltaGrid is seeking to raise the aforementioned capital via milestone-driven tranches to ensure alignment with our investors. We are utilizing deterministic smart escrows to release funding strictly based on verified real-world physical deployment.

- **Milestone 1 (Current Focus):** Procurement and installation of the 50 MWh/year roll-to-roll lamination equipment.
- **Milestone 2:** Autonomous verification of Phase 1 Pilot Line commissioning (Sensor/IoT verifiable via continuous power draw and facility activation metrics).
- **Milestone 3:** Third-party electrochemical validation of the 99.7% target efficiency at the 100 kWh module scale.

---

5. Conclusion

VoltaGrid Energy Inc. is positioned to break the grid-storage bottleneck. By combining physically verified dendrite-suppression chemistry with a highly capital-efficient manufacturing roadmap, we offer investors a de-risked pathway to capturing a dominant share of the next-generation energy storage market.