04 · Crash Recovery

Kill the worker at the worst possible moment, restart it, and every action still reaches a known state or an honest UNKNOWN.

The problem


A worker can die anywhere: a deploy, an out-of-memory kill, `kill -9`, a power cut. There are three crash windows around a provider call, and from the database they look **identical**:

Crash point	Request sent?	Effect applied?	What the DB shows
after the claim, before sending	no	no	`IN_FLIGHT`, open attempt
during the HTTP call	maybe	maybe	`IN_FLIGHT`, open attempt
after the response, before recording it	yes	yes (if 2xx)	`IN_FLIGHT`, open attempt

Recovery therefore cannot tell them apart, and it must not pretend to. It treats all three as **ambiguous** and hands them to the same policy that handles timeouts (doc 02).

Detecting a dead worker: leases

A worker never "holds" an action indefinitely. When it claims one, it writes `lease_owner = <worker id>` and `lease_expires_at = now + lease_seconds` (15 s by default). If the worker is still alive, it finishes well within that time, because `Settings` refuses any configuration where `lease_seconds <= 2 × provider_timeout_seconds`. If the lease expires and the action is still `IN_FLIGHT`, the worker is presumed dead.



The recovery algorithm

`Worker.recover()` in `oneshot/worker.py` runs on startup **and before every step**, so a long-running worker also adopts the work of a peer that died:

1. `ActionStore.expired_in_flight()` : find `IN_FLIGHT` actions whose `lease_expires_at` is in the past.
2. `ActionStore.take_over(id, me)` : a conditional UPDATE (`… WHERE status='IN_FLIGHT' AND lease_expires_at < now`). Only one recovering worker can win, and it fails harmlessly if the original worker finished at the last moment.
3. Close the open attempt with outcome `CRASHED` , then call `policy.after_ambiguous()` : * idempotent type, key still remembered: `PENDING` , same-key retry; * lookup available: `VERIFYING` after the settle window; * otherwise: `UNKNOWN` .

Verifications that were interrupted (an open `verify` attempt) need no special handling. `claim_next` re-claims a `VERIFYING` action whose lease expired and closes the abandoned lookup as `LOOKUP_FAILED` . Lookups are read-only, so repeating one is always safe.

Fencing: a slow worker must not overwrite a newer decision

A lease expiring does not prove the worker is dead; it may only be stalled (a long garbage-collection pause, a suspended laptop, `SIGSTOP`). If it wakes up after another worker took over, its result is stale. `ActionStore.apply_decision()` therefore re-checks `lease_owner = me` inside the write transaction and raises `LeaseLost` otherwise. The worker logs `DISCARDED` and moves on (`test_worker_that_lost_its_lease_cannot_record_a_result`).

This protects **OneShot's records**. It cannot recall a request the stalled worker has *already sent*. For idempotent endpoints that is harmless (same key). For non-idempotent ones it is gap 4 in doc 03.

Making crashes testable: failpoints

Random `kill -9` testing finds bugs but cannot reproduce them. `oneshot/failpoints.py` provides *deterministic* crash points: set `ONESHOT_FAILPOINTS=after_response` (or `before_send`) and the worker calls `os._exit(70)` at exactly that line. That is a hard exit with no cleanup and no `finally` blocks, just like `kill -9`. The same idea is used in production systems such as etcd (`gofail`) and TiKV (`fail-rs`).

The integration tests use both kinds of crash. Failpoints give exact placement; a real `SIGKILL` sent while the request is in the air (`test_sigkill_mid_request_is_recovered`) gives real-world timing. `test_many_actions_survive_repeated_worker_crashes` crashes three workers in a row over six actions and then checks that every action is `SUCCEEDED` with exactly one provider effect.

Because each worker runs as a **separate process** (`oneshot/worker_process.py`), these crashes are genuine. The test runner survives and inspects the wreckage.

Observed: the demo `worker-crash` scenario

```
$ python -m oneshot demo worker-crash
# captured 2026-11-03 by scripts/capture_outputs.py (exit code 0)

──────────────────────────────────────────── OneShot demo ────────────────────────────────────────────
Each scenario uses a fresh provider process with its own ledger, a fresh OneShot database, and real
worker processes. Faults are injected at the provider (or as failpoints in the worker).
Working directory: $TMPDIR/oneshot-demo-upin1_xq

1/1  worker-crash: OneShot's worker crashes after the provider applied the charge ──────────────────
  > agent POST /actions Idempotency-Key=agent-order-1006 -> HTTP 201 act_7e58578c3a18: charge
cus_ada 42.00 USD
  > start worker process #1 with failpoint after_response
  > worker process #1 DIED with exit code 70 (failpoint crash)
  After the crash: OneShot says IN_FLIGHT; provider ledger has 1 effect(s).
  [PASS] crash left the action IN_FLIGHT while the provider had applied it
  > start worker process #2 (fresh)
  > worker process #2 (fresh) finished: every action is SUCCEEDED, FAILED or UNKNOWN (exit 0)
  OneShot's record (event timeline):
  act_7e58578c3a18  charge cus_ada 42.00 USD  SUCCEEDED
    +  0.00s (new) -> PENDING  accepted and durably recorded
    +  0.07s PENDING -> IN_FLIGHT  attempt 1: claimed by worker-88952, intent recorded before
sending
    +  3.09s IN_FLIGHT -> PENDING  recovered: worker worker-88952 was lost during attempt 1
(crash/kill/stall); the request may or may not have reached the provider; outcome unknown -> retry
in 0.30s with the SAME idempotency key (provider deduplicates, so a retry cannot double-apply)
    +  3.44s PENDING -> IN_FLIGHT  attempt 2: claimed by worker-88953, intent recorded before
sending
    +  3.45s IN_FLIGHT -> SUCCEEDED  provider confirmed: replayed original result (provider
deduplicated) as eff_00001
  Provider's side of the story (its log):
```

```
    POST /v1/charges ref=act_7e58578c3a18 key=act_7e58578c3a18 mode=success -> APPLIED eff_00001,
responding 201
    POST /v1/charges ref=act_7e58578c3a18 key=act_7e58578c3a18 -> REPLAY of stored response (no new
effect)
  Provider's independent ledger:
    act_7e58578c3a18: 1 effect(s) ['eff_00001']
  [PASS] act_7e58578c3a18 is SUCCEEDED and provider ledger has 1 effect(s) (observed: SUCCEEDED, 1)
  Lesson: The worker recorded its intent BEFORE sending. After the crash the action is stuck
IN_FLIGHT; a new worker waits for the lease to expire, treats the attempt as ambiguous, and retries
with the same key.

Scorecard (every expectation checked
against the provider's real ledger)
```

scenario	checks	time	result
worker-crash	2/2	3.5s	PASS

Observed: all end-to-end scenario tests (including crash tests)

```
$ python -m pytest -v tests/test_scenarios.py
# captured 2026-11-03 by scripts/capture_outputs.py (exit code 0)

====================================== test session starts ======================================
collecting ... collected 25 items

tests/test_scenarios.py::test_happy_path PASSED                                          [  4%]
tests/test_scenarios.py::test_transient_failures_are_retried_with_backoff PASSED         [  8%]
tests/test_scenarios.py::test_permanent_rejection_is_not_retried PASSED                  [ 12%]
tests/test_scenarios.py::test_provider_unreachable_is_safe_to_retry_and_ends_failed PASSED   [ 16%]
tests/test_scenarios.py::test_ambiguous_charge_is_retried_with_same_key_and_applied_once[lost_response]
PASSED [ 20%]
tests/test_scenarios.py::test_ambiguous_charge_is_retried_with_same_key_and_applied_once[timeout] PASSED
[ 24%]
tests/test_scenarios.py::test_ambiguous_charge_is_retried_with_same_key_and_applied_once[slow_success]
PASSED [ 28%]
tests/test_scenarios.py::test_lost_response_message_is_verified_not_resent PASSED        [ 32%]
tests/test_scenarios.py::test_timed_out_message_is_verified_absent_then_resent_once PASSED   [ 36%]
tests/test_scenarios.py::test_duplicate_slips_through_when_provider_is_slower_than_settle_window PASSED [
40%]
tests/test_scenarios.py::test_same_key_retry_is_not_attempted_once_provider_may_have_forgotten_the_key
PASSED [ 44%]
tests/test_scenarios.py::test_misconfigured_retention_window_causes_a_duplicate PASSED   [ 48%]
tests/test_scenarios.py::test_worker_crash_after_provider_applied_is_recovered_without_duplicate PASSED [
52%]
tests/test_scenarios.py::test_worker_crash_before_send_on_message_is_verified_then_sent_once PASSED [
56%]
tests/test_scenarios.py::test_sigkill_mid_request_is_recovered PASSED                    [ 60%]
tests/test_scenarios.py::test_many_actions_survive_repeated_worker_crashes PASSED        [ 64%]
tests/test_scenarios.py::test_provider_crash_and_outage_lead_to_unknown_then_reconciliation_resolves
PASSED [ 68%]
tests/test_scenarios.py::test_unknown_with_no_effect_is_resolved_failed PASSED           [ 72%]
tests/test_scenarios.py::test_wiping_oneshot_database_cannot_erase_provider_evidence PASSED  [ 76%]
tests/test_scenarios.py::test_agent_retrying_with_new_key_creates_duplicate_that_reconciliation_flags
PASSED [ 80%]
tests/test_scenarios.py::test_reconciliation_dry_run_changes_nothing PASSED              [ 84%]
tests/test_scenarios.py::test_reconciliation_fails_loudly_when_provider_is_down PASSED   [ 88%]
tests/test_scenarios.py::test_settings_reject_lease_shorter_than_timeout PASSED          [ 92%]
tests/test_scenarios.py::test_error_after_apply_charge_is_retried_and_replayed_once PASSED   [ 96%]
tests/test_scenarios.py::test_error_after_apply_message_is_verified_not_resent PASSED    [100%]

====================================== 25 passed in 27.61s ======================================
```

Protects against: worker crashes and kills at any point (before, during or after the provider call); stuck `IN_FLIGHT` work after a crash; a stalled worker overwriting the decision of its successor; two recovering workers adopting the same action; provider crashes (actions become VERIFYING/UNKNOWN and are resolved when it returns).

Cannot protect against: loss of the database itself; clock jumps (leases use wall-clock time, and a clock moving backwards can make a lease look valid for too long, or forwards, expire too early); a stalled worker's already-sent request to a non-idempotent provider (leases are not fencing tokens that the *provider* can check). Recovery is also not instant: it takes up to `lease_seconds` to notice a dead worker. That is the price of not mistaking a slow worker for a dead one.

Design decisions and alternatives

- **Leases with expiry, not heartbeats.** A heartbeat (renewing the lease periodically) allows long-running attempts, but every attempt here is bounded by the HTTP timeout. A fixed lease that is longer than the timeout is simpler and has fewer moving parts. Heartbeats are a sensible addition if attempts ever become long (ROADMAP).
- **Rejected: holding a database row lock across the HTTP call.** This ties DB locks to network latency, blocks other work, and a crashed process still leaves the outcome unknown. You need the lease *and* the ambiguity handling anyway.
- **Rejected: distributed locks (for example a Redis lock).** That is another system to run, and without fencing tokens it has the same "stalled holder" problem; see Martin Kleppmann, *How to do distributed locking* (2016).
- **Fencing tokens** (a monotonically increasing number the *provider* checks) would close gap 4 completely, but they require provider support that most third-party APIs lack. For idempotent endpoints, the idempotency key plays that role.

Self-check questions

1. Why does recovery treat "crashed before sending" as ambiguous, even though nothing was sent?
2. Why must `lease_seconds` be more than twice `provider_timeout_seconds`?
3. Worker A stalls for 30 s after receiving a 201, worker B takes over and retries with the same key. What happens to A's result when it wakes?
4. What is the difference between a failpoint and `kill -9`, and why use both?
5. How long can it take, at most, for a dead worker's action to be picked up again with the default settings?

Answers. (1) From the database the three crash points look the same. Assuming "not sent" would be a guess, and if wrong it causes a duplicate. (2) So a live worker always finishes (its request times out) well before its lease expires and it gets mistaken for dead. (3) `apply_decision` sees `lease_owner = B` and raises `LeaseLost`; A's result is discarded. B's retry got a replay of the same effect, so nothing is lost or duplicated. (4) A failpoint crashes at an exact line, so it is reproducible; `kill -9` crashes at a real, random moment, so it is realistic. Together they give coverage and confidence. (5) About `lease_seconds` (15 s) plus one poll interval, once some worker is running.