06 · The Fake Provider

A small, deliberately flaky external service with its own permanent record, so that failures are real and evidence is independent.

Why a fake, and why this kind

OneShot must never touch real money or real APIs. But mocking HTTP *inside* the test process (with a mocking library) cannot reproduce the failures that matter here: a server that commits and then dies, a connection closed without a response, a request still running after the client gave up, evidence that survives a restart. So the fake provider is a **real server in its own process**:

- built on the standard library's `http.server`, which gives direct control of the socket. A "lost response" really closes the TCP connection without writing a byte; a "crash" really calls `os._exit`;
- with its **own SQLite ledger file**, written only by itself, as the outside record for reconciliation;
- controlled by a test-only **admin API** that scripts which failure the next request will hit.

API

Endpoint	Behaviour
`POST /v1/charges`	Validates `amount_cents`, `currency`, `customer`. **Honours** `Idempotency-Key` (reserve, apply, complete; replay on repeat; 409 while in progress; 422 if the same key comes with a different body). Customer `cus_declined` always gets 402.
`POST /v1/messages`	Validates `to`, `body`. **Ignores** `Idempotency-Key`, like many legacy SMS and email APIs.
`GET /v1/effects[?reference=]`	Lists applied effects (all, or for one reference). Used for verification and reconciliation.
`GET /healthz`	Liveness.
`POST/GET/DELETE /_admin/faults`	Push, inspect or clear scripted fault rules (test scaffolding).

Run it standalone: `uv run fakeprovider --port 8701 --db var/provider.db [--idempotency-ttl SECONDS]`.

Failure modes

`FaultMode`	Effect applied?	What the caller observes
`success`	yes	`201` with effect id
`decline`	no	`402 {"applied": false}`
`unavailable`	no	`503 {"applied": false}`
`timeout`	no	nothing until the client's timeout fires; then the provider drops the connection
`lost_response`	**yes**	connection closed with no response

`FaultMode`	Effect applied?	What the caller observes
`slow_success`	**yes, after a delay**	usually a client timeout, then the effect lands later
`crash_before_apply`	no	connection reset; the provider process is gone
`crash_after_apply`	**yes**	connection reset; the provider process is gone
`error_after_apply`	**yes**	`500` (added as the worked example in doc 07)


Notice how `timeout` and `lost_response` look **identical** to the caller while having opposite outcomes. `crash_before_apply` and `crash_after_apply` do too. Each `FaultMode` declares `applies_effect`, and `test_fault_mode_applies_effect_exactly_as_declared` checks that the declaration matches what the server actually does, for every mode.

Rules are consumed first-in, first-out. Each rule can be limited to an `endpoint` or a `reference`, and repeated `times`. For example:

```
curl -X POST localhost:8701/_admin/faults \
     -d '[{"mode":"unavailable","times":2},{"mode":"lost_response","endpoint":"/v1/messages"}]'
```

Replays, 409s and 422s are answered before a fault rule is consumed, so faults apply only to requests that would actually be processed.

How the provider implements idempotency



Key details, all in `fakeprovider/ledger.py`:

- **The effect and the key's completion are one transaction** (`ProviderLedger.apply_effect`). After any crash, the key is "completed" if and only if the effect exists. A retry can never be replayed a success that did not happen, nor processed twice.
- **Abandoned reservations are cleared at startup** (`clear_abandoned_reservations`). An `in_progress` key that survived a restart belongs to a request that provably did not apply, because of the point above. Without this, a key could stay "in progress" forever after a crash.
- **Keys expire** after `idempotency_ttl_seconds`; an expired key is treated as new. This is realistic (providers do not keep keys forever) and is the root of the retention-window rule in doc 02.
- `synchronous=FULL`: the ledger is the evidence, so it must survive power loss.
- `unavailable` and `timeout` *release* the reservation (the request did nothing, so a retry should be processed); `decline` *completes* it with the 402 (a retry gets the same answer).

Observed: provider contract tests

```
$ python -m pytest -v tests/test_fake_provider.py
# captured 2026-11-03 by scripts/capture_outputs.py (exit code 0)

==================================== test session starts =====================================
collecting ... collected 14 items

tests/test_fake_provider.py::test_success_records_effect_in_ledger PASSED                    [  7%]
tests/test_fake_provider.py::test_same_idempotency_key_replays_without_new_effect PASSED     [ 14%]
tests/test_fake_provider.py::test_key_reused_with_different_body_is_rejected PASSED          [ 21%]
tests/test_fake_provider.py::test_messages_endpoint_ignores_idempotency_keys PASSED          [ 28%]
tests/test_fake_provider.py::test_decline_and_unavailable_apply_nothing PASSED               [ 35%]
tests/test_fake_provider.py::test_unavailable_releases_key_so_retry_can_succeed PASSED       [ 42%]
tests/test_fake_provider.py::test_lost_response_applies_effect_but_client_sees_disconnect PASSED [ 50%]
tests/test_fake_provider.py::test_timeout_applies_nothing_but_client_cannot_tell PASSED      [ 57%]
tests/test_fake_provider.py::test_slow_success_applies_after_client_gave_up PASSED           [ 64%]
tests/test_fake_provider.py::test_crash_after_apply_keeps_evidence_across_restart PASSED     [ 71%]
tests/test_fake_provider.py::test_crash_before_apply_leaves_no_effect_and_frees_key PASSED   [ 78%]
tests/test_fake_provider.py::test_expired_idempotency_key_allows_a_duplicate PASSED          [ 85%]
tests/test_fake_provider.py::test_every_fault_mode_is_documented_as_applying_or_not PASSED   [ 92%]
tests/test_fake_provider.py::test_error_after_apply_returns_500_but_effect_exists PASSED     [100%]

==================================== 14 passed in 5.11s ======================================
```

What the fake provider makes possible: reproducible, real-socket, real-process failures; independent, durable evidence of what happened; idempotency semantics close to well-known payment APIs (reserve, replay, 409 in progress, 422 on mismatch, finite retention).

What it does not model: any specific real provider exactly; authentication, rate limits, webhooks, partial failures inside multi-step operations, network partitions *between* provider replicas, or eventual consistency in its lookup endpoint (its lookup is strongly consistent, which makes verification easier than in some real systems). It is single-node and stores everything in one file.

Design decisions and alternatives

- **stdlib `http.server` instead of FastAPI** for the provider: FastAPI/uvicorn abstracts the socket away, so "close the connection without a response" or "die mid-request" would need hacks. `ThreadingHTTPServer` handles concurrent requests (needed for the 409-while-in-progress case) with about 300 lines of readable code.
- **Scripted faults instead of random chaos** for the demo and most tests: every scenario is reproducible. Randomness is still exercised, with a fixed seed, in `test_guarantees_hold_under_random_fault_sequences`.
- **An in-memory fault queue**: it is test scaffolding, not evidence. Only the ledger must survive restarts.

Self-check questions

1. Why would an HTTP mocking library be insufficient for testing `crash_after_apply`?
2. What would go wrong if the provider inserted the effect and completed the idempotency key in two separate transactions?
3. Why does `unavailable` release the key reservation while `decline` completes it?

4. Which two pairs of fault modes are indistinguishable to the caller?
5. Why are abandoned `in_progress` keys safe to delete at startup?

Answers. (1) A mock raises an exception inside the client process; it cannot kill a separate server after it committed, so it cannot show evidence surviving a crash. (2) A crash between them could leave an effect with no completed key (a retry would apply it again) or a completed key with no effect (a retry would replay a success that never happened). (3) A 503 means "try again", so the retry must be processed; a decline is final, so retries should get the same answer. (4) `timeout` / `lost_response` and `crash_before_apply` / `crash_after_apply`. (5) Completion is atomic with the effect, so an in-progress key after a restart proves its effect was never applied.