




## System

### Jenkins Home-Verzeichnis ☐

By default, Jenkins stores all of its data in this directory on the file system

C:\Users\P.Karuppannan\.jenkins 

### Willkommensmeldung

This message will be displayed at the top of the Jenkins main page. This can be useful for posting notifications to your users

Nur Text [Vorschau](#)

### Anzahl der Build-Prozessoren

2

### Labels

### Auslastung ☐

Diesen Knoten so viel wie möglich verwenden

### Ruheperiode ☐

5

### Anzahl der SCM-Checkout Wiederholungen

0

☐ Namenskonventionen für Jobnamen erzwingen

## Jenkins Location

Jenkins URL ☐

http://localhost:8080/

Bitte verwenden Sie einen konkreten Hostnamen anstelle von `localhost`.

E-Mail-Adresse des Systemadministrators ☐

prakash.karuppannan@s-s-t.de

## Serve resource files from another domain

Resource Root URL ☐

Without a resource root URL, resources will be served from the Jenkins URL with Content-Security-Policy set.

## Globale Eigenschaften

- ☐ Schwellwerte für die Festplattenspeicherplatzüberwachung
- ☐ Umgebungsvariablen
- ☐ Verzeichnisse von Hilfsprogrammen anpassen
- ☐ Verzögertes Löschen auf diesem Knoten deaktivieren ☐

## Metrics

Access keys ☐

Add new access key

## Pipeline Speed / Durability

## Default Speed / Durability Level ☐

None: use pipeline default (Maximum survivability/durability but slowest)

Writes data with every step, using atomic writes for integrity. Provides maximum ability to retain running pipeline data and resume in the event of a Jenkins failure.

## Usage Statistics

Helfen Sie Jenkins zu verbessern, indem Sie anonyme Nutzungsstatistiken und Absturzprotokolle an das Jenkins-Projekt senden. ☐

## Folder

### Health Metrics

List of default health metrics for Folders

Hinzufügen

## HTTP Proxy Configuration

Setup

## Global Build Time Out

☐ Enable Global Time Out

## Develocity Build Scans

☐ Enable enriched summary ☐

## Develocity integration

☐ Enable auto-injection

## Timestamper

Systemzeitformat ☐

'<b>HH:mm:ss'</b> '

Laufzeitformat ☐

'<b>HH:mm:ss.S'</b> '

☐ Enabled for all Pipeline builds ☐

## Fingerprints

☐ Disable Fingerprint Cleanup

## Administrative monitors configuration

Administrative monitors 

## Global Build Discarders

### Project Build Discarder

Build discarders configured for a job are only run after a build finishes. This option runs jobs' configured build discarders periodically, applying configuration changes even when no new builds are run. This option has no effect if there is no build discarder configured for a job.

Hinzufügen 


## Default notification URL

Notification URL ☐

Default

## GitHub

### GitHub Servers ☐

Add GitHub Server 

Erweitert 



Edited

---

## GitHub API usage

### Github API usage rate limiting strategy ☐

Normalize API requests

---

## GitHub Enterprise Servers

Hinzufügen

---

## Global Trusted Pipeline Libraries

Sharable libraries available to any Pipeline jobs running on this system. These libraries will be trusted, meaning they run without "sandbox" restrictions and may use @Grab.

Hinzufügen

---

## Global Untrusted Pipeline Libraries

Sharable libraries available to any Pipeline jobs running on this system. These libraries will be untrusted, meaning they run with "sandbox" restrictions and cannot use @Grab.

Hinzufügen

## Build-timeout Plugin > BuildStep Action

☐ Enable BuildStep Action ☐

### Git plugin

Global Config user.name Value ☐

Global Config user.email Value ☐

☐ Create new accounts based on author/committer's email ☐

☐ Use existing account with same email if found ☐

☐ Show the entire commit summary in changes ☐

☐ Hide credential usage in job output ☐

☐ Disable performance enhancements ☐

☐ Preserve second fetch during checkout ☐

☐ Add git tag action to jobs ☐

### Shell

Speichern

Übernehmen

Shell Interpreter Befehl ☐

### Extended E-mail Notification

#### SMTP server

SMTP Port

465

Erweitert ^

 Edited

Credentials

prakashece69@gmail.com/\*\*\*\*\*

+ Add

☒ Use SSL

☐ Use TLS

☐ Use OAuth 2.0

Advanced Email Properties

Default user e-mail suffix ☐

Erweitert v

 Edited

Default Content Type ☐

Plain Text (text/plain)

List ID ☐

☐ Add 'Precedence: bulk' E-mail Header ☐

prakashece69@gmail.com

Reply To List



prakashece69@gmail.com

Emergency reroute



Allowed Domains



Excluded Recipients



Default Subject



\$PROJECT\_NAME - Build # \$BUILD\_NUMBER - \$BUILD\_STATUS!

Maximum Attachment Size



-1

Default Content



\$PROJECT\_NAME - Build # \$BUILD\_NUMBER - \$BUILD\_STATUS:

Check console output at \$BUILD\_URL to view the results.



Default Pre-send Script



Default Post-send Script





Additional groovy classpath ☐

Hinzufügen

☐ Enable Debug Mode ☐

☐ Require Administrator for Template Testing ☐

☐ Enable watching for jobs ☐

☐ Allow sending to unregistered users ☐

Default Triggers ☐

Content Token Reference ☐

## E-Mail Benachrichtigung

### SMTP-Server

smtp.gmail.com

Standardendung für E-Mail-Adressen ☐

Erweitert ☐

 Edited

SMTP-Authentifizierung verwenden ☐

Benutzername

prakashece69@gmail.com

Kennwort



Concealed

[Change Password](#)

SSL verwenden ☐

**Use TLS****SMTP-Port** ☐

465

**Reply-To Adresse**

prakashece69@gmail.com

**Zeichensatz**

UTF-8

☐ E-Mail versenden, um Konfiguration zu testen