




System

Jenkins Home-Verzeichnis ☐

By default, Jenkins stores all of its data in this directory on the file system

C:\Users\P.Karuppannan\.jenkins 

Willkommensmeldung

This message will be displayed at the top of the Jenkins main page. This can be useful for posting notifications to your users

Nur Text [Vorschau](#)

Anzahl der Build-Prozessoren

2

Labels

Auslastung ☐

Diesen Knoten so viel wie möglich verwenden

Ruheperiode ☐

5

Anzahl der SCM-Checkout Wiederholungen

0

☐ Namenskonventionen für Jobnamen erzwingen

Jenkins Location

Jenkins URL ☐

http://localhost:8080/

Bitte verwenden Sie einen konkreten Hostnamen anstelle von `localhost`.

E-Mail-Adresse des Systemadministrators ☐

prakash.karuppannan@s-s-t.de

Serve resource files from another domain

Resource Root URL ☐

Without a resource root URL, resources will be served from the Jenkins URL with Content-Security-Policy set.

Globale Eigenschaften

- ☐ Schwellwerte für die Festplattenspeicherplatzüberwachung
- ☐ Umgebungsvariablen
- ☐ Verzeichnisse von Hilfsprogrammen anpassen
- ☐ Verzögertes Löschen auf diesem Knoten deaktivieren ☐

Metrics

Access keys ☐

Add new access key

Pipeline Speed / Durability

Default Speed / Durability Level ☐

None: use pipeline default (Maximum survivability/durability but slowest)

Writes data with every step, using atomic writes for integrity. Provides maximum ability to retain running pipeline data and resume in the event of a Jenkins failure.

Usage Statistics

Helfen Sie Jenkins zu verbessern, indem Sie anonyme Nutzungsstatistiken und Absturzprotokolle an das Jenkins-Projekt senden. ☐

Folder

Health Metrics

List of default health metrics for Folders

Hinzufügen

HTTP Proxy Configuration

Setup

Global Build Time Out

☐ Enable Global Time Out

Develocity Build Scans

☐ Enable enriched summary ☐

Develocity integration

☐ Enable auto-injection

Timestamper

Systemzeitformat ☐

'HH:mm:ss' '

Laufzeitformat ☐

'HH:mm:ss.S' '

☐ Enabled for all Pipeline builds ☐

Fingerprints

☐ Disable Fingerprint Cleanup

Administrative monitors configuration

Administrative monitors 

Global Build Discarders

Project Build Discarder

Build discarders configured for a job are only run after a build finishes. This option runs jobs' configured build discarders periodically, applying configuration changes even when no new builds are run. This option has no effect if there is no build discarder configured for a job.

Hinzufügen 

Default notification URL

Notification URL ☐

Default

GitHub

GitHub Servers ☐

Add GitHub Server 

Erweitert 

 Edited

GitHub API usage

Github API usage rate limiting strategy ☐

Normalize API requests

GitHub Enterprise Servers

Hinzufügen

Global Trusted Pipeline Libraries

Sharable libraries available to any Pipeline jobs running on this system. These libraries will be trusted, meaning they run without "sandbox" restrictions and may use @Grab.

Hinzufügen

Global Untrusted Pipeline Libraries

Sharable libraries available to any Pipeline jobs running on this system. These libraries will be untrusted, meaning they run with "sandbox" restrictions and cannot use @Grab.

Hinzufügen

Build-timeout Plugin > BuildStep Action

☐ Enable BuildStep Action ☐

Git plugin

Global Config user.name Value ☐

Global Config user.email Value ☐

☐ Create new accounts based on author/committer's email ☐

☐ Use existing account with same email if found ☐

☐ Show the entire commit summary in changes ☐

☐ Hide credential usage in job output ☐

☐ Disable performance enhancements ☐

☐ Preserve second fetch during checkout ☐

☐ Add git tag action to jobs ☐

Shell

Shell Interpreter Befehl ☐

Extended E-mail Notification

SMTP server

SMTP Port

Erweitert ^



Edited

Credentials

+ Add

☒ Use SSL

Use TLS



Use OAuth 2.0

Advanced Email Properties

Default user e-mail suffix



Erweitert v



Edited

Default Content Type



List ID



Add 'Precedence: bulk' E-mail Header



Default Recipients



prakash.karuppannan@s-s-t.de

Reply To List ☐

prakash.karuppannan@s-s-t.de

Emergency reroute ☐

Allowed Domains ☐

Excluded Recipients ☐

Default Subject ☐

\$PROJECT_NAME - Build # \$BUILD_NUMBER - \$BUILD_STATUS!

Maximum Attachment Size ☐

1

Default Content ☐

\$PROJECT_NAME - Build # \$BUILD_NUMBER - \$BUILD_STATUS:

Check console output at \$BUILD_URL to view the results.

Default Pre-send Script ☐

Default Post-send Script ☐

Additional groovy classpath ☐

Hinzufügen

☐ Enable Debug Mode ☐

☐ Require Administrator for Template Testing ☐

☐ Enable watching for jobs ☐

☐ Allow sending to unregistered users ☐

Default Triggers ☐

Content Token Reference ☐

E-Mail Benachrichtigung

Dashboard

Jenkins verwalten

System

smtp.gmail.com

Standardendung für E-Mail-Adressen ☐

Erweitert ☐

 Edited

SMTP-Authentifizierung verwenden ☐

Benutzername

jenkinscicd202x@gmail.com

Kennwort



Concealed

Change Password

SSL verwenden ☐

☐ Use TLSSMTP-Port

465

Reply-To Adresse

jenkinscid202x@gmail.com

Zeichensatz

UTF-8

☐ E-Mail versenden, um Konfiguration zu testen

Speichern

Übernehmen