



Disabling or otherwise ignoring warnings is an extraordinarily bad idea. It's a bit like unplugging the check engine light on your car's dashboard because it bothers you. Ignoring the problem doesn't make it go away. It doesn't mean that you can always fix the problem — for example, I chose to overlook the warnings in Chapter 31 about `stringstream` being deprecated — but you need to at least understand the warning. What you don't know will hurt you.

If your compiler has a Syntax Check from Hell mode, enable it.

Adopt a Clear and Consistent Coding Style

Writing your C++ code in a clear and consistent style not only enhances the readability of your program, but also it results in fewer coding mistakes. This somewhat surprising state of affairs results from the fact that our brains have only a limited amount of computing power. When you read code that is clean and neat and that follows a style you're familiar with, you spend very little brain power parsing the syntax of the C++ statements. This leaves more brain CPU power to decode what the program is trying to do and not how it's doing it.

A good coding style lets you do the following with ease:

- ✓ Differentiate between class names, object names, and function names
- ✓ Understand what the class, function, or object is used for based on its name
- ✓ Differentiate preprocessor symbols from C++ symbols (that is, `#define` objects should stand out)
- ✓ Identify blocks of C++ code at the same level (this is the result of consistent indentation)

In addition, you need to establish a standard module header format that provides information about the functions or classes in the module, the author (presumably, that's you), the date, the version, and something about the modification history.



All programmers involved in a single project should use the same coding style. A program written in a patchwork of different coding styles is confusing and looks unprofessional.

Comment the Code While You Write It

You can avoid errors if you comment your code while you write it rather than wait until everything works and then go back and add comments. I can understand not taking the time to write voluminous headers and function descriptions until later, but I have never understood not writing short comments as you are coding.

Have you ever had the experience of asking someone a question, and even as you got to the end of the question you knew the answer? Somehow formulating the question forced you to organize your thoughts sufficiently so that the answer became clear.

Writing comments is like that. Formulating comments forces you to take stock of what it is you're trying to do. Short comments are enlightening, both when you read them later and as you're writing them.

Write comments like you're talking to another, knowledgeable programmer. You can assume that the reader understands the basics of the program, so please don't explain how C++ works. There's no point in writing comments that explain how a `switch` statement works unless you're relying on some obscure point of the language (like the fall-through capability of the `switch` statement).

Single-Step Every Path in the Debugger at Least Once

It may seem like an obvious statement, but I'll say it anyway: As a programmer, it's important that you understand what your program is doing. It isn't sufficient that the program outputs the expected value. You need to understand everything your program is doing. Nothing gives you a better feel for what's going on under the hood than single-stepping the program with a good debugger (like the one that comes with Code::Blocks).

Beyond that, as you debug a program, you sometimes need raw material to figure out some bizarre behavior. Nothing gives you that material better than single-stepping through each function as it comes into service.

Finally, when a function is finished and ready to be added to the program, every logical path needs to be traveled at least once. Bugs are much easier to find when the function is examined by itself rather than after it has been thrown into the pot with the rest of the functions — and your attention has gone on to new programming challenges.

Limit the Visibility

Limiting the visibility of class internals to the outside world is a cornerstone of object-oriented programming. The class should be responsible for its internal state — if something gets screwed up in the class, then it's the class programmer's fault. The application programmer should worry about solving the problem at hand.

Specifically, limited visibility means that data members should not be accessible outside of the class — that is, they should be marked as protected. In addition, member functions that the application software does not need to know about should also be marked protected. Don't expose any more of the class internals than necessary to get the job done.

A related rule is that public member functions should trust application code as little as possible, even if the class programmer and the application programmer are the same person. The class programmer should act like it's a fact that the application programmer is a felonious hacker; if your programmer is accessible over the Internet, all too often this assumption is true.

Keep Track of Heap Memory

Losing track of heap memory is the most common source of fatal errors in programs that have been released into the field and, at the same time, the hardest problem to track down and remove (because this class of error is so hard to find and remove, it's prevalent in programs that you buy). You may have to run a program for hours before problems start to arise (depending upon how big the memory leak is).

As a general rule, programmers should always allocate and release heap memory at the same "level." If a member function `MyClass::create()` allocates a block of heap memory and returns it to the caller, then there should be a member `MyClass::release()` that returns it to the heap. Specifically, `MyClass::create()` should not require the parent function to release the memory.

If at all possible, `MyClass` should keep track of such memory pointers on its own and delete them in the destructor.

Certainly, this doesn't avoid all memory problems, but it does reduce their prevalence somewhat.

Zero Out Pointers after Deleting What They Point To

Sort of a corollary to the warning in the preceding section is to make sure that you zero out pointers after they are no longer valid. The reasons for this become clear with experience: you can often continue to use a memory block that has been returned to the heap and not even know it. A program might run fine 99 percent of the time, making it very difficult to find the 1 percent of cases where the block gets reallocated and the program doesn't work.

If you zero out pointers that are no longer valid and you attempt to use them to store a value (you can't store anything at or near location 0), your program will crash immediately. Crashing sounds bad, but it's not. The problem is there; it's merely a question of whether you find it or not before putting it into production.

It's like finding a tumor at an early stage in an x-ray. Finding a tumor early when it's easy to treat is a good thing. Given that the tumor is there either way, not finding it is much worse.

Use Exceptions to Handle Errors

The exception mechanism in C++ is designed to handle errors conveniently and efficiently. In general, you should throw an error indicator rather than return an error flag. The resulting code is easier to write, read, and maintain. Besides, other programmers have come to expect it, and you wouldn't want to disappoint them, would you?

Having said that, limit your use of exceptions to true errors. It is not necessary to throw an exception from a function that returns a "didn't work" indicator if this is a part of everyday life for that function. Consider a function `lcd()` that returns the least common denominator of its two arguments. That function will not return any values when presented with two mutually prime numbers. This is not an error and should not result in an exception.

Declare Destructors Virtual

Don't forget to create a destructor for your class if the constructor allocates resources such as heap memory that need to be returned when the object

reaches its ultimate demise. This rule is pretty easy to teach. What's a little harder for students to remember is this: Having created a destructor, don't forget to declare it virtual.

"But," you say, "My class doesn't inherit from anything, and it's not subclassed by another class." Yes, but it *could* become a base class in the future. Unless you have some good reason for not declaring the destructor virtual, then do so when you first create the class. (See Chapter 29 for a detailed discussion of virtual destructors.)

Provide a Copy Constructor and Overloaded Assignment Operator

Here's another rule to live by: If your class needs a destructor, it almost surely needs a copy constructor and an overloaded assignment operator. If your constructor allocates resources such as heap memory, the default copy constructor and assignment operator will do nothing but create havoc by generating multiple pointers to the same resources. When the destructor for one of these objects is invoked, it will restore the assets. When the destructor for the other copy comes along, it will screw things up.

If you are too lazy or too confused or you just don't need a copy constructor and assignment operator, then declare "do nothing" versions, but make them protected so that application software doesn't try to invoke them by accident. See Chapter 30 for more details. (The 2009 C++ standard allows you to delete both the default copy constructor and assignment operator, but declaring them protected works almost as well.)

Chapter 34

Ten Features Not Covered in This Book

In This Chapter

- ▶ The `goto` command
 - ▶ The ternary operator
 - ▶ Binary logic
 - ▶ Enumerated types
 - ▶ Namespaces
 - ▶ Pure virtual functions
 - ▶ The `string` class
 - ▶ Multiple inheritance
 - ▶ Templates and the Standard Template Library
 - ▶ The 2009 C++ Standard
-

The C++ language contains so many features that covering every one in a single book — especially a book intended for beginning programmers — is impossible. Fortunately, you don't need to master all of the features of the language in order to write big, real-world programs.

Nevertheless, you may want to look ahead at some of the features that didn't make the cut for this beginner's book, just in case you see them in other people's programs.

The goto Command

This command goes all the way back to C, the progenitor of C++. In principle, using this command is easy. You can place `goto label;` anywhere you

want. When C++ comes across this command, control passes immediately to the label, as demonstrated in this code snippet:

```
for(;;)
{
    if (conditional expression)
    {
        goto outahere;
    }
    // ...whatever you want...
}
outahere:
// ...program continues here...
```

In practice, however, `goto` introduces a lot of ways to screw up — many more than I can go into here. In any case, it didn't take long before programmers noticed that the two most common uses of the `goto` were to exit loops and to go to the next case within a loop. The C Standards Committee introduced `break` and `continue` and almost completely removed the need for the `goto` command. I can say that I've been programming in C and C++ for almost 20 years, and I've never had an application for a `goto` that I couldn't handle in some other way more clearly.

The Ternary Operator

The ternary operator is an operator unique to C and C++. It works as follows:

```
int n = (conditional) ? expression1 : expression2;
```

The `?` operator first evaluates the `conditional`. If the condition is true, then the value of the expression is equal to the value of `expression1`; otherwise, it's equal to the value of `expression2`.

For example, you could implement a `maximum()` function as follows:

```
int max(int n1, int n2)
{
    return (n1 > n2) ? n1 : n2;
}
```

The ternary operator can be applied to any type of numeric but cannot be overloaded. The ternary operator is truly an expression and not a control statement like an `if`.

Binary Logic

I chose to skip entirely the topic of binary arithmetic. Some readers will consider this scandalous. After all, how can you talk about programming without getting down to ones and zeros? It's not that I don't consider the topic worthwhile — it's just that I find explaining the topic properly takes many pages of text and leaves readers somewhat confused, when in practice it's rarely used. Google the topic once you feel comfortable with the basics of C++ programming.

Enumerated Types

This is a topic that barely missed the cut for inclusion in the book. The simple idea is that you can define constants and let C++ assign them values, as shown here:

```
enum Colors {BLACK, BLUE, GREEN, YELLOW, RED};  
Colors myColor = BLACK;
```

The problem with enumerated types lies in the implementation: Rather than create a true type, C++ uses integers. In this case, `BLACK` is assigned the value 0, `BLUE` is assigned 1, `GREEN` 2, and so on. This leads to special cases that make the topic not worth the trouble.



The 2009 Standard Library for C++ “fixed” this problem by creating true enumerated types, but it didn't do away with the integer version in order to retain compatibility with existing programs. The result is even more confusing than before.

Namespaces

It's possible to give different entities in two different libraries the same name. For example, the `grade()` function within the `Student` library probably assigns a grade, whereas the `grade()` function within the `Civil Engineering` library might set the slope on the side of a hill. To avoid this problem, C++ allows the programmer to place her code in a separate namespace. Thus, the `grade` within the `Student` namespace is different from the `grade` within `CivilEngineering`.

The namespace is above and beyond the class name. The `grade()` member function of the class `BullDozer` in the `CivilEngineering` namespace has the extended name `CivilEngineering::BullDozer::grade()`.



All library objects and functions are in the namespace `std`. The statement at the beginning of the program template using `namespace std;` says if you don't see the specified object in the default namespace, then go look in `std`. Without this I would have to include the namespace explicitly, as in the following snippet:

```
std::cout << "Hello, world!" << std::endl;
```

Pure Virtual Functions

You saw how to declare functions virtual in Chapter 29. What I didn't mention there is that you don't have to define a function declared virtual. Such an undefined function is known as a *pure virtual member function*. However, things get complicated. For example, a class with one or more pure virtual functions is said to be abstract and cannot be used to create an object (see what I mean?). Tackle this subject after you feel comfortable with virtual functions and late binding.

The string Class

This is another topic that barely missed the cut. Most languages include a `string` class as an intrinsic type for handling strings of characters easily. In theory, the `string` class should do the same for C++. In practice, however, it's not that simple. Because `string` is not an intrinsic type, the error messages that the compiler generates when something goes wrong are more like those associated with user-defined classes. For a beginner, these messages can be very difficult to interpret.



It's actually worse than I'm describing here — `string` isn't even a class. It's an instance of a template class. The error messages can be breathtaking.

Multiple Inheritance

I describe how to base one class on another using inheritance in Chapter 28. What I didn't mention there is that one class can actually extend more than one base class. This sounds simple but can get quite complicated when the two base classes contain member functions with the same name. Or worse, when both base classes are themselves subclasses of some common class. In fact, there are so many problems that arise that C++ is the only C-like language that supports multiple inheritance. Java and C#, both languages derived from C++, decided to drop support for multiple inheritance. I recommend that beginning programmers avoid the subject.

Templates and the Standard Template Library

The makers of C++ noticed how similar functions like the following are:

```
int max(int n1, int n2)
{
    if (n1 > n2)
    {
        return n1;
    }
    return n2;
}
double max(double n1, double n2)
{
    if (n1 > n2)
    {
        return n1;
    }
    return n2;
}
char max(char n1, char n2)
{
    if (n1 > n2)
    {
        return n1;
    }
    return n2;
}
```

I can almost imagine the scene: “Wouldn’t it be cool,” one said to another, “if we could replace the type with a pseudo-type `T` that we could define at compile time?” Before you knew it, templates were a part of C++:

```
template <class T> T max(T t1, T t2)
{
    if (t1 > t2)
    {
        return t1;
    }
    return t2;
}
```

Now the programmer can create a `max(int, int)` by replacing `T` with `int` and compiling the result, create a `max(double, double)` by replacing `T` with `double`, and so forth. The Standards Committee even released an entire library of classes, known as the Standard Template Library (STL for short), based upon template classes.

For a beginner, however, the subject of template classes starts to get syntactically very complicated. In addition, the errors that the compiler generates when you get a template instantiation wrong are bewildering to an expert, never mind a beginner. This is definitely a topic that needs to wait until you feel comfortable with the basic language.

The 2009 C++ Standard

The C++ Standard was released and agreed to in the late 1990s. Things changed relatively little in the ensuing years, but the demand for additions to the language grew until finally the 2009 Standard was released for comment in late 2008. The problem with this standard is that it introduces a lot of new features for which there seems to be very little demand. The standard is more than 1,400 pages. (Admittedly, it includes a lot of very dry, very repetitive library definitions, but even so, that C++ is not a small language any more.) As of this writing (early 2010), no compilers implement the full 2009 standard.

Appendix

About the CD

In This Appendix

- ▶ System requirements
 - ▶ Using the CD with Windows, Linux, and Mac
 - ▶ What you'll find on the CD
 - ▶ Troubleshooting
-

This section describes the CD-ROM enclosed in the back of *Beginning Programs with C++ for Dummies*. All readers will appreciate the source code to the programs that appear in the book — using this code can save you a lot of typing. In addition, 32-bit Windows users will welcome the Code::Blocks C++ development environment coupled with the GNU C++ compiler ready to be installed on Windows 2000, Windows XP, Windows Vista, or Windows 7. (Macintosh, Linux, and 64-bit Windows users can download Code::Blocks from www.codeblocks.org.)

System Requirements

Make sure that your computer meets the minimum system requirements shown in the following list. If your computer doesn't match up to most of these requirements, you may have problems using the software and files on the CD. For the latest and greatest information, please refer to the ReadMe file located at the root of the CD-ROM.

- ✓ A PC running Microsoft Windows or Linux with kernel 2.4 or later
- ✓ A Macintosh running Apple OS X or later
- ✓ An Internet connection (only required for downloading versions of Code::Blocks for Macintosh or Linux)
- ✓ A CD-ROM drive

If you need more information on the basics, check out these books published by Wiley Publishing, Inc.: *PCs For Dummies* by Dan Gookin; *Macs For Dummies* by Edward C. Baig; *iMacs For Dummies* by Mark L. Chambers; and *Windows XP*

For Dummies, *Windows Vista For Dummies*, and *Windows 7 For Dummies*, all by Andy Rathbone.

Using the CD

These steps will help you install the items from the CD to your hard drive:

1. Insert the CD into your computer's CD-ROM drive.

The license agreement appears.

Note to Windows users: The interface won't launch if you have autorun disabled. In that case, choose Start→Run. (For Windows Vista, choose Start→All Programs→Accessories→Run.) In the dialog box that appears, type **D:\Start.exe**. (Replace *D* with the proper letter if your CD drive uses a different letter. If you don't know the letter, see how your CD drive is listed under My Computer.) Click OK.

Note for Mac Users: When the CD icon appears on your desktop, double-click the icon to open the CD and double-click the Start icon.

Note for Linux Users: The specifics of mounting and using CDs vary greatly between different versions of Linux. Please see the manual or help information for your specific system if you experience trouble using this CD.

2. Read through the license agreement and then click the Accept button if you want to use the CD.

The CD interface appears. The interface allows you to browse the contents and install the programs with just a click of a button (or two).

3. Copy the C++ source code onto your hard disk.

You can view the source code on the CD-ROM but you cannot build or execute programs there.

4. Windows users will want to install the Code::Blocks environment.

Chapter 2 takes you through step-by-step instructions on how to install Code::Blocks and how to create your first program.

What You'll Find on the CD

The following sections are arranged by category and provide a summary of the software and other goodies you'll find on the CD. If you need help with installing the items provided on the CD, refer to the installation instructions in the preceding section.

For each program listed, I provide the program platform (Windows or Mac) plus the type of software. The programs fall into one of the following categories:

- ✓ *Shareware programs* are fully functional, free, trial versions of copyrighted programs. If you like particular programs, register with their authors for a nominal fee and receive licenses, enhanced versions, and technical support.
- ✓ *Freeware programs* are free, copyrighted games, applications, and utilities. You can copy them to as many computers as you like — for free — but they offer no technical support.
- ✓ *GNU software* is governed by its own license, which is included inside the folder of the GNU software. There are no restrictions on distribution of GNU software. See the GNU license at the root of the CD for more details.
- ✓ *Trial, demo, or evaluation* versions of software are usually limited either by time or functionality (such as not letting you save a project after you create it).

CPP programs

For all environments. All the examples provided in this book are located in the `Beginning_Programming-CPP` directory on the CD and work with Macintosh, Linux, Unix, and Windows and later computers. These files contain the sample code from the book. Each example program is in its own folder. For example, the Conversion program is in:

```
Beginning_Programming-CPP\Conversion
```

For Windows. I have built a set of workspace and set of project files for Code::Blocks that allows you to recompile all the programs in the book with a single mouse click. The `AllPrograms.workspace` file is located in the `Beginning_Programming-CPP` folder. (See Chapter 2 for an explanation of Code::Blocks Project files.) You **must** copy the source code from the CD-ROM onto your hard disk before you use it.

Code::Blocks development environment

For Windows. Code::Blocks is an “open source, cross platform” freeware environment designed to work with a number of different compilers. The version included on the CD-ROM is bundled with the GNU gcc C++ compiler (version 4.4) for 32-bit versions of Windows (if you don’t know whether your Windows is 32-bit or not, it almost certainly is). Code::Blocks is supported by “The Code::Blocks Team/” You can find more information at www.codeblocks.org.

For non-Windows. You can download a version of Code::Blocks that works for your operating system at www.codeblocks.org. They’ve got versions of Code::Blocks for just about every environment short of the iPhone.

Troubleshooting

I tried my best to compile programs that work on most computers with the minimum system requirements. Alas, your computer may differ, and some programs may not work properly for some reason.

I include Code::Blocks workspace and project files for the included C++ source. This allows you to recompile all the programs with literally a single click. However, these project files assume that the programs are installed in the directory `C:\\Beginning_Programming-CPP`. You'll have to set up your own project files if you decide to install the source code in a different directory.

Other common problems are that you don't have enough memory (RAM) for the programs you want to use, or you have other programs running that are affecting installation or running of a program. If you get an error message such as `Not enough memory` or `Setup cannot continue`, try one or more of the following suggestions and then try using the software again:

- ✓ **Turn off any antivirus software running on your computer.** Installation programs sometimes mimic virus activity and may make your computer incorrectly believe that it's being infected by a virus.
- ✓ **Close all running programs.** The more programs you have running, the less memory is available to other programs. Installation programs typically update files and programs; so if you keep other programs running, installation may not work properly.
- ✓ **Have your local computer store add more RAM to your computer.** This is, admittedly, a drastic and somewhat expensive step. However, adding more memory can really help the speed of your computer and allow more programs to run at the same time.

Customer Care

If you have trouble with the CD-ROM, please call Wiley Product Technical Support at 800-762-2974. Outside the United States, call 317-572-3993. You can also contact Wiley Product Technical Support at <http://support.wiley.com>. Wiley Publishing will provide technical support only for installation and other general quality control items. For technical support on the applications themselves, consult the program's vendor or the author at www.stephendavis.com.

To place additional orders or to request information about other Wiley products, please call 877-762-2974.

Index

• *Numbers* •

- 0 (zero)
 - importance in debugging, 247
 - using with decimal point, 154
- 1GB, measurement of, 10

• *Symbols* •

- + (addition) operator, order of precedence, 52
- && (AND) logical operator, explained, 79
- > (arrow) operator, using, 270
- %= (assignment) operator, order of precedence, 52
- *= (assignment) operator, order of precedence, 52
- += (assignment) operator, order of precedence, 52
- = (assignment) operator, order of precedence, 52
- = (assignment) operator, order of precedence, 52
- * (asterisk), using with pointer variable, 188
- \ (backslash)
 - special symbol for, 66
 - use with filenames, 66
- \\ (backslash), indicating in Windows/DOS, 365
- | (binary OR) operator, using, 368
- { } (braces)
 - using, 72–73
 - using with classes, 224–225
- : (colon) syntax, using with variables, 320
- , (comma) operator, using, 113–115
- (decrement) operator
 - order of precedence, 52
 - prefix and postfix versions, 55–56
 - using, 54–55
- / (division) operator, order of precedence, 52
- " (double quotes)
 - special symbol for, 66
 - using with characters, 65
- == (equality) operator, explained, 70
- = (equals sign), using with variables, 49–50
- > (greater than) operator, meaning of, 70
- >= (greater than or equal to) operator, meaning of, 70
- ++ (increment) operator
 - order of precedence, 52
 - prefix and postfix versions, 55–56
 - using, 54–55
- != (inequality) operator, meaning of, 70
- << (left-shift) operator, role in stream I/O, 363
- < (less than) operator, meaning of, 70
- <= (less than or equal to) operator, meaning of, 70
- % (modulo) operator, order of precedence, 52–53
- * (multiplication) operator, order of precedence, 52
- (negative) operator
 - order of precedence, 52
 - using, 54–55
- ! (NOT) operator
 - explained, 79
 - using with streams, 377
- || (OR) logical operator, explained, 79
- () (parentheses)
 - combining for operators, 54
 - using with pointers and arrays, 206
 - using with pointers to objects, 270
- # (pound sign)
 - use with binary operators, 56–57
 - using with include files, 133
- >> (right-shift) operator, role in stream I/O, 363
- ; (semicolon), missing, 40–41
- ' (single quotes)
 - interpreting, 66
 - special symbol for, 66
 - using with characters, 65
- (subtraction) operator, order of precedence, 52
- ? (ternary operator), using, 406
- ~ (tilde), using with destructors, 297
- _ (underscore), using with variable names, 48

• A •

abstraction

level of, 254–255

relationship to classification, 256

access function, example of, 285

addition (+) operator, order of precedence, 52

algorithm

converting into program, 13–16

creating for “human computer,” 11–12

AmbiguousBinding program, 346–347, 350–351

AND (&&) logical operator, explained, 79

applications. *See* programs

ArgOutOfRange class, creating, 392–394

arguments

arrays of, 216–221

defaulting to constructors, 311

defining constructors with, 303–307

passing by reference, 193–195

passing by values, 190–193

passing from Code::Blocks, 219–220

passing through command line, 217–219

passing through Windows, 220–221

passing to functions, 123–126

promoting, 163

arithmetic, calculation speeds, 155–156.

See also mathematical operators

array length, specifying, 372–373

array pointers, using, 210–212

ArrayDemo program, 168–170

arrays. *See also* ASCIIZ array; parallel

arrays; pointers; variables

of arguments, 216–221

ASCII-zero character array, 173–174

computing size of, 198

declaring, 166–167

destroying to heap, 307

fixed-size, 197

indexing into, 167–168

initializing, 171–172

of objects, 226–227

overview of, 165–166

performing Bubble Sort on, 232–233

versus pointers, 214

of pointers, 215–216

retaining scores’ input in, 168–171

tracking amount of data in, 174

use of, 172

using `displayAverage()` function with, 170

using `for` loop with, 171

arrow syntax, using with pointers to objects, 270

ASCII character set, 60–62

ASCIIZ array. *See also* arrays

declaring and initializing, 174–175

string manipulation functions, 182–183

ASCIIZ string

copying, 198

terminating, 386

ASCII-zero character array, 173–174

assembler instructions, example from `Conversion` program, 18

assembly language, explained, 17

assignment operators

as destructors, 358

orders of precedence, 52

overloading, 356–358, 362

overloading to avoid bugs, 404

in `StudentAssignment` program, 361

using, 56–57

using with classes, 226

asterisk (*), using with pointer variable, 188

• B •

backslash (\)

special symbol for, 66

use with filenames, 66

backslash (\ \), indicating in Windows/DOS, 365

backup file, creating, 375–376

`bad()` function, returning for `fstream` object, 369

base 8, explained, 65

base 16, coding characters in, 66

`Beginning_Programming-CPP` folder

accessing, 33

subfolders in, 35

bell, special symbol for, 66

binary data, writing, 368

binary logic, omission of, 407

binary mode, using, 369, 377

binary operators

format of, 70

order of precedence, 52

- using # (pound sign) with, 56–57
- using in expressions, 51–53
- binary OR (`|`) operator, using, 368
- binary versus text mode, 368
- binding. *See* EarlyBinding program; LateBinding program
- birth year, using nested `if` statement with, 76–78
- bits, defined, 188
- `bool` methods, using with `fstream` classes, 373–374
- `bool` type, using in expressions, 75
- `boolalpha` flag, explained, 378
- braces (`{}`)
 - using, 72–73
 - using with classes, 224–225
- BranchDemo program, executing, 70–72
- `break` statement
 - adding during debugging, 146
 - necessity of, 104
 - using, 84–85
 - using with loops, 102–104
- breakpoints, setting in debugger, 240
- Bubble Sort. *See also* class objects performing, 232–233 using with class objects, 227
- buffer
 - adding newline to, 380
 - avoiding overflow of, 372–373
- bug avoidance. *See also* debugging; errors; exceptions
 - commenting code while writing, 401
 - declaring destructors virtual, 403–404
 - enabling error messages, 399–400
 - enabling warnings, 399–400
 - limiting visibility of class internals, 402
 - providing copy constructor, 404
 - providing overloaded assignment operator, 404
 - single-stepping paths in debugger, 401
 - tracking heap memory, 402
 - using exceptions to handle errors, 403
 - using good coding style, 400
 - zeroing out pointers, 403
- Build step, performing, 38
- byte, defined, 188

• C •

- C++
 - as high level language, 19–20
 - managing compile time errors, 40
 - rules, 40
 - syntax, 37
 - uppercase versus lowercase, 37, 84
- C++ programs, programs required for, 21. *See also* programs
- C++ Standard, release of, 410
- cache, flushing, 380
- calculator, implementing via `switch` statement, 85–87
- `calculator()` function
 - debugging, 148
 - displaying line numbers for, 146
 - testing, 141–143
- CalculatorError program, error message in, 147. *See also* SwitchCalculator program
- CalculatorError1 program, debugging, 139–141
- CalculatorError2 program, 144–145
- carriage return, special symbol for, 66
- casts, using in character encoding, 64
- `catch` keyword, using in exception mechanism, 387–389
- `catch(...)` phrase, using, 391
- `.cbp` extension, use in `Code::Blocks`, 27, 35
- CD-ROM
 - `Code::Blocks` IDE, 413
 - CPP programs, 413
 - demo software, 413
 - evaluation software, 413
 - freeware programs, 413
 - GNU software, 413
 - shareware programs, 413
 - trial software, 413
 - troubleshooting, 414
 - using, 41, 412
- Celsius to Fahrenheit conversion code, 18–19
- `cerr` object
 - versus `cout`, 365
 - use of, 364–365
- `char` keyword, using, 59

- char methods, using with `fstream`
 - classes, 373–374
- char type, number of bits in, 188
- char variable
 - contents of, 188
 - explained, 159
 - limitations of, 67
- char versus int values, 64
- character encoding
 - example of, 63–65
 - using casts in, 64
- character variables, defining, 59. *See also* variables
- characters. *See also* garbage characters
 - applying true/false values to, 75
 - encoding, 60–63
 - encoding strings of, 65
 - printable versus unprintable, 62–63
 - using double quotes (") with, 65
 - using single quotes (') with, 65
- `cin`, extracting from, 364
- class internals, limiting visibility of, 402
- class members
 - declaring as friends, 288
 - naming, 262–263
- class objects, initializing, 226, 289. *See also* Bubble Sort
- classes
 - assignment operators, 226
 - creating instances of, 225
 - declaring, 225
 - definition, 224
 - format of, 224
 - inheriting from, 340
 - naming rules for, 225
 - versus objects, 225
 - public keyword, 224–225
 - struct keyword, 225
 - use of open brace {}, 224–225
- `clear()` function, calling for `fail()` flag, 369
- COBOL (Common Business Oriented Language), 18–19
- code, commenting while writing, 401
- CodeBlocks, lengths of addresses in, 189
- Code::Blocks IDE
 - availability on CD-ROM, 413
 - Beginning_Programming-CPP folder, 27, 32
 - Build command, 30
 - .cbp extension, 27, 35
 - command line, 30
 - Console Application, 27
 - `cout`, 30
 - creating folders, 28
 - creating projects, 27–29
 - downloading, 23, 413
 - environment, 26
 - "Hello, world!" message, 32
 - HelloWorld project, 28–29
 - installing, 23–25
 - .layout extension, 27
 - main.cpp file, 30
 - organizing projects in, 35
 - passing arguments from, 219–220
 - Run command, 32
 - selecting C++ as language choice, 27–28
 - setting up subfolders, 29
 - starting, 26
 - Step Into command, 242
 - terminated status of process, 30–31
 - testing default project, 30–32
 - types of programs created by, 26–27
 - use of gcc compiler, 31
 - using to create include files, 134–135
- coding style
 - avoiding errors in, 90–91, 400
 - being consistent in, 90–91, 400
 - variable naming conventions, 91
- colon (:) syntax, using with variables, 320
- comma (,) operator, using, 113–115
- command line, passing arguments from, 217–219
- commands, misspelling, 38–39
- CommaOperator program, 113
- comments, examples of, 43
- Common Business Oriented Language (COBOL), 18–19
- comparison operators
 - binary format, 70
 - using in BranchDemo program, 71
- compile time errors, managing, 40
- compiler
 - function of, 22
 - requirement of, 21
- compound expressions
 - conditional, 78–80
 - decomposing, 53–54

- CompoundStudent program, 318–320
 - computer languages
 - assembly language, 17
 - C++, 19–20
 - high-level, 18–19
 - machine language, 17
 - ConcatenateError2 program, 245
 - ConcatenateHeap program, 199–201, 236–238
 - ConcatenateNString program, 181–182
 - concatenateString() function
 - bug in, 181
 - debugging, 245–249
 - executing in debugger, 242
 - pointer version of, 208–211
 - ConcatenateString program, 178–179
 - concatenating strings, 177–180
 - conditional expressions, compound, 78–80.
 - See also* expressions
 - Console Application
 - defined, 23
 - selecting in Code::Blocks, 27
 - const arguments, problems with, 163
 - const char[] type, using, 177
 - const descriptor, using with variables, 158
 - const keyword, using to declare variables, 160
 - const string, throwing pointer to, 391
 - const variable, initializing, 161
 - constant characters, modifying, 177
 - constant values, initializing data members to, 321
 - constants
 - managing, 212–214
 - for opening files, 366
 - types of, 51, 160–161
 - constructors. *See also* copy constructors
 - defaulting arguments to, 311
 - defaults, 312–313
 - defining with arguments, 303–307
 - versus destructors, 297
 - versus functions, 304
 - initializing data members with, 315–318
 - limitations on, 291
 - for opening files for output, 367
 - overloading, 307–311
 - in StudentAssignment program, 358–360
 - using, 289–291
 - using defaults with data members, 314–315
 - continue command, using with loops, 102–104
 - Conversion program
 - assembler instructions in, 18
 - building, 38
 - entering, 35–37
 - finding error in, 92–93
 - first version of, 92
 - running, 42
 - templates, 42–44
 - test data for, 94
 - without template, 44
 - Conversion project
 - addition to HelloWorld project, 35
 - creating, 33–34
 - ConversionError2 program, examining, 95
 - copies
 - avoiding, 330–331
 - deep versus shallow, 328
 - shallow, 356
 - copy constructors. *See also* constructors
 - creating, 327–330
 - default, 324–325
 - invoking, 330
 - making shallow copies, 325–327
 - overview of, 323–324
 - providing to avoid bugs, 404
 - in StudentAssignment program, 358–360
 - CopyFiles program, 375–376
 - copying objects, 323–327
 - counting, using floating point variables in, 155
 - coupling, reducing, 282, 285–286
 - cout
 - versus cerr, 365
 - declaration of, 364
 - CPP programs, availability on CD-ROM, 413
 - customer care, accessing, 414
 - CustomExceptionClass program, 392–395
- D •
- data, grouping, 223–224
 - data members
 - constructing, 294–296
 - destructing, 300–301
 - flagging with keyword static, 302
 - initializing to constant values, 321

- data members (*continued*)
 - initializing with constructors, 315–318
 - initializing with default constructor, 314–315
- data types, limit of number size in, 159–160
- debug code, writing for `calculator()`
 - function, 143
- debug functions, creating, 143–144
- debugger utility
 - components of, 241
 - Continue option, 247
 - Debug window, 246–247
 - executing `concatenateString()`
 - function, 242
 - features of, 236
 - fixing bugs, 245–249
 - Next Line option, 243–244, 246
 - rebuilding executable, 239
 - setting breakpoints, 240
 - single-step commands, 243
 - single-stepping paths in, 401
 - starting, 239–241
 - Tool Tips, 242
 - turning on information, 239
 - using to navigate through programs, 241–245
 - Watches window, 242, 246
 - while loop structure, 244
- debugging. *See also* bug avoidance; errors; exceptions
 - CalculatorError1 program, 139–141
 - ConcatenateHeap, 236–238
 - dividing programs into functions, 139–141
 - importance of 0 (zero) in, 247
 - outfitting functions for testing, 143–146
 - performing unit level testing, 141–143
 - unit testing, 146–148
- dec
 - flag, 378
 - manipulator, 381
- decimal point, using 0 with, 154
- decrement (–) operator
 - order of precedence, 52
 - prefix and postfix versions, 55–56
 - using, 54–55
- deep copy, performing for source object, 328
- DeepStudent program, 328–330
- delete keyword
 - using with memory heap, 198–199
 - using with objects allocated off heap, 277
- delete[] versus delete, 307
- demotion, defined, 155
- deposit() member function, defining, 261–262
- destructors
 - assignment operators as, 358
 - versus constructors, 297
 - declaring virtual, 352–354, 403–404
 - invoking, 297
 - in StudentAssignment program, 358–361
 - for subclasses in inheritance, 342
 - using with constructors and arguments, 304
 - using with data members, 300–301
- DisplayASCIIZ program, 175–176
- division (/) operator, order of precedence, 52
- DOS/Windows, indicating backslash in, 365
- double limitations
 - calculation speed, 155–156
 - counting, 155
 - loss of accuracy, 156–157
 - memory consumption, 156
 - range, 157
- double quotes (")
 - special symbol for, 66
 - using with characters, 65
- double variable
 - assigning to int, 155
 - digits of accuracy, 156–157
 - explained, 159
 - largest number stored by, 157
 - memory consumption, 156
 - promoting int to, 154
 - size and range of, 160
 - using to fix truncation, 153–154

• E •

- EarlyBinding program, 344–345
- else keyword, using, 73–74
- endl object
 - stringstream version, 386
 - using with output streams, 380
- endl value, explained, 65
- ends object, inserting, 386
- enumerated types, problem with, 407
- equality (==) operator, explained, 70
- equals sign (=), using with variables, 49–50
- error checking programs, 95–96

error messages, enabling to avoid bugs, 399–400

error return, defined, 120

errors. *See also* bug avoidance; debugging; exceptions; run-time errors

- avoiding introduction of, 90–91
- build- versus compile-time, 89–90
- finding, 92–93
- forgetting to initialize variables, 50
- handling, 391
- handling via exceptions, 403
- identifying types of, 89–90
- missing semicolon, 40–41
- misspelled commands, 38–39
- run-time, 90, 93–96
- shallow copies, 327

example programs. *See* program examples

exception classes

- customizing, 392–395
- restrictions on, 395

exception mechanism

- catch keyword, 387–388
- throw keyword, 387–388
- try keyword, 387–388

exceptions. *See also* bug avoidance; debugging; errors

- catching, 391
- processing, 390–391
- rethrowing, 391
- throwing, 391–392
- using to handle errors, 403

executable file, finding path to, 218

expressions. *See also* conditional expressions; mixed mode expression, defined

- binary operators, 51–53
- compound, 53–54
- decomposing compound, 53–54
- defined, 14
- example, 51
- multiple operators in, 53–54
- operators, 51
- values and types of, 75
- versus variables, 47

extensions, unhiding, 36

extractor, operator `>>()` as, 364

● F ●

factorial(), error encountered in, 392–394

Factorial program

- for loop in, 111–112
- parts of loop in, 109–110
- while loop in, 100–101

factorial.cpp, creating, 131–133

FactorialException program, 388–389

FactorialFunction program, 124–128

FactorialModule project

- building result, 137
- creating factorial.cpp, 131–133
- #include file, 133–134
- including #include files, 134–135
- main.cpp, 136
- steps for creation of, 130

fail() flag, setting and clearing, 369

fail() member function, using, 371–372

fields, sorting algorithms for, 232

FileCopy program, 375–376

filename extensions, unhiding, 36

files. *See also* input files; output files

- adding to contents of, 368
- open modes for, 367–368
- opening in binary mode, 368
- opening in text mode, 368
- reading from, 368
- saving, 37
- writing to, 368

fill(char), calling, 379

fixed flag, explained, 378

fixed-size arrays, problem with, 197

flags() member function

- format flags for, 378–379
- using, 379

flat tire, changing, 11–17

float variable

- explained, 159
- size and range of, 160

floating point constant, assumption

- about, 154

floating point result, assigning to int variable, 155

floating point variables

- overflow of, 160
- types of, 153
- using for counting, 155

flow, controlling via `switch` statement, 81–84
`flush()` member function, calling, 380
`fmtflags` methods, using with `fstream` classes, 374
`fn()` function
 calling in `NamedStudent` program, 306
 late-binding, 352
 making changes permanent, 192–193
 statements in, 192–193
 using in `StudentDestructor` program, 299–300
 folders, creating for projects, 33
`for` loop. *See also* loops
 in arrays of pointers, 215–216
 in `Factorial` program, 111–112
 flow of, 110
 sections of, 112
 setup section, 112, 114
 using in `ConcatenateHeap` program, 201
 using in `ConcatenateString` program, 180
 using with arrays, 171
 using with `main()` program, 122–123
 versus `while` loop, 111, 115
 format of input, controlling, 378–380
 formatting member functions, span of, 380–381. *See also* member functions
 friend declaration, using with functions, 286–288
`fstream` classes
 destructor for, 367
 explained, 365
 member functions of, 373–374
`fstream` objects
 constructing, 369
 errors related to, 369
 returning `bad()` function for, 369
 function arguments, using, 123–126
 function names, overloading, 126, 162
 function overloading, explained, 126
 function prototype declarations, defining, 127–128
`FunctionDemo` program, 121–123
 functions. *See also* getter function,
 example of; member functions; setter
 function, defined
 call, 120
 calling with object pointers, 272–274
 calling with object values, 271–272
 versus constructors, 304

declaration, 120
 definition, 120
 dividing programs into, 139–143
 elements of, 120
 flow of control, 120
 friend declaration, 286–288
 with multiple arguments, 125
 outfitting for testing, 143–146
 overloading, 307
 overview of, 118–119
 passing variables to, 161–164
 return, 120
 returning values to callers, 120–121
 similarities between, 409–410
 testing separately, 141–143
 writing and invoking, 119–120

• G •

garbage characters, displaying in
 debugging, 247–249. *See also*
 characters
`gcc` compiler, using with `Code::Blocks`, 31
`get()` method, using with input files, 375
`getline()` member function, using,
 372–373, 375, 382–385
 getter function, example of, 285. *See also*
 functions
`goto` command, using, 405–406
 greater than (`>`) operator, meaning of, 70
 greater than or equal to (`>=`) operator,
 meaning of, 70
`GSInherit` example, 338–340

• H •

`HAS_A` relationship, using in inheritance, 342
 heap
 allocating memory from, 197
 allocating objects off, 278
 returning memory to, 198–199
 heap memory, keeping track of, 402
`HelloWorld` project, creating in
 `Code::Blocks`, 28–29
 hex
 flag, 378
 manipulator, 381
 hexadecimal, coding characters in, 66

high level languages, overview of, 18–19
 “human computer”
 algorithm, 11–12
 processors, 16–17
 program, 13–16
 tire changing language, 12

● 1 ●

IDE (Integrated Development Environment), 22–23
 if clause, using with `else`, 74
 IF statement in TCL (Tire Changing Language), 13–14
 if statements
 encountering, 70
 format of, 69
 nesting, 75–78
 versus `switch` statements, 84
 ifstream class
 constructor for, 365
 definition of, 365
 destructor for, 366
 using with input objects, 365
 #include directives, inclusion in standard template, 137
 #include files
 creating for FactorialModule, 133–134
 including, 134–135
 include statements, examples of, 43
 increment (++) operator
 order of precedence, 52
 prefix and postfix versions, 55–56
 using, 54–55
 indentation, use of, 91
 index, providing for arrays, 167–168
 index operator, using on pointer variables, 207–208
 inequality (!=) operator, meaning of, 70
 inheritance. *See also* object-oriented programming, model for
 advantages of, 336–337
 from classes, 340
 defined, 337
 implementing, 337–342
 multiple, 409
 subclasses, 337
 terminology, 337

`init()` function
 in OverloadedStudent program, 310–311
 using with protected members, 289–291
 input files, using `get()` method with, 375.
 See also files
 input objects, creating, 365–366. *See also* objects
 input/output (I/O), errors related to, 369
 InputPerson program, 227–230
 inserter, `operator>>()` as, 364
 inserter operator, using with output objects, 366–367
`int` `gcount()` method, using with `fstream` classes, 374
`int` keyword, using with variables, 47–48
`int` variable
 assigning `double` to, 155
 assigning floating point result to, 155
 bytes taken up by, 191
 explained, 151, 158
 HAS_A relationship, 342
 limited range of, 152–153
 maximum value, 152–153
 memory consumption, 156
 promoting to `double`, 154
 round-off limitation, 151–152
 size and range of, 160
 standard size of, 159
`int` versus `char` values, 64
`int` `width()` methods, using with `fstream` classes, 374
 integer constants, legal versus illegal, 50–51
 integers
 interpreting, 60
 limited range of, 152–153
 round-off limitation, 151–152
 truncation of, 152
 Integrated Development Environment (IDE), 22–23
 intrinsic type, explained, 151
 I/O (input/output), errors related to, 369
 I/O manipulators, member functions for, 381
 I/O stream format flags, 378
`iomanip`, including for manipulators, 381
`ios_base::`, using, 377
`iostream` include
 declaration of, 364
 prototype declarations in, 363–364

`isalppha(char c)` function, described, 182
`isdigit(char c)` function, described, 182
`islower(char c)` function, described, 182
`isprint(char c)` function, described, 182
`isspace(char c)` function, described, 182
`istream& put()` method, using with `fstream` classes, 374
`istream` versus `istreamstream` classes, 382
`isupper(char c)` function, described, 182

• K •

keyboard input, performing, 364
 keystrokes, saving, 270
 keywords, using with variables, 48

• L •

languages. *See* computer languages
 LateBinding program, 349–351
`.layout` extension, use in Code::Blocks, 27
`left` flag, explained, 378
`left-shift (<<)` operator, role in stream I/O, 363
`less than (<)` operator, meaning of, 70
`less than or equal to (<=)` operator, meaning of, 70
 levels of abstraction, explained, 119
 logical expressions

- comparing values in, 70–72
- defined, 14
- values of, 75

 logical operators, explained, 79
`long double` descriptor, using with variables, 158
`long double` variable

- explained, 159
- size and range of, 160

`long int` descriptor, using with variables, 158
`long int` variable

- explained, 159
- size and range of, 160

`long long int` descriptor, using with variables, 158

`long long int` variable

- explained, 159
- size and range of, 160

 “loop and test” statement, including in TCL, 14–16
 loops. *See also* for loop; while loop

- body, 109
- increment, 109
- nesting, 105–108
- setup, 109
- test expression, 109

 lowercase versus uppercase, 37, 84

• M •

machine language, representing, 17
 Macintosh, system requirements for, 411
`main()`

- as function, 125–126
- requirement of, 43

`main()` arguments

- arrays of arguments, 216–221
- arrays of pointers, 215–216
- in program template, 214–215

`main()` program, using for loop with, 122–123
`main.cpp` file

- creating for FactorialModule, 136
- displaying, 35
- editing contents of, 36–37
- opening, 36

`main.cpp.backup` file, creating, 378
 manipulators, member functions for, 381
 mathematical operators. *See also*

- arithmetic, calculation speeds;
- operators, overloading

 combining parentheses, 54
 order of precedence, 52–53
 member functions. *See also* formatting

- member functions, span of; functions;
- overriding member functions; protected
- members, initializing objects with

 accessing members from, 264–266
 adding keyword `protected:`, 282–285
 binding considerations, 351
 calling, 263–264, 268
 defining, 261–262

defining outside classes, 266–267
 invoking for pointers to objects, 271
 for manipulators, 381
 overloading, 267–268, 343–344
 protected keyword, 281
 protecting, 282
 virtual, 350
 memory
 address in, 188
 arrangement for arrays of objects, 227
 handling, 191
 returning to heap, 198–199
 memory address, including in pointer
 variable, 188
 memory heap. *See* heap
 memory layout, example of, 192
 memory model, applying for pointers, 204
 mixed mode expression, defined, 154. *See also* expressions
 mixed mode overloading, 162–164
 modules
 breaking programs into, 129–130
 linking, 129
 naming, 132
 modulo (%) operator, order of precedence,
 52–53
 MS-DOS window, opening in Windows, 219
 multiplication (*) operator, order of
 precedence, 52
 multiplication table, creating, 105–108
 MyData.txt file
 opening and reading, 366
 opening and writing to, 367
 using with ReadIntegers program, 370–372

• N •

NamedStudent program, 304–307
 namespaces, using, 407–408
 negative (—) operator
 order of precedence, 52
 using, 54–55
 nested if statements, using, 75–78
 nested loops
 explained, 16
 using, 105–108

new keyword
 using to allocate objects off heap, 277
 using with memory heap, 197
 newline
 adding to buffer, 380
 special symbol for, 66
 NOT (!) operator
 explained, 79
 using with streams, 377
 null character
 adding after final while loop, 248–249
 using in string concatenation, 178
 using with arrays, 174
 NULL character, special symbol for, 66

• O •

object code, explained, 18
 object pointers, calling functions with,
 272–274
 object-oriented programming, model for,
 257–258. *See also* inheritance
 objects. *See also* input objects, creating;
 output objects, creating; pointers to
 objects; source object, performing
 deep copy of
 accessing members of, 225–226
 activating, 259–261
 allocating off heap, 278
 arrays of, 226–227
 avoiding creating copies of, 274
 versus classes, 225
 copying, 323–327
 initializing, 289
 passing addresses of, 274–276, 330–331
 passing by reference, 277
 passing by values, 271–272, 274–276
 “real types” of, 347
 oct
 flag, 378
 manipulator, 381
 octal, identifying, 65
 ofstream class
 constructor for, 366–367
 definition of, 365
 open modes, using with files, 367–368

`operator>>()`
 as inserter, 364
 use as extractor, 364
 operators, overloading, 355–356, 361–362.

See also mathematical operators

OR (`|`) operator, using, 368

OR (`||`) operator, explained, 79

ostream object, use of, 364

ostream& (`&`) methods, using with
 fstream classes, 374

ostream versus ostream classes, 382, 395

output and input. *See* I/O (input/output),
 errors related to

output files, using `put()` method with,
 375. *See also* files

output objects, creating, 366–367. *See also*
 objects

output statements, using to find errors, 95

output streams, terminating, 380

overflow, defined, 160

OverloadedStudent program, 308–310

overriding member functions. *See also*
 member functions

 AmbiguousBinding program, 346–347

 EarlyBinding program, 344–345

 late binding, 348–351

• p •

parallel arrays, storing data in, 223–224.

See also arrays

parentheses (`()`)

 combining for operators, 54

 using with pointers and arrays, 206

 using with pointers to objects, 270

PassByReference program, 191, 193–197

PassObjects program, 274–276

PC, system requirements for, 411

PL/1 language, 40

pointer increment operator, using, 208–210

pointer types, operations on, 212

pointer variables, using index operator on,
 207–208

pointers. *See also* arrays

 addition versus indexing, 205–208

 applying memory model for, 204

 versus arrays, 214

 arrays of, 215–216

 declaring, 188–190

 operations on, 203–205

 overview of, 187–188

 using constants with, 213

 zeroing out, 403

pointers to objects. *See also* objects

 arrow syntax, 270

 example of, 269–270

 invoking member functions, 271

 using parentheses (`()`) with, 270

pound sign (`#`)

 use with binary operators, 56–57

 using with include files, 133

precedence, order of, 52–53

PrintArgs program, 216–217

`printErr()` function, using, 144–146

Product program, break and continue
 in, 102–103

program examples

 AmbiguousBinding, 346–347

 ArrayDemo, 168–170

 BranchDemo, 70–72

 CalculatorError1, 139–141

 CalculatorError2, 144–145

 CommaOperator, 113

 CompoundStudent, 318–320

 ConcatenateError2, 245

 ConcatenateHeap, 199–201

 ConcatenateNString, 181–182

 ConcatenateString, 178–179

 Conversion, 44, 92

 ConversionError2, 95

 CopyFiles, 375–376

 CustomExceptionClass, 392–395

 debugging ConcatenateHeap, 236–238

 DeepStudent, 328–330

 DisplayASCII, 175–176

 EarlyBinding, 344–345

 Factorial, 100, 109–112

 factorial.cpp, 131–133

 FactorialException, 388–389

 FactorialFunction, 124–128

 FileCopy, 375–376

 FunctionDemo, 121–123

 GSIinherit, 338–340

 InputPerson, 227–230

 LateBinding, 349–350

 NamedStudent, 304–307

 NestedLoops, 105–106

OverloadedStudent, 308–310
 PassByReference, 191, 193–197
 PassObjects, 274–276
 pointer version of
 concatenateString(), 208–211
 PrintArgs, 216–217
 Product, 102–103
 prototype declaration, 128
 ReadIntegers, 370
 ShallowStudent, 325–327
 SimpleStudent, 283–284
 StringStream, 382–385
 StudentAssignment, 358–360
 StudentConstructor, 292–293
 StudentDestructor, 298–299
 StudentID class, 314–315
 SwitchCalculator, 85–86
 toupper() function, 183–184
 TutorPairConstructor, 295–296, 300–301
 programs. *See also* C++ programs,
 programs required for
 breaking into modules, 129–130
 building, 21–22
 development process, 22
 dividing into functions, 139–143
 error checking, 95–96
 linking step, 22
 project file, finding path to, 217–218
 projects
 activating, 35
 adding source files to, 131
 creating, 33–34
 organizing, 35
 protected: keyword adding, 282–285
 protected keyword versus public
 keyword, 281
 protected members, initializing objects
 with, 289–291. *See also* member
 functions
 prototype declaration, explained, 127–128
 psz prefix, using with pointers, 208
 public keyword
 versus protected keyword, 281
 using in inheritance, 337–338
 using with classes, 224–225
 pure virtual member function, explained, 408
 put() method, using with output files, 375

• R •

read() member function, using, 375–376
 ReadIntegers program, 370
 real numbers, defined, 153
 right flag, explained, 378
 right-shift (>>) operator, role in stream I/O,
 363
 run-time errors. *See also* errors
 adding output statements, 94
 versus compile-time errors, 40
 executing test cases, 94
 finding, 93–96
 formulating test data, 93–94
 run-time type, defined, 347

• S •

safeFn() function, using in ReadIntegers
 program, 371–372
 saving files, 37
 Savings account class
 calling member function in, 263–264
 current object in, 265–266
 deposits in, 260
 functions in, 261–262
 scientific flag, explained, 378
 scores, averaging, 168–171
 semicolon (;), missing, 40–41
 setf() member function, format flags for,
 378–379
 setfill(c) manipulator, described, 381
 setprecision(n) manipulator,
 described, 381
 setter function, defined, 285. *See also*
 functions
 setw(n) manipulator, described, 381
 shallow copy, defined, 356
 ShallowStudent program, 325–327
 short int descriptor, using with
 variables, 158
 short int variable
 explained, 159
 size and range of, 160
 showbase flag, explained, 378
 showpoint flag, explained, 378
 SimpleStudent program, 283–284

- single quotes (')
 - interpreting, 66
 - special symbol for, 66
 - using with characters, 65
- skipws flag, explained, 378
- SomeClass class example, 321
- sorting algorithm. *See* Bubble Sort
- source code, explained, 18
- source file windows, closing, 35
- source files, adding to projects, 131
- source object, performing deep copy of, 328. *See also* objects
- Sources folder, opening, 35
- special characters, examples of, 66
- stack unwinding, role in exceptions, 390
- statements
 - adding to find errors, 95
 - avoiding cramming of, 212
 - defined, 14
 - executing once, 93
- static data members, overview of, 302
- static keyword, using with variables, 138
- strcmp() function, described, 182
- stream I/O, overview of, 363–365
- streams, reading and writing directly, 375–378
- streamsize precision() methods,
 - using with fstream classes, 374
- string class
 - behavior of, 382
 - omission of, 408
 - resizing, 373
- strings
 - ASCII manipulation functions, 182–183
 - concatenating, 177–180
 - displaying, 175–176
- strlen() function, calling, 198
- strlen(char s[]) function, described, 182
- strncat() function, described, 183
- strncpy() function, described, 182
- strstream classes, deprecation of, 382
- strstream versus stringstream
 - classes, 382–386
- struct keyword, using with classes, 225
- Student class
 - constructor with arguments, 303–304
 - default copy constructor, 324
 - default default constructor, 312
 - inheritance in, 337
 - initializing data member with
 - constructor, 317–318
 - from OverloadedStudent program, 308–310
 - public member functions, 283
 - using constructor with, 290–291
- student object, performing deep copy of, 328–330
- StudentAssignment program, 358–360
- StudentConstructor program, 292–293
- StudentDestructor program, 298–299
- StudentID class example
 - with default constructor, 314–315
 - with different constructor, 315–318
- subtraction (—) operator, order of precedence, 52
- sumSequence() function, using, 121–123
- switch statement
 - calculator example, 84
 - versus if statements, 84
 - using to control flow, 81–84
- SwitchCalculator program, 85–86, 139–141.
 - See also* CalculatorError program
- syntax requirements, 37
- system requirements, 411–412

• 7 •

- tab, special symbol for, 66
- TCL (Tire Changing Language)
 - IF statement, 13–14
 - logical expression, 14
 - “loop and test” statement, 14–16
 - syntax, 13
 - verbs and nouns, 13
- Technical Support, contacting, 414
- templates
 - comments, 43
 - example, 42–43
 - features of, 409–410
 - include files, 43
 - main(), 43
 - system("PAUSE"), 44
- ternary operator (?), using, 406
- test cases. *See also* unit testing
 - executing, 94
 - generating for calculator() function, 141–143

test data
 for Conversion program, 94
 deciding on, 93
text data, writing, 368
text editors, requirement of, 21
text versus binary mode, 368
this object, overview of, 279
throw, encountering, 390
throw; keyword, executing, 391
throw keyword, using in exception
 mechanism, 387–389
throwing exceptions, 391–392
tilde (~), using with destructors, 297
Tire Changing Language (TCL). *See* TCL
 (Tire Changing Language)
tire-changing module, components of, 118
tolower(char c) function, described, 183
toupper() function
 described, 183
 program example, 183–184
truncation, defined, 152
truncation problem, fixing via double
 variable type, 153–154
try block, finding end of, 390
try keyword, using in exception
 mechanism, 387–389
TutorPairConstructor program, 295–296
types
 dynamic versus static, 347
 run-time versus declared, 347
typing, reducing via inheritance, 336

• U •

unary operators
 order of precedence, 52
 using, 54–56
underscore (_), using with variable names, 48
Unicode, variants of, 67
unit level testing, performing, 141–143
unit testing. *See also* test cases
 defined, 89
 performing, 146–148
unitbuf flag, explained, 378
unsafeFn() function, using in
 ReadIntegers program, 370
unsetf() member function, format flags
 for, 378–379
unsigned descriptor, using with variables, 158

unsigned int variable, explained, 158
unwinding the stack, role in exceptions, 390
uppercase flag, explained, 378
uppercase versus lowercase, 37, 84
UTF variants, explained, 67

• V •

variable types, size and range of, 159–160
variables. *See also* arrays; character variables
 assigning values to, 49
 const descriptor, 158
 declaring, 47–48
 declaring constant, 160
 establishing naming conventions for, 91
 versus expressions, 47
 forgetting to initialize, 50
 initializing at declaration, 49–50
 legal combinations of, 158–159
 local versus global scope, 137–138
 long double descriptor, 158
 long int descriptor, 158
 long long int descriptor, 158
 memory consumption, 156, 160
 naming conventions, 48, 155
 passing to functions, 161–164
 promoting versus demoting, 155
 short int descriptor, 158
 unsigned descriptor, 158
 using : (colon) syntax with, 320
 using equals sign (=) with, 49–50
 using static keyword with, 138
virtual declarations, using with
 destructors, 352–354, 403–404
virtual keyword, using in late binding,
 349–350
virtual member function, defined, 350
void keyword, using with functions, 121
void methods, using with fstream
 classes, 373–374

• W •

warnings, enabling to avoid bugs, 399–400
wchar_t variable, explained, 159
wchar_t “wide character,” 67
while loop. *See also* loops
 adding terminating null after, 248
 creating, 99–102

- while loop (*continued*)
 - versus for loop, 111, 115
 - structure in debugger, 244
- “wide character” of type `wchar_t`, 67
- `width(int)` member function, using, 379–380
- `width(n)` member function, using, 380–381
- Wiley Product Technical Support,
 - contacting, 414
- Windows
 - opening MS-DOS window in, 219
 - passing arguments from, 220–221
 - unhiding filename extensions in, 36
- Windows/DOS, indicating backslash in, 365
- `withdraw()` function, 266
- `withdraw()` member function, defining,
 - 261–262
- workspace, defined, 35
- `write()` member function, using, 375–376

• X •

`X: :X(const X&)` format, explained, 323

• Z •

zero (0)

- importance in debugging, 247
- using with decimal point, 154