

Agents that Search Together: Stochastic Search

Russell and Norvig: Chapter 5

CSE 240: Winter 2023

Lecture 7

Announcements

- Quiz 1 graded
 - Questions: talk to me
 - Guides and answer keys on Canvas.
- Canvas quiz conversation
- Feedback today.
 - If no laptop, you can turn it in after class.


Agenda and Topics

- Game agents in stochastic environments
 - Expectimax algorithm
- Local search and optimization algorithms

Other Game Types



Multi-Agent Utilities

- What if the game is not zero-sum, or has multiple players?
- Generalization of minimax:
 - Terminals have utility tuples
 - Node values are also utility tuples
 - Each player maximizes its own component
 - Can give rise to cooperation and competition dynamically...



Uncertain Outcomes

Worst Case Versus Average Case



**Idea: Uncertain outcomes controlled by chance,
not an adversary!**

Expectimax Search


- Why wouldn't know what the result of an action will be?
 - Explicit randomness: rolling dice
 - Unpredictable opponents: the ghosts respond randomly
 - Unpredictable humans: humans are not perfect
 - Actions can fail: when moving a robot, wheels might slip
- Values should now reflect average—case (expectimax) outcomes, not worst-case (minimax) outcomes
- Expectimax search”: compute the average score under optimal play
 - Max nodes as in minimax search
 - Chance nodes are like min nodes but the outcome is uncertain
 - Calculate their expected utilities
 - I.e., take weighted average (expectation) of children.

Expectimax Pseudocode

```
def value(s)
  if s is a max node return maxValue(s)
  if s is an exp node return expValue(s)
  if s is a terminal node return evaluation(s)
```


```
def maxValue(s)
  values = [value(s') for s' in successors(s)]
  return max(values)
```

```
def expValue(s)
  values = [value(s') for s' in successors(s)]
  weights = [probability(s, s') for s' in successors(s)]
  return expectation(values, weights)
```




Expectimax Pseudocode

```
def exp-value(state):  
    initialize v = 0  
    for each successor of state:  
        p = probability(successor)  
        v += p * value(successor)  
    return v
```




$$v = (1/2) (8) + (1/3) (24) + (1/6) (-12) = 10$$


Expectimax Example




Expectimax Pruning?



Depth-Limited Expectimax



What Utilities to Use?



- For worst-case minimax reasoning, terminal function scale doesn't matter
- We just want better states to have higher evaluations (get the ordering right)
- We call this **insensitivity to monotonic transformations**
- For average-case expectimax reasoning, we need *magnitudes* to be meaningful.

Modeling Assumptions

The Dangers of Optimism and Pessimism

Dangerous Optimism

Assuming chance when the world is adversarial




Dangerous Pessimism

Assuming the worst case when it's not likely



Assumption versus Reality




	Adversarial Ghost	Random Ghost
Minimax Pacman	Won 5/5 Avg. Score: 483	Won 5/5 Avg. Score: 493
Expectimax Pacman	Won 1/5 Avg. Score: -303	Won 5/5 Avg. Score: 503

Results from playing 5 games

Pacman used depth 4 search with an eval function that avoids trouble
Ghost used depth 2 search with an eval function that seeks Pacman

Mixed Layer Types

- E.g. Backgammon
- Expecti-minimax
- Environment is an extra “random agent” player that moves after each min/max agent
- Each node computes the appropriate combination of its children



CE 7: Feedback

- <https://forms.gle/ghXVUmjMJjpdcmH6A>

Local Search Algorithms

Local Search Algorithms


- In many optimization problems, the path to the goal is irrelevant; the goal state itself is the solution
 - Local search: widely used for *very big* problems
 - Returns good but *not optimal* solutions
- Local search algorithms
 - Keep a single "current" state, or small set of states
 - Iteratively try to improve it / them
 - Very memory efficient
 - Keeps only one or a few states
 - You control how much memory you use

Example Problems for Local and Systematic Search

- Systematic search: path to goal is important
 - Theorem solving
 - Route finding
 - 8-puzzle
 - Chess
- Local search: goal state itself is important
 - 8-Queen
 - Traveling Salesman Problem
 - Job Scheduling


State-space Landscape

- Local search algorithms explore the landscape
- A landscape has both
 - “location” (defined by the state)
 - “elevation” (defined by value of the heuristic cost function or objective function)
- Solution: a state with the optimal value of the objective function
 - Note that a minimization problem can turn into a maximization problem by adding a minus sign



A one-dimensional state-space landscape in which elevation corresponds to the objective function


Example: n-queen



- Put n queens on an $n \times n$ board with no two queens on the same row, column or diagonal.
- What is the state space?
- What is the objective function?


Local Search: 8-queen Problem

- **States:** 8 queens on the board, one per column ($8^8 \approx 17M$)
- **Successors(s):** all states resulted from state s by moving a single queen to another square of the same column ($8 \times 7 = 56$ successors per state)
- **Cost function $h(s)$:** number of queen pairs that are attacking each other (directly or indirectly)
- **Global minimum:** $h(s) = 0$



18	12	14	13	13	12	14	14
14	16	13	15	12	14	12	16
14	12	18	13	15	12	14	14
15	14	14	queen	13	16	13	16
queen	14	17	15	queen	14	16	16
17	queen	16	18	15	queen	15	queen
18	14	queen	15	15	14	queen	16
14	14	13	17	12	14	12	18

best moves reduce $h = 17$ to $h = 12$



local minimum with $h = 1$

Hill Climbing Search

```
function HILL-CLIMBING(problem) returns a state that is a local maximum
  inputs: problem, a problem
  local variables: current, a node
                  neighbor, a node

  current ← MAKE-NODE(INITIAL-STATE[problem])
  loop do
    neighbor ← a highest-valued successor of current
    if VALUE[neighbor] ≤ VALUE[current] then return STATE[current]
    current ← neighbor
```

- Search strategy: steepest ascent among immediate neighbors until reaching a peak.
- “...like trying to find the top of Mount Everest in a thick fog while suffering from amnesia”

Example: Hill Climbing, 8 queens

h = # of pairs of queens that are attacking each other, either directly or indirectly

$h = 17$ for this state


18	12	14	13	13	12	14	14
14	16	13	15	12	14	12	16
14	12	18	13	15	12	14	14
15	14	14	♙	13	16	13	16
♙	14	17	15	♙	14	16	16
17	♙	16	18	15	♙	15	♙
18	14	♙	15	15	14	♙	16
14	14	13	17	12	14	12	18

Each number indicates h if we move a queen in its column to that square

12 (boxed) = best h among all neighbors; select one randomly


Example: Hill Climbing, 8 queens

- A local minimum with $h = 1$
- All one-step neighbors have higher h values
- What can you do to get out of this local minimum?



Hill Climbing Strategy is Greedy


- Greedy local search: considering only one step ahead and select the best successor state (steepest ascent).
- Can provide rapid progress towards a solution
- Usually quite easy to improve a bad initial solution.



Optimal when starting
in one of these states

Hill Climbing Difficulties


- Depending on initial state, algorithm can get stuck in local optimum
- Local maxima: a peak that's not a global maximum
- Plateau: a flat area (shoulders or flat local maximum).



A one-dimensional state-space landscape in which elevation corresponds to the objective function

Hill Climbing Difficulties (Cont.)

- Ridge problem: every neighbor appears to be downhill
 - But, search space has an uphill (just not in neighbors)
- Ridge:
 - Fold a piece of paper and hold it tilted up at an unfavorable angle to every possible search space step.
 - Every step leads downhill; but the ridge leads uphill



Hill Climbing Properties

- **Completeness:** Not complete
- **Time complexity:** Worst-case exponential time
- **Space complexity:** Simple $O(1)$ space complexity

Summary

- Game agents in stochastic environments
 - Expectimax algorithm
- Local search and optimization algorithms

Next time:

- Continue: Local search and optimization algorithms