Reliable Server Pooling MIB Module Definition

Status of This Memo

   This memo defines an Experimental Protocol for the Internet
   community. It does not specify an Internet standard of any kind.
   Discussion and suggestions for improvement are requested.
   Distribution of this memo is unlimited.

Copyright Notice

Abstract

   Reliable Server Pooling (RSerPool) is a framework to provide reliable
   server pooling. The RSerPool framework consists of two protocols:
   ASAP (Aggregate Server Access Protocol) and ENRP (Endpoint
   Handlespace Redundancy Protocol). This document defines an SMIv2-
   compliant (Structure of Management Information Version 2) Management
   Information Base (MIB) module providing access to managed objects in
   an RSerPool implementation.

Table of Contents

1. Introduction

    This memo defines a Management Information Base (MIB) module that
    describes managed objects for RSerPool implementations.

2. The Reliable Server Pooling (RSerPool) Framework

    For a detailed overview of the documents that describe the current
    Reliable Server Pooling (RSerPool) framework, please refer to
    [RFC3237], [RFC5351], [RFC5352], [RFC5353], [RFC5354], [RFC5355], and
    [RFC5356]. A more informal introduction can be found at
    [RSerPoolPage] as well as in [Dre2006], [LCN2005], and [IJHIT2008].

3. Conventions

    The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT",
    "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this
    document are to be interpreted as described in [RFC2119].

4. The Internet-Standard Management Framework

    For a detailed overview of the documents that describe the current
    Internet-Standard Management Framework, please refer to section 7 of
    RFC 3410 [RFC3410].

    Managed objects are accessed via a virtual information store, termed
    the Management Information Base or MIB. MIB objects are generally
    accessed through the Simple Network Management Protocol (SNMP).

   Objects in the MIB are defined using the mechanisms defined in the
   Structure of Management Information (SMI). This memo specifies a MIB
   module that is compliant to the SMIv2, which is described in STD 58,
   RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580
   [RFC2580]. The textual conventions are compliant to RFC 4001
   [RFC4001].

5. Structure of the MIB

   The following diagram illustrates the structure of the MIB.

   Structure of MIB

```
  +--rserpoolMIB(125)
     |
     +--rserpoolMIBObjects(1)
     |  |
     |  +--rserpoolENRPServers(1)
     |  |  |
     |  |  +--rserpoolENRPTable(1)
     |  |  |  |
     |  |  |  +--rserpoolENRPEntry(1)
     |  |  |     |  Index: rserpoolENRPIndex
     |  |  |     |
     |  |  |     +-- ---- Unsigned  rserpoolENRPIndex(1)
     |  |  |     |         Range: 1..4294967295
     |  |  |     +-- -R-- String    rserpoolENRPOperationScope(2)
     |  |  |     |         Textual Conv.: RSerPoolOperationScopeTC
     |  |  |     |         Size: 0..65535
     |  |  |     +-- -R-- Unsigned  rserpoolENRPIdentifier(3)
     |  |  |     |         Textual Conv.: RSerPoolENRPServerIdentifierTC
     |  |  |     |         Range: 1..4294967295
     |  |  |     +-- -RW- String    rserpoolENRPDescription(4)
     |  |  |     |         Size: 0..255
     |  |  |     +-- -R-- TimeTicks rserpoolENRPUptime(5)
     |  |  |     +-- -R-- Unsigned  rserpoolENRPPort(6)
     |  |  |     |         Textual Conv.: InetPortNumber
     |  |  |     |         Range: 0..65535
     |  |  |     +-- -R-- Unsigned  rserpoolENRPASAPAnnouncePort(7)
     |  |  |     |         Textual Conv.: InetPortNumber
     |  |  |     |         Range: 0..65535
     |  |  |     +-- -R-- EnumVal    rserpoolENRPASAPAnnounceAddrType(8)
     |  |  |     |         Textual Conv.: InetAddressType
     |  |  |     |         Values: ipv4(1), ipv6(2)
     |  |  |     +-- -R-- String    rserpoolENRPASAPAnnounceAddr(9)
     |  |  |     |         Textual Conv.: InetAddress
     |  |  |     |         Size: 4 | 16
```

```
  | | |         +-- -R-- Unsigned  rserpoolENRPENRPAnnouncePort(10)
  | | |         |         Textual Conv.: InetPortNumber
  | | |         |         Range: 0..65535
  | | |       +-- -R-- EnumVal   rserpoolENRPENRPAnnounceAddrType(11)
  | | |       |         Textual Conv.: InetAddressType
  | | |       |         Values: ipv4(1), ipv6(2)
  | | |     +-- -R-- String    rserpoolENRPENRPAnnounceAddr(12)
  | | |     |         Textual Conv.: InetAddress
  | | |     |         Size: 4 | 16
  | | |
  | |   +--rserpoolENRPPoolTable(3)
  | | |   |
  | | |   +--rserpoolENRPPoolEntry(1)
  | | |   |   | Index: rserpoolENRPIndex, rserpoolENRPPoolIndex
  | | |   |   |
  | | |   |   +-- ---- Unsigned  rserpoolENRPPoolIndex(1)
  | | |   |   |         Range: 1..4294967295
  | | |   |   +-- -R-- String    rserpoolENRPPoolHandle(2)
  | | |   |           Textual Conv.: RSerPoolPoolHandleTC
  | | |   |           Size: 0..65535
  | | |
  | |   +--rserpoolENRPPoolElementTable(4)
  | | |   |
  | | |   +--rserpoolENRPPoolElementEntry(1)
  | | |   |   | Index: rserpoolENRPIndex, rserpoolENRPPoolIndex,
  | | |   |   |         rserpoolENRPPoolElementIndex
  | | |   |   |
  | | |   |   +-- ---- Unsigned  rserpoolENRPPoolElementIndex(1)
  | | |   |   |         Range: 1..4294967295
  | | |   |   +-- -R-- Unsigned  rserpoolENRPPoolElementID(2)
  | | |   |   |         Textual Conv.: RserpoolPoolElementIdentifierTC
  | | |   |   |         Range: 1..4294967295
  | | |   |   +-- -R-- Unsigned  rserpoolENRPASAPTransportPort(3)
  | | |   |   |         Textual Conv.: InetPortNumber
  | | |   |   |         Range: 0..65535
  | | |   |   +-- -R-- Unsigned  rserpoolENRPUserTransportProto(4)
  | | |   |   |         Range: 0..255
  | | |   |   +-- -R-- Unsigned  rserpoolENRPUserTransportPort(5)
  | | |   |   |         Textual Conv.: InetPortNumber
  | | |   |   |         Range: 0..65535
  | | |   |   +-- -R-- EnumVal   rserpoolENRPUserTransportUse(6)
  | | |   |   |         Textual Conv.: RSerPoolTransportUseTypeTC
  | | |   |   |         Values: dataOnly(0), dataPlusControl(1)
  | | |   |   +-- -R-- Unsigned  rserpoolENRPPolicyID(7)
  | | |   |   |         Textual Conv.: RSerPoolPolicyIdentifierTC
  | | |   |   |         Range: 1..4294967295
  | | |   |   +-- -R-- String    rserpoolENRPPolicyDescription(8)
  | | |   |   |         Size: 0..255
```

```
  |  |  |        +-- -R-- Unsigned  rserpoolENRPPolicyWeight(9)
  |  |  |        |          Textual Conv.: RSerPoolPolicyWeightTC
  |  |  |        |          Range: 0..4294967295
  |  |  |        +-- -R-- Unsigned  rserpoolENRPPolicyLoad(10)
  |  |  |        |          Textual Conv.: RSerPoolPolicyLoadTC
  |  |  |        |          Range: 0..4294967295
  |  |  |        +-- -R-- Unsigned  rserpoolENRPPolicyLoadDeg(11)
  |  |  |        |          Textual Conv.: RSerPoolPolicyLoadTC
  |  |  |        |          Range: 0..4294967295
  |  |  |        +-- -R-- TimeTicks rserpoolENRPRegistrationLife(12)
  |  |  |        +-- -R-- Unsigned  rserpoolENRPHomeENRPServer(13)
  |  |  |                   Textual Conv.: RSerPoolENRPServerIdentifierTC
  |  |  |                   Range: 1..4294967295
  |  |  |
  |  |  +--rserpoolENRPASAPAddrTable(5)
  |  |  |  |
  |  |  |  +--rserpoolENRPASAPAddrTableEntry(1)
  |  |  |     |   Index: rserpoolENRPIndex, rserpoolENRPPoolIndex,
  |  |  |     |          rserpoolENRPPoolElementIndex,
  |  |  |     |          rserpoolENRPASAPAddrTableIndex
  |  |  |     |
  |  |  |     +-- ---- Unsigned  rserpoolENRPASAPAddrTableIndex(1)
  |  |  |     |          Range: 1..4294967295
  |  |  |     +-- -R-- EnumVal   rserpoolENRPASAPL3Type(2)
  |  |  |     |          Textual Conv.: InetAddressType
  |  |  |     |          Values: ipv4(1), ipv6(2)
  |  |  |     +-- -R-- String    rserpoolENRPASAPL3Addr(3)
  |  |  |                Textual Conv.: InetAddress
  |  |  |                Size: 4 | 16
  |  |  |
  |  |  +--rserpoolENRPUserAddrTable(6)
  |  |  |  |
  |  |  |  +--rserpoolENRPUserAddrTableEntry(1)
  |  |  |     |   Index: rserpoolENRPIndex, rserpoolENRPPoolIndex,
  |  |  |     |          rserpoolENRPPoolElementIndex,
  |  |  |     |          rserpoolENRPUserAddrTableIndex
  |  |  |     |
  |  |  |     +-- ---- Unsigned  rserpoolENRPUserAddrTableIndex(1)
  |  |  |     |          Range: 1..4294967295
  |  |  |     +-- -R-- EnumVal   rserpoolENRPUserL3Type(2)
  |  |  |     |          Textual Conv.: InetAddressType
  |  |  |     |          Values: unknown(0), ipv4(1), ipv6(2)
  |  |  |     +-- -R-- String    rserpoolENRPUserL3Addr(3)
  |  |  |     |          Textual Conv.: InetAddress
  |  |  |     |          Size: 0 | 4 | 16
  |  |  |     +-- -R-- String    rserpoolENRPUserL3Opaque(4)
  |  |  |                Textual Conv.: RSerPoolOpaqueAddressTC
  |  |  |                Size: 0..65535
```

```
   |  |      |
   |  |   +--rserpoolENRPENRPAddrTable(7)
   |  |   |  |
   |  |   |  +--rserpoolENRPENRPAddrTableEntry(1)
   |  |   |     |   Index: rserpoolENRPIndex,
   |  |   |     |          rserpoolENRPENRPAddrTableIndex
   |  |   |     |
   |  |   |     +-- ---- Unsigned  rserpoolENRPENRPAddrTableIndex(1)
   |  |   |     |           Range: 1..4294967295
   |  |   |     +-- -R-- EnumVal   rserpoolENRPENRPL3Type(2)
   |  |   |     |           Textual Conv.: InetAddressType
   |  |   |     |           Values: ipv4(1), ipv6(2)
   |  |   |     +-- -R-- String    rserpoolENRPENRPL3Addr(3)
   |  |   |             Textual Conv.: InetAddress
   |  |   |             Size: 4 | 16
   |  |   |
   |  |   +--rserpoolENRPPeerTable(8)
   |  |   |  |
   |  |   |  +--rserpoolENRPPeerEntry(1)
   |  |   |     |   Index: rserpoolENRPPeerIndex
   |  |   |     |
   |  |   |     +-- ---- Unsigned  rserpoolENRPPeerIndex(1)
   |  |   |     |           Range: 1..4294967295
   |  |   |     +-- -R-- Unsigned  rserpoolENRPPeerIdentifier(2)
   |  |   |     |           Textual Conv.: RSerPoolENRPServerIdentifierTC
   |  |   |     |           Range: 1..4294967295
   |  |   |     +-- -R-- Unsigned  rserpoolENRPPeerPort(3)
   |  |   |     |           Textual Conv.: InetPortNumber
   |  |   |     |           Range: 0..65535
   |  |   |     +-- -R-- TimeTicks rserpoolENRPPeerLastHeard(4)
   |  |   |
   |  |   +--rserpoolENRPPeerAddrTable(9)
   |  |      |
   |  |      +--rserpoolENRPPeerAddrTableEntry(1)
   |  |      |   |   Index: rserpoolENRPPeerIndex,
   |  |   |  |           rserpoolENRPPeerAddrTableIndex
   |  |      |   |
   |  |      |   +-- ---- Unsigned  rserpoolENRPPeerAddrTableIndex(1)
   |  |      |   |           Range: 1..4294967295
   |  |      |   +-- -R-- EnumVal   rserpoolENRPPeerL3Type(2)
   |  |      |   |           Textual Conv.: InetAddressType
   |  |      |   |           Values: ipv4(1), ipv6(2)
   |  |      |   +-- -R-- String    rserpoolENRPPeerL3Addr(3)
   |  |                  Textual Conv.: InetAddress
   |  |                  Size: 4 | 16
   |  |
   |  +--rserpoolPoolElements(2)
   |  |  |
```

```
   | |    +--rserpoolPETable(1)
   | |    |    |
   | |    |  +--rserpoolPEEntry(1)
   | |    |    |   Index: rserpoolPEIndex
   | |    |    |
   | |    |     +-- ---- Unsigned  rserpoolPEIndex(1)
   | |    |    |         Range: 1..4294967295
   | |    |     +-- -R-- String    rserpoolPEOperationScope(2)
   | |    |    |         Textual Conv.: RSerPoolOperationScopeTC
   | |    |    |         Size: 0..65535
   | |    |     +-- -RW- String    rserpoolPEPoolHandle(3)
   | |    |    |         Textual Conv.: RSerPoolPoolHandleTC
   | |    |    |         Size: 0..65535
   | |    |     +-- -R-- Unsigned  rserpoolPEIdentifier(4)
   | |    |    |         Textual Conv.: RserpoolPoolElementIdentifierTC
   | |    |    |         Range: 1..4294967295
   | |    |     +-- -RW- String    rserpoolPEDescription(5)
   | |    |    |         Size: 0..255
   | |    |     +-- -R-- TimeTicks rserpoolPEUptime(6)
   | |    |     +-- -R-- Unsigned  rserpoolPEASAPTransportPort(7)
   | |    |    |         Textual Conv.: InetPortNumber
   | |    |    |         Range: 0..65535
   | |    |     +-- -R-- Unsigned  rserpoolPEUserTransportProto(8)
   | |    |    |         Range: 0..255
   | |    |     +-- -R-- Unsigned  rserpoolPEUserTransportPort(9)
   | |    |    |         Textual Conv.: InetPortNumber
   | |    |    |         Range: 0..65535
   | |    |     +-- -R-- EnumVal    rserpoolPEUserTransportUse(10)
   | |    |    |         Textual Conv.: RSerPoolTransportUseTypeTC
   | |    |    |         Values: dataOnly(0), dataPlusControl(1)
   | |    |     +-- -RW- Unsigned  rserpoolPEPolicyID(11)
   | |    |    |         Textual Conv.: RSerPoolPolicyIdentifierTC
   | |    |    |         Range: 1..4294967295
   | |    |     +-- -RW- String    rserpoolPEPolicyDescription(12)
   | |    |    |         Size: 0..255
   | |    |     +-- -RW- Unsigned  rserpoolPEPolicyWeight(13)
   | |    |    |         Textual Conv.: RSerPoolPolicyWeightTC
   | |    |    |         Range: 0..4294967295
   | |    |     +-- -R-- Unsigned  rserpoolPEPolicyLoad(14)
   | |    |    |         Textual Conv.: RSerPoolPolicyLoadTC
   | |    |    |         Range: 0..4294967295
   | |    |     +-- -RW- Unsigned  rserpoolPEPolicyLoadDeg(15)
   | |    |    |         Textual Conv.: RSerPoolPolicyLoadTC
   | |    |    |         Range: 0..4294967295
   | |    |     +-- -RW- TimeTicks rserpoolPERegistrationLife(16)
   | |    |     +-- -R-- Unsigned  rserpoolPEHomeENRPServer(17)
   | |    |    |         Textual Conv.: RSerPoolENRPServerIdentifierTC
   | |    |    |         Range: 1..4294967295
```

```
   |  |   |
   |  |   +--rserpoolPEASAPAddrTable(2)
   |  |   |  |
   |  |   |  +--rserpoolPEASAPAddrTableEntry(1)
   |  |   |  |    Index: rserpoolPEIndex, rserpoolPEASAPAddrTableIndex
   |  |   |  |
   |  |   |  +-- ---- Unsigned  rserpoolPEASAPAddrTableIndex(1)
   |  |   |  |         Range: 1..4294967295
   |  |   |  +-- -R-- EnumVal   rserpoolPEASAPL3Type(2)
   |  |   |  |         Textual Conv.: InetAddressType
   |  |   |  |         Values: ipv4(1), ipv6(2)
   |  |   |  +-- -R-- String    rserpoolPEASAPL3Addr(3)
   |  |   |  |         Textual Conv.: InetAddress
   |  |   |  |         Size: 4 | 16
   |  |   |
   |  |   +--rserpoolPEUserAddrTable(6)
   |  |      |
   |  |      +--rserpoolPEUserAddrTableEntry(1)
   |  |      |    Index: rserpoolPEIndex, rserpoolPEUserAddrTableIndex
   |  |      |
   |  |      +-- ---- Unsigned  rserpoolPEUserAddrTableIndex(1)
   |  |      |         Range: 1..4294967295
   |  |      +-- -R-- EnumVal   rserpoolPEUserL3Type(2)
   |  |      |         Textual Conv.: InetAddressType
   |  |      |         Values: unknown(0), ipv4(1), ipv6(2)
   |  |      +-- -R-- String    rserpoolPEUserL3Addr(3)
   |  |      |         Textual Conv.: InetAddress
   |  |      |         Size: 0 | 4 | 16
   |  |      +-- -R-- String    rserpoolPEUserL3Opaque(4)
   |  |                Textual Conv.: RSerPoolOpaqueAddressTC
   |  |                Size: 0..65535
   |  |
   |  +--rserpoolPoolUsers(3)
   |     |
   |     +--rserpoolPUTable(1)
   |        |
   |        +--rserpoolPUEntry(1)
   |        |    Index: rserpoolPUIndex
   |        |
   |        +-- ---- Unsigned  rserpoolPUIndex(1)
   |        |         Range: 1..4294967295
   |        +-- -R-- String    rserpoolPUOperationScope(2)
   |        |         Textual Conv.: RSerPoolOperationScopeTC
   |        |         Size: 0..65535
   |        +-- -RW- String    rserpoolPUPoolHandle(3)
   |        |         Textual Conv.: RSerPoolPoolHandleTC
   |        |         Size: 0..65535
   |        +-- -RW- String    rserpoolPUDescription(4)
```

```
     |          |            Size: 0..255
     |          +-- -R-- TimeTicks rserpoolPUUptime(5)
     |
  +--rserpoolMIBConformance(2)
       |
       +--rserpoolMIBCompliances(1)
       |  |
       |  +--rserpoolMIBCompliance(1)
       |
       +--rserpoolMIBGroups(2)
          |
          +--rserpoolENRPGroup(1)
          +--rserpoolPEGroup(2)
          +--rserpoolPUGroup(3)
```

   As the figure shows, the MIB consists of three main branches:
   "rserpoolENRPServers", "rserpoolPoolElements", and
   "rserpoolPoolUsers". The first branch, "rserpoolENRPServers", is
   used to access managed objects in the set of ENRP servers running on
   a given host. While it is assumed that it does not make much sense
   to run multiple ENRP servers for the same operation scope on one
   host, running multiple ENRP servers for different operation scopes is
   very likely when the ENRP server processes run on routers.
   Therefore, the MIB has to be able to manage multiple ENRP servers on
   the same host.

   "rserpoolPoolElements" is used to access managed objects in the set
   of pool elements that are running on a given host.

   The third branch, "rserpoolPoolUsers", is used to access managed
   objects in the set of pool users that are running on a given host.

   Note: "rserpoolENRPServers" is filled on hosts running ENRP server
   instances, "rserpoolPoolElements" is filled on hosts running pool
   element instances, and "rserpoolPoolUsers" is filled on hosts running
   pool user instances. Of course, multiple different components may
   run on the same host, which leads to filling of multiple different
   branches.

   In fact, the structure of the three branches is very similar.
   Because the other two branches are so similar, we describe only the
   first branch in detail, and provide a summary description of the
   second and third branch. We now proceed with a description of the
   branches.

5.1. Access to Managed Objects on ENRP Servers

   The first branch describes managed objects at a set of ENRP servers.
   Any given ENRP server of this set will, at a certain moment in time,
   have registration information for a set of active pools. Each of
   these pools in turn may have a list of pool elements that are
   registered under that pool. To allow this information to be
   retrieved via SNMP, the ERNP server branch of the RSerPool MIB uses
   the table-in-table technique described in [SNMPMIBS].

   Specifically, the ENRP servers branch creates four levels of nesting,
   as indicated in the following diagram:

   Nesting of the ENRP Server Branch

   Nesting Structure:

     Level 1: rserpoolENRPTable

     Level 2:   rserpoolENRPPoolTable
     Level 3:   rserpoolENRPPoolElementTable
     Level 4:   rserpoolENRPASAPAddrTable
                          rserpoolENRPUserAddrTable

     Level 2:   rserpoolENRPENRPAddrTable

     Level 2:   rserpoolENRPPeerTable
     Level 3:   rserpoolENRPPeerAddrTable

5.2. Access to Managed Objects on Pool Elements

   The construction of the Pool Elements branch is very similar to the
   pool elements table of the ENRP servers branch. But instead of
   grouping the pool elements into pools (which does not make sense
   here), the pool elements table is the top of the hierarchy, and each
   pool element entry specifies its operation scope and pool handle.

   That is, the nesting structure is as follows:

   Nesting of the Pool Elements Branch

     Level 1:   rserpoolPETable
     Level 2:   rserpoolPEASAPAddrTable
                      rserpoolPEUserAddrTable

5.3. Access to Managed Objects on Pool Users

   For the Pool Users branch, it is only necessary to list the pool user
   instances, including their operation scope and pool handle.

5.4. Persistency Behavior

   Upon changes of writable objects, an implementation SHOULD store the
   new values in a persistent manner if it has the capability to do
   this. An implementation SHOULD use these stored values upon reset or
   reinitialization.

6. Definitions

RSERPOOL-MIB DEFINITIONS ::= BEGIN

IMPORTS
   MODULE-IDENTITY, OBJECT-TYPE, experimental,
   TimeTicks, Unsigned32
      FROM SNMPv2-SMI
   TEXTUAL-CONVENTION
      FROM SNMPv2-TC
   MODULE-COMPLIANCE, OBJECT-GROUP
      FROM SNMPv2-CONF
   InetAddressType, InetAddress, InetPortNumber
      FROM INET-ADDRESS-MIB;

-- ## Module definition ###
rserpoolMIB MODULE-IDENTITY
   LAST-UPDATED
      "200904070000Z" -- April 07, 2009
   ORGANIZATION
      "IEM-TdR, UNIVERSITY OF DUISBURG-ESSEN"
   CONTACT-INFO
      " THOMAS-DREIBHOLZ

          Postal: University of Duisburg-Essen
                    Institute for Experimental Mathematics
                    Ellernstrasse 29
                    D-45326 Essen
                    Germany
          Phone: +49-201-183-7637
          Fax: +49-201-183-7673
          Email: dreibh@iem.uni-due.de

JAIWANT-MULIK

     Postal: Delaware State University
               CIS Department
               1200 N. DuPont Hw
               Dover, DE
               USA 19904
     Phone: +1-302-857-7910
     Fax: +1-302-857-6552
     Email: jaiwant@mulik.com"
DESCRIPTION
    "The MIB module for managing an RSerPool implementation.

```
         This version of this MIB module is part of RFC 5525;
         see the RFC itself for full legal notices."

      REVISION
         "200904070000Z" -- April 07, 2009
      DESCRIPTION
         "This version of the MIB module is published as RFC 5525"
      ::= { experimental 125 }

-- ## RSerPool type definitions ###############################
RSerPoolENRPServerIdentifierTC ::= TEXTUAL-CONVENTION
   DISPLAY-HINT "x"
   STATUS       current
   DESCRIPTION  "The ID of an ENRP server"
   SYNTAX       Unsigned32 (1..4294967295)

RSerPoolOperationScopeTC ::= TEXTUAL-CONVENTION
   DISPLAY-HINT "1024t"
   STATUS       current
   DESCRIPTION  "The ID of an operation scope"
   SYNTAX       OCTET STRING (SIZE (0..65535))

RSerPoolPoolHandleTC ::= TEXTUAL-CONVENTION
   DISPLAY-HINT "1024t"
   STATUS       current
   DESCRIPTION  "The pool handle"
   SYNTAX       OCTET STRING (SIZE (0..65535))

RserpoolPoolElementIdentifierTC ::= TEXTUAL-CONVENTION
   DISPLAY-HINT "x"
   STATUS       current
   DESCRIPTION  "The pool element ID"
   SYNTAX       Unsigned32 (1..4294967295)

RSerPoolPolicyIdentifierTC ::= TEXTUAL-CONVENTION
   DISPLAY-HINT "x"
   STATUS       current
   DESCRIPTION  "The ID of the pool policy"
   SYNTAX       Unsigned32 (1..4294967295)

RSerPoolPolicyLoadTC ::= TEXTUAL-CONVENTION
   DISPLAY-HINT "d"
   STATUS       current
   DESCRIPTION  "The load status of a pool element"
   SYNTAX       Unsigned32 (0..4294967295)
```

```
RSerPoolPolicyWeightTC ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS       current
    DESCRIPTION  "The weight of a pool element"
    SYNTAX       Unsigned32 (0..4294967295)

RSerPoolTransportUseTypeTC ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION "The transport use of a pool element"
    SYNTAX       INTEGER {
        dataOnly(0),
        dataPlusControl(1)
    }

RSerPoolOpaqueAddressTC ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "1024t"
    STATUS       current
    DESCRIPTION  "Opaque address"
    SYNTAX       OCTET STRING  (SIZE (0..65535))

-- ## Top-level definitions ###################################
rserpoolMIBObjects     OBJECT IDENTIFIER ::= { rserpoolMIB 1 }
rserpoolMIBConformance OBJECT IDENTIFIER ::= { rserpoolMIB 2 }

rserpoolENRPServers    OBJECT IDENTIFIER ::= { rserpoolMIBObjects 1 }
rserpoolPoolElements   OBJECT IDENTIFIER ::= { rserpoolMIBObjects 2 }
rserpoolPoolUsers      OBJECT IDENTIFIER ::= { rserpoolMIBObjects 3 }

-- ################################################################
-- #### ENRP Servers Section                                   ####
-- ################################################################

-- ## Definition of the ENRP server table ######################
rserpoolENRPTable OBJECT-TYPE
    SYNTAX     SEQUENCE OF RserpoolENRPEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
       "The table listing of ENRP servers."
    ::= { rserpoolENRPServers 1 }

rserpoolENRPEntry OBJECT-TYPE
    SYNTAX     RserpoolENRPEntry
    MAX-ACCESS not-accessible
    STATUS     current
```

```
   DESCRIPTION
      "An ENRP server entry in the table listing of ENRP
      servers."
   INDEX { rserpoolENRPIndex }
   ::= { rserpoolENRPTable 1 }

RserpoolENRPEntry ::= SEQUENCE {
rserpoolENRPIndex                  Unsigned32,
rserpoolENRPOperationScope         RSerPoolOperationScopeTC,
rserpoolENRPIdentifier             RSerPoolENRPServerIdentifierTC,
rserpoolENRPDescription            OCTET STRING,
rserpoolENRPUptime                 TimeTicks,
rserpoolENRPPort                   InetPortNumber,
rserpoolENRPASAPAnnouncePort       InetPortNumber,
rserpoolENRPASAPAnnounceAddrType   InetAddressType,
rserpoolENRPASAPAnnounceAddr       InetAddress,
rserpoolENRPENRPAnnouncePort       InetPortNumber,
rserpoolENRPENRPAnnounceAddrType   InetAddressType,
rserpoolENRPENRPAnnounceAddr       InetAddress }

rserpoolENRPIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (1..4294967295)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An integer to uniquely identify an ENRP server."
   ::= { rserpoolENRPEntry 1 }

rserpoolENRPOperationScope OBJECT-TYPE
   SYNTAX      RSerPoolOperationScopeTC
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The definition of the operation scope of this ENRP server."
   REFERENCE
      "Section 1.2 of RFC 3237 defines the term operation scope."
   ::= { rserpoolENRPEntry 2 }

rserpoolENRPIdentifier OBJECT-TYPE
   SYNTAX      RSerPoolENRPServerIdentifierTC
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The ENRP server identifier of this ENRP server."
   REFERENCE
      "Section 3.1 of RFC 5351 explains the ENRP server identifier."
   ::= { rserpoolENRPEntry 3 }
```

```
rserpoolENRPDescription OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (0..255))
    MAX-ACCESS read-write
    STATUS      current
    DESCRIPTION
        "A textual description of this ENRP server, e.g., its location
        and a contact address of its administrator.

        This object SHOULD be maintained in a persistent manner."
    ::= { rserpoolENRPEntry 4 }

rserpoolENRPUptime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The ENRP service uptime of this ENRP server."
    ::= { rserpoolENRPEntry 5 }

rserpoolENRPPort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The Stream Control Transmission Protocol (SCTP) port number of
        the ENRP protocol endpoint of this ENRP server."
    REFERENCE
        "RFC 5353 defines the ENRP protocol."
    ::= { rserpoolENRPEntry 6 }

rserpoolENRPASAPAnnouncePort OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The destination UDP port number to which ASAP multicast announce
        messages are sent."
    REFERENCE
        "Section 3.2 of RFC 5351 explains the server-discovery mechanism
        using ASAP announces."
    ::= { rserpoolENRPEntry 7 }

rserpoolENRPASAPAnnounceAddrType OBJECT-TYPE
    SYNTAX      InetAddressType { ipv4(1), ipv6(2) }
    MAX-ACCESS read-only
    STATUS      current
```

```
    DESCRIPTION
       "The network-layer protocol over which ASAP multicast announce
       messages are sent."
    REFERENCE
       "Section 3.2 of RFC 5351 explains the server-discovery mechanism
       using ASAP announces."
    ::= { rserpoolENRPEntry 8 }

rserpoolENRPASAPAnnounceAddr OBJECT-TYPE
    SYNTAX     InetAddress (SIZE(4|16))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The destination IP multicast address to which ASAP multicast
       announce messages are sent.  The type of this address is
       given in rserpoolENRPASAPAnnounceAddrType."
    REFERENCE
       "Section 3.2 of RFC 5351 explains the server-discovery mechanism
       using ASAP announces."
    ::= { rserpoolENRPEntry 9 }

rserpoolENRPENRPAnnouncePort OBJECT-TYPE
    SYNTAX     InetPortNumber
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The destination UDP port number to which ENRP multicast announce
       messages are sent."
    REFERENCE
       "Section 3.1 of RFC 5353 explains the ENRP multicast
       announce mechanism."
    ::= { rserpoolENRPEntry 10 }

rserpoolENRPENRPAnnounceAddrType OBJECT-TYPE
    SYNTAX     InetAddressType { ipv4(1), ipv6(2) }
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The network-layer protocol over which ENRP multicast announce
       messages are sent."
    REFERENCE
       "Section 3.1 of RFC 5353 explains the ENRP multicast
       announce mechanism."
    ::= { rserpoolENRPEntry 11 }

rserpoolENRPENRPAnnounceAddr OBJECT-TYPE
    SYNTAX     InetAddress (SIZE(4|16))
    MAX-ACCESS read-only
```

```
   STATUS       current
   DESCRIPTION
      "The destination multicast IP address to which ENRP multicast
      announce messages are sent.  The type of this address
      is given in rserpoolENRPENRPAnnounceAddrType."
   REFERENCE
      "Section 3.1 of RFC 5353 explains the ENRP multicast
      announce mechanism."
   ::= { rserpoolENRPEntry 12 }

-- ## Definition of the pool table ###############################
rserpoolENRPPoolTable OBJECT-TYPE
   SYNTAX       SEQUENCE OF RserpoolENRPPoolEntry
   MAX-ACCESS not-accessible
   STATUS       current
   DESCRIPTION
      "The table listing of pools."
   ::= { rserpoolENRPServers 3 }

rserpoolENRPPoolEntry OBJECT-TYPE
   SYNTAX       RserpoolENRPPoolEntry
   MAX-ACCESS not-accessible
   STATUS       current
   DESCRIPTION
      "The pool entry in the table listing of pools."
   INDEX { rserpoolENRPIndex, rserpoolENRPPoolIndex }
   ::= { rserpoolENRPPoolTable 1 }

RserpoolENRPPoolEntry ::= SEQUENCE {
   rserpoolENRPPoolIndex  Unsigned32,
   rserpoolENRPPoolHandle RSerPoolPoolHandleTC }

rserpoolENRPPoolIndex OBJECT-TYPE
   SYNTAX       Unsigned32 (1..4294967295)
   MAX-ACCESS not-accessible
   STATUS       current
   DESCRIPTION
      "An integer to uniquely identify a pool."
   ::= { rserpoolENRPPoolEntry 1 }

rserpoolENRPPoolHandle OBJECT-TYPE
   SYNTAX       RSerPoolPoolHandleTC
   MAX-ACCESS read-only
   STATUS       current
   DESCRIPTION
      "The pool handle of this pool."
   REFERENCE
      "Section 1.2 of RFC 3237 defines the term pool handle."
```

```
   ::= { rserpoolENRPPoolEntry 2 }

-- ## Definition of the pool element table #######################
rserpoolENRPPoolElementTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF RserpoolENRPPoolElementEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
      "The table listing of pool elements."
   ::= { rserpoolENRPServers 4 }

rserpoolENRPPoolElementEntry OBJECT-TYPE
   SYNTAX      RserpoolENRPPoolElementEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
      "A pool element in the table listing of pool elements."
   INDEX {
      rserpoolENRPIndex,
      rserpoolENRPPoolIndex,
      rserpoolENRPPoolElementIndex }
   ::= { rserpoolENRPPoolElementTable 1 }

RserpoolENRPPoolElementEntry ::= SEQUENCE {
   rserpoolENRPPoolElementIndex   Unsigned32,
   rserpoolENRPPoolElementID       RserpoolPoolElementIdentifierTC,
   rserpoolENRPASAPTransportPort   InetPortNumber,
   rserpoolENRPUserTransportProto Unsigned32,
   rserpoolENRPUserTransportPort   InetPortNumber,
   rserpoolENRPUserTransportUse    RSerPoolTransportUseTypeTC,
   rserpoolENRPPolicyID            RSerPoolPolicyIdentifierTC,
   rserpoolENRPPolicyDescription  OCTET STRING,
   rserpoolENRPPolicyWeight        RSerPoolPolicyWeightTC,
   rserpoolENRPPolicyLoad          RSerPoolPolicyLoadTC,
   rserpoolENRPPolicyLoadDeg       RSerPoolPolicyLoadTC,
   rserpoolENRPRegistrationLife    TimeTicks,
   rserpoolENRPHomeENRPServer      RSerPoolENRPServerIdentifierTC }


rserpoolENRPPoolElementIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (1..4294967295)
   MAX-ACCESS not-accessible
   STATUS      current
```

      DESCRIPTION
         "An integer to uniquely identify a pool element. Note,
         that uniqueness of a pool element identifier in the pool
         is not enforced; therefore, this index is required here!"
      ::={ rserpoolENRPPoolElementEntry 1 }

rserpoolENRPPoolElementID OBJECT-TYPE
      SYNTAX   RserpoolPoolElementIdentifierTC
      MAX-ACCESS read-only
      STATUS   current
      DESCRIPTION
         "The pool element identifier of this pool element."
      REFERENCE
         "Section 2.2 of RFC 5351 explains the pool element identifier
         usage."
      ::={ rserpoolENRPPoolElementEntry 2 }

rserpoolENRPASAPTransportPort OBJECT-TYPE
      SYNTAX   InetPortNumber
      MAX-ACCESS read-only
      STATUS   current
      DESCRIPTION
         "The SCTP port number of the ASAP endpoint of this pool
         element."
      REFERENCE
         "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
         which the port number is given here."
      ::= { rserpoolENRPPoolElementEntry 3 }

rserpoolENRPUserTransportProto OBJECT-TYPE
      SYNTAX   Unsigned32 (0..255)
      MAX-ACCESS read-only
      STATUS   current
      DESCRIPTION
         "The transport protocol number of the service endpoint
         of this pool element."
      REFERENCE
         "Section 3.10 of RFC 5354 defines the User Transport Parameter of
         which the transport protocol number is given here."
      ::= { rserpoolENRPPoolElementEntry 4 }

rserpoolENRPUserTransportPort OBJECT-TYPE
      SYNTAX   InetPortNumber
      MAX-ACCESS read-only
      STATUS   current
      DESCRIPTION
         "The transport protocol's port number of the service
         endpoint of this pool element."

```
   REFERENCE
      "Section 3.10 of RFC 5354 defines the User Transport Parameter of
      which the port number is given here."
   ::= { rserpoolENRPPoolElementEntry 5 }

rserpoolENRPUserTransportUse OBJECT-TYPE
   SYNTAX      RSerPoolTransportUseTypeTC
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The transport use of the service endpoint of this pool
      element."
   REFERENCE
      "Section 3.10 of RFC 5354 defines the User Transport Parameter of
      which the transport use is given here."
   ::= { rserpoolENRPPoolElementEntry 6 }

rserpoolENRPPolicyID OBJECT-TYPE
   SYNTAX      RSerPoolPolicyIdentifierTC
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The pool policy of this pool element."
   REFERENCE
      "Section 3.8 of RFC 5354 defines the Member Selection Policy
      Parameter of which the policy identifier is given here."
   ::= { rserpoolENRPPoolElementEntry 7 }

rserpoolENRPPolicyDescription OBJECT-TYPE
   SYNTAX      OCTET STRING (SIZE (0..255))
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The textual description of the pool policy of this pool
      element."
   ::= { rserpoolENRPPoolElementEntry 8 }

rserpoolENRPPolicyWeight OBJECT-TYPE
   SYNTAX      RSerPoolPolicyWeightTC
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The pool policy's weight parameter for this pool element."
   REFERENCE
      "Section 3.8 of RFC 5354 defines the Member Selection Policy
      Parameter of which the policy's weight parameter is given here."
   ::= { rserpoolENRPPoolElementEntry 9 }
```

```
rserpoolENRPPolicyLoad OBJECT-TYPE
    SYNTAX      RSerPoolPolicyLoadTC
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The pool policy's load status for this pool element."
    REFERENCE
       "Section 3.8 of RFC 5354 defines the Member Selection Policy
       Parameter of which the policy's load parameter is given here."
    ::= { rserpoolENRPPoolElementEntry 10 }

rserpoolENRPPolicyLoadDeg OBJECT-TYPE
    SYNTAX      RSerPoolPolicyLoadTC
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The pool policy's load degradation parameter for this pool
       element."
    REFERENCE
       "Section 3.8 of RFC 5354 defines the Member Selection Policy
       Parameter of which the policy's load degradation parameter is
       given here."
    ::= { rserpoolENRPPoolElementEntry 11 }

rserpoolENRPRegistrationLife OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The registration life of this pool element."
   REFERENCE
       "Section 3.10 of RFC 5354 defines the Registration Life."
    ::= { rserpoolENRPPoolElementEntry 12 }

rserpoolENRPHomeENRPServer OBJECT-TYPE
    SYNTAX      RSerPoolENRPServerIdentifierTC
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The ID of the Home ENRP server of this pool element."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the Home ENRP Server
       Identifier."
    ::= { rserpoolENRPPoolElementEntry 13 }

-- ## Definition of the ASAP transport address list table #########
rserpoolENRPASAPAddrTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RserpoolENRPASAPAddrTableEntry
```

```
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
       "A table listing of all IP addresses of the ASAP transport
       endpoint."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
       which the addresses are listed in this table."
    ::= { rserpoolENRPServers 5 }

rserpoolENRPASAPAddrTableEntry  OBJECT-TYPE
    SYNTAX      RserpoolENRPASAPAddrTableEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
       "An IP address of the ASAP transport endpoint."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
       which an address is contained by this entry."
    INDEX {
       rserpoolENRPIndex,
       rserpoolENRPPoolIndex,
       rserpoolENRPPoolElementIndex,
       rserpoolENRPASAPAddrTableIndex }
    ::= { rserpoolENRPASAPAddrTable 1 }

RserpoolENRPASAPAddrTableEntry ::= SEQUENCE {
    rserpoolENRPASAPAddrTableIndex Unsigned32,
    rserpoolENRPASAPL3Type          InetAddressType,
    rserpoolENRPASAPL3Addr          InetAddress }

rserpoolENRPASAPAddrTableIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
       "A unique identifier for the IP address of an ASAP transport
       endpoint."
    ::= { rserpoolENRPASAPAddrTableEntry 1 }

rserpoolENRPASAPL3Type OBJECT-TYPE
    SYNTAX      InetAddressType { ipv4(1), ipv6(2) }
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The network-layer protocol (IPv4 or IPv6) of an IP address of
       an ASAP transport endpoint."
    REFERENCE
```

```
      "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
      which the network-layer protocol number is given here."
   ::= { rserpoolENRPASAPAddrTableEntry 2 }


rserpoolENRPASAPL3Addr OBJECT-TYPE
   SYNTAX      InetAddress (SIZE(4|16))
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The IP address of an ASAP transport endpoint.  The type of
      this address is given in rserpoolENRPASAPL3Type."
   REFERENCE
      "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
      which the network-layer address (IPv4 or IPv6) is given here."
   ::= { rserpoolENRPASAPAddrTableEntry 3 }

-- ## Definition of the user transport address list table #########
rserpoolENRPUserAddrTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF RserpoolENRPUserAddrTableEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
      "A table listing of all IP addresses of the user
      transport endpoint."
   REFERENCE
      "Section 3.10 of RFC 5354 defines the User Transport Parameter of
      which the addresses are listed in this table."
   ::= { rserpoolENRPServers 6 }


rserpoolENRPUserAddrTableEntry  OBJECT-TYPE
   SYNTAX      RserpoolENRPUserAddrTableEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
      "An IP address of the user transport endpoint."
   REFERENCE
      "Section 3.10 of RFC 5354 defines the User Transport Parameter of
      which an address is contained by this entry."
   INDEX {
      rserpoolENRPIndex,
      rserpoolENRPPoolIndex,
      rserpoolENRPPoolElementIndex,
      rserpoolENRPUserAddrTableIndex }
   ::= { rserpoolENRPUserAddrTable 1 }


RserpoolENRPUserAddrTableEntry ::= SEQUENCE {
   rserpoolENRPUserAddrTableIndex Unsigned32,
   rserpoolENRPUserL3Type         InetAddressType,
```

```
    rserpoolENRPUserL3Addr          InetAddress,
    rserpoolENRPUserL3Opaque        RSerPoolOpaqueAddressTC }

rserpoolENRPUserAddrTableIndex OBJECT-TYPE
    SYNTAX     Unsigned32 (1..4294967295)
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
       "A unique identifier for the IP address of a user transport
       endpoint."
    ::= { rserpoolENRPUserAddrTableEntry 1 }

rserpoolENRPUserL3Type OBJECT-TYPE
    SYNTAX     InetAddressType { unknown(0), ipv4(1), ipv6(2) }
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The network-layer protocol (IPv4 or IPv6) of an IP address
       of a user transport endpoint.  Set to unknown for an opaque
       address."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the User Transport Parameter of
       which the network-layer protocol number is given here."
    ::= { rserpoolENRPUserAddrTableEntry 2 }

rserpoolENRPUserL3Addr OBJECT-TYPE
    SYNTAX     InetAddress (SIZE(0|4|16))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The IP address of a user transport endpoint.  The type of
       this address is given in rserpoolENRPUserL3Type."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the User Transport Parameter of
       which the network-layer address (IPv4 or IPv6) is given here."
    ::= { rserpoolENRPUserAddrTableEntry 3 }

rserpoolENRPUserL3Opaque OBJECT-TYPE
    SYNTAX     RSerPoolOpaqueAddressTC
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The opaque address of a user transport endpoint."
    REFERENCE
       "Section 3.16 of RFC 5354 defines the opaque transport address."
    ::= { rserpoolENRPUserAddrTableEntry 4 }
```

-- ## Definition of ENRP address list table #######################
rserpoolENRPENRPAddrTable OBJECT-TYPE
    SYNTAX   SEQUENCE OF RserpoolENRPENRPAddrTableEntry
    MAX-ACCESS not-accessible
    STATUS   current
    DESCRIPTION
       "A table listing of all IP addresses of the ENRP
       transport endpoint."
    ::= { rserpoolENRPServers 7 }

rserpoolENRPENRPAddrTableEntry OBJECT-TYPE
    SYNTAX   RserpoolENRPENRPAddrTableEntry
    MAX-ACCESS not-accessible
    STATUS   current
    DESCRIPTION
       "An IP address of the ENRP transport endpoint."
    INDEX {
       rserpoolENRPIndex,
       rserpoolENRPENRPAddrTableIndex }
    ::= { rserpoolENRPENRPAddrTable 1 }

RserpoolENRPENRPAddrTableEntry ::= SEQUENCE {
    rserpoolENRPENRPAddrTableIndex Unsigned32,
    rserpoolENRPENRPL3Type   InetAddressType,
    rserpoolENRPENRPL3Addr   InetAddress }

rserpoolENRPENRPAddrTableIndex OBJECT-TYPE
    SYNTAX   Unsigned32 (1..4294967295)
    MAX-ACCESS not-accessible
    STATUS   current
    DESCRIPTION
       "A unique identifier for the IP address of an ENRP transport
       endpoint."
    ::= { rserpoolENRPENRPAddrTableEntry 1 }

rserpoolENRPENRPL3Type OBJECT-TYPE
    SYNTAX   InetAddressType { ipv4(1), ipv6(2) }
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
       "The network-layer protocol (IPv4 or IPv6) of an IP address of
       an ENRP transport endpoint."
    REFERENCE
       "RFC 5353 defines the ENRP protocol."
    ::= { rserpoolENRPENRPAddrTableEntry 2 }

```
rserpoolENRPENRPL3Addr OBJECT-TYPE
   SYNTAX      InetAddress (SIZE(4|16))
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The IP address of an ENRP transport endpoint.  The type of
      this address is given in rserpoolENRPENRPL3Type."
   REFERENCE
      "RFC 5353 defines the ENRP protocol."
   ::= { rserpoolENRPENRPAddrTableEntry 3 }

-- ## Definition of peer table ###################################
rserpoolENRPPeerTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF RserpoolENRPPeerEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
      "The table listing of a peer table."
   ::= { rserpoolENRPServers 8 }

rserpoolENRPPeerEntry OBJECT-TYPE
   SYNTAX      RserpoolENRPPeerEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
      "A peer entry in the table listing of a peer table."
   INDEX { rserpoolENRPPeerIndex }
   ::= { rserpoolENRPPeerTable 1 }

RserpoolENRPPeerEntry ::= SEQUENCE {
   rserpoolENRPPeerIndex      Unsigned32,
   rserpoolENRPPeerIdentifier RSerPoolENRPServerIdentifierTC,
   rserpoolENRPPeerPort       InetPortNumber,
   rserpoolENRPPeerLastHeard  TimeTicks }

rserpoolENRPPeerIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (1..4294967295)
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
      "A unique identifier for a peer entry in the table
      listing of a peer table."
   ::= { rserpoolENRPPeerEntry 1 }

rserpoolENRPPeerIdentifier OBJECT-TYPE
   SYNTAX      RSerPoolENRPServerIdentifierTC
   MAX-ACCESS read-only
   STATUS      current
```

```
   DESCRIPTION
       "The ENRP identifier of this peer."
   REFERENCE
       "RFC 5353 explains the usage of the ENRP server identifier."
   ::= { rserpoolENRPPeerEntry 2 }

rserpoolENRPPeerPort OBJECT-TYPE
   SYNTAX      InetPortNumber
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
       "The SCTP port number of the ENRP transport endpoint of
       this peer."
   REFERENCE
       "RFC 5353 defines the ENRP protocol."
   ::= { rserpoolENRPPeerEntry 3 }

rserpoolENRPPeerLastHeard OBJECT-TYPE
   SYNTAX      TimeTicks
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
       "The time since the reception of the last ENRP Presence
       message of this peer."
   REFERENCE
       "Section 4.1 of RFC 5353 defines the last heard value."
   ::= { rserpoolENRPPeerEntry 4 }

-- ## Definition of peer address list table ######################
rserpoolENRPPeerAddrTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF RserpoolENRPPeerAddrTableEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
       "A table listing of the peer endpoint addresses."
   ::= { rserpoolENRPServers 9 }

rserpoolENRPPeerAddrTableEntry  OBJECT-TYPE
   SYNTAX      RserpoolENRPPeerAddrTableEntry
   MAX-ACCESS not-accessible
   STATUS      current
   DESCRIPTION
       "A table listing of all IP addresses of the ENRP
       transport endpoint of a peer referenced by rserpoolENRPPeerIndex."
   INDEX {
       rserpoolENRPPeerIndex,
       rserpoolENRPPeerAddrTableIndex }
   ::= { rserpoolENRPPeerAddrTable 1 }
```

```
RserpoolENRPPeerAddrTableEntry ::= SEQUENCE {
   rserpoolENRPPeerAddrTableIndex Unsigned32,
   rserpoolENRPPeerL3Type         InetAddressType,
   rserpoolENRPPeerL3Addr         InetAddress }

rserpoolENRPPeerAddrTableIndex OBJECT-TYPE
   SYNTAX     Unsigned32 (1..4294967295)
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "A unique identifier for the IP address of a peer ENRP
      transport endpoint."
   ::= { rserpoolENRPPeerAddrTableEntry 1 }

rserpoolENRPPeerL3Type OBJECT-TYPE
   SYNTAX     InetAddressType { ipv4(1), ipv6(2) }
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The network-layer protocol (IPv4 or IPv6) of an IP address
      of a peer ENRP transport endpoint."
   REFERENCE
      "RFC 5353 defines the ENRP protocol."
   ::= { rserpoolENRPPeerAddrTableEntry 2 }

rserpoolENRPPeerL3Addr OBJECT-TYPE
   SYNTAX     InetAddress (SIZE(4|16))
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The IP address of a peer ENRP transport endpoint.  The type
      of this address is given in rserpoolENRPPeerL3Type."
   REFERENCE
      "RFC 5353 defines the ENRP protocol."
   ::= { rserpoolENRPPeerAddrTableEntry 3 }

-- ###################################################################
-- #### Pool Elements Section                                     ####
-- ###################################################################

-- ## Definition of the pool element table #######################
rserpoolPETable OBJECT-TYPE
   SYNTAX     SEQUENCE OF RserpoolPEEntry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "The table listing of pool elements."
   ::= { rserpoolPoolElements 1 }
```

```
rserpoolPEEntry OBJECT-TYPE
   SYNTAX     RserpoolPEEntry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "A pool element in the table listing of pool elements."
   INDEX { rserpoolPEIndex }
   ::= { rserpoolPETable 1 }

RserpoolPEEntry ::= SEQUENCE {
   rserpoolPEIndex             Unsigned32,
   rserpoolPEOperationScope    RSerPoolOperationScopeTC,
   rserpoolPEPoolHandle        RSerPoolPoolHandleTC,
   rserpoolPEIdentifier        RserpoolPoolElementIdentifierTC,
   rserpoolPEDescription       OCTET STRING,
   rserpoolPEUptime            TimeTicks,
   rserpoolPEASAPTransportPort InetPortNumber,
   rserpoolPEUserTransportProto Unsigned32,
   rserpoolPEUserTransportPort  InetPortNumber,
   rserpoolPEUserTransportUse   RSerPoolTransportUseTypeTC,
   rserpoolPEPolicyID          RSerPoolPolicyIdentifierTC,
   rserpoolPEPolicyDescription OCTET STRING,
   rserpoolPEPolicyWeight      RSerPoolPolicyWeightTC,
   rserpoolPEPolicyLoad        RSerPoolPolicyLoadTC,
   rserpoolPEPolicyLoadDeg     RSerPoolPolicyLoadTC,
   rserpoolPERegistrationLife  TimeTicks,
   rserpoolPEHomeENRPServer     RSerPoolENRPServerIdentifierTC }


rserpoolPEIndex OBJECT-TYPE
   SYNTAX     Unsigned32 (1..4294967295)
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "An integer to uniquely identify a pool element.  Note,
      that uniqueness of a pool element identifier in the pool
      is not enforced; therefore, this index is required here!"
   ::={ rserpoolPEEntry 1 }

rserpoolPEOperationScope OBJECT-TYPE
   SYNTAX     RSerPoolOperationScopeTC
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The operation scope of this pool element."
   REFERENCE
      "Section 1.2 of RFC 3237 defines the term operation scope."
   ::= { rserpoolPEEntry 2 }
```

```
rserpoolPEPoolHandle OBJECT-TYPE
   SYNTAX      RSerPoolPoolHandleTC
   MAX-ACCESS read-write
   STATUS      current
   DESCRIPTION
      "The pool handle of this pool element.  Changing this object
      will update the pool element's pool handle and result in a
      re-registration.

      This object SHOULD be maintained in a persistent manner."
   REFERENCE
      "Section 1.2 of RFC 3237 defines the term pool handle."
   ::={ rserpoolPEEntry 3 }

rserpoolPEIdentifier OBJECT-TYPE
   SYNTAX      RserpoolPoolElementIdentifierTC
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The pool element identifier of this pool element."
   REFERENCE
      "Section 3.10 of RFC 5354 defines the pool element identifier."
   ::={ rserpoolPEEntry 4 }

rserpoolPEDescription OBJECT-TYPE
   SYNTAX      OCTET STRING (SIZE (0..255))
   MAX-ACCESS read-write
   STATUS      current
   DESCRIPTION
      "A textual description of this pool element, e.g., its location
      and a contact address of its administrator.

      This object SHOULD be maintained in a persistent manner."
   ::= { rserpoolPEEntry 5 }

rserpoolPEUptime OBJECT-TYPE
   SYNTAX      TimeTicks
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
      "The ENRP service uptime of this pool element."
   ::= { rserpoolPEEntry 6 }

rserpoolPEASAPTransportPort OBJECT-TYPE
   SYNTAX      InetPortNumber
   MAX-ACCESS read-only
   STATUS      current
   DESCRIPTION
```

          "The SCTP port number of the ASAP endpoint of this pool element."
       REFERENCE
          "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
          which the port number is given here."
       ::= { rserpoolPEEntry 7 }

rserpoolPEUserTransportProto OBJECT-TYPE
    SYNTAX   Unsigned32 (0..255)
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
       "The transport protocol number of the service endpoint
       of this pool element."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the User Transport Parameter of
       which the transport protocol number is given here."
    ::= { rserpoolPEEntry 8 }

rserpoolPEUserTransportPort OBJECT-TYPE
    SYNTAX   InetPortNumber
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
       "The transport protocol's port number of the service
       endpoint of this pool element."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the User Transport Parameter of
       which the port number is given here."
    ::= { rserpoolPEEntry 9 }

rserpoolPEUserTransportUse OBJECT-TYPE
    SYNTAX   RSerPoolTransportUseTypeTC
    MAX-ACCESS read-only
    STATUS   current
    DESCRIPTION
       "The transport use of the service endpoint of this pool element."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the User Transport Parameter of
       which the transport use is given here."
    ::= { rserpoolPEEntry 10 }

rserpoolPEPolicyID OBJECT-TYPE
    SYNTAX   RSerPoolPolicyIdentifierTC
    MAX-ACCESS read-write
    STATUS   current
    DESCRIPTION
       "The pool policy of this pool element. Changing this object
       will update the pool element's policy and result in a

          re-registration.

          This object SHOULD be maintained in a persistent manner."
       REFERENCE
          "Section 3.8 of RFC 5354 defines the Member Selection Policy
          Parameter of which the policy identifier is given here."
       ::= { rserpoolPEEntry 11 }

    rserpoolPEPolicyDescription OBJECT-TYPE
       SYNTAX   OCTET STRING (SIZE (0..255))
       MAX-ACCESS read-write
       STATUS   current
       DESCRIPTION
          "The textual description of the pool policy of this pool element.

          This object SHOULD be maintained in a persistent manner."
       ::= { rserpoolPEEntry 12 }

    rserpoolPEPolicyWeight OBJECT-TYPE
       SYNTAX   RSerPoolPolicyWeightTC
       MAX-ACCESS read-write
       STATUS   current
       DESCRIPTION
          "The pool policy's weight parameter for this pool element.
          Changing this object will update the pool element's policy
          weight setting and result in a re-registration.

          This object SHOULD be maintained in a persistent manner."
       REFERENCE
          "Section 3.8 of RFC 5354 defines the Member Selection Policy
          Parameter of which the policy's weight parameter is given here."
       ::= { rserpoolPEEntry 13 }

    rserpoolPEPolicyLoad OBJECT-TYPE
       SYNTAX   RSerPoolPolicyLoadTC
       MAX-ACCESS read-only
       STATUS   current
       DESCRIPTION
          "The pool policy's load status for this pool element."
       REFERENCE
          "Section 3.8 of RFC 5354 defines the Member Selection Policy
          Parameter of which the policy's load parameter is given here."
       ::= { rserpoolPEEntry 14 }

```
rserpoolPEPolicyLoadDeg OBJECT-TYPE
    SYNTAX      RSerPoolPolicyLoadTC
    MAX-ACCESS read-write
    STATUS      current
    DESCRIPTION
        "The pool policy's load degradation parameter for this pool
        element.  Changing this object will update the pool element's
        load degradation setting and result in a re-registration.

        This object SHOULD be maintained in a persistent manner."
    REFERENCE
        "Section 3.8 of RFC 5354 defines the Member Selection Policy
        Parameter of which the policy's load degradation parameter is
        given here."
    ::= { rserpoolPEEntry 15 }

rserpoolPERegistrationLife OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS read-write
    STATUS      current
    DESCRIPTION
        "The registration life of this pool element.  Changing this
        object will update the pool element's lifetime setting and
        result in a re-registration.

        This object SHOULD be maintained in a persistent manner."
    REFERENCE
        "Section 3.10 of RFC 5354 defines the Registration Life."
    ::= { rserpoolPEEntry 16 }

rserpoolPEHomeENRPServer OBJECT-TYPE
    SYNTAX      RSerPoolENRPServerIdentifierTC
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The ID of the Home ENRP server of this pool element."
    REFERENCE
        "Section 3.10 of RFC 5354 defines the Home ENRP Server
        Identifier."
    ::= { rserpoolPEEntry 17 }

-- ## Definition of the ASAP transport address list table #########
rserpoolPEASAPAddrTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RserpoolPEASAPAddrTableEntry
    MAX-ACCESS not-accessible
    STATUS      current
```

```
      DESCRIPTION
         "A table listing of all IP addresses of the ASAP transport
         endpoint."
      REFERENCE
         "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
         which the addresses are listed in this table."
      ::= { rserpoolPoolElements 2 }

rserpoolPEASAPAddrTableEntry  OBJECT-TYPE
      SYNTAX      RserpoolPEASAPAddrTableEntry
      MAX-ACCESS not-accessible
      STATUS      current
      DESCRIPTION
         "An IP address of the ASAP transport endpoint."
     REFERENCE
         "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
         which an address is contained by this entry."
     INDEX {
         rserpoolPEIndex,
         rserpoolPEASAPAddrTableIndex }
      ::= { rserpoolPEASAPAddrTable 1 }

RserpoolPEASAPAddrTableEntry ::= SEQUENCE {
      rserpoolPEASAPAddrTableIndex Unsigned32,
      rserpoolPEASAPL3Type         InetAddressType,
      rserpoolPEASAPL3Addr         InetAddress }

rserpoolPEASAPAddrTableIndex OBJECT-TYPE
      SYNTAX      Unsigned32 (1..4294967295)
      MAX-ACCESS not-accessible
      STATUS      current
      DESCRIPTION
         "A unique identifier for the IP address of an ASAP transport
         endpoint."
      ::= { rserpoolPEASAPAddrTableEntry 1 }

rserpoolPEASAPL3Type OBJECT-TYPE
      SYNTAX      InetAddressType { ipv4(1), ipv6(2) }
      MAX-ACCESS read-only
      STATUS      current
      DESCRIPTION
         "The network-layer protocol (IPv4 or IPv6) of an IP address of
         an ASAP transport endpoint."
      REFERENCE
         "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
         which the network-layer protocol number is given here."
      ::= { rserpoolPEASAPAddrTableEntry 2 }
```

```
rserpoolPEASAPL3Addr OBJECT-TYPE
    SYNTAX      InetAddress (SIZE(4|16))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The IP address of an ASAP transport endpoint.  The type of
        this address is given in rserpoolPEASAPL3Type."
    REFERENCE
        "Section 3.10 of RFC 5354 defines the ASAP Transport Parameter of
        which the network-layer address (IPv4 or IPv6) is given here."
    ::= { rserpoolPEASAPAddrTableEntry 3 }

-- ## Definition of the user transport address list table #########
rserpoolPEUserAddrTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RserpoolPEUserAddrTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table listing of all IP addresses of the user
        transport endpoint."
    REFERENCE
        "Section 3.10 of RFC 5354 defines the User Transport Parameter of
        which the addresses are listed in this table."
    ::= { rserpoolPoolElements 6 }

rserpoolPEUserAddrTableEntry  OBJECT-TYPE
    SYNTAX      RserpoolPEUserAddrTableEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An IP address of the user transport endpoint."
  REFERENCE
        "Section 3.10 of RFC 5354 defines the User Transport Parameter of
        which an address is contained by this entry."
    INDEX {
        rserpoolPEIndex,
        rserpoolPEUserAddrTableIndex }
    ::= { rserpoolPEUserAddrTable 1 }

RserpoolPEUserAddrTableEntry ::= SEQUENCE {
    rserpoolPEUserAddrTableIndex Unsigned32,
    rserpoolPEUserL3Type         InetAddressType,
    rserpoolPEUserL3Addr         InetAddress,
    rserpoolPEUserL3Opaque       RSerPoolOpaqueAddressTC }

rserpoolPEUserAddrTableIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..4294967295)
    MAX-ACCESS  not-accessible
```

```
    STATUS      current
    DESCRIPTION
       "A unique identifier for the IP address of a user transport
       endpoint."
    ::= { rserpoolPEUserAddrTableEntry 1 }

rserpoolPEUserL3Type OBJECT-TYPE
    SYNTAX      InetAddressType { unknown(0), ipv4(1), ipv6(2) }
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
       "The network-layer protocol of an IP address of a user transport
       endpoint.  Set to unknown for opaque address."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the User Transport Parameter of
       which the network-layer protocol number is given here."
    ::= { rserpoolPEUserAddrTableEntry 2 }

rserpoolPEUserL3Addr OBJECT-TYPE
    SYNTAX      InetAddress (SIZE(0|4|16))
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
       "The IP address of a user transport endpoint.  The type of
       this address is given in rserpoolPEUserL3Addr."
    REFERENCE
       "Section 3.10 of RFC 5354 defines the User Transport Parameter of
       which the network-layer address (IPv4 or IPv6) is given here."
    ::= { rserpoolPEUserAddrTableEntry 3 }

rserpoolPEUserL3Opaque OBJECT-TYPE
    SYNTAX      RSerPoolOpaqueAddressTC
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
       "The opaque address of a user transport endpoint."
    REFERENCE
       "Section 3.16 of RFC 5354 defines the opaque transport address."
    ::= { rserpoolPEUserAddrTableEntry 4 }

-- ##################################################################
-- #### Pool Users Section                                       ####
-- ##################################################################

-- ## Definition of the pool user table #########################
rserpoolPUTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RserpoolPUEntry
    MAX-ACCESS not-accessible
```

```
         STATUS      current
         DESCRIPTION
            "The table listing of pool users."
         ::= { rserpoolPoolUsers 1 }

   rserpoolPUEntry OBJECT-TYPE
         SYNTAX      RserpoolPUEntry
         MAX-ACCESS not-accessible
         STATUS      current
         DESCRIPTION
            "A pool user in the table listing of pool users."
         INDEX { rserpoolPUIndex }
         ::= { rserpoolPUTable 1 }

   RserpoolPUEntry ::= SEQUENCE {
      rserpoolPUIndex          Unsigned32,
      rserpoolPUOperationScope RSerPoolOperationScopeTC,
      rserpoolPUPoolHandle     RSerPoolPoolHandleTC,
      rserpoolPUDescription    OCTET STRING,
      rserpoolPUUptime         TimeTicks }

   rserpoolPUIndex OBJECT-TYPE
         SYNTAX      Unsigned32 (1..4294967295)
         MAX-ACCESS not-accessible
         STATUS      current
         DESCRIPTION
            "An integer to uniquely identify a pool user."
         ::= { rserpoolPUEntry 1 }

   rserpoolPUOperationScope OBJECT-TYPE
         SYNTAX      RSerPoolOperationScopeTC
         MAX-ACCESS read-only
         STATUS      current
         DESCRIPTION
            "The operation scope of this pool user."
         REFERENCE
            "Section 1.2 of RFC 3237 defines the term operation scope."
         ::= { rserpoolPUEntry 2 }

   rserpoolPUPoolHandle OBJECT-TYPE
         SYNTAX      RSerPoolPoolHandleTC
         MAX-ACCESS read-write
         STATUS      current
```

       DESCRIPTION
          "The pool handle of this pool user. Changing this object
          will update the pool user's pool handle for all future
          sessions.

          This object SHOULD be maintained in a persistent manner."
       REFERENCE
          "Section 1.2 of RFC 3237 defines the term pool handle."
       ::={ rserpoolPUEntry 3 }

   rserpoolPUDescription OBJECT-TYPE
       SYNTAX   OCTET STRING (SIZE (0..255))
       MAX-ACCESS read-write
       STATUS   current
       DESCRIPTION
          "A textual description of this pool user, e.g., its location
          and a contact address of its administrator.

          This object SHOULD be maintained in a persistent manner."
       ::= { rserpoolPUEntry 4 }

   rserpoolPUUptime OBJECT-TYPE
       SYNTAX   TimeTicks
       MAX-ACCESS read-only
       STATUS   current
       DESCRIPTION
          "The ENRP service uptime of this pool user."
       ::= { rserpoolPUEntry 5 }

   -- ## MIB conformance and compliance ############################
   rserpoolMIBCompliances OBJECT IDENTIFIER ::= {
      rserpoolMIBConformance 1
   }

   rserpoolMIBGroups OBJECT IDENTIFIER ::= {
      rserpoolMIBConformance 2
   }

   rserpoolMIBCompliance MODULE-COMPLIANCE
       STATUS   current
       DESCRIPTION
          "The compliance statement for SNMP entities that implement
          RSerPool."
       MODULE
       MANDATORY-GROUPS {
          rserpoolENRPGroup,
          rserpoolPEGroup,
          rserpoolPUGroup }

```
    ::= { rserpoolMIBCompliances 1 }

rserpoolENRPGroup OBJECT-GROUP
    OBJECTS {
        rserpoolENRPOperationScope,
        rserpoolENRPIdentifier,
        rserpoolENRPDescription,
        rserpoolENRPUptime,
        rserpoolENRPPort,
        rserpoolENRPASAPAnnouncePort,
        rserpoolENRPASAPAnnounceAddr,
        rserpoolENRPASAPAnnounceAddrType,
        rserpoolENRPENRPAnnounceAddrType,
        rserpoolENRPENRPAnnouncePort,
        rserpoolENRPENRPAnnounceAddr,

        rserpoolENRPPoolHandle,
        rserpoolENRPPoolElementID,

        rserpoolENRPASAPTransportPort,
        rserpoolENRPUserTransportProto,
        rserpoolENRPUserTransportUse,
        rserpoolENRPUserTransportPort,
        rserpoolENRPPolicyID,
        rserpoolENRPPolicyDescription,
        rserpoolENRPPolicyWeight,
        rserpoolENRPPolicyLoad,
        rserpoolENRPPolicyLoadDeg,
        rserpoolENRPRegistrationLife,
        rserpoolENRPHomeENRPServer,

        rserpoolENRPASAPL3Type,
        rserpoolENRPASAPL3Addr,

        rserpoolENRPUserL3Type,
        rserpoolENRPUserL3Addr,
        rserpoolENRPUserL3Opaque,

        rserpoolENRPENRPL3Type,
        rserpoolENRPENRPL3Addr,

        rserpoolENRPPeerIdentifier,
        rserpoolENRPPeerPort,
        rserpoolENRPPeerLastHeard,
        rserpoolENRPPeerL3Type,
        rserpoolENRPPeerL3Addr }
    STATUS current
    DESCRIPTION
```

```
        "The group contains all ENRP server instances
        running on the system"
    ::= { rserpoolMIBGroups 1 }

rserpoolPEGroup OBJECT-GROUP
    OBJECTS {
        rserpoolPEOperationScope,
        rserpoolPEPoolHandle,
        rserpoolPEIdentifier,
        rserpoolPEDescription,
        rserpoolPEUptime,
        rserpoolPEASAPTransportPort,
        rserpoolPEUserTransportProto,
        rserpoolPEUserTransportPort,
        rserpoolPEUserTransportUse,
        rserpoolPEPolicyID,
        rserpoolPEPolicyDescription,
        rserpoolPEPolicyWeight,
        rserpoolPEPolicyLoad,
        rserpoolPEPolicyLoadDeg,
        rserpoolPERegistrationLife,
        rserpoolPEHomeENRPServer,

        rserpoolPEASAPL3Type,
        rserpoolPEASAPL3Addr,

        rserpoolPEUserL3Type,
        rserpoolPEUserL3Addr,
        rserpoolPEUserL3Opaque }
    STATUS current
    DESCRIPTION
        "The group contains all pool element instances
        running on the system"
    ::= { rserpoolMIBGroups 2 }

rserpoolPUGroup OBJECT-GROUP
    OBJECTS { rserpoolPUOperationScope,
        rserpoolPUPoolHandle,
        rserpoolPUDescription,
        rserpoolPUUptime }
    STATUS current
    DESCRIPTION
        "The group contains all pool user instances
        running on the system"
    ::= { rserpoolMIBGroups 3 }

END
```

7. Operational Considerations

   The RSerPool MIB is an Experimental track MIB module, since the
   RSerPool documents are Experimental RFCs.

8. Security Considerations

   There are a number of management objects defined in this MIB module
   with a MAX-ACCESS clause of read-write and/or read-create. Such
   objects may be considered sensitive or vulnerable in some network
   environments. The support for SET operations in a non-secure
   environment without proper protection can have a negative effect on
   network operations. These are the tables and objects and their
   sensitivity/vulnerability:

      rserpoolENRPDescription (textual description change)

      rserpoolPEPoolHandle (pool handle of pool element change, similar
      to ASAP)

      rserpoolPEDescription (textual description change)

      rserpoolPEPolicyID (pool element ID change, similar to ASAP)

      rserpoolPEPolicyDescription (textual description change)

      rserpoolPEPolicyWeight (policy weight change, similar to ASAP)

      rserpoolPEPolicyLoadDeg (policy load degradation change, similar
      to ASAP)

      rserpoolPERegistrationLife (registration lifetime change, similar
      to ASAP)

      rserpoolPUPoolHandle (pool handle of accessed pool change, similar
      to ASAP)

      rserpoolPUDescription (textual description change)

   The security implications of changing these items are similar to
   changes via ASAP; the corresponding security implications are
   described in the threats document [RFC5355]. Modifying the textual
   descriptions of components may result in wrong administrator
   decisions upon malicious information.

Some of the readable objects in this MIB module (i.e., objects with a
MAX-ACCESS other than not-accessible) may be considered sensitive or
vulnerable in some network environments. It is thus important to
control even GET and/or NOTIFY access to these objects and possibly
to even encrypt the values of these objects when sending them over
the network via SNMP. Read access reveals the same information which
is also available by ASAP and ENRP access. The security implications
of these two protocols are explained in detail by the threats
document [RFC5355].

SNMP versions prior to SNMPv3 did not include adequate security.
Even if the network itself is secure (for example by using IPsec),
even then, there is no control as to who on the secure network is
allowed to access and GET/SET (read/change/create/delete) the objects
in this MIB module.

It is RECOMMENDED that implementers consider the security features as
provided by the SNMPv3 framework (see [RFC3410], section 8),
including full support for the SNMPv3 cryptographic mechanisms (for
authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT
RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to
enable cryptographic security. It is then a customer/operator
responsibility to ensure that the SNMP entity giving access to an
instance of this MIB module is properly configured to give access to
the objects only to those principals (users) that have legitimate
rights to indeed GET or SET (change/create/delete) them.

9. IANA Considerations

   The MIB module in this document uses the following IANA-assigned
   OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

   Descriptor OBJECT IDENTIFIER Value
   ---------- -----------------------
   rserpoolMIB { experimental 125 }

10. Acknowledgments

   The authors would like to express a special note of thanks to Phillip
   Conrad and Kevin Pinzhoffer for their efforts in the early formation
   of this document. Furthermore, the authors would like to thank Bert
   Wijnen and Dan Romascanu for their valuable comments on this
   document. Finally, the authors would like to thank Nihad Cosic, Dirk
   Hoffstadt, Michael Kohnen, Jobin Pulinthanath, Randall Stewart,
   Michael Tuexen, and Xing Zhou for their support.

11. References

11.1. Normative References

   [RFC2119]   Bradner, S., "Key words for use in RFCs to Indicate
                      Requirement Levels", BCP 14, RFC 2119, March 1997.

   [RFC2578]   McCloghrie, K., Ed., Perkins, D., Ed., and J.
                      Schoenwaelder, Ed., "Structure of Management
                      Information Version 2 (SMIv2)", STD 58, RFC 2578,
                      April 1999.

   [RFC2579]   McCloghrie, K., Ed., Perkins, D., Ed., and J.
                      Schoenwaelder, Ed., "Textual Conventions for SMIv2",
                      STD 58, RFC 2579, April 1999.

   [RFC2580]   McCloghrie, K., Perkins, D., and J. Schoenwaelder,
                      "Conformance Statements for SMIv2", STD 58, RFC 2580,
                      April 1999.

   [RFC4001]   Daniele, M., Haberman, B., Routhier, S., and J.
                      Schoenwaelder, "Textual Conventions for Internet
                      Network Addresses", RFC 4001, February 2005.

   [RFC5352]   Stewart, R., Xie, Q., Stillman, M., and M. Tuexen,
                      "Aggregate Server Access Protocol (ASAP)", RFC 5352,
                      September 2008.

   [RFC5353]   Xie, Q., Stewart, R., Stillman, M., Tuexen, M., and
                      A. Silverton, "Endpoint Handlespace Redundancy
                      Protocol (ENRP)", RFC 5353, September 2008.

   [RFC5354]   Stewart, R., Xie, Q., Stillman, M., and M. Tuexen,
                      "Aggregate Server Access Protocol (ASAP) and Endpoint
                      Handlespace Redundancy Protocol (ENRP) Parameters",
                      RFC 5354, September 2008.

   [RFC5356]   Dreibholz, T. and M. Tuexen, "Reliable Server Pooling
                      Policies", RFC 5356, September 2008.

11.2. Informative References

   [RFC3237]   Tuexen, M., Xie, Q., Stewart, R., Shore, M., Ong, L.,
                      Loughney, J., and M. Stillman, "Requirements for
                      Reliable Server Pooling", RFC 3237, January 2002.

   [RFC3410]   Case, J., Mundy, R., Partain, D., and B. Stewart,
                      "Introduction and Applicability Statements for
                      Internet-Standard Management Framework", RFC 3410,
                      December 2002.

   [RFC5351]   Lei, P., Ong, L., Tuexen, M., and T. Dreibholz, "An
                      Overview of Reliable Server Pooling Protocols",
                      RFC 5351, September 2008.

   [RFC5355]   Stillman, M., Gopal, R., Guttman, E., Sengodan, S.,
                      and M. Holdrege, "Threats Introduced by Reliable
                      Server Pooling (RSerPool) and Requirements for
                      Security in Response to Threats", RFC 5355,
                      September 2008.

   [Dre2006]   Dreibholz, T., "Reliable Server Pooling --
                      Evaluation, Optimization and Extension of a Novel
                      IETF Architecture", Ph.D. Thesis University of
                      Duisburg-Essen, Faculty of Economics, Institute for
                      Computer Science and Business Information Systems,
                      March 2007, <http://duepublico.uni-duisburg-essen.de/
                      servlets/DerivateServlet/Derivate-16326/
                      Dre2006-final.pdf>.

   [LCN2005]   Dreibholz, T. and E. Rathgeb, "On the Performance of
                      Reliable Server Pooling Systems", Proceedings of the
                      30th IEEE Local Computer Networks Conference,
                      November 2005.

   [IJHIT2008]   Dreibholz, T. and E. Rathgeb, "An Evaluation of the
                      Pool Maintenance Overhead in Reliable Server Pooling
                      Systems", International Journal of Hybrid Information
                      Technology (IJHIT) Volume 1, Number 2, April 2008.

   [RSerPoolPage]   Dreibholz, T., "Thomas Dreibholz's RSerPool Page",
                      <http://tdrwww.iem.uni-due.de/dreibholz/rserpool/>.

   [SNMPMIBS]   Perkins, D. and E. McGinnis, "Understanding SNMP
                      MIBs", 1997.

Authors' Addresses

   Thomas Dreibholz
   University of Duisburg-Essen, Institute for Experimental Mathematics
   Ellernstrasse 29
   45326 Essen, Nordrhein-Westfalen
   Germany

   Phone: +49-201-1837637
   Fax: +49-201-1837673
   EMail: dreibh@iem.uni-due.de
   URI: http://www.iem.uni-due.de/~dreibh/

   Jaiwant Mulik
   Delaware State University
   CIS Department
   Room 306A, Science Center North
   1200 N. DuPont Hwy
   Dover, DE 19904
   USA

   Phone: +1-302-857-7910
   Fax: +1-302-857-6552
   EMail: jaiwant@mulik.com
   URI: http://netlab.cis.desu.edu