

TIG P-Series (MOSFET) AC/DC TIG Welder

TIG 250P AC/DC



Standard Accessories

- 1 pc WP-26 TIG torch (4m)
- 1 set earth clamp with 16mm² cable (2m) + 35 -50 male connector
- 1 pc long cap, short cap
- 1 pc collet body 3.2, collet 2.0/2.4/3.2
- 1pc alumina nozzle #4/#5/#6/#7



MANUFACTURER / IMPORTER IN INDIA

SALES:- SALES@VIRGOPLUS.IN
SERVICES:- SUPPORT@VIRGOPLUS.IN

VIRGO SOLUTIONS INDIA LLP

AHMEDABAD, AURANGABAD, BHUBANESWAR, DELHI, GUWAHATI, HYDERABAD,
INDORE, JAIPUR, KOLKATA, LUCKNOW, LUDHIANA, MUMBAI, NAGPUR, PUNE, RAIPUR, VARANASI

Product description:

- SMT surface mount design, with advanced workmanship.
- Advanced inverter technology high working efficiency.
- Multipoint overheat protection with good protection of undervoltage and over current.
- Instantaneous arc starting with small current welding.
- With 2T/4T working mod smart operation.
- The frequency, duty ratio and valley current can be adjusted freely under Pulse function
- Aluminum welding is available under TIG.
- Clean welding adjustable under AC aluminum welding.
- Switch indication visible, high integration and simplified circuit.

Main technical parameters:

	TIG 250P AC/DC
Phase	1PH
Standard Input Voltage	AC220V±10%
Frequency(Hz)	50/60
Rated Input Capacity(TIG/MMA)	7.2V
Rated Input Current (TIG/MMA)	32.8A
Output Current Voltage	55 V
Duty cycle (%)	60%
Current Adjusting Range	10-250A
Arcing Way	HF
Rated Output Voltage	MMA:26.4V TIG:18V
Efficiency	85%
Insulation Class	F
Shell Protection Class	IP21S
Dimension (mm)	610x350x510
Net Weight	19 kg
Welding Thickness(Aluminum)	0.3-5mm(0.8-3.0mm)