VIRGO PLUS®
WELDING AND CUTTING EQUIPMENT

CUT Series (IGBT) Inverter DC AIR Plasma Cutter

CUT 60T

Standard Accessories

- 1 pc P80 torch (5m)
- 1 set earth clamp with 20mm2 cable (2m)
- 1 pc guide roller

VIRGO SOLUTIONS
MANUFACTURER / IMPORTER IN INDIA

SALES:- SALES@VIRGOPLUS.IN
SERVICES:- SUPPORT@VIRGOPLUS.IN
VIRGO SOLUTIONS INDIA LLP
AHMEDABAD, AURANGABAD, BHUBANESWAR, DELHI, GUWAHATI, HYDERABAD, INDORE, JAIPUR, KOLKATA, LUCKNOW, LUDHIANA, MUMBAI, NAGPUR, PUNE, RAIPUR, VARANASI

VIRGO PLUS®
WELDING AND CUTTING EQUIPMENT

Product description:

- Advanced IGBT inverter technology,is adopted for accurate feedback control, and the current output is stable.
- Pressure regulating valve does water-proof automatically,the gas meter was moulded together with machine,no need to install.
- Exact digital current preset, it makes machine be easy operated.
- Untouched pilot arc start system – Smooth Arc-Striking with HF Control.
- With 2T/4T working mode, convenient operation.
- Quality cutting thickness with fast cutting speed,smooth cutting,small deformation and less hang slag.
- Auto-Protection against over-voltage,over-current and over-heating, it makes machine safe and reliable
- Advanced airflow control system, it has a save of 30% air compare to traditional machine, which prolongs the using life of air compressor.
- Energy Saving - Compared with the traditional cutting machine more efficient.
- Can be used for carbon steel , stainless steel, galvanised steel, copper, aluminum and other metal sheet cutting

Main technical parameters:

	CUT 60T
Phase	1PH|2PH|3PH
Input voltage(V)	1P AC220V|2P/3P AC415V ±10%
Supply frequency(Hz)	50/60
Input capacity(KVA)	10.6KVA
No load voltage(V)	258V
Output current(A)	60A
Input current(A)	48.5A
Duty cycle(%)	60%
Ignition	HF Pilot ARC
Compatiable nozzle dia(mm)	1.0 -1.7mm
Working pressure (Bar)	5-7bar
Flow Rate(l/min)	115l/min
Good Cutting capacity (mm)	10mm
Postflow time(S)	5-10S