


# Parallelization in C<sub>o</sub>smoLattice

September 2025, Daejeon

Franz R. Sattler

Bielefeld University




# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,

$$d = 1$$

$$\partial_t^2 \phi(i) = \Delta_i^+ \Delta_i^- \phi(i)$$




# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,

$$d = 1$$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$



(Leapfrog scheme.)


# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,

$$d = 1$$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$



(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$


# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,

$$d = 1$$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$



(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

→ Only local information needed (neighbours).

# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,


$$d = 1$$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$

(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

→ Only local information needed (neighbours).



We could compute all lattice sites independently!

See lecture on Friday!

# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,


$$d = 1$$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$

(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

→ Only local information needed (neighbours).



We could compute all lattice sites independently!

See lecture on Friday!

# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,


$$d = 1$$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$

(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

→ Only local information needed (neighbours).



We could compute all lattice sites independently!

*See lecture on Friday!*

Less granular: split **sub-regions** of lattice across many computers (**nodes**)

# Parallelization

of CosmoLattice

simulations requires to split both computation and data across cores.

# Parallelization

of CosmoLattice

simulations requires to split both **computation** and **data** across **cores**.

**Cores:** **Nodes** (distributed) and **Threads** (shared).

# Parallelization

of CosmoLattice

simulations requires to split both **computation** and **data** across **cores**.

**Cores:** **Nodes** (distributed) and **Threads** (shared).

Type	<b>distributed</b>	<b>shared</b>
Data	split between <b>nodes</b>	shared by all <b>threads</b>
Computation	split between <b>nodes</b>	split between <b>threads</b>


# Why can we parallelize?

And why would we want to?

Example: Solving massless Klein-Gordon equation,

$$d = 1$$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$



(*Leapfrog scheme.*)

Stencil of update for **one** lattice site is  $s = 1$

- Only local information needed (neighbours).
- Each site can be updated independently.

# Why can we parallelize?

And why would we want to?


Example: Solving massless Klein-Gordon equation,  
 $d = 1$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$

(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

- Only local information needed (neighbours).
- Each site can be updated independently.



# Why can we parallelize?

And why would we want to?


Example: Solving massless Klein-Gordon equation,  
 $d = 1$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$

(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

- Only local information needed (neighbours).
- Each site can be updated independently.



**Problem:** Data is missing on node 1

# Why can we parallelize?

And why would we want to?


Example: Solving massless Klein-Gordon equation,  
 $d = 1$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$

(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

- Only local information needed (neighbours).
- Each site can be updated independently.



**Solution:** Use ghosts.

Ghosts are local copies of data on other nodes.

# Why can we parallelize?

And why would we want to?


Example: Solving massless Klein-Gordon equation,  
 $d = 1$

$$\begin{aligned}\partial_t \pi(i) &= \Delta_i^+ \Delta_i^- \phi(i), \\ \partial_t \phi(i) &= \pi(i).\end{aligned}$$

(Leapfrog scheme.)

Stencil of update for **one** lattice site is  $s = 1$

- Only local information needed (neighbours).
- Each site can be updated independently.



**Solution:** Use ghosts.

Ghosts are local copies of data on other nodes.


Need to update ghosts after every time-step.

# Data communication

The standard for communication in distributed-memory applications:

## Message Passing Interface (MPI)

Exchange ghost data between **nodes** over the **network** automatically if anything changes.




# Data communication

The standard for communication in distributed-memory applications:

## Message Passing Interface (MPI)

Exchange ghost data between **nodes** over the **network** automatically if anything changes.




*CosmoLattice does this automatically under the hood!*

# Data communication

The standard for communication in distributed-memory applications:

## Message Passing Interface (MPI)

Exchange ghost data between **nodes** over the **network** automatically if anything changes.



*CosmoLattice does this automatically under the hood!*

## How to turn it on?


```
$ cd build/  
$ cmake -DMPI=ON ..  
$ make  
$ mpirun -n 16 ./lphi4 input=./lphi4.in
```

# Data communication

The standard for communication in distributed-memory applications:

## Message Passing Interface (MPI)

Exchange ghost data between **nodes** over the **network** automatically if anything changes.



*CosmoLattice does this automatically under the hood!*

## How to turn it on?



```
$ cd build/  
$ cmake -DMPI=ON ..  
$ make  
$ mpirun -n 16 ./lphi4 input=./lphi4.in
```

You may need to install fftw3 with MPI support.

```
$ sudo apt-get install libfftw3-mpi-dev
```



# FFT parallelization

- FFTW supports parallelization along 1 direction.





# FFT parallelization

- FFTW supports parallelization along 1 direction.
- Improved scaling for many nodes: PFFT allows for parallelization in any dimensions.



# FFT parallelization

- FFTW supports parallelization along 1 direction.
- Improved scaling for many nodes: PFFT allows for parallelization in any dimensions.
- To keep data transfer due to ghost exchange manageable, parallelization along  $d - 1$  directions.



# FFT parallelization

- FFTW supports parallelization along 1 direction.
- Improved scaling for many nodes: PFFT allows for parallelization in any dimensions.
- To keep data transfer due to ghost exchange manageable, parallelization along  $d - 1$  directions.



1D

$$N = n_p * m$$

$$N = 50$$

2D

$$\begin{aligned} N &= n_p^{(1)} * m \\ &= n_p^{(2)} * m \end{aligned}$$



# FFT parallelization

- FFTW supports parallelization along 1 direction.
- Improved scaling for many nodes: PFFT allows for parallelization in any dimensions.
- To keep data transfer due to ghost exchange manageable, parallelization along  $d - 1$  directions.



1D

$$N = n_p * m$$

$$N = 50$$

2D

$$\begin{aligned} N &= n_p^{(1)} * m \\ &= n_p^{(2)} * m \end{aligned}$$



# FFT parallelization

- FFTW supports parallelization along 1 direction.
- Improved scaling for many nodes: PFFT allows for parallelization in any dimensions.
- To keep data transfer due to ghost exchange manageable, parallelization along  $d - 1$  directions.

1D

$$N = n_p * m$$

$$N = 50$$



50 nodes.

Maximum parallelization

2D

$$\begin{aligned} N &= n_p^{(1)} * m \\ &= n_p^{(2)} * m \end{aligned}$$

$$25^2 = 625 \text{ nodes.}$$



# FFT parallelization

- FFTW supports parallelization along 1 direction.
- Improved scaling for many nodes: PFFT allows for parallelization in any dimensions.
- To keep data transfer due to ghost exchange manageable, parallelization along  $d - 1$  directions.






Figure 3: Speed up factor in parallelized simulations as a number of cores (tested on the Gacrux cluster from the EPFL HPC center SCITAS, Switzerland).



# Questions?


Tomorrow: Shared-memory parallelization with GPUs.

# CosmoLattice on GPUs

September 2025, Daejeon

Franz R. Sattler

Bielefeld University



# Current computers

can be broadly said to have two main

processing units:

# Current computers

can be broadly said to have two main

processing units: **CPU**s (central processing units)

# Current computers

can be broadly said to have two main processing units: **CPU**s (central processing units) and **GPU**s (graphical processing units)


# Current computers

can be broadly said to have two main

processing units: **CPU**s (central processing units) and **GPU**s (graphical processing units)

**CPU**s: for **OS, computation, general applications**.

**GPU**s: dedicated just for **video and graphics** applications.



A consumer machine


# Current computers

can be broadly said to have two main processing units: **CPU**s (central processing units) and **GPU**s (graphical processing units)


**CPU**s: for **OS, computation, general applications**.

**GPU**s: dedicated just for **video and graphics** applications.

Current (heterogeneous) clusters have both **CPU**s and **GPU**s for **computations**.



A consumer machine



A typical heterogeneous computing cluster

# Why use GPUs for lattice?

Lattice points independently computed & updated → Limit of threads is number of lattice sites!

# Why use GPUs for lattice?

Lattice points independently computed & updated → Limit of threads is number of lattice sites!

	CPU	GPU	
■ AMD EPYC 7763: <b>64</b>	Cores/Node	$\mathcal{O}(10 - 100)$	$\mathcal{O}(10000)$
■ Intel Xeon 6148 (Skylake): <b>20</b>	Clock speed	~ 3 GHz	~ 1.5 GHz

■ Nvidia H100: **~15000**  
■ Nvidia RTX4070m: **~5000**

- AMD Ryzen 9 7945HX: **16**

# Why use GPUs for lattice?

Lattice points independently computed & updated → Limit of threads is number of lattice sites!

	CPU	GPU	
▪ AMD EPYC 7763: <b>64</b>	Cores/Node	$\mathcal{O}(10 - 100)$	$\mathcal{O}(10000)$
▪ Intel Xeon 6148 (Skylake): <b>20</b>	Clock speed	~ 3 GHz	~ 1.5 GHz

▪ AMD Ryzen 9 7945HX: **16**

▪ Nvidia H100: **~15000**

▪ Nvidia RTX4070m: **~5000**



**CPU:** Low parallelization, high clock speed

**GPU:** High parallelization, moderate clock speed

→ CosmoLattice on GPUs has the potential for *massive parallelism* with  $\gg 10^5$  simultaneous operations.

# Why use GPUs for lattice?

Lattice points independently computed & updated → Limit of threads is number of lattice sites!


	CPU	GPU
Cache/Thread	64KB / 16MB	1KB
Local Cache	64MB	256KB / 50MB
		

**CPU: Thread-constrained**

**GPU: Memory-constrained**


# Redesigning TempLat for GPUs

Device-centric programming.



# Redesigning TempLat for GPUs

Device-centric programming.




$$\text{expression} = \pi(t) + dt \cdot \Delta\phi(t)$$

Time evolution


# Redesigning TempLat for GPUs

Device-centric programming.



# Redesigning TempLat for GPUs

Device-centric programming.



$$\text{expression} = \pi(t) + dt \cdot \Delta\phi(t)$$

Time evolution

$$\pi(t + dt) = \text{expression}$$


```
auto functor = DEVICE_LAMBDA(device::IdxArray<NDim> idx,
                             double& max) {
    // ...
};

double maximum = 0.;
```

Maximum

# Redesigning TempLat for GPUs

Device-centric programming.



$$\text{expression} = \pi(t) + dt \cdot \Delta\phi(t)$$

Time evolution

$$\pi(t + dt) = \text{expression}$$

```
auto functor = DEVICE_LAMBDA(device::IdxArray<NDim> idx,
                             double& max) {
    // ...
};


double maximum = 0.;
```

Maximum

```
device::iteration::reduce("Maximum", functor, maximum);
```

# Redesigning TempLat for GPUs

Device-centric programming.




## Standard C++ on CPU

## Hardware-dependent

- NVIDIA: CUDA
- AMD: ROCM
- Intel: SYCL
- shared-memory CPUs
- FPGPAs

# Redesigning TempLat for GPUs

Device-centric programming.



**Standard C++ on CPU**

**Backends**

- *Kokkos*
- *Sequential STL (2020/2023)*
- ...

**Abstracted away in TempLat**

- `device::iterate::foreach`
- `device::iterate::reduce`
- `device::memory::copyHostToDevice`
- ...

Does this make CosmoLattice harder to use?

Does this make CosmoLattice harder to use?

No, but...

# Does this make CosmoLattice harder to use?

No, but...

## Model file

```
1 public:  
2  
3     MODELNAME(ParameterParser &parser, RunParameters<double> &runPar,  
4         std::shared_ptr<MemoryToolBox> toolBox)  
5     ...
```

# Does this make CosmoLattice harder to use?

No, but...

## Model file

```
1 public:  
2     static constexpr size_t NDim = Model<MODELNAME>::NDim;  
3  
4     MODELNAME(ParameterParser &parser, RunParameters<double> &runPar,  
5         std::shared_ptr<MemoryToolBox<NDim>> toolBox)  
6     ...
```

# Does this make CosmoLattice harder to use?

No, but...

## Model file

```
1 public:  
2     static constexpr size_t NDim = Model<MODELNAME>::NDim;  
3  
4     MODELNAME(ParameterParser &parser, RunParameters<double> &runPar,  
5             std::shared_ptr<MemoryToolBox<NDim>> toolBox)  
6     ...  
7 
```

## TempLat

```
1 vType computeConfigurationSpace() {  
2     vType localResult{};  
3  
4     auto& it = mT.getToolBox()->itX();  
5     for(it.begin();it.end();++it)  
6     {  
7         const ptrdiff_t i = it();  
8         localResult += GetValue::get(mT,i);  
9     }  
10    return mWorkspace;  
11 }  
12 }
```

# Does this make CosmoLattice harder to use?

No, but...

## Model file

```
1 public:  
2     static constexpr size_t NDim = Model<MODELNAME>::NDim;  
3  
4     MODELNAME(ParameterParser &parser, RunParameters<double> &runPar,  
5             std::shared_ptr<MemoryToolBox<NDim>> toolBox)  
6     ...  
7 
```

## TempLat

```
1 vType computeConfigurationSpace() {  
2     auto functor = DEVICE_CLASS_LAMBDA(const device::IdxArray<NDim> &idx,  
3                                         vType &update) {  
4         device::apply([&](const auto &...args) {  
5             update += GetValue::get(mT, args...);  
6         },  
7             idx);  
8     };  
9  
10    vType localResult{};  
11    device::iteration::reduce("Averager", cLayout, functor, localResult);  
12    return localResult;  
13 }
```

# Does this make CosmoLattice harder to use?

No, but...

## Model file

```
1 public:  
2     static constexpr size_t NDim = Model<MODELNAME>::NDim;  
3  
4     MODELNAME(ParameterParser &parser, RunParameters<double> &runPar,  
5             std::shared_ptr<MemoryToolBox<NDim>> toolBox)  
6     ...
```

## Building

Cosmolattice up to now:

```
1 $ cmake .. -DMODEL=lphi4  
2 ...
```

## TempLat

```
1 vType computeConfigurationSpace() {  
2     auto functor = DEVICE_CLASS_LAMBDA(const device::IdxArray<NDim> &idx,  
3                                         vType &update) {  
4         device::apply([&](const auto &...args) {  
5             update += GetValue::get(mT, args...);  
6         },  
7                     idx);  
8     };  
9  
10    vType localResult{};  
11    device::iteration::reduce("Averager", cLayout, functor, localResult);  
12    return localResult;  
13 }
```

# Does this make CosmoLattice harder to use?

No, but...

## Model file

```
1 public:  
2     static constexpr size_t NDim = Model<MODELNAME>::NDim;  
3  
4     MODELNAME(ParameterParser &parser, RunParameters<double> &runPar,  
5             std::shared_ptr<MemoryToolBox<NDim>> toolBox)  
6     ...
```

## Building

New version: CUDA is detected automatically:

```
1 $ cmake .. -DMODEL=lphi4  
2 ...
```

## TempLat

```
1 vType computeConfigurationSpace() {  
2     auto functor = DEVICE_CLASS_LAMBDA(const device::IdxArray<NDim> &idx,  
3                                         vType &update) {  
4         device::apply([&](const auto &...args) {  
5             update += GetValue::get(mT, args...);  
6         },  
7                     idx);  
8     };  
9  
10    vType localResult{};  
11    device::iteration::reduce("Averager", cLayout, functor, localResult);  
12    return localResult;  
13 }
```

# Does this make CosmoLattice harder to use?

No, but...

## Model file

```
1 public:  
2     static constexpr size_t NDim = Model<MODELNAME>::NDim;  
3  
4     MODELNAME(ParameterParser &parser, RunParameters<double> &runPar,  
5             std::shared_ptr<MemoryToolBox<NDim>> toolBox)  
6     ...  
7 
```

## Building

Granular control: shared memory OpenMP through Kokkos

```
1 $ cmake .. -DMODEL=lphi4 -DDEVICE=KOKKOS -DCUDA=OFF  
2 ...  
3 
```

## TempLat


```
1 vType computeConfigurationSpace() {  
2     auto functor = DEVICE_CLASS_LAMBDA(const device::IdxArray<NDim> &idx,  
3                                         vType &update) {  
4         device::apply([&](const auto &...args) {  
5             update += GetValue::get(mT, args...);  
6         },  
7             idx);  
8     };  
9  
10    vType localResult{};  
11    device::iteration::reduce("Averager", cLayout, functor, localResult);  
12    return localResult;  
13 }
```

For "average" user:

Only minimal  
changes

# GPU architecture


GPU thread hierarchy



# GPU architecture

GPU thread hierarchy


- GPUs have  $\mathcal{O}(10)$  *Streaming multiprocessors*.



# GPU architecture

## GPU thread hierarchy


- GPUs have  $\mathcal{O}(10)$  *Streaming multiprocessors*.
  - SMs execute *kernels* with series of parallel instructions.
  - SMs schedule their execution.



# GPU architecture

## GPU thread hierarchy


- GPUs have  $\mathcal{O}(10)$  *Streaming multiprocessors*.
  - SMs execute *kernels* with series of parallel instructions.
  - SMs schedule their execution.
- Work given to SMs in *blocks*.



# GPU architecture

## GPU thread hierarchy


- GPUs have  $\mathcal{O}(10)$  *Streaming multiprocessors*.
  - SMs execute *kernels* with series of parallel instructions.
  - SMs schedule their execution.
- Work given to SMs in *blocks*.
  - A block has to fit onto a SM's hardware capabilities (~1024 threads/block).
  - Each block's (sub-)contexts are persistent throughout its execution.



# GPU architecture

## GPU thread hierarchy


- GPUs have  $\mathcal{O}(10)$  *Streaming multiprocessors*.
  - SMs execute *kernels* with series of parallel instructions.
  - SMs schedule their execution.
- Work given to SMs in *blocks*.
  - A block has to fit onto a SM's hardware capabilities (~1024 threads/block).
  - Each block's (sub-)contexts are persistent throughout its execution.
- Internally, blocks are subdivided into *warps*.



# GPU architecture

## GPU thread hierarchy

- GPUs have  $\mathcal{O}(10)$  *Streaming multiprocessors*.
  - SMs execute *kernels* with series of parallel instructions.
  - SMs schedule their execution.
- Work given to SMs in *blocks*.
  - A block has to fit onto a SM's hardware capabilities (~1024 threads/block).
  - Each block's (sub-)contexts are persistent throughout its execution.
- Internally, blocks are subdivided into *warps*.
  - Each warp runs a single instruction in a *kernel* in parallel.
  - Warp size is always 32 for Nvidia, 32 or 64 for AMD.




# Memory access patterns

Coalescing vs. sequential access

Example: Solving massless Klein-Gordon equation in  $d = 3$ ,

$$\partial_t^2 \phi(t, x) = \Delta \phi(t, x).$$

- Calculation of 1 thread at **red site**.
- **Blue sites** dependents for lattice Laplacian.



# Memory access patterns


Coalescing vs. sequential access

Example: Solving massless Klein-Gordon equation in  $d = 3$ ,

$$\partial_t^2 \phi(t, x) = \Delta \phi(t, x).$$

- Calculation of 1 thread at **red site**.
- **Blue sites** dependents for lattice Laplacian.

What is the optimal way to iterate over sites?



# Memory access patterns


Coalescing vs. sequential access

Example: Solving massless Klein-Gordon equation in  $d = 3$ ,

$$\partial_t^2 \phi(t, x) = \Delta \phi(t, x).$$

- Calculation of 1 thread at **red site**.
- **Blue sites** dependents for lattice Laplacian.
- Memory is ordered row-major.

What is the optimal way to iterate over sites?



# Memory access patterns

Coalescing vs. sequential access


Example: Solving massless Klein-Gordon equation in  $d = 3$ ,

$$\partial_t^2 \phi(t, x) = \Delta \phi(t, x).$$

- Calculation of 1 thread at **red site**.
- **Blue sites** dependents for lattice Laplacian.
- Memory is ordered row-major.

What is the optimal way to iterate over sites?

CPU: **Sequential access pattern** allows for caching of subsequent operations of a single thread.



# Memory access patterns

Coalescing vs. sequential access

Example: Solving massless Klein-Gordon equation in  $d = 3$ ,


$$\partial_t^2 \phi(t, x) = \Delta \phi(t, x).$$

- Calculation of 1 thread at **red site**.
- **Blue sites** dependents for lattice Laplacian.
- Memory is ordered row-major.

What is the optimal way to iterate over sites?

CPU: **Sequential access pattern** allows for caching of subsequent operations of a single thread.

GPU: **Coalesced access pattern** allows for simultaneous reading of memory for multiple threads.



# Memory access patterns

Coalescing vs. sequential access

Example: Solving massless Klein-Gordon equation in  $d = 3$ ,

$$\partial_t^2 \phi(t, x) = \Delta \phi(t, x).$$

- Calculation of 1 thread at **red site**.
- **Blue sites** dependents for lattice Laplacian.
- Memory is ordered row-major.


What is the optimal way to iterate over sites?

CPU: **Sequential access pattern** allows for caching of subsequent operations of a single thread.

GPU: **Coalesced access pattern** allows for simultaneous reading of memory for multiple threads.

This is similar to vectorization on a CPU!

**SIMD** (Single Instruction, Multiple Data) vs **SIMT** (Single Instruction, Multiple Threads)



# Memory access patterns

Coalescing vs. sequential access


Example: Solving massless Klein-Gordon equation in  $d = 3$ ,

$$\partial_t^2 \phi(t, x) = \Delta \phi(t, x).$$

- Calculation of 1 thread at **red site**.
- **Blue sites** dependents for lattice Laplacian.
- Memory is ordered row-major.

CPU: Prefer **prefer row-major access pattern**.

GPU: Prefer **column-major access pattern**.



How does this perform *in vivo*?

```
1 #define FORCE_ACCESS_PATTERN 0 // or 1
2 ...
3
4 int main(int argc, char **argv)
5 {
6     constexpr size_t NDim = 3;
7     using T = double;
8     constexpr size_t nGrid = 512;
9     constexpr size_t nGhost = 1;
10    constexpr size_t nSteps = 512;
11    constexpr T dt = 0.01;
12    ...
13    Field<NDim, T> phi("phi", toolBox);
14    Field<NDim, T> pi("pi", toolBox);
15
16    Benchmark bench([&](Benchmark::Measurer &measurer) {
17        phi.inFourierSpace() = RandomGaussianField<NDim, T>("Rand", toolBox);
18        pi.inFourierSpace() = RandomGaussianField<NDim, T>("Rand2", toolBox);
19
20        for (size_t i = 0; i < nSteps; ++i) {
21            pi.updateGhosts();
22            device::iteration::fence();
23            measurer.measure("timestepping", [&]() {
24                pi = pi + dt * LatticeLaplacian<NDim, decltype(phi)>(phi); // kick
25                phi = phi + dt * pi; // drift
26                device::iteration::fence();
27            });
28        });
29    });
30}
```

```
1 ...
2     for (size_t i = 0; i < nSteps; ++i) {
3         pi.updateGhosts();
4         device::iteration::fence();
5         measurer.measure("timestepping", [&](){
6             pi = pi + dt * LatticeLaplacian<NDim, decltype(phi)>(phi); // kick
7             phi = phi + dt * pi; // drift
8             device::iteration::fence();
9         });
10    }
```

---

## Running this on my PC:

**GPU**: NVIDIA 4070RTX mobile - 4788 Cores @ 2.175 GHz

**CPU**: Ryzen 9 7945HX - 16 Cores @ 5.4GHz

# Taking a closer look

```
...
Benchmark bench([&](Benchmark::Measurer &measurer) {
    measurer.measure("x->k fourier", [&]() {
        phi.getMemoryManager()->confirmFourierSpace();
        pi.getMemoryManager()->confirmFourierSpace();
    });

    measurer.measure("initialize field", [&]() {
        phi.inFourierSpace() = RandomGaussianField<NDim, T>("Hoi", toolBox);
        pi.inFourierSpace() = RandomGaussianField<NDim, T>("Hai", toolBox);
    });

    measurer.measure("k->x fourier", [&]() {
        phi.getMemoryManager()->confirmConfigSpace();
        pi.getMemoryManager()->confirmConfigSpace();
    });

    for (size_t i = 0; i < nSteps; ++i) {
        measurer.measure("ghosts", [&]() {
            pi.updateGhosts();
            device::iteration::fence();
        });
        measurer.measure("timestepping", [&]() {
            pi = pi + dt * LatticeLaplacian<NDim, decltype(phi)>(phi);
        });
    }
});
```


# Taking a closer look

```
...
Benchmark bench([&](Benchmark::Measurer &measurer) {
    measurer.measure("x->k fourier", [&]() {
        phi.getMemoryManager()->confirmFourierSpace();
        pi.getMemoryManager()->confirmFourierSpace();
    });

    measurer.measure("initialize field", [&]() {
        phi.inFourierSpace() = RandomGaussianField<NDim, T>("Hoi", toolBox);
        pi.inFourierSpace() = RandomGaussianField<NDim, T>("Hai", toolBox);
    });

    measurer.measure("k->x fourier", [&]() {
        phi.getMemoryManager()->confirmConfigSpace();
        pi.getMemoryManager()->confirmConfigSpace();
    });

    for (size_t i = 0; i < nSteps; ++i) {
        measurer.measure("ghosts", [&]() {
            pi.updateGhosts();
            device::iteration::fence();
        });
        measurer.measure("timestepping", [&]() {
            pi = pi + dt * LatticeLaplacian<NDim, decltype(phi)>(phi);
        });
    }
});
```




# Taking a closer look

```
...
Benchmark bench([&](Benchmark::Measurer &measurer) {
    measurer.measure("x->k fourier", [&]() {
        phi.getMemoryManager()->confirmFourierSpace();
        pi.getMemoryManager()->confirmFourierSpace();
    });

    measurer.measure("initialize field", [&]() {
        phi.inFourierSpace() = RandomGaussianField<NDim, T>("Hoi", toolBox);
        pi.inFourierSpace() = RandomGaussianField<NDim, T>("Hai", toolBox);
    });

    measurer.measure("k->x fourier", [&]() {
        phi.getMemoryManager()->confirmConfigSpace();
        pi.getMemoryManager()->confirmConfigSpace();
    });

    for (size_t i = 0; i < nSteps; ++i) {
        measurer.measure("ghosts", [&]() {
            pi.updateGhosts();
            device::iteration::fence();
        });
        measurer.measure("timestepping", [&]() {
            pi = pi + dt * LatticeLaplacian<NDim, decltype(phi)>(phi);
        });
    }
});
```



- Fourier transformation: cuFFT  
(automatic switch to GPU native FFTs)


# Taking a closer look

```
...
Benchmark bench([&](Benchmark::Measurer &measurer) {
    measurer.measure("x->k fourier", [&]() {
        phi.getMemoryManager()->confirmFourierSpace();
        pi.getMemoryManager()->confirmFourierSpace();
    });

    measurer.measure("initialize field", [&]() {
        phi.inFourierSpace() = RandomGaussianField<NDim, T>("Hoi", toolBox);
        pi.inFourierSpace() = RandomGaussianField<NDim, T>("Hai", toolBox);
    });

    measurer.measure("k->x fourier", [&]() {
        phi.getMemoryManager()->confirmConfigSpace();
        pi.getMemoryManager()->confirmConfigSpace();
    });

    for (size_t i = 0; i < nSteps; ++i) {
        measurer.measure("ghosts", [&]() {
            pi.updateGhosts();
            device::iteration::fence();
        });
        measurer.measure("timestepping", [&]() {
            pi = pi + dt * LatticeLaplacian<NDim, decltype(phi)>(phi);
        });
    }
});
```



- Fourier transformation: cuFFT  
(automatic switch to GPU native FFTs)

# Benchmarking $\lambda\phi^4$ -theory

with the  $\lambda\phi^4$  model in CosmoLattice

# Benchmarking $\phi^4$ -theory

with the `lphi4` model in CosmoLattice

PRELIMINARY



# Benchmarking -theory

with the `lphi4` model in CosmoLattice




# Benchmarking -theory

with the lphi4 model in CosmoLattice




# Benchmarking -theory

with the `lphi4` model in CosmoLattice



# Benchmarking -theory

with the `lphi4` model in CosmoLattice



Slightly unfair comparison  
(my CPU is "stronger")

# Benchmarking -theory


with the `lphi4` model in CosmoLattice

$N = 512$

PRELIMINARY

# Benchmarking $\phi$ -theory

with the `lphi4` model in CosmoLattice




$N = 512$


PRELIMINARY

# Benchmarking $\phi$ -theory

with the `lphi4` model in CosmoLattice




$N = 512$




# Benchmarking $\phi$ -theory

with the `lphi4` model in CosmoLattice




$N = 512$



# Scaling it up

Using large GPU clusters

- To use large clusters and link up many nodes, CosmoLattice uses the **Message-Passing Interface (MPI)** (see lecture yesterday).
- Send data in RAM (e.g. ghosts) between neighbouring nodes.




# Scaling it up

Using large GPU clusters

- To use large clusters and link up many nodes, CosmoLattice uses the **Message-Passing Interface (MPI)** (see lecture yesterday).
- Send data in RAM (e.g. ghosts) between neighbouring nodes.

What about MPI+GPUs?



# Scaling it up

Using large GPU clusters


- To use large clusters and link up many nodes, CosmoLattice uses the **Message-Passing Interface (MPI)** (see lecture yesterday).
- Send data in RAM (e.g. ghosts) between neighbouring nodes.

What about MPI+GPUs?

- GPU-aware MPI** can exchange data directly between device memory.

Support since before 2013:

- OpenMPI
  - MVAPICH2
  - Cray MPI
  - IBM MPI
- No changes in MPI-code!



# Questions?

Thanks for your attention!

Release of CosmoLattice with GPUs ~ early 2026