

FlexNet Manager for SAP Applications 2014

Installation Guide

Legal Information

Book Name: FlexNet Manager for SAP Applications 2014 Installation Guide
Part Number: FNMS-2014R1-IG04
Product Release Date: February 2014

Copyright Notice

Copyright © 2014 Flexera Software LLC. All Rights Reserved.

This publication contains proprietary and confidential information and creative works owned by Flexera Software LLC and its licensors, if any. Any use, copying, publication, distribution, display, modification, or transmission of such publication in whole or in part in any form or by any means without the prior express written permission of Flexera Software LLC is strictly prohibited. Except where expressly provided by Flexera Software LLC in writing, possession of this publication shall not be construed to confer any license or rights under any Flexera Software LLC intellectual property rights, whether by estoppel, implication, or otherwise.

All copies of the technology and related information, if allowed by Flexera Software LLC, must display this notice of copyright and ownership in full.

FlexNet Manager Suite incorporates software developed by others and redistributed according to license agreements. Copyright notices and licenses for this externally developed software are provided in the section *Legal Information* in the FlexNet Manager Suite online help.

Intellectual Property

For a list of trademarks and patents that are owned by Flexera Software, see <http://www.flexerasoftware.com/intellectual-property>.

SAP and SAP NetWeaver are registered trademarks of SAP AG in Germany and in several other countries.

All other brand and product names mentioned in Flexera Software products, product documentation, and marketing materials are the trademarks and registered trademarks of their respective owners.

Restricted Rights Legend

The Software is commercial computer software. If the user or licensee of the Software is an agency, department, or other entity of the United States Government, the use, duplication, reproduction, release, modification, disclosure, or transfer of the Software, or any related documentation of any kind, including technical data and manuals, is restricted by a license agreement or by the terms of this Agreement in accordance with Federal Acquisition Regulation 12.212 for civilian purposes and Defense Federal Acquisition Regulation Supplement 227.7202 for military purposes. The Software was developed fully at private expense. All other use is prohibited.

Contents

Introduction	1
Components Terminology	1
Technical Requirements	2
Upgrading from Previous Versions	2
Import of Transports	2
Before Importing	2
Importing the Transports	2
Checks after the Import	3
Authorizations for FlexNet Manager for SAP Applications	4
Authorization Roles	4
Authorization Object J_5NL_UPD	5
Authorizations Required by the SAP Inventory Agent	5
Setting up RFC Connections	6
Non-CUA Satellites	6
CUA Satellites	7
Installing the Product License	7
Configuring SAP Systems to Communicate with FlexNet Manager Suite	9
Communication Using Basic Authentication	10
Configuring Communication with Basic Authentication on Systems Running SAP Basis 7.00, 7.01, 7.10, 7.11, 7.30, or 7.31	10
Configuring Communication with Basic Authentication on Systems Running SAP Basis 7.4	12
Communication Using SSL Authentication	14
Configuring Communication with SSL Authentication on Systems Running SAP Basis 7.00, 7.01, 7.10, 7.11, 7.30, or 7.31	15
Configuring Communication with SSL Authentication on Systems Running SAP Basis 7.4	18
Configuring the SAP Admin Module to Communicate with an Inventory Beacon	20
Enabling SAP Enterprise Portal Data Collection	20
Uninstalling FlexNet Manager for SAP Applications	21

Contents

A	Authorization Objects in Standard Authorization Roles	22
B	Tables Read and Data Collected by the SAP Inventory Agent	29
C	Functions Executed and Data Collected by the SAP Inventory Agent	36
	Index	39

Introduction

FlexNet Manager for SAP Applications is installed on your system using SAP transport requests.

All objects of FlexNet Manager for SAP Applications are within the /LICMAN/ namespace (registered and reserved by SAP). There will be no conflicts with SAP standard developments or your own developments in the customer namespace. The SAP standard is not modified.

You will find a list of the current transports in the file `Transport_Overview.xls` or `Transport_Overview.pdf` on the product CD or the product download.

The product CD or the product download usually contains the following folders and subfolders:

- **0_Documentation**—Contains the product documentation.
- **1_Basis**—Contains the transports for the SAP Admin module and the satellites in subfolders for the relevant SAP Basis release.
- **2_Roles**—Contains the Role transport in a subfolder for the relevant SAP Basis release.
- **3_AdminModule**—Contains the transports for the SAP Admin module in subfolders for the relevant SAP Basis release.
- **4_Deletion**—Contains subfolders with the deletion transports. The transports must be executed in the order of the subfolder names (Step_1, Step_2, Step_3).
- **5_Portal**—Contains an EAR file that must be deployed in the SAP enterprise portal to enable data collection from an SAP enterprise portal.

Components Terminology

The FlexNet Manager for SAP Applications documentation uses the following terminology:

- The *SAP Admin module* is a component of FlexNet Manager for SAP Applications. The SAP administrator uses this module to perform remediation, package measurements, and activity checks.
- The SAP Admin module is usually installed on an *SAP master* system. A master system receives services updates which it distributes to the managed satellite systems.
- The SAP Admin module is installed by importing the *AdminModule* transport into the SAP master system.
- The *Satellite* transport enables you to collect SAP package data and run activity checks. It must be installed on all SAP systems with SAP packages, if you want to optimize the relevant package licenses and run activity checks. If no package data is collected and no activity checks are run, the use of the Satellite transport is not required.
- All systems on which the Satellite transport is installed are referred to as *satellites*.

For more information about the individual components of FlexNet Manager for SAP Applications, refer to the *FlexNet Manager for SAP Applications User Guide*.

Technical Requirements

Front-end SAP Admin module:

- The SAP GUI matching the SAP release must be installed.
- ActiveX must be installed.

SAP Admin module:

- SAP Basis release between 7.00 and 7.4

FlexNet Manager for SAP Applications satellite(s):

- SAP Basis release between 4.6C and 7.4

Upgrading from Previous Versions

FlexNet Manager for SAP Applications 2014 is a complete release. If you are upgrading from a previous version of FlexNet Manager for SAP Applications, no additional steps are required.

All data originating from the previous version, such as consumption data, license rules, and measurements, will be preserved in their original tables.

When upgrading from a previous version, you do not need to reinstall the license file.

Import of Transports

Before Importing

Copy the transport files to a transport directory of your choice, such as, for example, `/usr/sap/trans/cofiles`.

If you install FlexNet Manager for SAP Applications on a Unix system, remove the read-only flag for all K* files after copying to the transport directory. (Example: `chmod 755 K900629.AP2`.) This step is not relevant for Windows systems.

Importing the Transports

For current transport numbers, see the document `Transport_Overview.xls` or `Transport_Overview.pdf`.



Important • If you are installing FlexNet Manager for SAP Applications on a system running SAP Basis 702 or higher, the system might display a warning message with the explanation *The installed release does not match or Does not match component version*. This is because SAP Basis 702 systems or higher compare the support pack level of the target system with that of the objects in the transport that you are trying to import. If the support pack levels do not match, a warning message might be displayed. This is not a concern for FlexNet Manager for SAP Applications transports, because all objects in FlexNet Manager for SAP Applications transports are in the /LICMAN/ namespace.

To avoid such a warning message, on the **Import Transport Request** dialog, click the **Options** tab and select the **Ignore Invalid Component Version** check box. For more information, refer to the following SAP documentation: SAP Knowledge Base Article 1688610 and SAP Note 1742547.



Task: *To import the transports, perform the following steps:*

1. Install FlexNet Manager for SAP Applications on the master system:
 - a. Determine an SAP system that is running SAP Basis version 7.x and that is assigned as master system.
 - b. Import the **AdminModule** transport for the SAP Basis release into the master system.
After FlexNet Manager for SAP Applications has been installed, the SAP Admin module will run on this master system.
 - c. Import the appropriate **Role** transport that matches the SAP Basis release into the master system. The **Role** transport is client dependent.
2. Install FlexNet Manager for SAP Applications on the satellite systems:
 - a. Import the **Basis/Satellite** transport into all satellite systems that you want to manage using FlexNet Manager for SAP Applications. Ensure that you import the transport that is appropriate for the relevant SAP Basis version of each satellite system.
 - b. Import the **Role** transport into all satellite systems that you want to manage using FlexNet Manager for SAP Applications. Ensure that you import the transport that is appropriate for the relevant SAP Basis version of each satellite system. The **Role** transport is client dependent.



Note • It is not necessary to import the **Basis/Satellite** transport into the master system.

Checks after the Import

Check the import logs generated for the individual import steps for errors (transaction STMS).

Because some transports contain entire dictionary objects, warning messages may be displayed during the import process. Transports with an error message up to the return code level 4 are successful.



Important • If you encounter other errors (RC = 8 or above), contact Flexera Software technical support for assistance.

Authorizations for FlexNet Manager for SAP Applications

Authorization Roles

FlexNet Manager for SAP Applications comes with the following authorization roles:

- **/LICMAN/SATELLITE**: This role contains all required authorizations for the RFC user on the satellite systems.
- **/LICMAN/MASTER_ALL**: This role contains all authorizations for the user of FlexNet Manager for SAP Applications on the SAP Admin module. It also includes standard authorizations, for example, for creating the dialog RFC destinations that are used optionally by FlexNet Manager for SAP Applications.
- **/LICMAN/MASTER_READ_ONLY**: This role, which has been derived from /LICMAN/MASTER_ALL, entitles the user only to view data in FlexNet Manager for SAP Applications.
- **/LICMAN/INTERFACE**: This role is for the communications user on the SAP Admin module to enable access from FlexNet Manager Platform to the data saved in FlexNet Manager for SAP Applications.
- **/LICMAN/SATELLITE_CHARGEBACK**: This role must be assigned to the RFC user on the satellite system, if the cost center data used for the chargeback report are loaded from this system.

For detailed information about the objects contained in these roles, refer to *Authorization Objects in Standard Authorization Roles* on page 22.

The roles /LICMAN/MASTER_ALL and /LICMAN/MASTER_READ_ONLY can be used as templates if certain users should be allowed only to display or maintain specific systems or system groups. To do this, customize the authorizations for the object J_5NL_SYST, using the information provided in the following table.

Table 1 • Customization of authorizations for object J_5NL_SYST

Field	Description
Installation number	The installation number of the SAP system
Client	The client within the SAP system
System ID	The 3-digit system ID of the SAP system

Table 1 • Customization of authorizations for object J_5NL_SYST

Field	Description
FlexNet Manager for SAP Applications activities	02: Update user data 03: Display data 11: Invoke LAW 12: Import SAP package data 23: Customizing 30: Import usage data CCMS 33: Customizing system overall 43: Display LAW data 44: Load LAW data 50: Start USMM 51: USMM results download 60: Start consolidation 61: Display consolidation In order to allow only the display of data, you should give authorization only for the activity 03.

Authorization Object J_5NL_UPD

The authorization object J_5NL_UPD checks the authorizations of a user during updates of the user master data. By customizing the object, you can define the fields of the user master data that a user is allowed to update. The object contains only one field called **Field Name**. Use this field to specify the names of the fields from the user master data that can be updated from within FlexNet Manager for SAP Applications.

Authorizations Required by the SAP Inventory Agent

The SAP Inventory Agent requires a small number of authorizations to collect the relevant user and consumption data. These authorizations are shown in the following table:

Table 2 • List of SAP authorizations required by the SAP Inventory Agent of FlexNet Manager for SAP Applications

Authorization Object	Activity	Fields and Values
S_TABU_DIS	03	N/A
S_TOOLS_EX	N/A	*

Table 2 • List of SAP authorizations required by the SAP Inventory Agent of FlexNet Manager for SAP Applications

Authorization Object	Activity	Fields and Values
S_RFC	*	ARFC ERFC LAW* RFC* SCSM* SDIF* SDTX STUW* SUU6 SYST SYSU

Each SAP system that should be inventoried by the SAP Inventory Agent requires a user account with all these authorizations. This account is used for all RFC-based communication between the SAP Inventory Agent and the SAP system. To ensure that the account has the required roles, it is recommended to import the **Role** transport and assign the /LICMAN/SATELLITE role (see *Authorization Roles* on page 4). However, you can also assign these authorizations manually.

The above authorizations only give permission to the SAP Inventory Agent to read data from the SAP systems. The SAP Admin module requires additional authorizations which are available in the **Role** transport (see *Importing the Transports* on page 2).

Refer to *Authorization Objects in Standard Authorization Roles* on page 22 and *Tables Read and Data Collected by the SAP Inventory Agent* on page 29 for information about which data is collected by the SAP Inventory Agent.

Setting up RFC Connections

Non-CUA Satellites

For each non-CUA satellite, create an RFC connection of type 3. The connection has to be client-specific, therefore you need to specify the target client and the RFC user in the parameter block **Login**. This RFC user (recommended type: **Communication**) must exist in the target client on the satellite system and must have the user role /LICMAN/SATELLITE.

CUA Satellites

All FlexNet Manager for SAP Applications activities (such as reading and modifying user data) are performed using the CUA center, therefore only an RFC connection between the SAP Admin module and the CUA center is required. This connection must be given the same name as the logical system of the CUA center (even if the SAP Admin module and the CUA center are installed on the same system and in the same client) and it must be of type 3. The connection is client-specific (see the preceding section) and the RFC user must have the user role /LICMAN/SATELLITE.

For communication with the subsidiary systems, the existing RFC connections between CUA center and subsidiary systems are used. The RFC users simply need to be assigned the role /LICMAN/SATELLITE.

Installing the Product License

Before using the analytic functions of FlexNet Manager for SAP Applications, you need to activate the software by installing a license file. This is an XML file such as DLC_LIC_20090210151856.XML (where 20090210151856 is a unique ID identifying the product license).



Important • The license allows running FlexNet Manager for SAP Applications master on all systems with a given installation number. If you are installing the master on a system with a different installation number, contact Flexera Software technical support to obtain a new license file.

In order to import a license file, you need to save it on a drive of your SAP GUI PC, for example C:\TEMP\ DLC_LIC_20090210151856.XML.



Task: To import a license file:

1. Execute the transaction /LICMAN/START.
2. Open the **Administration** menu and select **License**, then click **Install License**.
3. Select the license file and click **Open** to import it. After the license file has been successfully imported, the license information is displayed.



Important • Directly after installing the license—and from time to time in regular production—FlexNet Manager for SAP Applications will automatically start a batch job to recount systems and users for the product licensing. Because FlexNet Manager for SAP Applications also has to use batch jobs for its analytic functions, ensure that the user working with FlexNet Manager for SAP Applications has the authority to schedule batch jobs.

Information presented in the License Overview screen

Option	Description
For	Name of your organization.
License ID	The unique ID that identifies your product license.
Installation No.	Installation number for the system that is registered with SAP. The number is issued by SAP and identifies the system on which the FlexNet Manager for SAP Applications master is installed.
Valid from	Start date for the validity of the license.
Valid to	End date when the license will expire.
Platform Enabled	This field contains an X if the full range of features of FlexNet Manager for SAP Applications is available in FlexNet Manager Platform.
Status indicator	<p>Enables you to quickly observe the license status for each license pool:</p> <ul style="list-style-type: none"> • A green status indicates that sufficient licenses are available for all systems (1%-90%). • An amber status indicates that the number of licenses is approaching the limit (91%-100%) • A red status indicates that there are insufficient licenses for the number of systems (101% or higher).
License Pool	Shows the license pool containing the license types. An asterisk (*) indicates that there is no differentiation made between the different license types. The DEFAULT pool contains all licenses that are not included in any other pool.
License Types	Indicates the number of licenses and their license type.
Licenses	Shows the number of licenses that are currently available of the type indicated in the License Type column.
Used	Shows the number of licenses of the type indicated in the License Type column that are currently in use.
%	Shows the percentage of the number of licenses that are currently in use.

Option	Description
No. of System Licenses	<p>Indicates the licensed maximum number of systems which can be connected to FlexNet Manager for SAP Applications. (A system can have any number of clients.)</p> <ul style="list-style-type: none"> • A green status indicates that sufficient licenses are available for all systems (1%-90%). • An amber status indicates that the number of licenses is approaching the limit (91%-100%). • A red status indicates that there are insufficient licenses for the number of systems (101% or higher).
Connected + Reconnected Systems	<p>Indicates the number of currently connected systems plus the number of systems which have been reconnected at least three times.</p>
1-Month-History (incl. Tolerance)	<p>Indicates the total number of systems which have been connected to FlexNet Manager for SAP Applications during a 1-month period. A tolerance is subtracted. This is to allow for situations in which systems have been connected erroneously.</p> <p>This number and the number for Connected + Reconnected Systems are not allowed to exceed the licensed number of systems.</p>

Configuring SAP Systems to Communicate with FlexNet Manager Suite

Communication between FlexNet Manager Suite and FlexNet Manager for SAP Applications is facilitated using web services. Web services support the interaction of different software applications over the World Wide Web infrastructure.

After installation of FlexNet Manager Suite and FlexNet Manager for SAP Applications, you need to configure a web service called *SAPServiceSoap* to enable the applications to communicate with each other.

There are different security levels for the communication, and you can choose the level that you would like to use. The security settings are independent of the functionality of the applications. However, the settings need to be set up properly, otherwise communication is not possible.

The following security levels are available:

- No authentication—Without authentication, communication between FlexNet Manager Suite and FlexNet Manager for SAP Applications is not secure. This security level is not desirable and therefore not described in this document.
- Basic authentication—Authentication is based on the user name and password. See *Communication Using Basic Authentication* on page 10 for more information.
- SSL authentication—Authentication is based on the exchange of certificates. This is the most secure level. See *Communication Using SSL Authentication* on page 14 for more information.

The SOA Manager

You use the SOA Manager in SAP to configure the web service settings. The web service is client-dependent, and you need to customize it in the SOA Manager (transaction SOAMANAGER) on each client that the **AdminModule** transport will be used on. These settings are not required on the satellite systems. Administrator privileges are required for using the SOA Manager.

In the SOA Manager, the options that need to be selected depend on the SAP Basis release and the support package that is installed. Due to the number of different combinations of SAP Basis release and support package that are possible, not all combinations are documented here. Instead, the following steps only outline the required options based on the SAP Basis release that is installed.

Testing the Web Service Connection

During configuration, the SOA Manager enables you to test the web service connection using the Ping Web Service button. In SAP Basis release 7.3 and newer versions, this test can produce a false negative result. Although the SOA Manager displays an error such as “Web service ping failed (RC=405). Service Ping Error: Method Not Allowed”, the web service connection may be working correctly. Therefore, the ping result should be ignored.

The false error is generated because FlexNet Manager Suite sends a GET message, but the ping expects a HEAD message.

Communication Using Basic Authentication

It is recommended to use basic authentication only when the connection between FlexNet Manager Suite and FlexNet Manager for SAP Applications is secure and can be trusted.

Configuring Communication with Basic Authentication on Systems Running SAP Basis 7.00, 7.01, 7.10, 7.11, 7.30, or 7.31



Task: *To configure communication using basic authentication on a system running SAP Basis 7.00, 7.01, 7.10, 7.11, 7.30, or 7.31:*

1. Start the SOA Manager on the SAP system on which you want to configure the web service using the transaction code SOAMANAGER.
2. On the **SOA Management** page, do the following, depending on which version of SAP Basis your system is running:
 - SAP Basis 7.00 or 7.10: Select the **Business Administration** tab and click **Web Service Administration**.
 - SAP Basis 7.01 or 7.11: Select the **Application and Scenario Communication** tab and click **Single Service Administration**.
 - SAP Basis 7.30 or 7.31: Select the **Service Administration** tab and click **Web Service Configuration**.

3. On the next page, on the **Search** tab, locate the **Search by** menu and select **Consumer Proxy** from the list. In the **Search Pattern** field, type ***SAPSERVICE***, and click **Go**.
4. The search returns the web service SAPServiceSoap. Select it and click **Apply Selection**.
5. In the **Details of Proxy Definition** section, select the **Configurations** tab. Click **Create Logical Port**.
6. The **SOA Management** dialog opens. Provide the following information:
 - **Logical Port Name:** Enter a unique name for your logical port.
 - **Logical Port is Default:** Select this check box to ensure that the default logical port is called.



Important • If this check box is not selected, communication between FlexNet Manager Suite and FlexNet Manager for SAP Applications is not possible.

- **Description:** Enter a description.
- **Configuration Type:** Select the radio button **Manual Configuration**.

Click **Apply Settings**.

7. On the **Configuration for Logical Port 'name'** page, on the **Consumer Security** tab, select the **User ID / Password** radio button to enable basic authentication.

Under **User ID/Password**, provide the user name and password that are used in FlexNet Manager Suite.



Important • If the user name and password change in FlexNet Manager Suite, you need to make the same changes in the SOA Manager.

8. On the **Messaging** tab, open the **Message ID Protocol** menu and select **Suppress ID Transfer**.

Accept the default values for all other options on this tab.

9. On the **Transport settings** tab, provide the following information:

- **URL Access Path:** Enter the URL access path **/SAPService/SAPService.asmx**.
- **URL Protocol Information:** Select **HTTP**.
- **Computer Name of Access URL:** Enter the IP address of the relevant FlexNet Manager Suite server.
- **Port Number of Access URL:** Enter the relevant port number. For basic authentication, the port number is 80.

Accept the default values for all other options on this tab.

10. On the **Operation specific** tab, you need to manually add the SOAP action for every web-service operation.
 - a. Add the following web-service operations in the grid on the left. For each operation, specify the appropriate SOAP action in the **SOAP Action** field. The table below lists the operations and corresponding SOAP action.



Note • If you copy the SOAP actions from the table below to paste each action into the **SOAP Action** field, ensure that you copy the entire line.

Table -1: SOAP actions for the web-service operation

Web Service Operation	SOAP Action
GetAllActiveSapLandscapes	http://www.flexera.com/webservices/GetAllActiveSapLandscapes
GetSapLandscapeMembers	http://www.flexera.com/webservices/GetSapLandscapeMembers
GetAvailableSapRecommendationsSummary	http://www.flexera.com/webservices/GetAvailableSapRecommendationSummary
GetSapRecommendationsByLandscapeUID	http://www.flexera.com/webservices/GetSapRecommendationsByLandscapeUID
GetSapConsumptionByLicenseRecommendationUID	http://www.flexera.com/webservices/GetSapConsumptionByLicenseRecommendationUID
AcknowledgeSapRecommendationsUploaded	http://www.flexera.com/webservices/AcknowledgeSapRecommendationsUploaded
AcknowledgeSapRecommendation	http://www.flexera.com/webservices/AcknowledgeSapRecommendation
AcknowledgeSapRecommendations	http://www.flexera.com/webservices/AcknowledgeSapRecommendations

- b. If you configure the SOA Manager on a system that is running SAP Basis 7.3, under **Transport Binding**, clear the check box next to the **SOAP Action** field to ensure that the SOAP action is active for the configuration.

11. Click **Save**.

Configuring Communication with Basic Authentication on Systems Running SAP Basis 7.4



Task: To configure communication using basic authentication on a system running SAP Basis 7.4:

1. Start the SOA Manager on the SAP system on which you want to configure the web service using the transaction code SOAMANAGER.
2. On the **SOA Management** page, on the **Service Administration** tab, click **Web Service Configuration**.
3. On the **Web Service Configuration** page, under **Search Criteria**, specify the following search parameters:

- **Object Type is All**
- **Consumer Proxy contains *SAPSERVICE*.**

4. Click **Search**.

The search returns the web service SAPServiceSoap.

5. In the **Internal Name** column, click the hyperlinked name for the SAP web service.

6. On the next page, on the **Configurations** tab, click the **Edit logical port** button.

7. On the **Consumer Security** tab, select **User ID / Password**.

Under **User ID/Password**, provide the user name and password that are used in FlexNet Manager Suite.



Important • If the user name and password change in FlexNet Manager Suite, you need to make the same changes in the SOA Manager.

8. On the **Messaging** tab, open the **Message ID Protocol** menu and select **Suppress ID Transfer**.

Accept the default values for all other options on this tab.

9. On the **Transport settings** tab, provide the following information:

- **URL Access Path:** Enter the URL access path `/SAPService/SAPService.asmx`.
- **Computer Name of Access URL:** Enter the IP address of the relevant FlexNet Manager Suite server.
- **Port Number of Access URL:** Enter the relevant port number. For basic authentication, the port number is 80.
- **URL Protocol Information:** Select **HTTP**.

Accept the default values for all other options on this tab.

10. On the **Operation Settings** tab, you need to manually add the SOAP action for every web-service operation.

- Select the **Use non-default value for SOAP Action** check box to ensure that the SOAP action is active for the configuration, and to enable the **SOAP Action** field.
- Add the following web-service operations in the grid on the left. For each operation, specify the appropriate SOAP action in the **SOAP Action** field. The table below lists the operations and corresponding SOAP action.



Note • If you copy the SOAP actions from the table below to paste each action into the **SOAP Action** field, ensure that you copy the entire line.

Table -2: SOAP actions for the web-service operation

Web Service Operation	SOAP Action
GetAllActiveSapLandscapes	<code>http://www.flexera.com/webservices/GetAllActiveSapLandscapes</code>

Table -2: SOAP actions for the web-service operation

Web Service Operation	SOAP Action
GetSapLandscapeMembers	http://www.flexera.com/webservices/GetSapLandscapeMembers
GetAvailableSapRecommendationsSummary	http://www.flexera.com/webservices/GetAvailableSapRecommendationSummary
GetSapRecommendationsByLandscapeUID	http://www.flexera.com/webservices/GetSapRecommendationsByLandscapeUID
GetSapConsumptionByLicenseRecommendationUID	http://www.flexera.com/webservices/ GetSapConsumptionByLicenseRecommendationUID
AcknowledgeSapRecommendationsUploaded	http://www.flexera.com/webservices/ AcknowledgeSapRecommendationsUploaded
AcknowledgeSapRecommendation	http://www.flexera.com/webservices/AcknowledgeSapRecommendation
AcknowledgeSapRecommendations	http://www.flexera.com/webservices/AcknowledgeSapRecommendations

11. Click **Save**.

Communication Using SSL Authentication

You can configure the web service to use Secure Sockets Layer (SSL) encryption to protect the sensitive data that is exchanged between FlexNet Manager Suite and FlexNet Manager for SAP Applications.

To use SSL authentication, you need to install a Root Certificate (in [Step 13](#) and [Step 14](#)). Contact the Certificate Authority (CA) for an SSL certificate that is used by the FlexNet Manager Suite server. You can download the Root Certificate in binary format or base64 format.



Important • The SAP system needs to be configured to accept SSL communication. For this, a cryptographic library has to be installed. For more information, see SAP Note 510007.

Configuring Communication with SSL Authentication on Systems Running SAP Basis 7.00, 7.01, 7.10, 7.11, 7.30, or 7.31



Task: *To configure communication using SSL authentication on a system running SAP Basis 7.00, 7.01, 7.10, 7.11, 7.30, or 7.31:*

1. Start the SOA Manager on the SAP system on which you want to configure the web service using the transaction code SOAMANAGER.
2. On the **SOA Management** page, do the following, depending on which version of SAP Basis your system is running:
 - SAP Basis 7.00 or 7.10: Select the **Business Administration** tab and click **Web Service Administration**.
 - SAP Basis 7.01 or 7.11: Select the **Application and Scenario Communication** tab and click **Single Service Administration**.
 - SAP Basis 7.30 or 7.31: Select the **Service Administration** tab and click **Web Service Configuration**.
3. On the next page, on the **Search** tab, locate the **Search by** menu and select **Consumer Proxy** from the list. In the **Search Pattern** field, type **SAPSERVICE**, and click **Go**.
4. The search returns the web service SAPServiceSoap. Select it and click **Apply Selection**.
5. In the **Details of Proxy Definition** section, select the **Configurations** tab. Click **Create Logical Port**.
6. The **SOA Management** dialog opens. Provide the following information:
 - **Logical Port Name:** Enter a unique name for your logical port.
 - **Logical Port is Default:** Select this check box to ensure that the default logical port is called.



Important • *If this check box is not selected, communication between FlexNet Manager Suite and FlexNet Manager for SAP Applications is not possible.*

- **Description:** Enter a description.
- **Configuration Type:** Select the radio button **Manual Configuration**.

Click **Apply Settings**.

7. On the **Configuration for Logical Port 'name'** page, on the **Consumer Security** tab, select the **User ID / Password** radio button.

Under **User ID/Password**, provide the user name and password that are used in FlexNet Manager Suite.



Important • *If the user name and password change in FlexNet Manager Suite, you need to make the same changes in the SOA Manager.*

8. On the **Messaging** tab, open the **Message ID Protocol** menu and select **Suppress ID Transfer**.

Accept the default values for all other options on this tab.

9. On the **Transport settings** tab, provide the following information:

- **URL Access Path:** Enter the URL access path `/SAPService/SAPService.asmx`.
- **URL Protocol Information:** Select **HTTPS**.
- **Computer Name of Access URL:** Enter the IP address of the relevant FlexNet Manager Suite server.
- **Port Number of Access URL:** Enter the port number **443**.

Accept the default values for all other options on this tab.

10. On the **Operation specific** tab, you need to manually add the SOAP action for every web-service operation.


- a. Add the following web-service operations in the grid on the left. For each operation, specify the appropriate SOAP action in the **SOAP Action** field. The table below lists the operations and corresponding SOAP action.




Note • If you copy the SOAP actions from the table below to paste each action into the **SOAP Action** field, ensure that you copy the entire line.

Table -3: SOAP actions for the web-service operation

Web Service Operation	SOAP Action
GetAllActiveSapLandscapes	http://www.flexera.com/webservices/GetAllActiveSapLandscapes
GetSapLandscapeMembers	http://www.flexera.com/webservices/GetSapLandscapeMembers
GetAvailableSapRecommendationSummary	http://www.flexera.com/webservices/GetAvailableSapRecommendationSummary
GetSapRecommendationsByLandscapeUID	http://www.flexera.com/webservices/GetSapRecommendationsByLandscapeUID
GetSapConsumptionByLicenseRecommendationUID	http://www.flexera.com/webservices/GetSapConsumptionByLicenseRecommendationUID
AcknowledgeSapRecommendationsUploaded	http://www.flexera.com/webservices/AcknowledgeSapRecommendationsUploaded
AcknowledgeSapRecommendation	http://www.flexera.com/webservices/AcknowledgeSapRecommendation
AcknowledgeSapRecommendations	http://www.flexera.com/webservices/AcknowledgeSapRecommendations

- b. If you configure the SOA Manager on a system that is running SAP Basis 7.3, under **Transport Binding**, clear the check box next to the **SOAP Action** field to ensure that the SOAP action is active for the configuration.
- 11. Click **Save**.
- 12. Connect to the SAP system and run transaction STRUST to start the Trust Manager.
- 13. Click **Import Certificate** .
- 14. On the **Import Certificate** dialog, select the appropriate Root Certificate.
- 15. Under **File format**, select the file format of the Root Certificate. Click **OK**.
- 16. In the system tree on the left pane of the Trust Manager, select **SSL client SSL Client (Anonymous)** and click **Add to Certificate List**.
- 17. Start the Internet Communication Manager (ICM) using the transaction SMICM. (The ICM sends and receives requests to and from the Internet.)
- 18. In the **ICM Monitor** screen, open the **Administration** menu and select **ICM > Exit Soft > Global**.

This step resets the ICM Monitor. The new certificate is activated only after the reset.
- 19. On the toolbar of the **ICM Monitor** screen, click **Services** .
- 20. On the **ICM Monitor - Service Display** screen, click **Refresh**.

If the **Active Services** grid does not show a line for HTTPS, you need to add it.
 - a. Open the **Service** menu and click **Create**.
 - b. In the **Define New Service** dialog, provide the following information:
 - **New Service Port**: Enter **443**.
 - **Log**: Enter **HTTPS**.
 - **Keep Alive (in Sec.)**: Keep the default value or change to a value of your choice.
 - **Max. Processing Time**: Keep the default value or change to a value of your choice.
 - c. Click **OK**.

The **Active Services** grid should now contain an HTTPS service.

Configuring Communication with SSL Authentication on Systems Running SAP Basis 7.4



Task: *To configure communication using SSL authentication on a system running SAP Basis 7.4:*

1. Start the SOA Manager on the SAP system on which you want to configure the web service using the transaction code SOAMANAGER.
2. On the **SOA Management** page, on the **Service Administration** tab, click **Web Service Configuration**.
3. On the **Web Service Configuration** page, under **Search Criteria**, specify the following search parameters:
 - **Object Type is All**
 - **Consumer Proxy contains *SAPSERVICE***.

4. Click **Search**.

The search returns the web service SAPServiceSoap.

5. In the **Internal Name** column, click the hyperlinked name for the SAP web service.
6. On the next page, on the **Configurations** tab, click the **Edit logical port** button.
7. On the **Consumer Security** tab, select **User ID / Password**.

Under **User ID/Password**, provide the user name and password that are used in FlexNet Manager Suite.



Important • If the user name and password change in FlexNet Manager Suite, you need to make the same changes in the SOA Manager.

8. On the **Messaging** tab, open the **Message ID Protocol** menu and select **Suppress ID Transfer**.

Accept the default values for all other options on this tab.

9. On the **Transport settings** tab, provide the following information:

- **URL Access Path:** Enter the URL access path `/SAPService/SAPService.asmx`.
- **Computer Name of Access URL:** Enter the IP address of the relevant FlexNet Manager Suite server.
- **Port Number of Access URL:** Enter the relevant port number. For basic authentication, the port number is 80.
- **URL Protocol Information:** Select **HTTPS**.

Accept the default values for all other options on this tab.

10. On the **Operation Settings** tab, you need to manually add the SOAP action for every web-service operation.
 - a. Select the **Use non-default value for SOAP Action** check box to ensure that the SOAP action is active for the configuration, and to enable the **SOAP Action** field.


- b. Add the following web-service operations in the grid on the left. For each operation, specify the appropriate SOAP action in the **SOAP Action** field. The table below lists the operations and corresponding SOAP action.



Note • If you copy the SOAP actions from the table below to paste each action into the **SOAP Action** field, ensure that you copy the entire line.

Table -4: SOAP actions for the web-service operation

Web Service Operation	SOAP Action
GetAllActiveSapLandscapes	http://www.flexera.com/webservices/GetAllActiveSapLandscapes
GetSapLandscapeMembers	http://www.flexera.com/webservices/GetSapLandscapeMembers
GetAvailableSapRecommendationsSummary	http://www.flexera.com/webservices/GetAvailableSapRecommendationSummary
GetSapRecommendationsByLandscapeUID	http://www.flexera.com/webservices/GetSapRecommendationsByLandscapeUID
GetSapConsumptionByLicenseRecommendationUID	http://www.flexera.com/webservices/GetSapConsumptionByLicenseRecommendationUID
AcknowledgeSapRecommendationsUploaded	http://www.flexera.com/webservices/AcknowledgeSapRecommendationsUploaded
AcknowledgeSapRecommendation	http://www.flexera.com/webservices/AcknowledgeSapRecommendation
AcknowledgeSapRecommendations	http://www.flexera.com/webservices/AcknowledgeSapRecommendations

11. Click **Save**.
12. Connect to the SAP system and run transaction STRUST to start the Trust Manager.
13. Click **Import Certificate** .
14. On the **Import Certificate** dialog, select the appropriate Root Certificate.
15. Under **File format**, select the file format of the Root Certificate. Click **OK**.
16. In the system tree on the left pane of the Trust Manager, select **SSL client SSL Client (Anonymous)** and click **Add to Certificate List**.
17. Start the Internet Communication Manager (ICM) using the transaction SMICM. (The ICM sends and receives requests to and from the Internet.)
18. In the **ICM Monitor** screen, open the **Administration** menu and select **ICM > Exit Soft > Global**.

This step resets the ICM Monitor. The new certificate is activated only after the reset.

19. On the toolbar of the **ICM Monitor** screen, click **Services** .

20. On the **ICM Monitor - Service Display** screen, click **Refresh**.

If the **Active Services** grid does not show a line for HTTPS, you need to add it.

- a. Open the **Service** menu and click **Create**.
- b. In the **Define New Service** dialog, provide the following information:
 - **New Service Port**: Enter **443**.
 - **Log**: Enter **HTTPS**.
 - **Keep Alive (in Sec.)**: Keep the default value or change to a value of your choice.
 - **Max. Processing Time**: Keep the default value or change to a value of your choice.
- c. Click **OK**.

The **Active Services** grid should now contain an HTTPS service.

Configuring the SAP Admin Module to Communicate with an Inventory Beacon

Inventory beacons are lightweight applications that gather inventory data, stage and package it as appropriate, and forward it to the central inventory server.

Communication between an inventory beacon and the SAP Admin module is facilitated using web services, just like the communication between FlexNet Manager Suite and the SAP Admin module. The configuration encompasses exactly the same steps as the procedures described under *Communication Using Basic Authentication* on page 10 and *Communication Using SSL Authentication* on page 14, with the following exception: In step 9 of each procedure, the IP address of the relevant inventory beacon web server must be provided.

Enabling SAP Enterprise Portal Data Collection

FlexNet Manager for SAP Applications provides the ability to collect and display user master and statistical data from an SAP enterprise portal or any SAP system running a Java stack. To enable this data collection, note the following and ensure that the SAP enterprise portal and CEN (Central Monitoring System/Transaction ST03G) are set up properly:

- Collection of user master data is done by a JSP (Java server page), which is part of an EAR (enterprise archive) file that is included with the FlexNet Manager for SAP Applications installation files (in the Portal folder). This EAR file must be deployed in the SAP enterprise portal.
- Statistical data is collected from a CEN. A CCMS agent must be set up at the Java stack, to push statistical data into the CEN. For information about installing a CCMS agent, see the SAP documentation.



Important • In order to access SAP enterprise portal data using the FlexNet Manager for SAP Applications interface, you must insert a new SAP enterprise portal system. Refer to the FlexNet Manager for SAP Applications User Guide for more detailed information.

Uninstalling FlexNet Manager for SAP Applications

FlexNet Manager for SAP Applications is removed using deletion transports. The deletion of all objects of FlexNet Manager for SAP Applications is split into three import steps which have to be executed in the specified order. Before executing a step, the import of the preceding step must be finished.

The transport request files for each step are stored in the folders Step_1, Step_2, and Step_3. These folders also contain the object lists of the transports.

Step 1

In this step, all roles delivered with FlexNet Manager for SAP Applications will be deleted.

Step 2

This step deletes entries in database tables of the development workbench which otherwise—depending on the Basis release and service pack of the importing SAP system—would not be deleted by the deletion transport of [Step 3](#).

The transport in this step contains the report /LICMAN/DELETION_XPRA_WB in the /LICMAN/ namespace. It is automatically executed in the XPRA step after import. For the following database tables, entries in the /LICMAN/ namespace will be deleted:

- DOKHL
- DOKIL
- DOKTL
- FUNCT
- TADIR

Step 3

The deletion transport of this step deletes all workbench objects of FlexNet Manager for SAP Applications. This includes the report that was imported in [Step 2](#).

Authorization Objects in Standard Authorization Roles

The following tables contain detailed information about the authorization objects that are contained in the authorization roles that are included by default in FlexNet Manager for SAP Applications.

Table A-1 • Role /LICMAN/SATELLITE

Object	Field Name	Value
S_RFC	ACTVT	*
	RFC_NAME	/LICMAN/* ARFC ERFC LAW* RFC* SCSM* SDIF* SDTX STUW* SUU6 SYST SYSU
	RFC_TYPE	FUGR
S_BTCH_ADM	BTCADMIN	Y

Table A-1 • Role /LICMAN/SATELLITE

Object	Field Name	Value
S_BTCHJOB	JOBACTION	*
	JOBGROUP	*
S_TABU_DIS	ACTVT	03
	DICBERCLS	*
S_TOOLS_EX	AUTH	*
S_USER_GRP	ACTVT	02 03 05
	CLASS	*
S_PROGRAM	P_ACTION	*
	P_GROUP	/LICMAN*

Table A-2 • Role /LICMAN/MASTER_ALL

Object	Field Name	Value
S_RFC	ACTVT	*
	RFC_NAME	/LICMAN/* ARFC ERFC LAW* RFC* SCSM* SDIF* SDTX STUW* SUU6 SYST SYSU
	RFC_TYPE	FUGR
S_RFC_ADM	ACTVT	01 02 03 06
	ICF_VALUE	*
	RFCDEST	*
	RFCTYPE	*
S_TCODE	TCD	/LICMAN/*
	TCD	/LICMAN/START
S_BTCH_ADM	BTCADMIN	Y

Table A-2 • Role /LICMAN/MASTER_ALL

Object	Field Name	Value
S_GUI	ACTVT	04
		60
		61
S_TABU_DIS	ACTVT	03
	DICBERCLS	*
S_TOOLS_EX	AUTH	*
S_PROGRAM	P_ACTION	*
	P_GROUP	/LICMAN*
S_ALV_LAYO	ACTVT	23
S_APPL_LOG	ACTVT	03
	ALG_OBJECT	J_5N_DLC
	ALG_SUBOBJECT	J_5N_UPD
J_5NL_SYST	J_5NL_ACTV	*
	J_5NL_CLNT	*
	J_5NL_INST	*
	J_5NL_SYST	*
J_5NL_UPD	J_5NL_UPDF	*



Note • The object `S_RFC_ADM` is not part of the role `/LICMAN/MASTER_READ_ONLY`.

Table A-3 • Role `/LICMAN/MASTER_READ_ONLY`

Object	Field Name	Value
S_RFC	ACTVT	*
	RFC_NAME	/LICMAN/* ARFC ERFC LAW* RFC* SCSM* SDIF* SDTX STUW* SUU6 SYST SYSU
	RFC_TYPE	FUGR
S_TCODE	TCD	/LICMAN/START
	TCD	/LICMAN/*
S_BTCH_ADM	BTCADMIN	Y
S_GUI	ACTVT	04
		61
S_TABU_DIS	ACTVT	03
	DICBERCLS	*
S_PROGRAM	P_ACTION	*
	P_GROUP	/LICMAN*

Table A-3 • Role /LICMAN/MASTER_READ_ONLY

Object	Field Name	Value
S_APPL_LOG	ACTVT	03
	ALG_OBJECT	J_5N_DLC
	ALG_SUBOBJECT	J_5N_UPD
J_5NL_SYST	J_5NL_ACTV	03 23 43
	J_5NL_CLNT	*
	J_5NL_INST	*
	J_5NL_SYST	*

Table A-4 • Role /LICMAN/INTERFACE

Object	Field Name	Value
S_RFC	ACTVT	16
	RFC_NAME	/LICMAN/IF
		RFC1
		SDIFRUNTIME
		SYST
	RFC_TYPE	FUGR

Table A-5 • Role /LICMAN/SATELLITE_CHARGEBACK

Object	Field Name	Value
S_RFC	ACTVT	*
	RFC_NAME	0012
		KGR2
	RFC_TYPE	FUGR
K_CCA	CO_ACTION	0003
	KSTAR	*
	RESPAREA	*
K_CSKS	ACTVT	03
	KOKRS	*
	KOSTL	*
K_CSKS_SET	ACTVT	03
	KOKRS	*

Tables Read and Data Collected by the SAP Inventory Agent

This appendix describes which data is collected by the SAP Inventory Agent.

Table B-1 • System information

Table	Field Name	Definition
TUCON	SYM_GRP	Group for measurement data
TUCON	SYM_KEY	Key for measurement data
TUCON	SYM_VAL	Value for measurement data
TUPL	DEFLT_UTYP	ID for the user types of the SAP system
TUPL	ACTIVE	General flag
T000	CCCATEGORY	Role of client (production, test, ...)

Table B-2 • Active servers

Table Name	Field Name	Definition
DD03L	HOST	Host used for collecting consumption data
DD03L	INSTSHORT	Instance used for collecting consumption data

Table B-3 • Programs, jobs and transaction codes

Table Name	Field Name	Definition
TRDIR	NAME	ABAP program name
TBTCP	JOBNAME	Background job name
TBTCP	PROGNAME	Program name within a step (e.g. report)
TSTC	PGMNA	Program name
TSTC	TCODE	Transaction code

Table B-4 • Languages

Table Name	Field Name	Definition
T002	SPRAS	Language key
T002	LAISO	Language key according to ISO 639

Table B-5 • Users

Table Name	Field Name	Definition
USR02	BNAME	User name in user master record
USR02	GLTGV	User valid from date
USR02	GLTGB	User valid to date
USR02	USTYP	User type
USR02	TRDAT	Last logon date
USR02	LTIME	Last logon time
USR02	CLASS	User group in user master maintenance

Table B-5 • Users

Table Name	Field Name	Definition
USR02	ERDAT	Creation date of the user master record
USR02	ACCNT	Account ID
USR02	UFLAG	User lock status
USR06	BNAME	User name in user master record
USR06	LIC_TYPE	ID for the user types of the SAP system
USR06	VONDAT	Substitute “from date”
USR06	BISDAT	Substitute “to date”
USR06	SURCHARGE	System measurement: country surcharge (3 characters)
USR06	SPRAS	Assignment to special version
USR06	MANDT2	Client
USR06	SYSID	Name of the SAP system
USR06	ANAME	Chargeable user
USR21	BNAME	User name in user master record
USR21	ADDRNUMBER	Address number
USR21	PERSNUMBER	Person number
USR21	KOSTL	Cost Centre
ADR6	ADDRNUMBER	Address number
ADR6	PERSNUMBER	Person number
ADR6	SMTP_ADDR	Email address
ADRP	PERSNUMBER	Person number
ADRP	NAME_FIRST	First name

Table B-5 • Users

Table Name	Field Name	Definition
ADRP	NAME_LAST	Last name
ADRC	ADDRNUMBER	Address number
ADRC	NAME1	Company name 1
ADRC	NAME2	Company name 2
V_ADDR_USR	ADDRNUMBER	Address number
V_ADDR_USR	PERSNUMBER	Person number
V_ADDR_USR	DEPARTMENT	Department
V_ADDR_USR	TEL_NUMBER	First telephone number: dialling code + number
V_ADDR_USR	TEL_EXTENS	First telephone number: extension
V_ADDR_USR	FUNCTION	Function
DEVACCESS	UNAME	Developer user
USR41_MLD	BNAME	User name in user master record
USR41_MLD	CAL_YEAR	Calendar year
USR41_MLD	COUNTER	Number of concurrent logons
USR41_MLD	PEAK	Maximum number of concurrent logons

Table B-6 • License types

Table Name	Field Name	Definition
TUTYP	LANGU	Language Key
TUTYP	USERTYP	ID for the user types of the SAP system

Table B-6 • License types

Table Name	Field Name	Definition
TUTYP	UTYPLONGTEXT	System measurement: Text of length 55 (case sensitive)
TUTYP	UTYPTTEXT	Short test for user types
TUTYP A	ACTIVE	Active flag
TUTYP A	COUNTRY	Active flag
TUTYP A	SONDERVERS	Active flag
TUTYP A	SSCR_ALLOW	General flag
TUTYP A	USERTYP	ID for the user types of the SAP system
LAW_CONT	ACTION	Action for value pair
LAW_CONT	CONTAINSU	ID for the user types of the SAP system
LAW_CONT	USERTYP	ID for the user types of the SAP system
TUZUS	LANGU	Language Key
TUZUS	SONDERVERS	Assignment to special version
TUZUS	TEXTVERS	Special version

Table B-7 • Roles

Table Name	Field Name	Definition
AGR_DEFINE	AGR_NAME	Role name
AGR_FLAGS	AGR_NAME	Role name
AGR_FLAGS	FLAG_VALUE	Default license type for the role
AGR_USERS	AGR_NAME	Role name
AGR_USERS	UNAME	User name in master record

Table B-7 • Roles

Table Name	Field Name	Definition
AGR_USERS	COL_FLAG	Flag: assignment from composite role
AGR_USERS	FROM_DAT	Role valid from date
AGR_USERS	TO_DAT	Role valid to date
AGR_AGRS	AGR_NAME	Composite role
AGR_AGRS	CHILD_AGR	Single role in composite role
AGR_1251	AGR_NAME	Role name
AGR_1251	HIGH	Authorization value
AGR_1251	LOW	Authorization value

Table B-8 • Packages

Table Name	Field Name	Definition
TUAPPT	SPRSL	Language key
TUAPPT	APPLIC	ID for an application for system measurement
TUAPPT	APPLICNAME	Name of an application for system measurement
TUAPP	APPLIC	ID for an application for system measurement
TUAPP	PERIOD	Type (length) of period for system measurement
TUUNTT	SPRSL	Language key
TUUNTT	UNIT	ID for a unit for system measurement
TUUNTT	UNITNAME	Name of a unit for system measurement

Table B-9 • Package measurements (not applicable for offline POC)

Table Name	Field Name	Definition
/LICMAN/BSENGI	DATUM	Measurement date
/LICMAN/BSENGI	APPLIC	ID for an application for system measurement
/LICMAN/BSENGI	UNIT	ID for a unit for system measurement
/LICMAN/BSENGI	COUNTER	Counter for system measurement objects
/LICMAN/BSENGI	PER_START	Start of measurement period
/LICMAN/BSENGI	PER_END	End of measurement period

Table B-10 • Database schema (read but not collected)

Table Name	Field Name	Definition
DD03L	FIELDNAME	Field name

Functions Executed and Data Collected by the SAP Inventory Agent

This appendix lists the functions that the SAP Inventory Agent executes.

Table C-1 • RFC_SYSTEM_INFO

Function	Definition
RFCSAPRL	Release version
RFCKERNRL	Kernel release version
RFCDBSYS	Database system
RFCHOST	Host
RFCSYSID	System ID
RFCMACH	Machine ID
RFCOPSYS	Operating system type
RFCIPADDR	IP (v4) address

Table C-2 • SAPWL_WORKLOAD_GET_STATISTIC (Basis version < 7.0)

Function	Definition
MANDT	Client ID
ACCOUNT	User account

Table C-2 • SAPWL_WORKLOAD_GET_STATISTIC (Basis version < 7.0)

Function	Definition
ENTRY_ID	Entry ID
CPUTI	Total CPU time (across multiple clients)
TTYPE	Type of task
MEMSUM	Memory consumed
COUNTER	Counter
PRIVSUM	Private memory consumed

Table C-3 • SWNC_COLLECTOR_GET_AGGREGATES (Basis version >= 7.0)

Function	Definition
MANDT	Client ID
ACCOUNT	User account
ENTRY_ID	Entry ID
CPUTI	Total CPU time (across multiple clients)
TASKTYPE	Type of task
MEMSUM	Memory consumed
COUNTER	Counter
PRIVSUM	Private memory consumed

Table C-4 • /LICMAN/BS_GET_SAP_MODULES (not applicable for offline POC)

Function	Definition
ACCTEXT	User account
MODULE1	Module
MODULE2	Sub-module

Index

Symbols

/LICMAN/ namespace [1](#)
/LICMAN/DELETION_XPRA_WB, report [21](#)
/LICMAN/INTERFACE, role [4](#)
/LICMAN/MASTER_ALL, role [4](#)
/LICMAN/MASTER_READ_ONLY, role [4](#)
/LICMAN/SATELLITE_CHARGEBACK, role [4](#)
/LICMAN/SATELLITE, role [4](#)

A

AdminModule transport, definition [1](#)
authorizations
 customizing [4](#)
 for FlexNet Manager for SAP Applications [4](#)
 for object J_5NL_SYST [4](#)
 for object J_5NL_UPD [5](#)
 required by SAP Inventory Agent [5](#)

B

basic authentication in web services [10](#)
batch jobs [7](#)

C

check
 after import [3](#)
 import log [3](#)
collecting data [20](#)
communication
 between FlexNet Manager Suite and FlexNet Manager for

 SAP Applications [9](#)
 with inventory beacons [20](#)
configuring
 basic authentication [10](#)
 SSL authentication [14](#)
 web services [9](#)
CUA satellites [7](#)
customizing authorizations [4](#)

D

data collection
 from SAP enterprise portal [20](#)
 statistical data [20](#)
 user master data [20](#)
definitions
 AdminModule transport [1](#)
 master system [1](#)
 SAP Admin module [1](#)
 satellite [1](#)
 Satellite transport [1](#)
deleting FlexNet Manager for SAP Applications [21](#)
deletion transport [21](#)

E

errors [3](#)

I

ICM transaction [14](#)
import logs [3](#)
importing

Index

- FlexNet Manager for SAP Applications [1](#)
 - license file [7](#)
 - transports [2](#)
 - warning message [3](#)
- inserting SAP enterprise portal system [21](#)
- installation number [7](#)
- installation requirements [2](#)
- installing product license [7](#)
- Inventory Agent, authorizations [5](#)
- inventory beacons, communicating with [20](#)

J

- J_5NL_SYST, object [4](#)
- J_5NL_UPD, object [5](#)

L

- license file, importing [7](#)

M

- master system, definition [1](#)

N

- namespace, /LICMAN/ [1](#)
- non-CUA satellites [6](#)

P

- portal, collecting data from [20](#)
- product license, installing [7](#)

R

- read-only flag [2](#)
- removing FlexNet Manager for SAP Applications [21](#)
- requirements for installation [2](#)
- RFC connection
 - for CUA satellites [7](#)
 - for non-CUA satellites [6](#)
- role
 - /LICMAN/INTERFACE [4](#)
 - /LICMAN/MASTER_ALL [4](#)
 - /LICMAN/MASTER_READ_ONLY [4](#)
 - /LICMAN/SATELLITE [4](#)
 - /LICMAN/SATELLITE_CHARGEBACK [4](#)
 - transport [3](#)

S

- SAP Admin module
 - definition [1](#)
 - installing [3](#)
- SAP enterprise portal, collecting data from [20](#)
- SAP Inventory Agent, authorizations [5](#)
- SAPServiceSoap, web service [9](#)
- satellite
 - definition [1](#)
 - installing [3](#)
- Satellite transport, definition [1](#)
- SM [14](#)
- SOA Manager [10](#)
 - basic authentication [10](#)
 - SSL authentication [14](#)
- SOAMANAGER transaction [10](#), [14](#)
- SSL authentication in web services [14](#)
- STRUST transaction [14](#)

T

- technical requirements [2](#)
- transaction
 - SMICM, Internet Communication Manager [14](#)
 - SOAMANAGER [10](#), [14](#)
 - STRUST [14](#)
- transport
 - AdminModule [3](#)
 - AdminModule, definition [1](#)
 - Basis/Satellite [3](#)
 - current numbers of [2](#)
 - deletion [21](#)
 - importing [2](#)
 - Role [3](#)
 - Satellite, definition [1](#)
 - warning message [3](#)
- Trust Manager [14](#)

U

- uninstalling FlexNet Manager for SAP Applications [21](#)
- upgrading from previous versions [2](#)

W

- warning message
 - Does not match component version [3](#)
 - during import [3](#)
 - The installed release does not match [3](#)
- web services

basic authentication [10](#)
configuring [9](#)
SAPServiceSoap [9](#)
SOA Manager [10](#)
SSL authentication [14](#)