SAP DBM

SAP ABAP Technical

SAP FI/Finance Functional

SAP Sales/SD Functional

OTF File attachment to SAP DMS/Content Server

In DMS you can upload or attach the PDF of various transactions without downloading them to the Desktop or Mobile devices.

You need to convert the PDF into Binary format data and then you need to try uploading it into the SAP DMS system or content server.

Example will make it more clear say you are printing the Invoice and you wish that the invoice should be uploaded to the content server or SAP DMS. Just need to convert the Smartforms or Adobe form to binary format.

- 1. You create a DMS document using the BAPI BAPI DOCUMENT CREATE2.
- 2. Then you need to call the another BAPI which will help you upload or attach the form CVAPI_DOC_CHECKIN.

Below Code will guide you:-

TYPES: BEGIN OF zst_ts_raw_line, line(2550) type x, END OF zst ts raw line.

*now after successful document creation we have to attach document to this dms document

DATA: Is_file TYPE cvapi_doc_file,
Is_api_cntl TYPE cvapi_api_control,
Is_bintab type zst_ts_raw_line, "needed for HTTP response
Is_drao TYPE drao,
Is_msg TYPE messages,
binlen TYPE i,
I_filename TYPE char50,
It_files TYPE TABLE OF cvapi_doc_file,
It_bintab TYPE TABLE OF zst_ts_raw_line,
It_drao TYPE TABLE OF drao.

**—here we will get lv_pdfsource as zstrong data now Convert XSTRING TO Blnary DAta.

*DATA: lt_bintab TYPE TABLE OF ls_bintab.

• wa_bintab TYPE ls_bintab.

CALL FUNCTION 'SCMS_XSTRING_TO_BINARY'

EXPORTING

buffer = I_out

IMPORTING

output_length = binlen

TABLES

binary_tab = lt_bintab.

**FIELD-SYMBOLS: TYPE ls_bintab.

LOOP AT lt_bintab INTO ls_bintab.

CLEAR ls_drao.

Is drao-orblk = Is bintab-line.

ls_drao-orln = binlen.

APPEND Is drao TO It drao.

ENDLOOP.

CONCATENATE 'TEST' 'pdf'

INTO I_filename SEPARATED BY '.'.

ls_file-updateflag = 'l'.

ls_file-dappl = 'PDF'.

ls_file-storage_cat = 'DMS_C1_ST'.

```
Is file-filename = I filename.
ls_file-description = 'AcrobatReader'. "l_docname."file_st-
cvtext."'AcrobatReader'.
Is file-checked in = 'X'.
APPEND Is_file TO It_files.
ls_api_cntl-no_update_task = 'X'.
BREAK-POINT.
CALL FUNCTION 'CVAPI_DOC_CHECKIN'
EXPORTING
pf_dokar = 'ZIN'"gs_draw-dokar
pf doknr = 'INV000000002' "attr draw-doknr
pf dokvr = '01' "attr draw-dokvr
pf doktl = '000' "attr draw-doktl
pf_hostname = 'DEFAULT'
ps_api_control = ls_api_cntl
pf replace = 'X'
pf_content_provide = 'TBL'
pf_ftp_dest = 'SAPFTPA'
pf http dest = 'SAPHTTPA'
IMPORTING
psx_message = ls_msg
TABLES
```

pt_files_x = lt_files
pt_content = lt_drao.

BREAK-POINT.

CALL FUNCTION 'BAPI_TRANSACTION_COMMIT' EXPORTING

wait = 'X'.

SAP ABAP Technical

Powered by WordPress and zeeMagazine.