




### Sorun Cevaplayalım

İşinizle ilgili öngörüler edinin, gerçek zamanlı bilgilere göre karar alın.



### SAP Eğitim ve Sertifika Dönemleri

Uzmanlığınızı ve deneyiminizi SAP çözümleri kullanarak tasdik edin.



### Çözüm Ekibi Başvurusu

Kullanıcılara hızlı ve pratik çözümler üreterek görev almak isteyenler.

[Ana Sayfa](#) [Forumlar](#) [SAP Modules Overview - Transaction Codes](#) [Sales and Distribution \(SD\)](#)

## SAP BLOG SD Invoice Output Type – External Email to Multiple Customer Recipient

SAP Blog · 22 Ara 2017



### Be DevOps Certified in 18 Days

Industry's highest course completion rate. EMI starts at only INR 1,799. Find out more

Ad Edureka

# S

### SAP Blog

Kayıtlı Üye

Katılım: 22 Ara 2017  
Mesajlar: 644  
Tepki puanı: 4

22 Ara 2017

↑ 🔗 #1

Hello Friends:

I would like to share my knowledge about **SD – Billing Invoice should send to multiple customer via email from SAP environment in PDF format**. I know it may possible that to achieve this there may be a variety of option are available, but I would like to share my work knowledge which I had proceed for this business requirement.

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

✓ Kabul Et

Detaylı Bilgi...


trigger the mail with some additional column information along with custom message which can be easily understood by the business end user.

To overcome we need to go with Techno-Functional Configuration as per below steps:


#### Functional Configuration:

Transaction Code: NACE

Select V3 Application and click on Output types button.



Create any custom output as shown in below snap shot with the following below setups.



Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

I had selected option # 3 under Dispatch time field, because the Invoice will trigger on the basis of business requirement, i.e. it would be on their dependencies.

The screenshot shows the 'Billing' configuration dialog for 'Output Type' ZEMA, 'Mail Output'. The 'Default values' tab is active. The 'Dispatch time' is set to '3 Send with application own transaction'. The 'Transmission Medium' is set to '5 External send'. The 'Partner Function' is set to 'BP' (Bill-to party). The 'Communication strategy' is set to 'ZEMA' (Mail Output).

Field	Value
Dispatch time	3 Send with application own transaction
Transmission Medium	5 External send
Partner Function	BP Bill-to party
Communication strategy	ZEMA Mail Output

Along with that , I also created separate custom communication strategy and assign it with our created custom output type.

The screenshot shows the 'Billing' configuration dialog for 'Output Type' ZEMA, 'Mail Output'. The 'Storage system' tab is active. The 'Storage Mode' is set to '1 Print only'. The 'Document type' is set to 'SDOINVOICE'.

Field	Value
Storage Mode	1 Print only
Document type	SDOINVOICE

Remark: Time Tab and Sort Order Tab is not applicable to filled for this scenario.

The screenshot shows the 'Billing' configuration dialog for 'Output Type' ZEMA, 'Mail Output'. The 'Print' tab is active. The 'Print param.' is set to '1 Sales organization'.

Field	Value
Print param.	1 Sales organization

**Dialog Structure**

- Output Types
  - Mail title and texts
  - Processing routines
  - Partner functions

**Billing**

Output Type

General data | Default values | Time | Storage system | Print | **Mail** | Sort order

Document name

Priority

☐ Not changeable

Replacement of execution parameters

Program

FORM routine

After completion of all the details under required tabs, click on “Mail title and texts” option.

**Dialog Structure**

- Output Types
  - Mail title and texts**
  - Processing routines
  - Partner functions

**Billing**

Output Type

General data | Default values | Time | Storage system | Print | Mail | Sort order

Access sequence  SalesOrg/BP/Billing Type

**Dialog Structure**

- Output Types
  - Mail title and texts**
  - Processing routines
  - Partner functions

**Application**  **Billing**

Output Type

---

Language

Title

After completion of Mail title and text structure, click on “Processing Routines” structure.

Dialog Structure

- Output Types
  - Mail title and texts
  - Processing routines
  - Partner functions

Output Type: ZEMA Mail Output

Application: V3 Billing

Transm. Medium: 5 External send

Layout module:

Processing routines

Processing 1

Program: ZRLB\_INVOICE

Form Routine: ENTRY

Form:

PDF/Smartform Form: ZBUS\_SDINV\_NEW Form Type: 1 SmartForm

Note: We have created a custom program ZRLB\_INVOICE with required coding logic for our output source.

Dialog Structure

- Output Types
  - Mail title and texts
  - Processing routines
  - Partner functions

Application: V3 Billing

Output Type: ZEMA Mail Output

Partner functions

Medium	Funct	Name
5 External send	BP	Bill-to party

In Partner Functions structure, update the data as shown in above snap shot.

Once all above functional configuration is done, save it.

Now, Output Type is created and now we need to assign it under Billing Output Procedure as shown in below snap shot.


Dialog Structure

- Procedures
  - Control

Procedure: V10000 Billing Output

Reference Step Overview

Step	Co...	CTyp	Description	Requiremnt	Manual only
20	0	ZEMA	Mail Output	0	

Communication 

Sales Organization

Bill-to party

Condition Recs.

Bill...	Name	Funct	Partner	M...	Da...	Lan...
F2	Invoice	BP	0800000035	5	3	EN

Save it.

### Technical Coding:

```
*-----*
* Print of a invoice by SAPscript SMART FORMS *
*-----*

REPORT ZRLB_INVOICE.
*****

* MODULE : Sales & Distribution
*****

TABLES : ADR6.

* declaration of data
INCLUDE RLB_INVOICE_DATA_DECLARE.

* definition of forms
INCLUDE RLB_INVOICE_FORM01.
INCLUDE RLB_PRINT_FORMS.
*-----*
* FORM ENTRY
*-----*
FORM ENTRY USING RETURN_CODE US_SCREEN.

DATA: LF_RETCODE TYPE SY-SUBRC.
CLEAR RETCODE.
XSCREEN = US_SCREEN.
PERFORM PROCESSING USING US_SCREEN
```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```
ELSE.  
RETURN_CODE = 0.  
ENDIF.  
  
ENDFORM. "ENTRY  
*-----*  
* FORM PROCESSING *  
*-----*  
FORM PROCESSING USING PROC_SCREEN  
CHANGING CF_RETCODE.  
  
DATA: LS_PRINT_DATA_TO_READ TYPE LBBIL_PRINT_DATA_TO_READ.  
DATA: LS_BIL_INVOICE TYPE LBBIL_INVOICE.  
DATA: LF_FM_NAME TYPE RS38L_FNAM.  
DATA: LS_CONTROL_PARAM TYPE SSFCTRLP.  
DATA: LS_COMPOSER_PARAM TYPE SSFCOMPOP.  
DATA: LS_RECIPIENT TYPE SWOTOBJID.  
DATA: LS_SENDER TYPE SWOTOBJID.  
DATA: LF_FORMNAME TYPE TDSFNAME.  
DATA: LS_ADDR_KEY LIKE ADDR_KEY.  
DATA: LS_DLV-LAND LIKE VBRK-LAND1.  
DATA: LS_JOB_INFO TYPE SSFCRESCL,  
LS_DOC_INFO TYPE SSFCRESPD,  
LS_JOB_OUTPUT TYPE SSFCRESOP.
```

```
* SmartForm from customizing table TNAPR  
LF_FORMNAME = TNAPR-SFORM.
```

```
* determine print data  
PERFORM SET_PRINT_DATA_TO_READ USING LF_FORMNAME  
CHANGING LS_PRINT_DATA_TO_READ  
CF_RETCODE.
```

```
IF CF_RETCODE = 0.  
* select print data  
PERFORM GET_DATA USING LS_PRINT_DATA_TO_READ  
CHANGING LS_ADDR_KEY
```

ENDIF.

\*\*\*\*\*

TYPES : BEGIN OF TY\_ADR6,

ADDRNUMBER TYPE AD\_ADDRNUM,

SMTP\_ADDR TYPE AD\_SMTPADR,

END OF TY\_ADR6.

DATA : WA\_ADR6 TYPE TY\_ADR6,

IT\_ADR6 TYPE TABLE OF TY\_ADR6,

S\_EMAIL TYPE TABLE OF ADR6-SMTP\_ADDR WITH HEADER LINE.

SELECT ADDRNUMBER SMTP\_ADDR FROM ADR6 INTO CORRESPONDING FIELDS OF TABLE IT\_ADR6 WHERE ADDRNUMBER = LS\_ADDR\_KEY-  
ADDRNUMBER.

IF SY-SUBRC = 0.

LOOP AT IT\_ADR6 INTO WA\_ADR6.

S\_EMAIL = WA\_ADR6-SMTP\_ADDR.

APPEND S\_EMAIL.

ENDLOOP.

ENDIF.

\*\*\*\*\*

IF CF\_RETCODE = 0.

PERFORM SET\_PRINT\_PARAM USING LS\_ADDR\_KEY

LS\_DLV-LAND

CHANGING LS\_CONTROL\_PARAM

LS\_COMPOSER\_PARAM

LS\_RECIPIENT

LS\_SENDER

CF\_RETCODE.

ENDIF.

IF CF\_RETCODE = 0.

\* determine smartform function module for invoice

CALL FUNCTION 'SSF\_FUNCTION\_MODULE\_NAME'

EXPORTING FORMNAME = LF\_FORMNAME

\* variant = ''

\* direct\_call = ''

IMPORTING FM\_NAME = LF\_FM\_NAME

EXCEPTIONS NO\_FORM = 1

NO\_FUNCTION\_MODULE = 2

OTHERS = 3.

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.

Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et



```
PERFORM PROTOCOL_UPDATE.  
ENDIF.  
ENDIF.  
  
IF CF_RETCODE = 0.  
PERFORM CHECK_REPEAT.  
IF LS_COMPOSER_PARAM-TDCOPIES EQ 0.  
NAST_ANZAL = 1.  
ELSE.  
NAST_ANZAL = LS_COMPOSER_PARAM-TDCOPIES.  
ENDIF.  
LS_COMPOSER_PARAM-TDCOPIES = 1.  
* BEGIN: Country specific extension for Hungary  
DATA: LV_CCNUM TYPE IDHUCCNUM.  
  
* If a valid entry exists for the form in customizing view  
* IDHUBILLINGOUT then the localized output shall be used.  
SELECT SINGLE CCNUM INTO LV_CCNUM FROM IDHUBILLINGOUT WHERE  
KSCHL = NAST-KSCHL.  
  
IF SY-SUBRC EQ 0.  
IF LV_CCNUM IS INITIAL.  
LV_CCNUM = 1.  
ENDIF.  
ELSE.  
CLEAR LV_CCNUM.  
ENDIF.  
* END: Country specific extension for Hungary  
DO NAST_ANZAL TIMES.  
* In case of repetition only one time archiving  
IF SY-INDEX > 1 AND NAST-TDARMOD = 3.  
NAST_TDARMOD = NAST-TDARMOD.  
NAST-TDARMOD = 1.  
LS_COMPOSER_PARAM-TDARMOD = 1.  
ENDIF.  
IF SY-INDEX NE 1 AND REPEAT IS INITIAL.  
REPEAT = 'X'.  
ENDIF.  
* BEGIN: Country specific extension for Hungary
```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```

ELSE.
NAST-REPID = NAST-REPID + 1.
ENDIF.
NAST-PFLD1 = LV_CCNUM.
ENDIF.
* END: Country specific extension for Hungary
*****

IF LS_CONTROL_PARAM-PREVIEW = ' '.
LS_CONTROL_PARAM-GETOTF = 'X'.
ENDIF.
*****

* call smartform invoice
CALL FUNCTION LF_FM_NAME
EXPORTING
ARCHIVE_INDEX = TOA_DARA
ARCHIVE_PARAMETERS = ARC_PARAMS
CONTROL_PARAMETERS = LS_CONTROL_PARAM
* mail_appl_obj =
MAIL_RECIPIENT = LS_RECIPIENT
MAIL_SENDER = LS_SENDER
OUTPUT_OPTIONS = LS_COMPOSER_PARAM
USER_SETTINGS = SPACE
IS_BIL_INVOICE = LS_BIL_INVOICE
IS_NAST = NAST
IS_REPEAT = REPEAT
IMPORTING JOB_OUTPUT_INFO = LS_JOB_INFO
DOCUMENT_OUTPUT_INFO = LS_DOC_INFO
JOB_OUTPUT_OPTIONS = LS_JOB_OUTPUT
EXCEPTIONS FORMATTING_ERROR = 1
INTERNAL_ERROR = 2
SEND_ERROR = 3
USER_CANCELED = 4
OTHERS = 5.
IF SY-SUBRC <> 0.
* error handling
CF_RETCODE = SY-SUBRC.
PERFORM PROTOCOL_UPDATE.
* get SmartForm protocoll and store it in the NAST protocoll
PERFORM ADD_SMFRM_PROT.

```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```
DATA LS_SPOOLID LIKE LINE OF LS_JOB_INFO-SPOOLIDS.  
LOOP AT LS_JOB_INFO-SPOOLIDS INTO LS_SPOOLID.  
IF LS_SPOOLID NE SPACE.  
PERFORM PROTOCOL_UPDATE_SPOOL USING '342' LS_SPOOLID  
SPACE SPACE SPACE.  
ENDIF.  
ENDLOOP.  
LS_COMPOSER_PARAM-TDCOPIES = NAST_ANZAL.  
IF NOT NAST_TDARMOD IS INITIAL.  
NAST-TDARMOD = NAST_TDARMOD.  
CLEAR NAST_TDARMOD.  
ENDIF.  
  
ENDIF.
```

```
* get SmartForm protocoll and store it in the NAST protocoll  
* PERFORM ADD_SMFRM_PROT.
```

```
*****
```

```
IF LS_CONTROL_PARAM-PREVIEW = ' '.  
DATA : V_BIN_FILESIZE TYPE I,  
IT_LINES TYPE STANDARD TABLE OF TLINE WITH HEADER LINE,  
IT_OTF_FINAL TYPE ITCOO OCCURS 0 WITH HEADER LINE,  
PDF_BIN TYPE XSTRING,  
PDF_CONTENT TYPE SOLIX_TAB.
```

```
IT_OTF_FINAL[] = LS_JOB_INFO-OTFDATA[].
```

```
CALL FUNCTION 'CONVERT_OTF'  
EXPORTING  
FORMAT = 'PDF'  
MAX_LINEWIDTH = 132  
* ARCHIVE_INDEX = ''  
* COPYNUMBER = 0  
* ASCII_BIDI_VIS2LOG = ''  
* PDF_DELETE_OTFTAB = ''  
* PDF_USERNAME = ''  
IMPORTING  
BIN_FILESIZE = V_BIN_FILESIZE  
BIN_FILE = PDF_BIN
```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```
EXCEPTIONS
ERR_MAX_LINEWIDTH = 1
ERR_FORMAT = 2
ERR_CONV_NOT_POSSIBLE = 3
ERR_BAD_OTF = 4
OTHERS = 5
.
IF SY-SUBRC <> 0.
* MESSAGE ID SY-MSGID TYPE SY-MSGTY NUMBER SY-MSGNO
* WITH SY-MSGV1 SY-MSGV2 SY-MSGV3 SY-MSGV4.
ENDIF.

PDF_CONTENT = CL_DOCUMENT_BCS=>XSTRING_TO_SOLIX( PDF_BIN ).

*****

* Email *
*****

TYPES: TY_DOCUMENT_DATA TYPE SODOCCHG1,
TY_PACKING_LIST TYPE SOPCKLST1,
TY_ATTACHMENT TYPE SOLIST1,
TY_BODY_MSG TYPE SOLIST1,
TY_RECEIVERS TYPE SOMLRECI1.
DATA: IT_DOCUMENT_DATA TYPE STANDARD TABLE OF TY_DOCUMENT_DATA,
IT_PACKING_LIST TYPE STANDARD TABLE OF TY_PACKING_LIST,
IT_ATTACHMENT TYPE STANDARD TABLE OF TY_ATTACHMENT,
IT_BODY_MSG TYPE STANDARD TABLE OF TY_BODY_MSG,
IT_RECEIVERS TYPE STANDARD TABLE OF TY_RECEIVERS,
GT_ATTCH TYPE STANDARD TABLE OF SOLIST1.
DATA :WA_DOCUMENT_DATA TYPE TY_DOCUMENT_DATA,
WA_PACKING_LIST TYPE TY_PACKING_LIST,
WA_ATTACHMENT TYPE TY_ATTACHMENT,
WA_BODY_MSG TYPE TY_BODY_MSG,
WA_RECEIVERS TYPE TY_RECEIVERS,
GS_ATTCH TYPE SOLIST1,
GS_SOLI TYPE SOLI.
DATA: G_TAB_LINES TYPE I,
G_SENT_TO_ALL TYPE SONV-FLAG,
LV_DATE(10) TYPE C,
```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et ☐ Detaylı Bilgi...

DATA: IT\_EMAIL TYPE STANDARD TABLE OF ZSD\_EMAIL\_DLIST,  
WA\_EMAIL TYPE ZSD\_EMAIL\_DLIST.

CONSTANTS: C\_TAB TYPE C VALUE CL\_ABAP\_CHAR\_UTILITIES=>HORIZONTAL\_TAB,  
C\_CRET TYPE C VALUE CL\_ABAP\_CHAR\_UTILITIES=>CR\_LF,  
COMMA TYPE C VALUE ',' ,  
C\_1 VALUE '1',  
C\_0 VALUE '0'.

\* SUBJECT OF THE MAIL.

CLEAR: LV\_DATE, LV\_TIME, WA\_DOCUMENT\_DATA-OBJ\_DESCR.

\* CONCATENATE SY-DATUM+4(2) '\_' SY-DATUM+6(2) '\_' SY-DATUM(4) INTO LV\_DATE.

\* CONCATENATE SY-UZEIT(2) '\_' SY-UZEIT+2(2) '\_' SY-UZEIT+4(2) INTO LV\_TIME.

\* CONCATENATE 'XXX Invoice(s)' LV\_DATE '\_' LV\_TIME INTO WA\_DOCUMENT\_DATA-OBJ\_DESCR.

WA\_DOCUMENT\_DATA-OBJ\_DESCR = 'XXX Invoice(s)'.

\* BODY OF THE MAIL

WA\_BODY\_MSG = SPACE.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = 'Dear Valued Customer:'.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = SPACE.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = 'Attached please find invoice(s) for XXX products provided by XXX. If you have any questions, please'.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = 'contact us at xxx-xxx-xxxx or at [accountsreceivable@XXX.com](mailto:accountsreceivable@XXX.com)'.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = SPACE.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = 'Thank you in advance for choosing XXX products to be sold at your locations.'.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = SPACE.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = 'Sincerely,'.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = SPACE.

APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.

WA\_BODY\_MSG = 'XXX'.

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

WA\_BODY\_MSG = SPACE.  
APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.  
WA\_BODY\_MSG = 'Please do not respond to this message. This email account is not monitored. This message was distributed by XXX,'.  
APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.  
WA\_BODY\_MSG = 'XXX and related trademarks are registered trademarks and'.  
APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.  
WA\_BODY\_MSG = 'trademarks in the United States and/or other countries, used under license from XXX. This electronic message is'.  
APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.  
WA\_BODY\_MSG = 'not an advertisement or solicitation.'.  
APPEND WA\_BODY\_MSG TO IT\_BODY\_MSG.  
CLEAR WA\_BODY\_MSG.  
WA\_DOCUMENT\_DATA-OBJ\_NAME = 'SMARTFORM'.

\* WRITE PACKING LIST FOR BODY  
DESCRIBE TABLE IT\_BODY\_MSG LINES G\_TAB\_LINES.  
WA\_PACKING\_LIST-HEAD\_START = 1.  
WA\_PACKING\_LIST-HEAD\_NUM = 0.  
WA\_PACKING\_LIST-BODY\_START = 1.  
WA\_PACKING\_LIST-BODY\_NUM = G\_TAB\_LINES.  
WA\_PACKING\_LIST-DOC\_TYPE = 'RAW'.  
APPEND WA\_PACKING\_LIST TO IT\_PACKING\_LIST.  
CLEAR WA\_PACKING\_LIST.

"Write Packing List for Attachment  
WA\_PACKING\_LIST-TRANSF\_BIN = 'X'.  
WA\_PACKING\_LIST-HEAD\_START = 1.  
WA\_PACKING\_LIST-HEAD\_NUM = 1.  
WA\_PACKING\_LIST-BODY\_START = 1.  
DESCRIBE TABLE PDF\_CONTENT LINES G\_TAB\_LINES.  
WA\_PACKING\_LIST-DOC\_TYPE = 'PDF'.  
WA\_PACKING\_LIST-OBJ\_DESCR = WA\_DOCUMENT\_DATA-OBJ\_DESCR.  
WA\_PACKING\_LIST-OBJ\_NAME = 'PDF\_ATTACHMENT'.  
WA\_PACKING\_LIST-BODY\_NUM = G\_TAB\_LINES.  
WA\_PACKING\_LIST-DOC\_SIZE = WA\_PACKING\_LIST-BODY\_NUM \* 255.  
APPEND WA\_PACKING\_LIST TO IT\_PACKING\_LIST.  
CLEAR WA\_PACKING\_LIST.

"Fill the document data and get size of attachment  
WA\_DOCUMENT\_DATA-OBJ\_LANGU = SY-LANGU.

```
LOOP AT S_EMAIL.  
WA_RECEIVERS-REC_TYPE = 'U'. "Internet address  
WA_RECEIVERS-RECEIVER = S_EMAIL.  
WA_RECEIVERS-COM_TYPE = 'INT'.  
WA_RECEIVERS-NOTIF_DEL = 'X'.  
WA_RECEIVERS-NOTIF_NDEL = 'X'.  
APPEND WA_RECEIVERS TO IT_RECEIVERS .  
CLEAR:WA_RECEIVERS.  
ENDLOOP.
```

```
"Function module to send mail to Recipients  
CALL FUNCTION 'SO_DOCUMENT_SEND_API1'  
EXPORTING  
DOCUMENT_DATA = WA_DOCUMENT_DATA  
PUT_IN_OUTBOX = 'X'  
* SENDER_ADDRESS = SY-UNAME  
* SENDER_ADDRESS_TYPE = 'B'  
COMMIT_WORK = 'X'  
IMPORTING  
SENT_TO_ALL = G_SENT_TO_ALL  
* NEW_OBJECT_ID =  
* SENDER_ID =  
TABLES  
PACKING_LIST = IT_PACKING_LIST  
* OBJECT_HEADER =  
* CONTENTS_BIN =  
CONTENTS_TXT = IT_BODY_MSG  
CONTENTS_HEX = PDF_CONTENT  
* OBJECT_PARA =  
* OBJECT_PARB =  
RECEIVERS = IT_RECEIVERS  
EXCEPTIONS  
TOO_MANY_RECEIVERS = 1  
DOCUMENT_NOT_SENT = 2  
DOCUMENT_TYPE_NOT_EXIST = 3  
OPERATION_NO_AUTHORIZATION = 4  
PARAMETER_ERROR = 5  
X_ERROR = 6  
ENQUEUE_ERROR = 7
```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

MESSAGE S303(ME) WITH 'Mail has been Successfully Sent.'  
ELSE.  
MESSAGE S303(ME) WITH 'Mail has not been Successfully Sent.'  
ENDIF.

ENDIF.  
ENDFORM. "PROCESSING "

Code Logic for Custom Program:

```
*&-----*
*& Report ZR_INVOICE_SEND_EMAIL
*&-----*

*&-----*
REPORT ZR_INVOICE_SEND_EMAIL NO STANDARD PAGE HEADING.
TABLES : VBRK.
TYPE-POOLS : SLIS.
*&-----*
*& Declarations *&
*&-----*
TYPES : BEGIN OF TY_FINAL,
CHECK TYPE CHECKBOX,
VBELN TYPE VBELN_VF,
FKART TYPE FKART,
VKORG TYPE VKORG,
VTWEG TYPE VTWEG,
SPART TYPE SPART,
FKDAT TYPE FKDAT,
ERNAM TYPE ERNAM,
KUNRG TYPE KUNRG,
KUNAG TYPE KUNNR,
FLAG TYPE C,
END OF TY_FINAL,
```



END OF TY\_ADR6,

BEGIN OF TY\_ADR61,  
EMAIL1 TYPE AD\_SMTPADR,  
EMAIL2 TYPE AD\_SMTPADR,  
EMAIL3 TYPE AD\_SMTPADR,  
EMAIL4 TYPE AD\_SMTPADR,  
EMAIL5 TYPE AD\_SMTPADR,  
END OF TY\_ADR61,

BEGIN OF TY\_OUTPUT,  
CHECK TYPE CHECKBOX,  
VBELN TYPE VBELN\_VF,  
FKART TYPE FKART,  
VKORG TYPE VKORG,  
VTWEG TYPE VTWEG,  
SPART TYPE SPART,  
FKDAT TYPE FKDAT,  
ERNAM TYPE ERNAM,  
KUNRG TYPE KUNRG,  
KUNAG TYPE KUNNR,  
VTEXT TYPE BEZEI20,  
NAME1\_P TYPE NAME1\_GP,  
NAME1\_S TYPE NAME1\_GP,  
VSTAT TYPE NA\_VSTAT,  
EMAIL1 TYPE AD\_SMTPADR,  
EMAIL2 TYPE AD\_SMTPADR,  
EMAIL3 TYPE AD\_SMTPADR,  
EMAIL4 TYPE AD\_SMTPADR,  
EMAIL5 TYPE AD\_SMTPADR,  
FLAG TYPE C,  
END OF TY\_OUTPUT.

\*&-----\*

\*& Internal Table Declarations \*&

\*&-----\*

DATA : IT\_FINAL TYPE TABLE OF TY\_FINAL,  
IT\_FINAL1 TYPE TABLE OF TY\_FINAL,  
IT\_OUTPUT TYPE TABLE OF TY\_OUTPUT,  
IT\_VBPA TYPE STANDARD TABLE OF VBPA,

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```

IT_FINAL2 TYPE STANDARD TABLE OF TY_FINAL,
IT_FINAL3 TYPE STANDARD TABLE OF TY_FINAL,
IT_FCAT TYPE SLIS_T_FIELDCAT_ALV,
IT_BDCMSG TYPE TABLE OF BDCMSGCOLL,
IT_NAST TYPE STANDARD TABLE OF NAST,
*&-----*
*& Work Area Declarations *&
*&-----*
WA_OUTPUT TYPE TY_OUTPUT,
WA_TVFKT TYPE TVFKT,
WA_VBPA TYPE VBPA,
WA_KNA1 TYPE KNA1,
WA_ADR6 TYPE TY_ADR6,
WA_ADR61 TYPE TY_ADR61,
WA_NAST TYPE NAST,
WA_FINAL TYPE TY_FINAL,
WA_FINAL3 TYPE TY_FINAL,
WA_FINAL2 TYPE TY_FINAL,
WA_FINAL1 TYPE TY_FINAL,
WA_FCAT TYPE SLIS_FIELDCAT_ALV,
S_LAYOUT TYPE SLIS_LAYOUT_ALV,
BDCDATA TYPE BDCDATA OCCURS 1 WITH HEADER LINE,
WA_BDCMSG TYPE BDCMSGCOLL,
CURR_LINE TYPE SY-TABIX,
WA_CTUPARAMS TYPE CTU_PARAMS.
FIELD-SYMBOLS : <F5> TYPE ANY,
<F52> TYPE ANY.
*&-----*
*& Select-Options *&
*&-----*
SELECTION-SCREEN BEGIN OF BLOCK B1 WITH FRAME TITLE TEXT-001.
SELECT-OPTIONS: S_VBELN FOR VBRK-VBELN,
S_FKDAT FOR VBRK-FKDAT OBLIGATORY,
S_ERNAM FOR VBRK-ERNAM,
S_FKART FOR VBRK-FKART DEFAULT 'F2',
S_VKORG FOR VBRK-VKORG,
S_VTWEG FOR VBRK-VTWEG,
S_SPART FOR VBRK-SPART,
S_KUNRG FOR VBRK-KUNRG,

```

```

*& Start-of-Selection *&
*&-----*
START-OF-SELECTION.
PERFORM GET_DISPLAY_DATA.
*&-----*
*& Form GET_DISPLAY_DATA
*&-----*
* text
*-----*

FORM GET_DISPLAY_DATA .
SELECT VBELN
FKART
VKORG
VTWEG
SPART
FKDAT
ERNAM
KUNRG
KUNAG FROM VBRK
INTO CORRESPONDING FIELDS OF TABLE IT_FINAL
WHERE VBELN IN S_VBELN
AND FKART IN S_FKART
AND VKORG IN S_VKORG
AND VTWEG IN S_VTWEG
AND SPART IN S_SPART
AND FKDAT IN S_FKDAT
AND ERNAM IN S_ERNAM
AND KUNRG IN S_KUNRG
AND KUNAG IN S_KUNAG.

* SELECT OBJKY ERUHR VSTAT FROM NAST INTO CORRESPONDING FIELDS OF TABLE IT_NAST
* FOR ALL ENTRIES IN IT_FINAL
* WHERE OBJKY = IT_FINAL-VBELN
* AND KSCHL = 'ZEMA'
* ORDER BY ERUHR DESCENDING.
* ENDSELECT.
** SORT DESCENDING BY WA_NAST-ERUHR.
* IF SY-SUBRC = 0.
* IF WA_NAST-VSTAT = 0.

```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```
* ENDIF.  
* ELSE.  
* WA_OUTPUT-VSTAT = 'N'.  
* WA_OUTPUT-FLAG = 'X'.  
* ENDIF.  
  
IF IT_FINAL IS NOT INITIAL.  
SELECT FKART VTEXT FROM TVFKT INTO CORRESPONDING FIELDS OF TABLE IT_TVFKT  
FOR ALL ENTRIES IN IT_FINAL  
WHERE FKART = IT_FINAL-FKART  
AND SPRAS = 'E'.  
  
LOOP AT IT_FINAL INTO WA_FINAL.  
MOVE-CORRESPONDING WA_FINAL TO WA_OUTPUT.  
  
READ TABLE IT_TVFKT INTO WA_TVFKT WITH KEY FKART = WA_FINAL-FKART.  
IF SY-SUBRC = 0.  
WA_OUTPUT-VTEXT = WA_TVFKT-VTEXT.  
ENDIF.  
  
SELECT SINGLE KUNNR NAME1 FROM KNA1 INTO CORRESPONDING FIELDS OF WA_KNA1  
WHERE KUNNR = WA_FINAL-KUNRG.  
IF SY-SUBRC = 0.  
WA_OUTPUT-NAME1_P = WA_KNA1-NAME1.  
CLEAR : WA_KNA1.  
ENDIF.  
  
SELECT SINGLE KUNNR NAME1 FROM KNA1 INTO CORRESPONDING FIELDS OF WA_KNA1  
WHERE KUNNR = WA_FINAL-KUNAG.  
IF SY-SUBRC = 0.  
WA_OUTPUT-NAME1_S = WA_KNA1-NAME1.  
CLEAR : WA_KNA1.  
ENDIF.  
  
SELECT OBJKY ERDAT ERUHR VSTAT FROM NAST INTO CORRESPONDING FIELDS OF TABLE IT_NAST  
* FOR ALL ENTRIES IN WA_FINAL  
WHERE OBJKY = WA_FINAL-VBELN  
AND KSCHL = 'ZEMA'.  
" ORDER BY ERDAT DESCENDING
```

```

*DATA : INDEX TYPE SY-INDEX.
IF SY-SUBRC = 0.
  READ TABLE IT_NAST INTO WA_NAST WITH KEY OBJKY = WA_FINAL-VBELN.
  IF SY-SUBRC = 0.
    IF WA_NAST-VSTAT = 0.
      WA_OUTPUT-VSTAT = 'N'.
    ELSEIF WA_NAST-VSTAT = 1.
      WA_OUTPUT-VSTAT = 'Y'.
    ELSEIF WA_NAST-VSTAT = 2.
      WA_OUTPUT-VSTAT = 'N'.
    WA_OUTPUT-FLAG = 'X'.
  ENDIF.
ENDIF.
ELSE.
  WA_OUTPUT-VSTAT = 'N'.
  WA_OUTPUT-FLAG = 'X'.
ENDIF.

SELECT SINGLE VBELN PARVW KUNNR ADRNR FROM VBPA INTO CORRESPONDING FIELDS OF WA_VBPA
WHERE VBELN = WA_FINAL-VBELN
AND KUNNR = WA_FINAL-KUNRG
AND PARVW = 'AG'.

IF SY-SUBRC = 0.
  SELECT SMTP_ADDR FROM ADR6 INTO CORRESPONDING FIELDS OF TABLE IT_ADR6
  WHERE ADDRNUMBER = WA_VBPA-ADRNR.
  DELETE ADJACENT DUPLICATES FROM IT_ADR6 COMPARING ALL FIELDS.
  LOOP AT IT_ADR6 INTO WA_ADR6.
  CLEAR WA_ADR61.
  ASSIGN COMPONENT SY-TABIX OF STRUCTURE WA_ADR61 TO <FS>.
  CURR_LINE = SY-TABIX.
  DO.
  ASSIGN COMPONENT SY-INDEX OF STRUCTURE WA_ADR6 TO <FS2>.
  IF SY-SUBRC NE 0.
    EXIT.
  ENDIF.
  IF CURR_LINE = 1.
    <FS> = <FS2>.
  APPEND WA_ADR61 TO IT_ADR61 .

```

MODIFY IT\_ADR61 FROM WA\_ADR61 INDEX SY-INDEX.  
ENDIF.

ENDDO.  
ENDLOOP.

LOOP AT IT\_ADR61 INTO WA\_ADR61.  
IF SY-SUBRC = 0.  
WA\_OUTPUT-EMAIL1 = WA\_ADR61-EMAIL1.  
WA\_OUTPUT-EMAIL2 = WA\_ADR61-EMAIL2.  
WA\_OUTPUT-EMAIL3 = WA\_ADR61-EMAIL3.  
WA\_OUTPUT-EMAIL4 = WA\_ADR61-EMAIL4.  
WA\_OUTPUT-EMAIL5 = WA\_ADR61-EMAIL5.  
ENDIF.  
ENDLOOP.  
ENDIF.

APPEND WA\_OUTPUT TO IT\_OUTPUT.  
CLEAR : WA\_OUTPUT.  
REFRESH : IT\_ADR61.  
ENDLOOP.

PERFORM SUB\_POPULATE USING : '1' 'CHECK' '' 'X' 'X',  
'2' 'VBELN' 'Billing Doc.No.' '' '' ,  
'3' 'FKART' 'Billing Type' '' '' ,  
'4' 'VTEXT' 'Billing Type Desc.' '' '' ,  
'4' 'VKORG' 'Sales Organization' '' '' ,  
'5' 'VTWEG' 'Distribution Channel' '' '' ,  
'6' 'SPART' 'Division' '' '' ,  
'7' 'FKDAT' 'Billing Date' '' '' ,  
'8' 'ERNAM' 'Created By' '' '' ,  
'9' 'KUNRG' 'Payer' '' '' ,  
'10' 'NAME1\_P' 'Payer Name' '' '' ,  
'11' 'KUNAG' 'Sold-to Party' '' '' ,  
'12' 'NAME1\_S' 'Sold-to Party Name' '' '' ,  
'13' 'VSTAT' 'Email Sent(Y/N)' '' '' ,  
'14' 'EMAIL1' 'E-mail Address 1' '' '' ,  
'15' 'EMAIL2' 'E-mail Address 2' '' '' ,  
'16' 'EMAIL3' 'E-mail Address 3' '' '' ,

```
CALL FUNCTION 'REUSE_ALV_GRID_DISPLAY'
EXPORTING
  * I_INTERFACE_CHECK = ''
  * I_BYPASSING_BUFFER = ''
  * I_BUFFER_ACTIVE = ''
  I_CALLBACK_PROGRAM = SY-REPID
  I_CALLBACK_PF_STATUS_SET = 'PF'
  I_CALLBACK_USER_COMMAND = 'USER_COMMAND'
  * I_CALLBACK_TOP_OF_PAGE = ''
  * I_CALLBACK_HTML_TOP_OF_PAGE = ''
  * I_CALLBACK_HTML_END_OF_LIST = ''
  * I_STRUCTURE_NAME =
  * I_BACKGROUND_ID = ''
  * I_GRID_TITLE =
  * I_GRID_SETTINGS =
  IS_LAYOUT = S_LAYOUT
  IT_FIELDCAT = IT_FCAT
  * IT_EXCLUDING =
  * IT_SPECIAL_GROUPS =
  * IT_SORT =
  * IT_FILTER =
  * IS_SEL_HIDE =
  I_DEFAULT = 'X'
  I_SAVE = 'A'
  * IS_VARIANT =
  * IT_EVENTS =
  * IT_EVENT_EXIT =
  * IS_PRINT =
  * IS_REPREP_ID =
  * I_SCREEN_START_COLUMN = 0
  * I_SCREEN_START_LINE = 0
  * I_SCREEN_END_COLUMN = 0
  * I_SCREEN_END_LINE = 0
  * I_HTML_HEIGHT_TOP = 0
  * I_HTML_HEIGHT_END = 0
  * IT_ALV_GRAPHICS =
  * IT_HYPERLINK =
  * IT_ADD_FIELDCAT =
  * IT_EXCEPT_QINFO =
```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```

* ES_EXIT_CAUSED_BY_USER =
TABLES
T_OUTTAB = IT_OUTPUT
* EXCEPTIONS
* PROGRAM_ERROR = 1
* OTHERS = 2
.
IF SY-SUBRC <> 0.
* MESSAGE ID SY-MSGID TYPE SY-MSGTY NUMBER SY-MSGNO
* WITH SY-MSGV1 SY-MSGV2 SY-MSGV3 SY-MSGV4.
ENDIF.
ELSE.
MESSAGE 'No records found for the selection criteria' TYPE 'S' DISPLAY LIKE 'E'.
ENDIF.
ENDFORM. " GET_DISPLAY_DATA
*&-----*
*& Form SUB_POPULATE
*&-----*
* text
*-----*

FORM SUB_POPULATE USING COL_POS
FIELDNAME
SELTEXT_M
* JUST.
* INPUT
CHECKBOX
EDIT.

WA_FCAT-COL_POS = COL_POS.
WA_FCAT-FIELDNAME = FIELDNAME.
WA_FCAT-SELTEXT_M = SELTEXT_M.
* WA_FCAT-INPUT = INPUT.
WA_FCAT-CHECKBOX = CHECKBOX.
WA_FCAT-EDIT = EDIT.
APPEND WA_FCAT TO IT_FCAT.
CLEAR : WA_FCAT.

S_LAYOUT-ZEBRA = 'X'.
S_LAYOUT-COLWIDTH_OPTIMIZE = 'X'.

```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

✓ Kabul Et Detaylı Bilgi...



```

*& Form PF
*&-----*
*
*-----*
FORM PF USING RT_EXTAB TYPE SLIS_T_EXTAB.
SET PF-STATUS 'ZSTANDARD'." EXCLUDING RT_EXTAB.
ENDFORM. "PF
*&-----*
*& Form PF
*&-----*
*
*-----*
FORM USER_COMMAND USING R_UCOMM LIKE SY-UCOMM
RS_SELFIELD TYPE SLIS_SELFIELD.

DATA REF_GRID TYPE REF TO CL_GUI_ALV_GRID.

IF REF_GRID IS INITIAL.
CALL FUNCTION 'GET_GLOBALS_FROM_SLVC_FULLSCR'
IMPORTING
E_GRID = REF_GRID.
ENDIF.

IF NOT REF_GRID IS INITIAL.
CALL METHOD REF_GRID->CHECK_CHANGED_DATA.
ENDIF.

IF R_UCOMM = '&EXE'.
* CLEAR : FLAG.
DATA : WA_NAST TYPE NAST.
LOOP AT IT_OUTPUT INTO WA_OUTPUT.
IF WA_OUTPUT-CHECK = 'X' AND WA_OUTPUT-FLAG = ' '.
REFRESH BDCDATA.
PERFORM BDC_DYNPRO USING 'SD70AV3A' '1000'.
PERFORM BDC_FIELD USING 'BDC_CURSOR'
'PM_VERMO'.
PERFORM BDC_FIELD USING 'BDC_OKCODE'
'=ONLI'.
PERFORM BDC_FIELD USING 'RG_KSCHL-LOW'

```

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

```
PERFORM BDC_FIELD USING 'PM_NSORT'
'01'.
IF WA_OUTPUT-VSTAT = 'N'.
PERFORM BDC_FIELD USING 'PM_VERMO'
'1'.
ELSEIF WA_OUTPUT-VSTAT = 'Y'.
PERFORM BDC_FIELD USING 'PM_VERMO'
'2'.
ENDIF.
PERFORM BDC_FIELD USING 'RG_VBELN-LOW'
WA_OUTPUT-VBELN.
PERFORM BDC_FIELD USING 'PM_ALLEL'
'X'.
PERFORM BDC_FIELD USING 'PM_ALLEA'
'X'.
PERFORM BDC_FIELD USING 'N_SELECT'
'X'.
PERFORM BDC_DYNPRO USING 'SAPMSSYO' '0120'.
PERFORM BDC_FIELD USING 'BDC_CURSOR'
'04/03'.
PERFORM BDC_FIELD USING 'BDC_OKCODE'
'=&ALL'.
PERFORM BDC_DYNPRO USING 'SAPMSSYO' '0120'.
PERFORM BDC_FIELD USING 'BDC_CURSOR'
'04/03'.
PERFORM BDC_FIELD USING 'BDC_OKCODE'
'=&PROC'.
*
WA_CTUPARAMS-DISMODE = 'N'.
WA_CTUPARAMS-UPDMODE = 'A'.
WA_CTUPARAMS-CATTMODE = ' '.
WA_CTUPARAMS-RACOMMIT = 'X'.
WA_CTUPARAMS-DEFSIZE = 'X'.
WA_CTUPARAMS-NOBINPT = ' '.
WA_CTUPARAMS-NOBIEND = ' '.

CALL TRANSACTION 'VF31' USING BDCDATA "MODE 'N' UPDATE 'S'
OPTIONS FROM WA_CTUPARAMS
MESSAGES INTO IT_BDCMSG.
```

```
CLEAR : WA_OUTPUT.
ELSE.
APPEND WA_OUTPUT TO IT_FINAL2.
CLEAR : WA_OUTPUT.
ENDIF.

LEAVE TO LIST-PROCESSING AND RETURN TO SCREEN 0.
SET PF-STATUS SPACE.
SUPPRESS DIALOG.
NEW-PAGE NO-TITLE NO-HEADING.
ENDIF.
IF WA_OUTPUT-CHECK = 'X' AND WA_OUTPUT-FLAG = 'X'.
APPEND WA_OUTPUT TO IT_FINAL3.
LEAVE TO LIST-PROCESSING AND RETURN TO SCREEN 0.
SET PF-STATUS SPACE.
SUPPRESS DIALOG.
NEW-PAGE NO-TITLE NO-HEADING.
ENDIF.
ENDLOOP.

IF IT_FINAL1 IS NOT INITIAL.
LOOP AT IT_FINAL1 INTO WA_FINAL1.
WRITE :/ 'E-mail has been sent for Invoice Number',WA_FINAL1-VBELN.
ENDLOOP.
ENDIF.
IF IT_FINAL2 IS NOT INITIAL.
LOOP AT IT_FINAL2 INTO WA_FINAL2.
WRITE :/ 'E-mail has not been sent for Invoice Number',WA_FINAL2-VBELN.
ENDLOOP.
ENDIF.
IF IT_FINAL3 IS NOT INITIAL.
LOOP AT IT_FINAL3 INTO WA_FINAL3.
WRITE :/ 'E-mail cannot be sent for the Invoice Number',WA_FINAL3-VBELN.
ENDLOOP.
ENDIF.
ELSEIF R_UCOMM = '&IC1'.
CASE RS_SELFIELD-FIELDNAME.
WHEN 'VBELN'.
SET PARAMETER ID 'VF' FIELD RS_SELFIELD-VALUE.
```

```
CALL TRANSACTION 'XD03' AND SKIP FIRST SCREEN.  
ENDCASE.  
ENDIF.  
ENDFORM. "USER_COMMAND  
*&-----*  
*& Form bdc_dynpro  
*&-----*  
FORM BDC_DYNPRO USING PROGRAM DYNPRO.  
CLEAR BDCDATA.  
  
BDCDATA-PROGRAM = PROGRAM.  
BDCDATA-DYNPRO = DYNPRO.  
BDCDATA-DYNBEGIN = 'X'.  
APPEND BDCDATA.  
ENDFORM. "bdc_dynpro  
*&-----*  
*& Form BDC_FIELD  
*&-----*  
FORM BDC_FIELD USING FNAME FVAL.  
IF FVAL <> SPACE.  
CLEAR BDCDATA.  
  
BDCDATA-FNAME = FNAME.  
BDCDATA-FVAL = FVAL.  
APPEND BDCDATA.  
ENDIF.  
ENDFORM. "BDC_FIELD
```

## Send Email for Invoice



### Specify Inputs

Billing Doc. No.	<input type="text"/>	to	<input type="text"/>	
Billing Date	12/06/2017	to	<input type="text"/>	
Created By	<input type="text"/>	to	<input type="text"/>	
Billing Type	F2	to	<input type="text"/>	
Sales Organization	<input type="text"/>	to	<input type="text"/>	
Distribution Channel	<input type="text"/>	to	<input type="text"/>	
Division	<input type="text"/>	to	<input type="text"/>	
Payer	<input type="text"/>	to	<input type="text"/>	
Sold-to Party	<input type="text"/>	to	<input type="text"/>	

## Send Email for Invoice

Selections

	Billing Doc.No.	Billing Type	Billing Type Desc.	Sales Organization	Distribution Channel	Division	Billing Date	Created By	Payer	Payer Name	Sold-to Party	Sold-to Party Name	Email Sent(Y/N)
	0090131280	F2	Invoice	1000	10	10	12/06/2017		0800000035		0800000035		Y

Document Completed.

I hope you will like this document. If any suggestion, please let me know. I would like to have you guidance and suggestion.

Thanks,

Kundan Vishwakarma

[Okumaya devam et...](#)

constantine

C

10 Ağu 2018

↑ #2

these informations very useful. thank you.

Son düzenleme: 10 Ağu 2018

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.






✓ Kabul Et

Detaylı Bilgi...

Tepki puanı: 1  
Kullandığınız SAP  
Modülleri:  
SAP MM, SAP SD, SAP  
ABAP  
Katılım Bölgesi:  
İstanbul

Yanıt için giriş yapmanız veya üye olmanız gerekir.

## İlginizi Çekebilecek Benzer Konular

E	<b>YARDIM</b> Sipariş teslimat fatura uyarlaması hk.	Cevaplar: 0 Görüntüleme: 748	27 Mar 2019 Esraezmeci	E
	<b>Müşteri bazında ambalajlama</b> gokcemt · 19 Şub 2019	Cevaplar: 0 Görüntüleme: 320	19 Şub 2019 gokcemt	
E	<b>ÇÖZÜLDÜ</b> Sd çıkışlar stoktan düşmüyor	Cevaplar: 3 Görüntüleme: 456	28 Ocak 2019 Esraezmeci	E
F	<b>ÇÖZÜLDÜ</b> Yardım	Cevaplar: 6 Görüntüleme: 2K	9 Ocak 2019 fred	F
	<b>MODULE</b> SAP Satış ve Dağıtım ( SD ) Faturalama Süreci Övünç DİNÇ · 6 Kas 2018	 Cevaplar: 4 Görüntüleme: 2K	29 Kas 2018 CEMOKA	

Bu site, içeriği kişiselleştirmek, deneyiminize uyarlamak ve kayıt olmanız durumunda giriş yapmanızı sağlamak için yasal düzenlemelere uygun çerezler (cookies) kullanır.  
Bu siteyi kullanmaya devam ederek, çerez kullanımına izin veriyorsunuz.

☒ Kabul Et

## Hakkımızda

SAP Ofis Türkiye'nin hiçbir kurum ve kuruluşla bağı bulunmamaktadır. Gönüllü SAP kullanıcıları tarafından kurulmuştur.

Bilgi paylaştıkça değer kazanır sözünü hatırlatarak aramızda bulunduğunuz ve destek olduğunuz için teşekkür ederiz.

## Destek ve İlkeler

 [SAP Eğitimi Kaynakları](#)

 [SAP Gui Versiyonları](#)

 [SAP Kullanıcı Soru-Cevap](#)

 [WhatsApp Destek](#)

## Çevrimiçi İstatistikleri

Çevrimiçi Kullanıcılar: 0

Çevrimiçi Ziyaretçiler: 46

Toplam Ziyaretçi: 46

Toplamlar, gizli ziyaretçiler içerebilir.