

Technical Articles



Paul McFarling

December 29, 2019 | 8 minute read

SAPUI5 and OData UploadCollection Example

4 16 10,382

Follow

Like

RSS Feed

Overview

In this post you will see an end to end example of implementing file upload/download with the UploadCollection control. This post is meant to help you get basic upload/download functionality working.

I have studied several blog posts, questions as well as personal experience to produce this post. I couldn't find a "one stop" example so I decided to put this together help the community get started.

Assumptions:

- You have an on premise SAP Netweaver Gateway system
- You have access to WebIDE and a connection to your Gateway System

- This was developed on an S4/1909 system using primarily ADT*.
- The front end was targeted for SAPUI5 Version 1.73*

**I have implemented a similar solution on an R/3 ABAP 7.50 System using SAPUI5 version 1.52 so it should work with very little to no changes on earlier versions.*

Basic Steps:

- Define a Z-Table to hold files data and attributes
- Use the gateway service builder (T-Code SEGW) to create the Entity Type/Entity Sets
- Redefine methods in DPC and MPC classes.
- Expose the Service on the Gateway
- Create a new SAPUI5 Application using WebIDE on SAP Cloud Platform
- Configure neo-app.json and manifest.json
- Add the UploadCollection to the View.
- Implement Supporting controller code



Create Z Table and OData Service:

1. Create a ztable to store the file and file attributes. This could easily be adapted to store the file in a content server or on the file system. Note:I have used a UUID as the Primary Key should this table be used in a draft enabled BOPF in the future.

```
@EndUserText.label : 'Files'
@AbapCatalog.enhancementCategory : #NOT_EXTENSIBLE
@AbapCatalog.tableCategory : #TRANSPARENT
@AbapCatalog.deliveryClass : #A
@AbapCatalog.dataMaintenance : #LIMITED
define table zfile {
    key client : abap.clnt not null;
    key id      : uuid not null;
    filename   : char255;
    sydate     : dats;
    sytime     : tims;
```

```
value      : xstringval;  
mimetype   : char100;  
  
}
```


2. Using T-Code SEGW on your business system, Create a new Project


 **Create Project** 

* Project:


* Description:

Attributes



* Project Type: 

Generation Strategy: 

Object Directory Entry

* Package: 

* Person Responsible:

 **Local Object** 

3. Enter a Name and give the Z-Table name from step 1. Make sure "Create Default Entity Set" is checked. Then, press Next

Create an Entity Type or Complex Type

* Name:

☒ Entity Type

☐ Complex Type

Import from ABAP Structure

* ABAP Structure:

☒ Create Default Entity Set

4. Select all the fields, and press next. (Selecting CLIENT is not necessary)



Wizard Step 2 of 3: Import from DDIC Structure

Select Parameter(s)



Data Source Parameter	Assign Structure	Description	Type	Length	Decimals	Import Search Help	Search Help	Output Length	Conversion Exit
<input checked="" type="checkbox"/> ZFILE	<input type="checkbox"/>		ZFILE			<input type="checkbox"/>			
<input type="checkbox"/> CLIENT	<input type="checkbox"/>		CLNT	3		<input type="checkbox"/>		3	
<input checked="" type="checkbox"/> ID	<input type="checkbox"/>	UUID	RAW	16		<input type="checkbox"/>		32	
<input checked="" type="checkbox"/> FILENAME	<input type="checkbox"/>	Char255	CHAR	255		<input type="checkbox"/>		255	
<input checked="" type="checkbox"/> SYDATE	<input type="checkbox"/>	Date	DATS	8		<input type="checkbox"/>		10	
<input checked="" type="checkbox"/> SYTIME	<input type="checkbox"/>	Field of type TIMS	TIMS	6		<input type="checkbox"/>		8	
<input checked="" type="checkbox"/> VALUE	<input type="checkbox"/>	Binary String	RSTR			<input type="checkbox"/>			
<input checked="" type="checkbox"/> MIMETYPE	<input type="checkbox"/>	Character 100	CHAR	100		<input type="checkbox"/>		100	

5. Select "ID" as the Key and give a meaningful name and label to the fields. Then, Press Finish.

Modify Entity Type

ABAP Name	Is Key	Type	Name	Label
ID	<input checked="" type="checkbox"/>	RAW	ID	ID
FILENAME	<input type="checkbox"/>	CHAR	FileName	File Name
SYDATE	<input type="checkbox"/>	DATS	Date	Date Created/Modified
SYTIME	<input type="checkbox"/>	TIMS	Time	Time Created/Modified
VALUE	<input type="checkbox"/>	RSTR	Value	Binary File Data
MIMETYPE	<input type="checkbox"/>	CHAR	MIMEType	MIME Type

6. Select the entity type you just created (File) from the tree hierarchy on the left. Check the check box in the “Media” column.

SAP Gateway Service Builder

More ▾

☐ > ZCONTRACTFILES
 ☐ > ZDSN_CONTRACTS_V4
 ☐ > ZFILE
 ☒ ZFILE_EX
 ☐ Data Model
 ☐ Entity Types
 ☐ File
 ☐ > Properties
 ☐ Navigation Properties

Entity Types

<input type="checkbox"/> Name	Base Type	Abstract	Label	Lab...	Semantics	Thing	Media
<input type="checkbox"/> File		<input type="checkbox"/>		T		<input type="checkbox"/>	<input checked="" type="checkbox"/>



7. Open the Entity Type Properties and set the check boxes per below

Name	Is Key	Edm Core Type	Precisio...	Scale	Max Ln...	Unit...	Creatab...	Updata...	Sortable	Nullable	Filt.	Lab
ID	<input checked="" type="checkbox"/>	Edm.Guid	0	0	0		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	ID
FileName	<input type="checkbox"/>	Edm.String	0	0	255		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	File
Date	<input type="checkbox"/>	Edm.DateTime	7	0	0		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Dat
Time	<input type="checkbox"/>	Edm.Time	0	0	0		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Tim
Value	<input type="checkbox"/>	Edm.Binary	0	0	0		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Bin
MIMEType	<input type="checkbox"/>	Edm.String	0	0	100		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	MIM

8. Open the “FileSet” Entity Set and set the check boxes per below.

Name	Entity Type Name	Label	Lab	Semantics	Creatab...	Updata...	Deletab...	Pageab...	Addr.ab...	Search...	Subscr...	Req. Filtr
FileSet	File		T		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

9. Press “Generate Runtime Objects” Icon. Take the defaults in the screen that pops up then, press the check box.

Model and Service Definition

Model Provider Class

* Class Name:

* Base Class Name:

Data Provider Class

☒ Generate Classes

* Class Name:

* Base Class Name:



Service Registration

* Technical Model Name:


* Model Version:

* Technical Service Name:

* Service Version:



10. in ADT (or SE24) navigate to the generated Model Provider Class i.e. the *MPC_EXT class. Redefine the “DEFINE” Method. with the code below. Hint: Pressing <CTRL>+<SPACE> in ADT will allow you to select the DEFINE method to redefine.



```
METHOD define.
    super->define( ).

DATA: lo_entity TYPE REF TO /iwbsp/if_mgw_odata_entity_typ,

      lo_property TYPE REF TO /iwbsp/if_mgw_odata_property.

lo_entity = model->get_entity_type( iv_entity_name = 'File' ).

IF lo_entity IS BOUND.

    lo_property = lo_entity->get_property( iv_property_name = 'FileName' ).

    lo_property->set_as_title( ).
```



```

        lo_property = lo_entity->get_property( iv_property_name = 'MIMEType').

        lo_property->set_as_content_type( ).

    ENDIF.
ENDMETHOD.

```

11. Now open the generated Data Provider Class i.e. *_DPC_EXT. There are several methods here to redefine.

i. Redefine FILESET_GET_ENTITY with the below code

```

method fileset_get_entity.
    DATA lw_pk TYPE zfile.
    " DO. ENDDO.
    READ TABLE it_key_tab INTO DATA(lw_key_tab) WITH KEY name = 'ID'.
    IF sy-subrc = 0.
        SELECT single id, filename, sydate, sytime, mimetype from zfile into CORRESPONDING FIE
    ENDIF.
    er_entity = lw_pk.
endmethod.

```

ii. Redefine FILESET_GET_ENTITYSET with the below code.

```

METHOD fileset_get_entityset.
    DATA:
        it_final    TYPE STANDARD TABLE OF zfile,
        lt_filters  TYPE                                /iwbep/t_mgw_select_option,
        ls_filter   TYPE                                /iwbep/s_mgw_select_option,
        ls_so       TYPE                                /iwbep/s_cod_select_option,
        p_name      TYPE c LENGTH 15.

    SELECT

```

```

        id
        filename
        sydate
        sytime
        "value
        mimetype

FROM zfile
      INTO CORRESPONDING FIELDS OF TABLE et_entityset.
ENDMETHOD.

```

- iii. Redefine method /IWBEP/IF_MGW_APPL_SRV_RUNTIME~CREATE_STREAM. Note that there is a call to FILESET_GET_ENTITY. This is required or the upload will succeed but will return an HTTP 500 error of “Service provider did not return any business data”

```

METHOD /iwbsp/if_mgw_appl_srv_runtime~create_stream.
  DATA: lw_file TYPE zfile.

  lw_file-id = cl_system_uuid=>create_uuid_x16_static( ).
  lw_file-filename = iv_slug.
  lw_file-value     = is_media_resource-value.
  lw_file-mimetype = is_media_resource-mime_type.
  lw_file-sydate   = sy-datum.
  lw_file-sytime   = sy-uzeit.

  INSERT INTO zfile VALUES lw_file.

TRY.
  DATA : ls_key_tab TYPE /iwbsp/s_mgw_name_value_pair,

          lt_key_tab TYPE /iwbsp/t_mgw_name_value_pair.

  DATA: ls_filemetadata TYPE zfile.
  DATA: lw_key_tab LIKE LINE OF lt_key_tab.

```

```

" data: lt_key_tab TYPE /iwbep/t_mgw_name_value_pair.

lw_key_tab-name = 'ID'.
lw_key_tab-value = lw_file-id.
APPEND lw_key_tab TO lt_key_tab.


CALL METHOD fileset_get_entity
  EXPORTING
    iv_entity_name      = iv_entity_name
    iv_entity_set_name  = iv_entity_set_name
    iv_source_name      = iv_source_name
    it_key_tab          = lt_key_tab
*    io_request_object   =
*    io_tech_request_context =
    it_navigation_path  = it_navigation_path
  IMPORTING
    er_entity           = ls_filemetadata.
*    es_response_context =

copy_data_to_ref(

EXPORTING

is_data = ls_filemetadata

CHANGING

cr_data = er_entity ).

"do. enddo.
CATCH /iwbep/cx_mgw_busi_exception.
CATCH /iwbep/cx_mgw_tech_exception.
ENDTRY.
ENDMETHOD.

```

iv. Redefine /IWBEP/IF_MGW_APPL_SRV_RUNTIME~GET_STREAM.

```
method /IWBEP/IF_MGW_APPL_SRV_RUNTIME~GET_STREAM.  
  DATA : ls_stream TYPE ty_s_media_resource,  
  
          ls_upld    TYPE zfile.  
  
  DATA: lv_id TYPE zfile-id.  
  
  FIELD-SYMBOLS:<fs_key> TYPE /iwbsp/s_mgw_name_value_pair.  
  DATA ls_header TYPE ihttpnvp.  
  ls_header-name = 'Content-Disposition'.  
  
  READ TABLE it_key_tab ASSIGNING <fs_key> with key name = 'ID'.  
  lv_id = <fs_key>-value.  
  SELECT SINGLE * FROM zfile INTO ls_upld WHERE id = lv_id.  
  IF ls_upld IS NOT INITIAL.  
    ls_stream-value = ls_upld-value.  
    ls_stream-mime_type = ls_upld-mimetype.  
    ls_header-value = 'outline; filename="' && ls_upld-filename && '";'.  
    set_header( is_header = ls_header ).  
  
    copy_data_to_ref( EXPORTING is_data = ls_stream    CHANGING  cr_data = er_stream ).  
  ENDIF.  
endmethod.
```

v. Additional methods from interface /IWBEP/IF_MGW_APPL_SRV_RUNTIME can be redefined. Such as UPDATE_STREAM etc.. I will limit this post to just File creation and retrieval.

Add the new service to the Gateway System:

1. On the gateway system run T-Code /n/iwfnd/maint_service

2. Click “Add Service”
3. Select the System Alias for the system where the OData service was created.
4. Enter the Odata Service name in “Technical Service Name”
5. Click “Get Services”

✓

🔗 Get Services

Cancel

More ▾

Filter

System Alias	SV7CLNT100
Technical Service Name	ZFILE_EX_SRV
External Service Name	

Select Backend Services

🔍

☰

☰

🔍

🔍+

🔼

▾

⬇ ▾

📊

⊕ Add Selected Services

	Type	Technical Service Name
<input type="checkbox"/>	BEP	<u>ZFILE_EX_SRV</u>

6. Select the Service and click “Add Selected Services”
7. In the pop up, enter a package assignment and accept the defaults and press the check box.
8. Press back, you should see the service listed it. Select it and chose “Gateway Service Client”
 - i. You can test out the service here, there is ample documentation on the Gateway Service Client so I will not go into it here
9. At this point the service is now ready to be consumed in a UI5 App.

Creating the SAPUI5 application via WebIDE on SAP Cloud Platform

1. Login to your SAP Cloud account and navigate to WebIDE
2. Click on File->New->Project From Template
3. Select SAPUI5 Application
4. Give the Project a name "FileUpload" and a namespace i.e "test" and press Next
5. Keep the default XML View type and give the new view a name (or accept the default) Then press "Finish"

Initial View Details

View Type*

XML



View Name

File

6. Expand the project tree to FileUpload->webapp->View and select your view "File.view.xml"
7. Insert the following code between the <content> and </content> tags to add the UploadCollection to the view.

```
<UploadCollection
  maximumFilenameLength="55"
  maximumFileSize="1000"
  fileDeleted="onFileDeleted"
  filenameLengthExceed="onFilenameLengthExceed"
  fileRenamed="onFileRenamed"
  fileSizeExceed="onFileSizeExceed"
  id="UploadCollection"
  change="onChange"
  mode="SingleSelectMaster"
  beforeUploadStarts="onBeforeUploadStarts"
  items="{path: '/FileSet'}" multiple="true"
  uploadUrl="/sap/opu/odata/sap/ZFILE_EX_SRV/FileSet"
  uploadComplete="onUploadComplete" noDataText="No files found."
  noDataDescription="Drop files to upload, or use the &quot;+&quot; button.">
<items>
  <UploadCollectionItem
    documentId="{ID}"
    fileName="{FileName}"
```

```

        url="/sap/opu/odata/sap/ZFILE_EX_SRV/FileSet(guid'{ID}')/$value"
        mimeType="{MIMEType}"
        enableEdit="false"
        enableDelete="false"
        visibleDelete="false"
        visibleEdit="false">
    </UploadCollectionItem>
</items>
</UploadCollection>

```

8. In the controller folder open File.controller.js
 - i. Add the following code to the init method

```

onInit: function () {
    var oUploadCollection = this.getView().byId('UploadCollection');
    oUploadCollection.setUploadUrl("/sap/opu/odata/sap/ZFILE_EX_SRV/FileSet");
    var oModel = new sap.ui.model.odata.ODataModel("/sap/opu/odata/sap/ZFILE_EX_SRV",false);
    this.getView().setModel(oModel);
}

```

- ii. Create the onBeforeUploadStarts method

```

onBeforeUploadStarts: function (oEvent) {

    var oCustomerHeaderSlug = new sap.m.UploadCollectionParameter({
        name: "slug",
        value: oEvent.getParameter("fileName")
    });
    oEvent.getParameters().addHeaderParameter(oCustomerHeaderSlug);

    var oModel = this.getView().getModel();

    oModel.refreshSecurityToken();
}

```

```

        var oHeaders = oModel.oHeaders;

        var sToken = oHeaders['x-csrf-token'];

        var oCustomerHeaderToken = new sap.m.UploadCollectionParameter({

            name: "x-csrf-token",

            value: sToken

        });
        oEvent.getParameters().addHeaderParameter(oCustomerHeaderToken);

    }

```

iii. Create the onUploadComplete method

```

onUploadComplete: function(oEvent){
    this.getView().getModel().refresh();
}

```

9. For the WebIDE environment you must add a route entry in neo-app.json. This should reference a configured destination on your cloud account to your gateway system. Setting up the Cloud Connector and destinations is outside the scope of this blog. Below is an example entry needed in the “routes” array in the neo-app.json file

```

{
    "path": "/sap/opu/odata",
    "target": {
        "type": "destination",
        "name": "SG7_OnPremise",
        "entryPath": "/sap/opu/odata"
    },

```




```
    "description": "SG7_OnPremise"
  }
}
```

10. Now setup a `dataSources` attribute of `"sap.app"` in `manifest.json`. The only the `"dataSources"` entry should be added. the rest of the code is given for context. (This step isn't 100% necessary for this example)

```
"_version": "1.12.0",
"sap.app": {
  "id": "dsn.File",
  "type": "application",
  "i18n": "i18n/i18n.properties",
  "applicationVersion": {
    "version": "1.0.0"
  },
  "title": "{{appTitle}}",
  "description": "{{appDescription}}",
  "sourceTemplate": {
    "id": "ui5template.basicSAPUI5ApplicationProject",
    "version": "1.40.12"
  },
  "dataSources": {
    "mainService": {
      "uri": "/sap/opu/odata/sap/ZFILE_EXT_SRV/",
      "type": "OData",
      "settings": {
        "annotations": [
          "ZFILE_EXT_ANNO_MDL"
        ],
        "localUri": "localService/metadata.xml"
      }
    },
    "ZFILE_EXT_ANNO_MDL": {
      "uri": "/sap/opu/odata/IWFND/CATALOGSERVICE;v=2/Annotations(TechnicalName='ZFILE_
      "type": "ODataAnnotation",
    }
  }
}
```

```
    "settings": {  
      "localUri": "localService/ZFILE_EXT_ANNO_MDL.xml"  
    }  
  }  
},
```

11. Run the project via index.html and you should be able to upload and download files



Conclusion

This blog is intended to give a bare minimum to get you up and running uploading and downloading files. There are numerous improvements that could be made. I welcome all suggestions for improvement or questions. Thanks for reading.

Assigned tags

SAPUI5

NW ABAP Gateway (OData)

SAP Fiori

SAP Gateway

SAP Web IDE

CREATE_STREAM

GET_STREAM

[View more...](#) >

Similar Blog Posts

[New E2E Tutorial: Gain Hands-on Developer Experience with SAPUI5 and SAP NetWeaver Gateway](#)

By Bertram Ganz Dec 10, 2012

[Navigation and Routing Simple Example SAPUI5](#)

By Sk Manirujjaman Feb 20, 2016

[SAPUI5 Application Consuming OData service with SAP WEB IDE](#)

By rajeesh o Apr 13, 2016

Related Questions



[How to send uploadcollection attached documents to sap using odata in sapui5 project?](#)

By DURAI VENKATESH Jan 05, 2017

[Uploadcollection Unable to load existing documents from Odata](#)

By Srinivasu Y Feb 27, 2020

[Unable to set UploadUrl of uploadcollection in code](#)

By Lesedi Diamond Damane Aug 30, 2016

4 Comments

You must be [Logged on](#) to comment or reply to a post.



Mahesh Kumar Palavalli

December 30, 2019 at 4:59 am

Good End-End example Paul !!! Couple of small suggestions.

1. You can use odata v2 model instead of odata model as it is deprecated.
2. As I can see that you are using upload collection, you can go with the [attachment service](#) which will make the development a lot easier (Assuming that you are working in s4hana system, it should be available) for older ones your's is a good approach.

Thanks,

Mahesh

Like 1 | Share



Paul McFarling | Blog Post Author

December 30, 2019 at 5:18 pm

Thanks! I was unaware of the attachment service. I do intend to use this with a draft enabled list report so it appears the attachment service might work better.

Like 1 | Share



pavan kumar Mallipeddi

May 18, 2020 at 10:35 am

Hi [Paul McFarling](#)

How can we use the MIME type and Value in back end to attach the documents to Email.

Thanks,

Pavan

Like 0 | Share

Danil Badykshanov



August 25, 2021 at 3:41 pm

I found a little bug.

It is better to use the following code, otherwise there will be an error

```
var oCustomerHeaderSlug = new sap.m.UploadCollectionParameter({  
  name: "slug",  
  value: encodeURIComponent(oEvent.getParameter("fileName"))  
});
```

Like 0 | Share

Find us on

Privacy	Terms of Use
Legal Disclosure	Copyright
Trademark	Cookie Preferences
Newsletter	Support