



SW1

SW1 VALN CONFIG



VLAN	Name	Status	Ports
1	default	active	Et0/3
10	HR	active	Et0/0
20	SALES	active	Et0/1
1002	fddi-default	act/unsup	
1003	token-ring-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trnet-default	act/unsup	

SW1#sh int trunk

Port	Mode	Encapsulation	Status	Native vlan
Et0/2	on	802.1q	trunking	1

Port	Vlans allowed on trunk
Et0/2	1-4094

Port	Vlans allowed and active in management domain
Et0/2	1,10,20

Port	Vlans in spanning tree forwarding state and not pruned
Et0/2	1,10,20

SW1#

VLAN	Name	Status	Ports
1	default	active	Et0/3
10	HR	active	Et0/0
20	SALES	active	Et0/1
1002	fddi-default	act/unsup	
1003	token-ring-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trnet-default	act/unsup	

SW2#sh int trunk

Port	Mode	Encapsulation	Status	Native vlan
Et0/2	on	802.1q	trunking	1

Port	Vlans allowed on trunk
Et0/2	1-4094

Port	Vlans allowed and active in management domain
Et0/2	1,10,20

Port	Vlans in spanning tree forwarding state and not pruned
Et0/2	1,10,20

SW2#

Network Tasks

- Create a new connection
- Set up a home or office network
- Change Windows Firewall settings
- Disable this device
- Repair this connection
- Rename this connection
- View status of connection
- Change settings of connection

Other Places

- Control Panel
- My Network Places
- My Documents
- My Computer

Details

Local Area Connection
LAN or High-Speed Internet

C:\WINDOWS\system32\cmd.exe

```
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>
C:\Documents and Settings\user>ping 10.0.0.10
```

Pinging 10.0.0.10 with 32 bytes of data:

```
Reply from 10.0.0.10: bytes=32 time=1ms TTL=128
Reply from 10.0.0.10: bytes=32 time=1ms TTL=128
Reply from 10.0.0.10: bytes=32 time=1ms TTL=128
Reply from 10.0.0.10: bytes=32 time=1ms TTL=128
```

Ping statistics for 10.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 1ms, Average = 1ms

```
C:\Documents and Settings\user>
```

Properties

Disable

Close

PING 10.10 FROM 10.20