



SPANNING TREE PROTOCOL







SW1



```
SW1#sh spanning-tree
```

```
VLAN0001
```

```
Spanning tree enabled protocol ieee
```

```
Root ID      Priority      32769
             Address      aabb.cc00.0100
             Cost        100
             Port        1 (Ethernet0/0)
             Hello Time   2 sec  Max Age 20 sec  Forward Delay 15 sec
```

```
Bridge ID    Priority      32769  (priority 32768 sys-id-ext 1)
             Address      aabb.cc00.0400
             Hello Time    2 sec  Max Age 20 sec  Forward Delay 15 sec
             Aging Time    15   sec
```

Interface	Role	Sts	Cost	Prio.Nbr	Type
Et0/0	Root	FWD	100	128.1	P2p
Et0/1	Desg	FWD	100	128.2	P2p

```
SW1#
```

SW3#sh spanning-tree

VLAN0001

Spanning tree enabled protocol ieee

Root ID Priority 32769
 Address aabb.cc00.0100
 Cost 100
 Port 1 (Ethernet0/0)
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 32769 (priority 32768 sys-id-ext 1)
 Address aabb.cc00.0500
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300 sec

Interface	Role	Sts	Cost	Prio.Nbr	Type
Et0/0	Root	FWD	100	128.1	P2p
Et0/1	Altn	BLK	100	128.2	P2p

SW3#

```
SW5#sh spanning-tree
```

```
VLAN0001
```

```
Spanning tree enabled protocol ieee
```

```
Root ID      Priority      32769
```

```
Address      aabb.cc00.0100
```

```
This bridge is the root
```

```
Hello Time    2 sec  Max Age 20 sec  Forward Delay 15 sec
```

```
Bridge ID    Priority      32769  (priority 32768 sys-id-ext 1)
```

```
Address      aabb.cc00.0100
```

```
Hello Time    2 sec  Max Age 20 sec  Forward Delay 15 sec
```

```
Aging Time    300 sec
```

```
Interface      Role Sts Cost      Prio.Nbr Type
```

```
-----
```

Interface	Role	Sts	Cost	Prio.Nbr	Type
Et0/0	Desg	FWD	100	128.1	P2p
Et0/1	Desg	FWD	100	128.2	P2p
Et0/2	Desg	FWD	100	128.3	P2p
Et0/3	Desg	FWD	100	128.4	P2p

```
SW5#
```



SW2



```
SW2#sh spanning-tree
```

```
VLAN0001
```

```
Spanning tree enabled protocol ieee
```

```
Root ID      Priority      32769
```

```
Address      aabb.cc00.0100
```

```
Cost         100
```

```
Port         1 (Ethernet0/0)
```

```
Hello Time   2 sec  Max Age 20 sec  Forward Delay 15 sec
```

```
Bridge ID    Priority      32769  (priority 32768 sys-id-ext 1)
```

```
Address      aabb.cc00.0200
```

```
Hello Time   2 sec  Max Age 20 sec  Forward Delay 15 sec
```

```
Aging Time   300 sec
```

```
Interface      Role Sts Cost      Prio.Nbr Type
```

```
-----
```

Interface	Role	Sts	Cost	Prio.Nbr	Type
Et0/0	Root	FWD	100	128.1	P2p
Et0/1	Desg	FWD	100	128.2	P2p
Et0/2	Desg	FWD	100	128.3	P2p

```
SW2#
```

SW4#sh spanning-tree

VLAN0001

Spanning tree enabled protocol ieee

Root ID Priority 32769
 Address aabb.cc00.0100
 Cost 100
 Port 1 (Ethernet0/0)
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 32769 (priority 32768 sys-id-ext 1)
 Address aabb.cc00.0300
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300 sec

Interface	Role	Sts	Cost	Prio.Nbr	Type
Et0/0	Root	FWD	100	128.1	P2p
Et0/1	Altn	BLK	100	128.2	P2p
Et0/2	Altn	BLK	100	128.3	P2p

SW4#