

# HTML Tag List With Description

NEW - New tag introduce in HTML5

REMOVE - Not Support in HTML5

NEW/REMOVE - New Tag introduce in HTML5, But now yet support in HTML5

Tag	Description	In HTML5?
<b>&lt;!--...--&gt;</b> (html_comment_tag.php)	Describe a comment text in the source code	
<b>&lt;!doctype&gt;</b> (html_doctype_tag.php)	Defines a document type	
<b>&lt;a&gt;</b> (html_a_tag.php)	Specific a anchor (Hyperlink) Use for link in internal/external web documents.	
<b>&lt;abbr&gt;</b> (html_abbr_tag.php)	Describes an abbreviation (acronyms)	
<b>&lt;acronym&gt;</b> (html_acronym_tag.php)	Describes an acronyms	REMOVE
<b>&lt;address&gt;</b> (html_address_tag.php)	Describes an address information	
<b>&lt;applet&gt;</b> (html_applet_tag.php)	Embedding an applet in HTML document	REMOVE
<b>&lt;area&gt;</b> (html_area_tag.php)	Defines an area in an image map	
<b>&lt;article&gt;</b> (html_article_tag.php)	Defines an article	NEW
<b>&lt;aside&gt;</b> (html_aside_tag.php)	Describes contain set(or write) on aside place in page contain	NEW
<b>&lt;audio&gt;</b> (html_audio_tag.php)	Specific audio content	NEW
<b>&lt;b&gt;</b> (html_b_tag.php)	Specific text weight bold	
<b>&lt;base&gt;</b> (html_base_tag.php)	Define a base URL for all the links with in a web page	
<b>&lt;basefont&gt;</b> (html_basefont_tag.php)	Describes a default font color, size, face in a document	REMOVE
<b>&lt;bb&gt;</b> (html_bb_tag.php)	Define browser command, that command invoke as per client action	NEW/ REMOVE

<b>&lt;bdo&gt;</b> (html_bdo_tag.php)	Specific direction of text display	
<b>&lt;big&gt;</b> (html_big_tag.php)	Defines a big text	REMOVE
<b>&lt;blockquote&gt;</b> (html_blockquote_tag.php)	Specifies a long quotation	
<b>&lt;body&gt;</b> (html_body_tag.php)	Defines a main section(body) part in HTML document	
<b>&lt;br /&gt;</b> (html_br_tag.php)	Specific a single line break	
<b>&lt;button&gt;</b> (html_button_tag.php)	Specifies a press/push button	
<b>&lt;canvas&gt;</b> (html_canvas_tag.php)	Specifies the display graphics on HTML web documment	NEW
<b>&lt;caption&gt;</b> (html_caption_tag.php)	Define a table caption	
<b>&lt;center&gt;</b> (html_center_tag.php)	Specifies a text is display in center align	REMOVE
<b>&lt;cite&gt;</b> (html_cite_tag.php)	Specifies a text citation	
<b>&lt;code&gt;</b> (html_code_tag.php)	Specifies computer code text	
<b>&lt;col&gt;</b> (html_col_tag.php)	Specifies a each column within a <colgroup> element in table	
<b>&lt;colgroup&gt;</b> (html_colgroup_tag.php)	Defines a group of one or more columns inside table	
<b>&lt;command&gt;</b> (html_command_tag.php)	Define a command button, invoke as per user action	NEW
<b>&lt;datagrid&gt;</b> (html_datagrid_tag.php)	Define a represent data in datagrid either list wise or tree wise	NEW/ REMOVE
<b>&lt;datalist&gt;</b> (html_datalist_tag.php)	Define a list of pre-defined options surrounding <input> tag	NEW
<b>&lt;dd&gt;</b> (html_dd_tag.php)	Defines a definition description in a definition list	
<b>&lt;del&gt;</b> (html_del_tag.php)	Specific text deleted in web document	
<b>&lt;details&gt;</b> (html_details_tag.php)	Define a additional details hide or show as per user action	NEW
<b>&lt;dfn&gt;</b> (html_dfn_tag.php)	Define a definition team	

<b>&lt;dialog&gt;</b> (html_dialog_tag.php)	Define a chat conversation between one or more person	NEW/ REMOVE
<b>&lt;dir&gt;</b> (html_dir_tag.php)	Define a directory list	REMOVE
<b>&lt;div&gt;</b> (html_div_tag.php)	Define a division part	
<b>&lt;dl&gt;</b> (html_dl_tag.php)	Define a definition list	
<b>&lt;dt&gt;</b> (html_dt_tag.php)	Define a definition team	
<b>&lt;em&gt;</b> (html_em_tag.php)	Define a text is emphasize format	
<b>&lt;embed&gt;</b> (html_embed_tag.php)	Define a embedding external application using a relative plug-in	NEW
<b>&lt;eventsource&gt;</b> (html_eventsource_tag.php)	Defines a source of event generates to remote server	NEW/ REMOVE
<b>&lt;fieldset&gt;</b> (html_fieldset_tag.php)	Defines a grouping of related form elements	
<b>&lt;figcaption&gt;</b> (html_figcaption_tag.php)	Represents a caption text corresponding with a figure element	NEW
<b>&lt;figure&gt;</b> (html_figure_tag.php)	Represents self-contained content corresponding with a <figcaption> element	NEW
<b>&lt;font&gt;</b> (html_font_tag.php)	Defines a font size, font face and font color for its text	REMOVE
<b>&lt;footer&gt;</b> (html_footer_tag.php)	Defines a footer section containing details about the author, copyright, contact us, sitemap, or links to related documents.	NEW
<b>&lt;form&gt;</b> (html_form_tag.php)	Defines a form section that having interactive input controls to submit form information to a server.	
<b>&lt;frame&gt;</b> (html_frame_tag.php)	Defines frame window.	REMOVE
<b>&lt;frameset&gt;</b> (html_frameset_tag.php)	Used to holds one or more <frame> elements.	REMOVE
<b>&lt;h1&gt; to &lt;h6&gt;</b> (html_h1_to_h6_tag.php)	Defines a Headings level from 1 to 6 different sizes.	
<b>&lt;head&gt;</b> (html_head_tag.php)	Defines header section of HTML document.	

<b>&lt;header&gt;</b> (html_header_tag.php)	Defines as a container that hold introductory content or navigation links.	NEW
<b>&lt;hgroup&gt;</b> (html_hgroup_tag.php)	Defines the heading of a section that hold the h1 to h6 tags.	NEW/ REMOVE
<b>&lt;hr /&gt;</b> (html_hr_tag.php)	Represent a thematic break between paragraph-level tags. It is typically draw horizontal line.	
<b>&lt;html&gt;</b> (html_html_tag.php)	Define a document is a HTML markup language	
<b>&lt;i&gt;</b> (html_i_tag.php)	Defines a italic format text	
<b>&lt;iframe&gt;</b> (html_iframe_tag.php)	Defines a inline frame that embedded external content into current web document.	
<b>&lt;img&gt;</b> (html_img_tag.php)	Used to insert image into a web document.	
<b>&lt;input&gt;</b> (html_input_tag.php)	Define a get information in selected input	
<b>&lt;ins&gt;</b> (html_ins_tag.php)	Used to indicate text that is inserted into a page and indicates changes to a document.	
<b>&lt;isindex&gt;</b> (html_isindex_tag.php)	Used to create a single line search prompt for querying the contents of the document.	REMOVE
<b>&lt;kbd&gt;</b> (html_kbd_tag.php)	Used to identify text that are represents keyboard input.	
<b>&lt;keygen&gt;</b> (html_keygen_tag.php)	Used to generate signed certificate, which is used to authenticate to services.	NEW/ REMOVE
<b>&lt;label&gt;</b> (html_label_tag.php)	Used to caption a text label with a form <input> element.	
<b>&lt;legend&gt;</b> (html_legend_tag.php)	Used to add a caption (title) to a group of related form elements that are grouped together into the <fieldset> tag.	
<b>&lt;li&gt;</b> (html_li_tag.php)	Define a list item either ordered list or unordered list.	
<b>&lt;link&gt;</b> (html_link_tag.php)	Used to load an external stylesheets into HTML document.	
<b>&lt;map&gt;</b> (html_map_tag.php)	Defines an clickable image map.	
<b>&lt;mark&gt;</b> (html_mark_tag.php)	Used to highlighted (marked) specific text.	NEW

<b>&lt;menu&gt;</b> (html_menu_tag.php)	Used to display a unordered list of items/menu of commands.	
<b>&lt;meta&gt;</b> (html_meta_tag.php)	Used to provide structured metadata about a web page.	
<b>&lt;meter&gt;</b> (html_meter_tag.php)	Used to measure data within a given range.	NEW
<b>&lt;nav&gt;</b> (html_nav_tag.php)	Used to defines group of navigation links.	NEW
<b>&lt;noframes&gt;</b> (html_noframes_tag.php)	Used to provide a fallback content to the browser that does not support the <frame> element.	REMOVE
<b>&lt;noscript&gt;</b> (html_noscript_tag.php)	Used to provide an fall-back content to the browser that does not support the JavaScript.	
<b>&lt;object&gt;</b> (html_object_tag.php)	Used to embedded objects such as images, audio, videos, Java applets, and Flash animations.	
<b>&lt;ol&gt;</b> (html_ol_tag.php)	Defines an ordered list of items.	
<b>&lt;optgroup&gt;</b> (html_optgroup_tag.php)	Used to create a grouping of options, the related options are grouped under specific headings.	
<b>&lt;option&gt;</b> (html_option_tag.php)	Represents option items within a <b>&lt;select&gt;</b> , <b>&lt;optgroup&gt;</b> or <b>&lt;datalist&gt;</b> element.	
<b>&lt;output&gt;</b> (html_output_tag.php)	Used for representing the result of a calculation.	NEW
<b>&lt;p&gt;</b> (html_p_tag.php)	Used to represents a paragraph text.	
<b>&lt;param&gt;</b> (html_param_tag.php)	Provides parameters for embedded <b>object</b> element.	
<b>&lt;pre&gt;</b> (html_pre_tag.php)	Used to represents preformatted text.	
<b>&lt;progress&gt;</b> (html_progress_tag.php)	Represents the progress of a task.	NEW
<b>&lt;q&gt;</b> (html_q_tag.php)	Represents the short quotation.	
<b>&lt;rp&gt;</b> (html_rp_tag.php)	Used to provide parentheses around fall-back content to the browser that does not support the ruby annotations.	NEW
<b>&lt;rt&gt;</b> (html_rt_tag.php)	Specifies the ruby text of ruby annotation.	NEW

<b>&lt;ruby&gt;</b> (html_ruby_tag.php)	Used to represents a ruby annotation.	NEW
<b>&lt;s&gt;</b> (html_s_tag.php)	Text display in strikethrough style.	
<b>&lt;samp&gt;</b> (html_samp_tag.php)	Represents text that should be interpreted as sample output from a computer program.	
<b>&lt;script&gt;</b> (html_script_tag.php)	Defines client-side JavaScript.	
<b>&lt;section&gt;</b> (html_section_tag.php)	Used to divide a document into number of different generic section.	NEW
<b>&lt;select&gt;</b> (html_select_tag.php)	Used to create a drop-down list.	
<b>&lt;small&gt;</b> (html_small_tag.php)	Used to makes the text one size smaller.	
<b>&lt;source&gt;</b> (html_source_tag.php)	Used to specifies multiple media resources.	NEW
<b>&lt;span&gt;</b> (html_span_tag.php)	Used to grouping and applying styles to inline elements.	
<b>&lt;strike&gt;</b> (html_strike_tag.php)	Represents strikethrough text.	REMOVE
<b>&lt;strong&gt;</b> (html_strong_tag.php)	Represents strong emphasis greater important text.	
<b>&lt;style&gt;</b> (html_style_tag.php)	Used to add CSS style to an HTML document.	
<b>&lt;sub&gt;</b> (html_sub_tag.php)	Represents inline subscript text.	
<b>&lt;sup&gt;</b> (html_sup_tag.php)	Represents inline superscript text.	
<b>&lt;table&gt;</b> (html_table_tag.php)	Used to defines a table in an HTML document.	
<b>&lt;tbody&gt;</b> (html_tbody_tag.php)	Used for grouping table rows.	
<b>&lt;td&gt;</b> (html_td_tag.php)	Used for creates standard data cell in HTML table.	
<b>&lt;textarea&gt;</b> (html_textarea_tag.php)	Create multi-line text input.	
<b>&lt;tfoot&gt;</b> (html_tfoot_tag.php)	Used to adding a footer to a table that containing summary of the table data.	

<b>&lt;th&gt;</b> (html_th_tag.php)	Used for creates header of a group of cell in HTML table.	
<b>&lt;thead&gt;</b> (html_thead_tag.php)	Used to adding a header to a table that containing header information of the table.	
<b>&lt;time&gt;</b> (html_time_tag.php)	Represents the date and/or time in an HTML document.	NEW
<b>&lt;title&gt;</b> (html_title_tag.php)	Represents title to an HTML document.	
<b>&lt;tr&gt;</b> (html_tr_tag.php)	Defines a row of cells in a table.	
<b>&lt;track&gt;</b> (html_track_tag.php)	Represents text tracks for both the <b>&lt;audio&gt;</b> and <b>&lt;video&gt;</b> tags.	NEW
<b>&lt;tt&gt;</b> (html_tt_tag.php)	Represents teletype text.	REMOVE
<b>&lt;u&gt;</b> (html_u_tag.php)	Represents underlined text.	
<b>&lt;ul&gt;</b> (html_ul_tag.php)	Defines an unordered list of items.	
<b>&lt;var&gt;</b> (html_var_tag.php)	Represents a variable in a computer program or mathematical equation.	
<b>&lt;video&gt;</b> (html_video_tag.php)	Used to embed video content.	NEW
<b>&lt;wbr&gt;</b> (html_wbr_tag.php)	Defines a word break opportunity in a long string of text.	NEW

*« Previous*

*Next »*