

DIGITAL WALLET AND PAYMENT GATEWAY SIMULATOR

Secure Software Engineering End Semester Capstone Laboratory Report

Course Code: 24CYS401 — Secure Software Engineering

Candidate Name / Student ID	Sathvik Valivety (GitHub: sathvikvalivety)
Degree & Program	B.Tech Computer Science and Engineering (Cyber Security)
Institution / Department	Amrita Vishwa Vidyapeetham, Department of Cyber Security
Examination / Semester	24CYS401 End Semester Laboratory Examination
Academic Year / Date	October 2026 Academic Session 2026–2027
Repository URL	https://github.com/sathvikvalivety/digital-wallet-and-payment-gateway-simulator

Executive Summary

The Digital Wallet and Payment Gateway Simulator (DWPG) is an end-to-end, high-integrity financial transaction simulator engineered in compliance with rigorous secure software engineering standards for the 24CYS401 End Semester Laboratory Examination. The primary objective is to simulate a complete electronic payment ecosystem —spanning user onboarding, credential issuance, digital wallet provisioning, atomic top-ups, merchant registration, idempotent checkout settlement, stateful refunds, and immutable double-entry ledger bookkeeping —while systematically resolving critical distributed financial security challenges: race condition double-spending, replay attacks, parameter tampering, broken authorization, and forensic audit evasion.



Curricular Examination Compliance & Evidence Standard

This report documents complete empirical evidence for all 16 prescribed phases of the Secure Software Engineering examination. In strict accordance with curricular guidelines, all 24 architectural, UML, data flow, and threat diagrams were authored as editable draw.io sources (docs/diagrams/drawio/) and exported via the official draw.io CLI. 15 real Playwright UI screenshots, 18 authentic Jira figures, 7 SonarQube SAST screenshots, and verified Kubernetes runtime workloads are embedded as immutable proof. Zero synthetic or fabricated figures are included.

Core System Metrics at a Glance

Engineering Dimension	Implemented Specification	Empirical Verification Status
Target Platform	Java 21 LTS, Spring Boot 3.3.4, React 18, MariaDB 10.11	Operational on localhost:8080 & localhost:3000
Containerization & K8s	Multi-stage Docker, Minikube Namespace 'dwpg'	Non-root UID 10001, NetworkPolicy isolate-mariadb active
Scrum Cadence	2 Sprints (52 Story Points committed, 47 delivered)	Jira Board #101, 13 user stories, defect DEF-001 resolved
Automated Test Suite	42 Tests: 25 JUnit 5 + 9 REST Integration + 8 Security	100% Passed (0 Failures, 0 Errors) in 4.281s
SAST Quality Gate	SonarQube 9.9.8 LTS (dwpg-simulator)	Quality Gate: OK 0 Vulnerabilities, 0 Hotspots, 0 Bugs, 62.6% Coverage
Draw.io Source Diagrams	24 Diagrams authored in Draw.io / Diagrams.net	All 24 available in docs/diagrams/drawio/, PNG & SVG exported

1. Agile Process and Development Approach (Phase 1)

1.1 Agile Approach and Justification

The project followed an agile Scrum framework executed across two 2-week timeboxed sprints. Scrum was selected over traditional Waterfall because modern financial gateway engineering is characterized by evolving attack vectors, high concurrency risks, and iterative integration requirements. By organizing development into rapid cadences with mandatory security acceptance criteria embedded into the Definition of Done (DoD), the engineering team could continuously inspect and adapt security postures—catching critical concurrency race conditions early and refactoring before system deployment.

1.2 Agile Manifesto Principles Mapped to DWPG

The development lifecycle systematically operationalized five core principles of the Agile Manifesto:

- **Principle 1:** 1. Working Software Over Comprehensive Documentation: Rather than relying solely on theoretical threat models, functional software increments (such as wallet funding, atomic checkout settlement, and replay traps) were deployed and verified via automated JUnit 5 tests at the end of each sprint.
- **Principle 2:** 2. Responding to Change Over Following a Plan: When initial concurrency stress testing uncovered a critical balance race condition defect (DEF-001) in Sprint 1, the sprint backlog was dynamically reprioritized for Sprint 2 to integrate database pessimistic row locking and distributed idempotency filters.
- **Principle 3:** 3. Individuals and Interactions Over Processes and Tools: Daily Scrum standups were conducted between the lead architect, full-stack developer, and security QA engineer to synchronize on concurrency boundaries and eliminate blocking integration bottlenecks.
- **Principle 4:** 4. Customer and Merchant Collaboration: Product features (such as self-service merchant onboarding, transparent API credential management, and one-click refund dialogs) were designed through continuous feedback to optimize user ergonomics without compromising security.
- **Principle 5:** 5. Simplicity—The Art of Maximizing Work Not Done: The system architecture was deliberately engineered as a Modular Monolith rather than a fragmented distributed microservices mesh. This minimized network serialization latency, eliminated distributed two-phase commit overhead, and drastically curtailed attack surfaces.

1.3 Refactoring Opportunities Implemented

During the sprint execution cycle, two substantial refactoring opportunities were identified and executed:

Refactoring 1: Overdraft and Double-Spending Defense (Concurrency Remediation). In Sprint 1, wallet debit checks used naive application-level verification: fetching the wallet, checking if balance $\geq$ amount, subtracting the funds, and saving back to MariaDB. Under concurrent load (multiple HTTP threads hitting `/api/payments/initiate` simultaneously), this check-then-act pattern resulted in race conditions allowing accounts to be drawn negative. The logic was refactored in Sprint 2 to employ database-level pessimistic row locking (`@Lock(LockModeType.PESSIMISTIC_WRITE) SELECT ... FOR UPDATE`).

```
// Refactoring 1: Before (Vulnerable Check-then-Act)
// Vulnerable: Race condition allows simultaneous debits to overdraft
@Transactional
```

```

public PaymentResponse initiatePayment(PaymentRequest req) {
    Wallet wallet = walletRepository.findById(req.getUserId())
        .orElseThrow();
    if (wallet.getBalance().compareTo(req.getAmount()) < 0) {
        throw new InsufficientFundsException("Balance too low");
    }
    wallet.setBalance(wallet.getBalance().subtract(req.getAmount()));
    walletRepository.save(wallet); // Thread race causes negative balance!
    ...
}

```

// Refactoring 1: After (Pessimistic Row Locking Enforced)

// Refactored: MariaDB SELECT ... FOR UPDATE blocks concurrent threads

@Transactional(isolation = Isolation.READ_COMMITTED)

```

public PaymentResponse initiatePayment(PaymentRequest req) {
    // Row locked at the database storage engine level
    Wallet wallet = walletRepository.findByIdWithLock(req.getUserId())
        .orElseThrow();
    if (wallet.getBalance().compareTo(req.getAmount()) < 0) {
        throw new InsufficientFundsException("Balance too low");
    }
    wallet.setBalance(wallet.getBalance().subtract(req.getAmount()));
    walletRepository.save(wallet); // Atomic serialization guaranteed
    ...
}

```

Refactoring 2: Replay Attack Defense (Centralized Idempotency Filter). In early increments, idempotency was handled inconsistently inside individual service methods. This was refactored into a centralized `IdempotencyFilter` and dedicated `IdempotencyRecord` persistence layer that intercepts incoming POST requests, computes a SHA-256 payload digest, detects duplicate `Idempotency-Key` headers, returns cached HTTP responses for identical retries, and rejects altered payloads with HTTP 409 Conflict.

// Refactoring 2: Centralized Idempotency Filter Validation

@Component

```

public class IdempotencyFilter extends OncePerRequestFilter {
    @Override
    protected void doFilterInternal(HttpServletRequest req, HttpServletResponse res, FilterChain chain) {
        String key = req.getHeader("Idempotency-Key");
        if (key != null && "POST".equalsIgnoreCase(req.getMethod())) {
            String payloadHash = sha256(readBody(req));
            Optional<IdempotencyRecord> rec = idempotencyRepo.findByKey(key);
            if (rec.isPresent()) {
                if (!rec.get().getPayloadHash().equals(payloadHash)) {
                    res.sendError(409, "Idempotency key reused with different payload");
                    return;
                }
            }
            res.setStatus(rec.get().getStatusCode());
            res.getWriter().write(rec.get().getResponseBody());
            return; // Served from immutable cache without duplicate debit
        }
        chain.doFilter(req, res);
    }
}

```

```

    }
  }
  chain.doFilter(req, res);
}
}

```

1.4 Agile Limitations, Risks, and Mitigations

- Limitation 1:** 1. Risk 1: Inadequate Upfront Security Architecture. Agile teams often emphasize rapid feature delivery, potentially neglecting foundational architectural security (such as database concurrency constraints). Mitigation: Embedded STRIDE threat modeling directly into Sprint 0 and established security acceptance criteria for every user story before estimation.
- Limitation 2:** 2. Risk 2: Velocity Pressure Causing Deferred Security Debt. Sprint timeboxes can pressure engineers to skip automated static analysis or bypass peer reviews. Mitigation: Enforced an automated SonarQube SAST Quality Gate in the CI/CD pipeline, requiring 0 vulnerabilities, 0 hotspots, and >60% coverage as an unnegotiable gate before merging.




Figure 1: Agile Secure Software Engineering Lifecycle. Comprehensive 16-phase development workflow spanning requirements, threat modeling, sprint execution, containerization, and SonarQube SAST verification (authored in Draw.io). [Phase 1: Agile Process]

2. Requirement Engineering (Phase 2)

2.1 Problem Statement and Case Study Context

Modern digital payment gateways and electronic wallets form the lifeblood of contemporary e-commerce. However, implementing financial platforms introduces severe systemic risks: network retries leading to duplicate debits, race conditions allowing users to double-spend simultaneous balances across parallel threads, and parameter tampering enabling arbitrary payment modifications. Instead of integrating with live banking rails or processing real fiat currency, the Digital Wallet and Payment Gateway Simulator implements an academic, zero-risk simulation of an enterprise payment gateway.

2.2 System Stakeholders

Stakeholder Role	Operational Focus	Primary Security Concerns
Consumer / Customer User	Manages simulated wallet, tops up balances, checks out at merchant portals.	Account takeover, balance theft, duplicate debit on network retry.
Merchant Business	Onboards commercial profile, receives settlement payments, issues refunds.	API key leakage, unauthorized refunds, transaction dispute fraud.
System Administrator / Auditor	Monitors gateway health, inspects SIEM forensic logs, tracks alerts.	Audit tampering, log injection, undetected privilege escalation.
Adversary / Threat Actor	Attempts race condition exploits, replay attacks, and parameter tampering.	Extraction of unauthorized funds, ledger desynchronization, DoS.

2.3 Functional Requirements (FR)

Req ID	Requirement Summary	Operational Scope	Verification Method
FR-01	User Registration	Allow new consumers, merchants, and admins to create accounts.	REST API / UI form validation
FR-02	User Authentication	Authenticate principals and issue signed HMAC-SHA256 JWT tokens.	POST /api/auth/login
FR-03	Wallet Provisioning	Provision a simulated digital wallet initialized with \$0.00 USD.	Automatic upon registration
FR-04	Simulated Funds Top-Up	Permit consumers to top up wallet balance with positive simulated funds.	POST /api/wallet/topup
FR-05	Merchant Onboarding	Enable merchants to register businesses and obtain 256-bit API keys.	POST /api/merchant/register
FR-06	Payment Initiation	Submit payment with target merchant ID, amount, order reference.	POST /api/payments/initiate
FR-07	Payment Confirmation	Atomically execute debit on customer and credit on merchant wallet.	Double-entry ledger commit
FR-08	Refund Processing	Reverse confirmed payments, restoring funds to customer balance.	POST /api/refunds
FR-09	Transaction History	Provide immutable, paginated ledger entries with tamper-evident hashes.	GET /api/transactions/my
FR-10	Administrative Audit	Provide compliance auditors	GET /api/admin/audit-logs

with searchable forensic security event logs.

2.4 Non-Functional Requirements (NFR)

NFR ID	Quality Dimension	Target Specification	Enforcement & Verification
NFR-01	Performance Latency	Payment initiation & top-up latency <= 200 ms under normal load.	JMeter benchmark, HikariCP pool
NFR-02	Transactional Concurrency	Support simultaneous operations without deadlocks or dirty reads.	Pessimistic locking, READ_COMMITTED
NFR-03	Availability & Uptime	Service availability target >= 99.9% in containerized deployment.	Kubernetes ReplicaSets & Probes
NFR-04	Maintainability & Quality	Zero SonarQube blocker/critical bugs; Tech Debt ratio < 1.0%.	SonarQube 9.9 LTS Quality Gate
NFR-05	Portability & Packaging	Zero host OS dependencies; packaged as OCI-compliant containers.	Multi-stage Dockerfile (Alpine/Temurin)
NFR-06	Auditability & SIEM	100% of mutations logged with IP, correlation ID, and timestamp.	AuditService immutable table stream

2.5 Security Requirements (SR)

Sec ID	Security Principle	Priority	Enforcement Mechanism	Verification Method
SR-01	Credential Confidentiality	Must-Have	BCrypt hashing (cost 12), zero plaintext passwords.	AuthServiceTest unit test
SR-02	Stateless Session Integrity	Must-Have	HMAC-SHA256 signed JWT; 1-hour expiry token.	Expired JWT rejection probe
SR-03	Idempotency Enactment	Must-Have	Mandatory Idempotency-Key header; SHA-256 payload binding.	Replay attack integration test
SR-04	Race Condition Prevention	Must-Have	Pessimistic row locking (PESSIMISTIC_WRITE) on wallets.	10-thread parallel fuzz test
SR-05	BOLA / IDOR Defense	Must-Have	Principal ownership	Cross-tenant access

			assertions on wallet queries.	403 probe
SR-06	State Transition Guard	Must-Have	Strict FSM: Only CONFIRMED payments can be REFUNDED.	Double refund rejection test
SR-07	Sensitive Data Scrubbing	Should-Have	Centralized regex redaction of PAN, CVV, passwords in logs.	SIEM log inspection test
SR-08	Least Privilege Runtime	Should-Have	Docker non-root execution (UID 10001); dropped capabilities.	Pod securityContext audit

3. Requirements Analysis and UML (Phase 3)

3.1 System Context Architecture

The DWPG Simulator defines four primary human and systemic actors interacting across well-defined trust perimeters: Consumer, Merchant, Admin Auditor, and Adversary. External HTTPS clients communicate with the Spring Boot REST API layer, which encapsulates security filters, business services, and MariaDB ACID persistence.




Figure 2: DWPG System Context Architecture. Boundary context illustrating interaction between actors, REST API boundary, core business micro-modules, and isolated data tier (authored in Draw.io). [Phase 3: System Context]

3.2 Domain Mapping: Real Banking vs Simulator

To bridge academic simulation and production financial engineering, the system explicitly maps standard real-world banking domain concepts to simulated software abstractions:

1. Acquiring Institution: • Acquiring Bank -> Simulated Merchant Settlement Service: In real banking, the acquirer processes payments on behalf of merchants. Here, the MerchantService coordinates with the payment engine to deposit funds into the merchant's simulated wallet.

2. Issuing Institution: • Issuing Bank -> Customer Wallet Vault: In live finance, the issuer holds customer checking lines. In DWPG, the WalletService manages simulated balances backed by MariaDB ACID row constraints.

3. Payment Rails: • Payment Network Rails (Visa/Mastercard) -> Double-Entry Ledger Engine: Network clearing and settlement are simulated via atomic MariaDB transaction boundaries executing synchronized debits and credits.

4. Settlement: • Clearing & Settlement Clearinghouse -> Internal Transaction History: Interbank net settlement is represented via the immutable `transactions` table recording cryptographic hashes.

3.3 Use Case Modeling

The UML Use Case model captures functional capabilities and security relationships. Essential interactions use `<<include>>` associations for mandatory authentication, idempotency validation, and audit recording.




Figure 3: UML Use Case Diagram. Actor-to-use-case associations highlighting core functional cases and `<<include>>` security validation relationships (authored in Draw.io). [Phase 3: Use Case Model]

3.4 Formal Use Case Specifications

Detailed specifications for two core security-critical use cases are documented below:

- Use Case Specification: UC-PAY-001 (Payment Initiation and Settlement)

Actor: Registered Customer User.

Preconditions: Customer is authenticated with a valid JWT token; Customer possesses an active digital wallet with positive balance.

Trigger: Customer clicks 'Authorize & Process Payment' on the checkout view.

Main Success Scenario:

1. Customer submits POST `/api/payments/initiate` with `merchantId`, `amount`, `description`, and `Idempotency-Key` header.

2. System intercepts request in IdempotencyFilter, hashing the payload with SHA-256 and verifying key uniqueness.
3. System acquires a PESSIMISTIC_WRITE row lock on Customer's wallet via MariaDB.
4. System asserts wallet balance is greater than or equal to payment amount.
5. System debits customer wallet balance and credits merchant settlement wallet balance atomically.
6. System creates Payment entity in CONFIRMED state and writes double-entry rows to transactions table.
7. System stores cached response in idempotency_records and appends AuditLog entry.
8. System returns HTTP 200 with payment confirmation receipt and tamper seal hash.

Alternative Flows:

- 2a. Idempotency Key Reused with Identical Payload: System bypasses balance debit, retrieves cached response from idempotency_records, and returns HTTP 200 with original receipt.
- 4a. Insufficient Funds: System logs PAYMENT_FAILED audit event and returns HTTP 400 Bad Request without modifying balances.

Exception Flows:

- 2b. Idempotency Key Reused with Altered Payload: System detects hash mismatch, records REPLAY_DETECTED security alert, and returns HTTP 409 Conflict.
- 3b. Database Lock Timeout: MariaDB query times out under excessive deadlock load; system returns HTTP 503 Service Unavailable; no balance mutation occurs.

Security Controls: Bearer JWT validation, SHA-256 payload binding, Pessimistic row lock, BOLA owner check, SIEM audit trail.

- Use Case Specification: UC-REF-001 (Merchant Payment Refund Processing)

Actor: Registered Merchant Principal or Customer Owner.

Preconditions: Principal is authenticated; target Payment exists in CONFIRMED state; no prior refund issued for payment.

Trigger: Merchant initiates refund from the transaction ledger modal.

Main Success Scenario:

1. Actor submits POST /api/refunds with paymentId, reason, and Idempotency-Key header.
2. System validates principal authorization against merchant or customer record.
3. System queries Payment record, verifying status is CONFIRMED (not REFUNDED or FAILED).
4. System acquires pessimistic write locks on both merchant and customer wallets.
5. System asserts merchant wallet has sufficient balance to cover the reversal.
6. System debits merchant wallet and credits customer wallet atomically.
7. System transitions Payment status to REFUNDED, persists Refund entity, and logs transaction rows.
8. System records PAYMENT_REFUNDED audit event and returns HTTP 200 with refund confirmation.

Alternative & Exception Flows:

- 3a. Payment Already Refunded: System rejects duplicate refund request, returning HTTP 400 with 'Payment already refunded'.
- 5a. Merchant Insufficient Balance: System rejects refund, returning HTTP 400 with 'Merchant settlement balance insufficient'.
- 2a. Unauthorized Caller: If caller does not own the payment, system returns HTTP 403 Forbidden.

Security Controls: Role-based authorization, Payment state machine validation, Pessimistic wallet row locking, Idempotent refund execution.

3.5 Analysis Model and Behavioral Sequence

The static analysis model categorizes software elements into Boundary, Control, and Entity stereotypes. Dynamic interactions are captured via detailed sequence diagrams modeling transactional atomicity, cryptographic authentication, wallet top-up, payment processing, refund reversal, and replay traps.




Figure 4: Robustness Analysis Model. BCE (Boundary-Control-Entity) decomposition of the payment checkout and dispute subsystems (authored in Draw.io). [Phase 3: Analysis Model]




Figure 5: UML Sequence Diagram: JWT Authentication & RBAC. Step-by-step authentication protocol including BCrypt verification, JWT token minting, and Bearer token filter validation (authored in Draw.io). [Phase 3: Auth Sequence]




Figure 6: UML Sequence Diagram: Wallet Provisioning & Funds Top-Up. Step-by-step sequence of simulated wallet funding, pessimistic balance locking, and transaction logging (authored in Draw.io). [Phase 3: Wallet Sequence]




Figure 7: UML Sequence Diagram: Idempotent Payment Settlement. Chronological interaction between Customer, PaymentController, IdempotencyService, WalletService, and MariaDB showing row locking and commit boundaries (authored in Draw.io). [Phase 3: Payment Sequence]




Figure 8: UML Sequence Diagram: Authorized Payment Refund & Reversal. State machine transition from CONFIRMED to REFUNDED, atomic wallet balance reversal, and refund audit ledger entry (authored in Draw.io). [Phase 3: Refund Sequence]




Figure 9: UML Sequence Diagram: Idempotency Cache & Replay Trap Defense. Dual-scenario sequence modeling: Scenario 1 (identical replay served from cache without extra debit) and Scenario 2 (tampered payload returning HTTP 409 Conflict) (authored in Draw.io). [Phase 3: Replay Defense Sequence]

4. Data and Information Flow Modeling (Phase 4)

4.1 Entity Relationship Diagram (ERD) & Relational Integrity

The database architecture enforces strict third normal form (3NF) principles across 8 relational tables. The ER diagram features 10 explicit crow-foot relationships with labeled cardinalities and foreign key references:

- **Relation 1:** 1. users -> wallets (1 to 1): Each user owns exactly one customer wallet (user_id FK).
- **Relation 2:** 2. users -> merchants (1 to 1): A user may register a commercial profile (user_id FK).
- **Relation 3:** 3. merchants -> wallets (1 to 1): Each merchant links to an isolated settlement wallet (settlement_wallet_id FK).
- **Relation 4:** 4. wallets -> transactions (1 to Many): A wallet records an append-only ledger of debit and credit rows (wallet_id FK).
- **Relation 5:** 5. merchants -> payments (1 to Many): A merchant receives payments from customers (merchant_id FK).
- **Relation 6:** 6. users -> payments (1 to Many): A customer initiates payment transactions (customer_id FK).
- **Relation 7:** 7. payments -> refunds (1 to 1): A confirmed payment may yield exactly one refund record (payment_id FK).
- **Relation 8:** 8. payments -> transactions (1 to Many): A payment generates synchronized double-entry debit and credit transactions (payment_id FK).
- **Relation 9:** 9. users -> audit_logs (1 to Many): Administrative and customer actions generate audit trail events (actor_username reference).
- **Relation 10:** 10. users -> idempotency_records (1 to Many): Principals scope their request idempotency keys (user_id FK).




Figure 10: Entity Relationship Diagram (ERD) with Crow-Foot Cardinalities. Complete 3NF Relational schema illustrating 8 entities and 10 explicit crow-foot relationships (authored in Draw.io). [Phase 4: Data Modeling]

4.2 Data Flow Modeling (DFD Level 0 & Level 1)

Data flow modeling tracks the lifecycle of sensitive financial information as it crosses trust boundaries from external HTTPS clients into core transactional engines and storage subsystems.




Figure 11: DFD Level 0: System Context Data Flow. High-level process flow showing principal inputs, transactional mutations, and external data storage sinks (authored in Draw.io). [Phase 4: DFD Level 0]




Figure 12: DFD Level 1: Subsystem Data Flow Decomposition. Decomposition into Auth Process (1.0), Wallet Operations (2.0), Payment Engine (3.0), Refund Engine (4.0), and Audit SIEM Sink (5.0) (authored in Draw.io). [Phase 4: DFD Level 1]




Figure 13: Trust Boundary and Data Flow Security Perimeter. Demarcation between Untrusted Client Network, DMZ Ingress Gateway, Protected Internal Microservices, and Secure Persistence Vault (authored in Draw.io). [Phase 4: Trust Perimeter]

4.3 Cross-Model Consistency Verification

To prevent requirement or architectural drift, a formal consistency verification table was executed across Use Cases, ERD tables, and DFD processes:

Functional Use Case	Corresponding DFD Process	Primary ERD Entities Accessed	Consistency Status
UC-01: User Registration	P1.0: Authentication & Identity	users, audit_logs	100% Consistent
UC-02: User Authentication	P1.0: Authentication & Identity	users, audit_logs	100% Consistent
UC-03: Wallet Provisioning	P2.0: Wallet & Funds Vault	users, wallets, audit_logs	100% Consistent
UC-04: Funds Top-Up	P2.0: Wallet & Funds Vault	wallets, transactions, audit_logs	100% Consistent

UC-05: Merchant Onboarding	P2.0: Wallet & Funds Vault	users, merchants, wallets	100% Consistent
UC-06: Payment Initiation	P3.0: Payment Gateway Core	payments, wallets, idempotency_records	100% Consistent
UC-07: Payment Settlement	P3.0: Payment Gateway Core	payments, wallets, transactions, audit_logs	100% Consistent
UC-08: Refund Reversal	P4.0: Dispute & Refund Engine	payments, refunds, wallets, transactions	100% Consistent
UC-09: Transaction History	P3.0 & P4.0 Data Stores	transactions, wallets	100% Consistent
UC-10: SIEM Security Audit	P5.0: Forensic SIEM Engine	audit_logs	100% Consistent

5. Software Architecture and Design Engineering (Phase 5)

5.1 Architectural Style: Modular Monolith Rationale

The DWPG Simulator is deliberately architected as a secure Modular Monolith rather than distributed microservices. While microservices offer decoupled scaling for multi-thousand developer organizations, financial transaction processing introduces severe distributed systems vulnerabilities: distributed transaction failures requiring complex saga orchestrations, network partition risks, increased serialization latency, and expanded RPC attack surfaces. By implementing clean internal bounded contexts inside a single Spring Boot container, the simulator guarantees zero-overhead ACID database transactions, predictable in-memory method dispatch, and robust local pessimistic locking.

5.2 Applied Software Design Patterns

- **Filter Pattern:** 1. Intercepting Filter Pattern: Implemented via `JwtAuthenticationFilter` and `IdempotencyFilter`. Intercepts incoming HTTP requests to validate bearer credentials, calculate payload SHA-256 hashes, and serve cached idempotency responses prior to controller invocation.
- **Repository Pattern:** 2. Repository Pattern: Implemented via Spring Data JPA repositories (`WalletRepository`, `PaymentRepository`). Decouples business domain entities from database persistence and exposes row-locking query APIs (`findByIdWithLock`).
- **State Machine Pattern:** 3. State Machine Pattern: Governs the lifecycle of the Payment entity (PENDING -> CONFIRMED -> REFUNDED or FAILED). Guarantees that invalid state transitions (such as refunding an already refunded or failed transaction) are physically rejected.
- **Strategy Pattern:** 4. Strategy / Adapter Pattern: Implemented via `PaymentProcessor` interfaces to isolate payment gateway execution logic, allowing simulated authorization adapters to be swapped without modifying core wallet ledger services.




Figure 14: Layered Software Architecture. Tiered representation of Frontend Presentation, Security Filter Chain, Business Domain Services, and Data Access Persistence (authored in Draw.io). [Phase 5: Architecture]




Figure 15: UML Component Diagram. Component interfaces and dependency injection bindings connecting controllers, security utilities, and persistence repositories (authored in Draw.io). [Phase 5: Component Design]




Figure 16: Physical Deployment Architecture. Multi-tier container deployment across Kubernetes Pods, ClusterIP services, MariaDB PVC storage, and Minikube NodePort ingress (authored in Draw.io). [Phase 5: Deployment]

5.3 Technology Stack and Governance

Layer / Domain	Technology Choice	Security Rationale & Governance
Backend Runtime	Java 21 LTS / Spring Boot 3.3.4	Strong typing, virtual threads, robust memory safety, enterprise ecosystem.
Security Framework	Spring Security 6 / BCrypt / JWT	Declarative RBAC, stateless HMAC-SHA256 bearer tokens, OWASP session control.
Persistence Layer	Spring Data JPA / Hibernate 6	ORM parameterized queries eliminating SQL injection, row-level locking APIs.
Relational Database	MariaDB 10.11 / In-Memory H2	ACID transactional boundaries, row-level SELECT ... FOR UPDATE locking, strict schemas.
Frontend UI	React 18 / Vite SPA	Modern componentized architecture, automatic XSS context encoding, zero vulnerable dependencies.
Containerization	Docker Multi-Stage (Alpine/Temurin)	Minimal attack surface, non-root user execution (UID 10001), dropped Linux capabilities.
Orchestration	Kubernetes / Minikube	Declarative YAML manifests, NetworkPolicy egress/ingress isolation, ConfigMap/Secret decoupling.
SAST & Quality Gate	SonarQube 9.9.8 LTS / JaCoCo	Static analysis enforcing zero blocker/critical vulnerabilities, automated coverage metrics.

6. User Interface Design and Evidence (Phase 6)

6.1 UI Ergonomics and Security Design Philosophy

The frontend application was engineered using React 18 and Vite. Secure UI principles were prioritized throughout: automatic context-sensitive HTML escaping to eliminate XSS, real-time security banners, visual cryptographic pills displaying SHA-256 tamper hashes, clear transaction state badges, revealed credential controls, and explicit adversarial attack simulation sandboxes.

6.2 UI Screen Specifications

Screen ID & Name	Target User	Primary Goal	Key Inputs	Security Controls & Error Handling
UI-01: Registration	New User	Onboard user account	Username, Email, Password, Role	NIST password complexity; client validation; generic duplicate errors.

UI-02: Authentication	All Principals	Authenticate & acquire JWT	Username, Password	Generic error on bad credentials; password masking; lockout feedback.
UI-03: Dashboard	Customer	Inspect wallet balance & state	None (Display only)	Masked account ID; zero initial balance; active vault security banner.
UI-04: Top-Up Modal	Customer	Fund wallet with simulated money	Amount (\$USD)	Positive decimal validation; maximum deposit ceiling limit.
UI-05: Top-Up Success	Customer	Verify atomic balance credit	None (Receipt view)	Real-time balance update; atomic ledger credit notification.
UI-06: Merchant Onboard	Merchant	Provision business profile	Business Name	Input sanitization; settlement wallet automated binding.
UI-07: Merchant Portal	Merchant	Manage business & API keys	Reveal key button	High-entropy 256-bit API key revealed on user demand; settlement display.
UI-08: Checkout Form	Customer	Initiate payment to merchant	Merchant ID, Amount, Description	Auto-generated UUID Idempotency-Key; positive amount constraint.
UI-09: Confirmation	Customer	Authorize & commit funds	Submit button	Atomic execution telemetry; live latency meter; correlation ID.
UI-10: Receipt View	Customer	Verify payment completion	None (Receipt view)	SHA-256 digital tamper seal; CONFIRMED status badge; payment ID.
UI-11: Ledger View	All Principals	Inspect double-entry history	Pagination controls	Append-only chronological audit rows; debit/credit colored pills.
UI-12: Refund Dialog	Merchant/Owner	Request authorized reversal	Payment ID, Refund Reason	State machine check (CONFIRMED only); idempotency tracking.
UI-13: Refund Success	Merchant/Owner	Verify settlement reversal	None (Confirmation alert)	Atomic customer credit and merchant debit; REFUNDED status badge.
UI-14: Defense Lab	Security Tester	Simulate replay & tamper attack	Payload modifiers, Replay trigger	Live visual demonstration of cached response vs

				HTTP 409 trap.
UI-15: SIEM Explorer	Admin Auditor	Inspect immutable audit stream	Action filter, Pagination	Strict ROLE_ADMIN guard; forensic details, IP address, and outcome.

6.3 Empirical UI Screen Captures






Figure 17: UI-01: User Registration. Real client view demonstrating consumer registration with client-side NIST SP 800-63B password complexity validation. [FR-01, SR-01]



The image shows the 'Sign In' screen of the DWPG Simulator. At the top left, there is a logo and the text 'DWPG Simulator' followed by 'SECURE V1.0'. At the top right, there are links for 'Sign In' and 'Register'. The main content area is a white box with a light gray border. Inside, the title 'Sign In' is followed by the subtitle 'Access your secure digital wallet'. Below this, there are two input fields: 'Username' with the value 'alice_fin_20683' and 'Password' with a masked value '*****'. A blue 'Sign In' button is positioned below the password field. Underneath the button, there is a link: 'Don't have an account? Create an Account'. At the bottom of the white box, there is a section titled 'SIMULATOR TEST SHORTCUTS:' with three buttons: 'Fill Alice (User)', 'Fill Bob (Merchant)', and 'Fill Admin'.

Figure 18: UI-02: User Authentication & Login. Secure sign-in screen featuring generic error messaging on authentication failure to thwart username enumeration. [FR-02, SR-01]



The image shows the 'Customer Wallet Dashboard' of the DWPG Simulator. At the top left, there is a logo and the text 'DWPG Simulator' followed by 'SECURE V1.0'. The top navigation bar includes links for 'Wallet', 'Checkout / Payment', 'Ledger & History', 'Merchant', 'alice_fin_20683', 'USER', and 'Sign Out'. The main content area is a white box with a light gray border. At the top, there is a dark blue banner with the title 'Simulated Vault & Wallet Safeguards' and the text 'Row-level pessimistic locking & ACID boundaries prevent negative balance or double spending.' Below the banner, there are three buttons: 'Row-Lock Active', 'Balance Non-Negative', and 'Atomic Top-Up'. The dashboard is divided into two main sections. The left section is titled 'Digital Wallet' and 'ACTIVE'. It shows the account number 'Account #DWPG-880013'. Below this, there is a green box with the text 'AVAILABLE BALANCE' and '\$0.00 USD'. Underneath the green box, there is a note: 'Zero real fiat money. Strictly simulated educational funds.' At the bottom of the left section, there is a table with the following data: 'Wallet ID: #13', 'Created At: 10/8/2026, 1:06:52 PM', and 'Last Updated: 10/8/2026, 1:06:52 PM'. The right section is titled 'Add Simulated Funds' and 'Top up your wallet balance instantly'. It has an input field for 'Amount (USD)' with the value '0.00'. Below the input field, there are five buttons: '+\$50', '+\$100', '+\$250', '+\$500', and '+\$1000'. At the bottom of the right section, there is a blue 'Top-Up Wallet' button.

Figure 19: UI-03: Customer Wallet Dashboard. Customer portal displaying account number, active vault safeguards banner, and zero initial balance. [FR-03, SR-05]

DWPG Simulator

SECURE V1.0

Wallet

Checkout / Payment

Ledger & History

Merchant

alice_fin_20683

USER

Sign Out

Simulated Vault & Wallet Safeguards

Row-level pessimistic locking & ACID boundaries prevent negative balance or double spending.

Row-Lock Active

Balance Non-Negative

Atomic Top-Up

Digital Wallet

Account #DWPG-880013

ACTIVE

AVAILABLE BALANCE

\$0.00 USD

Zero real fiat money. Strictly simulated educational funds.

Wallet ID: #13

Created At: 10/8/2026, 1:06:52 PM

Last Updated: 10/8/2026, 1:06:52 PM

Add Simulated Funds

Top up your wallet balance instantly

Amount (USD)

500.00

+\$50

+\$100

+\$250

+\$500

+\$1000

Top-Up Wallet

Figure 20: UI-04: Simulated Funds Top-Up Interface. Simulated funds deposit interface with preset increments and client-side positive decimal validation. [FR-04, SR-04]

DWPG Simulator

SECURE V1.0

Wallet

Checkout / Payment

Ledger & History

Merchant

alice_fin_20683

USER

Sign Out

Simulated Vault & Wallet Safeguards

Row-level pessimistic locking & ACID boundaries prevent negative balance or double spending.

Row-Lock Active

Balance Non-Negative

Atomic Top-Up

Successfully added \$500.00 simulated funds!

Digital Wallet

Account #DWPG-880013

ACTIVE

AVAILABLE BALANCE

\$500.00 USD

Zero real fiat money. Strictly simulated educational funds.

Wallet ID: #13

Created At: 10/8/2026, 1:06:57 PM

Last Updated: 10/8/2026, 1:06:57 PM

Add Simulated Funds

Top up your wallet balance instantly

Amount (USD)

0.00

+\$50

+\$100

+\$250

+\$500

+\$1000

Top-Up Wallet

Figure 21: UI-05: Top-Up Confirmation & Balance Update. Atomic top-up confirmation displaying updated wallet balance (\$500.00 USD) and atomic ledger entry. [FR-04, SR-04]

DWPG Simulator SECURE V1.0

Wallet Checkout / Payment Ledger & History Merchant alice_fin_20683 USER Sign Out

Merchant Credential & API Security
Merchants receive a unique 256-bit API key for HMAC signing and merchant-only operational authorization.

Register Merchant Profile
Accept simulated payments from registered wallets

Business / Store Name
Apex Cloud Stores #20683

Provision Merchant Profile

Figure 22: UI-06: Merchant Onboarding Form. Merchant registration portal enabling business profile creation and settlement wallet association. [FR-05, SR-02]

DWPG Simulator SECURE V1.0

Wallet Checkout / Payment Ledger & History Merchant alice_fin_20683 USER Sign Out

Merchant Credential & API Security
Merchants receive a unique 256-bit API key for HMAC signing and merchant-only operational authorization.

Merchant account registered successfully!

Apex Cloud Stores #20683
Merchant Account #7 ACTIVE

MERCHANT IDENTIFIER
#7
Users submit this ID when making payments.

ACCOUNT STATUS
ACTIVE
Provisioned on 10/8/2026

API Security Key
mkey_4cb20e8357fa4837b4efeebbc3ded777
Keep this API key confidential. Never expose in public client-side scripts.

Hide Key

Figure 23: UI-07: Merchant Security Portal & Revealed API Key. Merchant management portal displaying active business status, settlement account, and high-entropy 256-bit API key visibly revealed. [FR-05, SR-02]

DWPG Simulator

SECURE V1.0

Wallet

Checkout / Payment

Ledger & History

Merchant

alice_fin_20683

USER

Sign Out

Idempotency & Replay Attack Defense Lab

Submit payments with an Idempotency-Key. Retrying with identical keys returns cached status without double debiting.

Idempotent API

SHA-256 Tamper Sealed

Anti-Replay Guard

Initiate Payment

Available Wallet Balance: \$500.00

Merchant ID

7

Enter target registered merchant ID (e.g. 1)

Amount (USD)

65.00

Description / Order Reference

Simulator order checkout test

Idempotency-Key (Header)

31d830f8-2d4b-47f7-bc6a-cc5c39bb43d0

Generate New UUID

Unique request identifier enforcing strictly once-only processing.

Submit Payment

Simulate Replay Attack

Transaction Receipt

Verified cryptographic receipt

No active payment transaction submitted yet.

Submit the form to inspect response telemetry.

Figure 24: UI-08: Payment Initiation Form. Checkout terminal showing target merchant selection, order reference, and auto-generated UUID Idempotency-Key header. [FR-06, SR-03]

DWPG Simulator

SECURE V1.0

Wallet

Checkout / Payment

Ledger & History

Merchant

alice_fin_20683

USER

Sign Out

Idempotency & Replay Attack Defense Lab

Submit payments with an Idempotency-Key. Retrying with identical keys returns cached status without double debiting.

Idempotent API

SHA-256 Tamper Sealed

Anti-Replay Guard

Initiate Payment

Available Wallet Balance: \$500.00

Merchant ID

7

Enter target registered merchant ID (e.g. 1)

Amount (USD)

65.00

Description / Order Reference

Simulator order checkout test

Idempotency-Key (Header)

31d830f8-2d4b-47f7-bc6a-cc5c39bb43d0

Generate New UUID

Unique request identifier enforcing strictly once-only processing.

Submit Payment

Simulate Replay Attack

Transaction Receipt

Verified cryptographic receipt

CONFIRMED

PAID AMOUNT

\$65.00

Status: CONFIRMED

Payment ID:

#8

Merchant ID:

#13

Correlation ID:

CORR-31d830f8

SHA-256 Tamper-Evident Hash:

7e8920121c261b374d526c2104f144fd6d615b02aa048e180e449c7aa473de6c

Idempotency & Replay Audit Feed

1 INVOCATIONS LOGGED

Figure 25: UI-09: Payment Execution & Processing. Live payment processing telemetry verifying atomic customer debit, merchant settlement credit, and correlation ID. [FR-07, SR-03]

Amrita Vishwa Vidyapeetham — Department of Cyber Security | End Semester Academic Examination




Figure 26: UI-10: Cryptographic Payment Receipt. Verified digital receipt presenting payment ID, timestamp, and SHA-256 tamper-evident digital seal. [FR-07, SR-07]




Figure 27: UI-11: Tamper-Evident Transaction Ledger. Append-only double-entry financial ledger displaying debit, credit, top-up, and refund records with cryptographic hashes. [FR-09, SR-07]




Figure 28: UI-12: Refund Initiation Modal. Authorized refund dialog visibly open, allowing reason specification and idempotency tracking for transaction reversal. [FR-08, SR-06]




Figure 29: UI-13: Refund Success & Ledger Entry. Successful refund notification confirming \$65.00 restored to customer balance and updated ledger entry displayed. [FR-08, SR-06]




Figure 30: UI-14: Security Tamper & Replay Defense Lab. Adversarial replay simulation showing identical payment retried with unchanged Idempotency-Key. Cached response returned without double debiting. [SR-03, SR-04]




Figure 31: UI-15: SIEM Security Audit Explorer. Administrative compliance view showing populated chronological audit trail of authentication, mutations, and replay traps. [FR-10, SR-08]

7. Threat Modeling and Security Analysis (Phase 7)

7.1 Asset Identification & CIA Triad

Systematic threat modeling commenced by cataloging the eight primary assets comprising the gateway ecosystem, analyzing their confidentiality, integrity, and availability valuations:

Asset ID & Name	Asset Owner	Confidentiality	Integrity	Availability	Asset Valuation Rationale
AST-01: Wallet Balances	Customer / Merchant	Medium	Critical	High	Integrity failure leads directly to double-spending or unauthorized overdraft.
AST-02: Password Hashes	Identity Service	Critical	Critical	Medium	Confidentiality loss enables offline dictionary or credential stuffing attacks.
AST-03: JWT Signing Keys	Auth Service	Critical	Critical	High	Compromise allows adversary to forge arbitrary tokens with ROLE_ADMIN.
AST-04: Merchant API Keys	Registered Merchant	Critical	Critical	High	Leaked keys allow adversary to trigger automated settlement actions.
AST-05: Payment Records	Payment Engine	Medium	Critical	High	Falsification corrupts transaction reconciliation and billing audits.
AST-06: Ledger Transactions	Financial Vault	Low	Critical	High	Immutable double-entry book of records; tampering violates accounting rules.
AST-07: Idempotency Records	Filter Engine	Low	Critical	Critical	Loss enables replay attacks; corruption leads to duplicate debits.
AST-08: SIEM Audit Logs	Compliance Auditor	Medium	Critical	High	Tampering destroys forensic evidence during breach investigations.

7.2 STRIDE Threat Classification

Threat ID	STRIDE Category	Target Component	Attacker Motivation	Countermeasure Applied
THR-01	Spoofing	AuthController	Credential stuffing / account takeover	BCrypt hashing (cost 12), ephemeral JWT with expiration.
THR-02	Tampering	PaymentController	Modify transaction amount in flight	SHA-256 payload digest binding; HTTPS transport encryption.
THR-03	Repudiation	TransactionRepository	Deny initiating payment or refund	Cryptographically hashed audit records & immutable ledger.
THR-04	Information Disclosure	WalletController	Inspect foreign wallet balances (BOLA)	Ownership authorization assertions on all principal queries.
THR-05	Denial of Service	Tomcat Thread Pool	Exhaust database pool via request spam	HikariCP connection pool limits, idempotency fast-fail.
THR-06	Elevation of Privilege	AdminController	Access SIEM logs without admin role	Spring Security @PreAuthorize("hasRole('ADMIN')") check.
THR-07	Tampering	WalletRepository	Concurrent double spending race	Pessimistic row locking (PESSIMISTIC_WRITE) at DB level.
THR-08	Spoofing	IdempotencyFilter	Replay intercepted payment request	Mandatory Idempotency-Key cache returning original receipt.
THR-09	Tampering	RefundService	Issue duplicate or excessive refund	Strict Payment state machine; only CONFIRMED payments eligible.
THR-10	Information Disclosure	AuditLogger	Leak plaintext credentials in logs	Centralized regex scrubbing of PAN, CVV, and passwords.

7.3 Analysis of Sensitive Information Flows Across Trust Boundaries

● **Flow 1:** 1. Flow 1: Customer Credential Flow (Client -> AuthController -> AuthService -> MariaDB). Traverses Untrusted Internet into DMZ. Threat: Eavesdropping and brute-force credential stuffing. Mitigations: Enforce

HTTPS TLS 1.3 transport encryption, BCrypt cost 12 adaptive password hashing, and generic error responses preventing username enumeration.

- **Flow 2:** 2. Flow 2: Payment Payload & Card Simulation Flow (Client -> IdempotencyFilter -> PaymentController -> WalletService -> MariaDB). Traverses Trust Boundary between presentation and domain services. Threat: In-flight parameter tampering and replay attacks. Mitigations: SHA-256 request body hashing bound to UUID Idempotency-Key, MariaDB pessimistic locking on wallet rows, and atomic double-entry ledger transaction commit.

- **Flow 3:** 3. Flow 3: Idempotency Token Flow (Client -> IdempotencyFilter -> IdempotencyRepository -> MariaDB). Intercepts every POST mutation. Threat: Token collision and altered payload injection. Mitigations: Dual verification—asserting token existence AND payload digest equality. Mismatched digests trigger immediate HTTP 409 Conflict rejection.

7.4 Vulnerabilities Analysis and Qualitative Risk Matrix

Vuln ID	CWE Mapping	Vulnerability Description	CVSS v3.1	Architectural Defense
VULN-01	CWE-362	Concurrent Race Condition in Balance Debit	High (8.1)	Pessimistic DB row locking (@Lock{PESSIMISTIC_WRITE}).
VULN-02	CWE-294	Payment Transaction Replay Attack	High (7.5)	Mandatory Idempotency-Key header with SHA-256 binding.
VULN-03	CWE-285	Broken Object Level Authorization (BOLA)	High (7.8)	Ownership verification against SecurityContext principal.
VULN-04	CWE-20	Improper Input Validation (Negative Amounts)	Medium (6.5)	Jakarta Validation (@Positive, @NotNull) and DB constraints.
VULN-05	CWE-79	Stored Cross-Site Scripting (XSS)	Medium (5.4)	React automated context encoding; HTML entity escaping.
VULN-06	CWE-319	Cleartext Transmission of Sensitive Telemetry	Medium (5.3)	Enforced HTTPS TLS; regex scrubbing of logs.




Figure 32: STRIDE Threat Matrix and Mitigation Model. Systematic mapping of threat categories to architectural defense controls and security verification gates (authored in Draw.io). [Phase 7: Threat Modeling]

8. Attack Tree Analysis (Phase 8)

8.1 Attacker Goal: Double Spending and Balance Theft

The primary objective of a financial adversary targeting the gateway is to execute Double Spending—spending identical wallet funds multiple times before balances synchronize, or forcing balance inversions below zero.




Figure 33: Attack Tree Decomposition: Double Spending & Gateway Tampering. Hierarchical attack paths detailing race condition exploitation, replay interception, parameter tampering, and mitigation barriers (authored in Draw.io). [Phase 8: Attack Tree]

8.2 Attack Path Mitigation & Defense Mapping

Attack Node ID	Attacker Action / Vector	Target Weakness	Countermeasure & Verification
AT-1.1	Fire 10 simultaneous threads to drain \$100 balance	Check-then-act race window	Pessimistic row lock serializes threads; 8 rejected.
AT-1.2	Intercept network request and	Unchecked idempotent state	IdempotencyFilter traps key,

	replay raw POST packet		returns original receipt.
AT-2.1	Replay valid Idempotency-Key with altered \$500 amount	Token reuse tampering	SHA-256 digest mismatch detected; HTTP 409 Conflict.
AT-3.1	Submit refund for already refunded transaction	Missing state transition guard	Payment FSM asserts status == CONFIRMED; rejects refund.
AT-3.2	Non-owner attempts to refund foreign merchant payment	BOLA authorization bypass	Principal ownership check blocks request with HTTP 403.
AT-4.1	Inject negative decimal (- \$1000) in payment or top-up	Unbounded numeric input	Jakarta @Positive validation and MariaDB CHECK constraint.




Figure 34: Refined Security Architecture & Defense Layers. Layered defensive barriers: Ingress Gateway -> JWT Auth -> Idempotency Cache -> Pessimistic DB Lock -> SIEM Logger (authored in Draw.io). [Phase 8: Security Architecture]

9. Product Backlog and Jira/Scrum (Phase 9)

9.1 Backlog Structure and User Story Specifications

The product backlog was structured into 8 functional and security epics encompassing 13 prioritized work items. Story estimation used Fibonacci planning poker points based on complexity, architectural risk, and security validation requirements. Every user story is formulated using the standard format: 'As a [role], I want [capability], so that [benefit]' with explicit acceptance criteria.

Key	Story ID	Epic	SP	Sprint	User Story Specification & Acceptance Criteria
DWPG-10	STORY-01	DWPG-2: Auth	5	Sprint 1	As a User, I want secure registration & JWT auth, so

					that my account is protected. Criteria: BCrypt cost 12, signed JWT, generic error msgs.
DWPG-11	STORY-02	DWPG-3: Wallet	5	Sprint 1	As a Customer, I want wallet creation & simulated top-up, so that I can hold funds. Criteria: BOLA owner check, non-negative balance.
DWPG-12	STORY-03	DWPG-3: Wallet	3	Sprint 1	As a Merchant, I want registration & API key generation, so that I can receive funds. Criteria: 256-bit API key, XSS sanitization.
DWPG-13	STORY-04	DWPG-4: Payment	8	Sprint 1	As a Customer, I want payment initiation, so that I can purchase items. Criteria: Double-entry accounting, atomic debit/credit.
DWPG-14	STORY-05	DWPG-6: Security	5	Sprint 1	As an Auditor, I want security audit logging, so that events are recorded. Criteria: Append-only table, credential scrubbing.
DWPG-15	DEF-001	DWPG-6: Security	5	S1 -> S2	BUG: Fix race condition & duplicate payment defect via pessimistic locking. Criteria: Pass 10-thread parallel fuzz test.
DWPG-16	STORY-06	DWPG-6: Security	5	Sprint 2	As a System, I want pessimistic row locking on wallets, so that double

					spending is prevented. Criteria: SELECT ... FOR UPDATE query.
DWPG-17	STORY-07	DWPG-6: Security	5	Sprint 2	As a System, I want mandatory Idempotency-Key validation, so that replays are rejected. Criteria: HTTP 409 on altered payload.
DWPG-18	STORY-08	DWPG-5: Refunds	5	Sprint 2	As a Merchant, I want refund processing, so that returned transactions credit customer. Criteria: Payment status CONFIRMED only.
DWPG-19	STORY-09	DWPG-5: Refunds	3	Sprint 2	As a User, I want immutable transaction history, so that I can verify all movements. Criteria: BOLA isolation, tamper hashes.
DWPG-20	STORY-10	DWPG-6: Security	5	Sprint 2	As an Admin, I want a SIEM audit explorer, so that I can inspect attacks in real time. Criteria: ROLE_ADMIN enforcement.
DWPG-21	STORY-11	DWPG-7: DevSecOps	3	Sprint 2	As a DevSecOps Eng, I want non-root Docker & K8s NetworkPolicies, so that pods are hardened. Criteria: UID 10001, isolate-mariadb.
DWPG-22	STORY-12	DWPG-8: Testing	3	Sprint 2	As a QA Eng, I want automated regression & fuzz testing, so that regressions are

blocked. Criteria:
100% pass on
security suite.

10. Sprint Execution and Scrum Metrics (Phase 10)

10.1 Two-Sprint Cadence Summary

- Sprint 1 Focus: Core MVP architecture, authentication, wallet provisioning, merchant onboarding, and initial payment processing. Committed: 26 Story Points. Completed: 21 Story Points. Defect DEF-001 (5 SP) identified during concurrency testing was carried over to Sprint 2 for comprehensive architectural remediation.
- Sprint 2 Focus: Security hardening, pessimistic database row locking, mandatory idempotency token cache, multi-role refund processing, Docker containerization, Minikube Kubernetes deployment, and automated security test suite. Committed: 26 Story Points. Completed: 26 Story Points (100% velocity achieved).

10.2 Defect DEF-001 Lifecycle

Defect DEF-001 ('Race Condition and Duplicate Balance Debit') was flagged on Day 8 of Sprint 1 when automated multi-threaded tests demonstrated that two simultaneous \$50 payments against a \$50 balance both succeeded, resulting in an illicit -\$50 overdraft. Root cause analysis revealed non-atomic check-then-act logic in WalletService. The defect was assigned 5 Story Points, transitioned through the 4-column Scrum board (TO DO -> IN PROGRESS -> TESTING -> CARRIED OVER), and resolved in Sprint 2 via pessimistic database row locking.

10.3 Scrum Metrics Analysis

Metric Dimension	Sprint 1 Delivered	Sprint 2 Delivered	Aggregated Project Total
Committed Story Points	26 SP	26 SP	52 SP
Delivered Story Points	21 SP	26 SP	47 SP (90.4% total delivery rate)
Carried Over Story Points	5 SP (DEF-001)	0 SP	0 SP residual debt
Defect Escape Rate	1 Defect (caught in QA)	0 Defects escaped	0 Defects to production
Sprint Burndown Slope	Disrupted on Day 8 (-5 SP)	Ideal linear slope to 0 SP	100% Sprint 2 completion rate
Automated Test Pass Rate	91.3% (Defect DEF-001 failed)	100% (42/42 tests passing)	100% Final verification status




Figure 35: JIRA-01: DWPG Jira Project & Board Overview. Atlassian Jira project configuration showing DWPG Board #101, Scrum cadence, and 52 total committed story points. [Phase 10: Jira Configuration]



Figure 36: JIRA-02: Product Backlog Prioritization View. Complete product backlog view displaying all 13 work items, user story specifications, priorities, and acceptance criteria. [Phase 9: Product Backlog]



Figure 37: JIRA-03: Sprint 1 Planning Scope Allocation. Sprint 1 scope commitment comprising 26 Story Points allocated across core MVP user stories. [Phase 10: Sprint 1 Planning]






Figure 39: JIRA-05: Sprint 1 Burndown Chart. Burndown curve illustrating velocity drop on Day 8 due to discovery of concurrency race condition defect DEF-001. [Phase 10: Sprint 1 Burndown]

Sprint 2 Planning Security Hardening & Completion			
Duration: 2 Weeks Committed: 26 Story Points Goal: Pessimistic Locks, Idempotency, K8s & QA			
DWPG-15	DEF-001: Race Condition Fix (Pessimistic Locking)	5 SP	Priority: Highest
DWPG-16	Pessimistic Row Locking & Double Spending Defense	5 SP	Priority: Highest
DWPG-17	Mandatory Idempotency-Key & SHA-256 Tamper Binding	5 SP	Priority: Highest
DWPG-18	Merchant Refund Processing & Ledger Reversal	5 SP	Priority: High
DWPG-19	Immutable Transaction History Ledger	3 SP	Priority: Medium
DWPG-21	Containerized Docker & Kubernetes Hardening	3 SP	Priority: High

Figure 40: JIRA-06: Sprint 2 Planning & Hardening Scope. Sprint 2 scope allocation comprising 26 Story Points focused on row locking, idempotency, K8s, and QA. [Phase 10: Sprint 2 Planning]




Figure 41: JIRA-07: Sprint 2 Active Scrum Board. Final Sprint 2 Scrum board with 4 columns showing 100% of user stories and carried-over defect DEF-001 closed in DONE column. [Phase 10: Sprint 2 Board]




Figure 42: JIRA-08: Sprint 2 Burndown Chart. Ideal and actual burndown curve showing smooth trajectory to 0 remaining story points on Day 10. [Phase 10: Sprint 2 Burndown]




Figure 43: JIRA-09: Epic DWPG-2 Authentication Details. Jira Epic card detailing NIST compliance, BCrypt factor 12 hashing, and JWT session handling. [Phase 9: Epic DWPG-2]




Figure 44: JIRA-10: Epic DWPG-3 Wallet Details. Jira Epic card detailing wallet balance provisioning, non-negative balance constraints, and BOLA defense. [Phase 9: Epic DWPG-3]




Figure 45: JIRA-11: Epic DWPG-4 Payment Core Details. Jira Epic card detailing double-entry accounting, atomic debit/credit settlement, and state transitions. [Phase 9: Epic DWPG-4]



Figure 46: JIRA-12: Epic DWPG-5 Refunds & Ledger Details. Jira Epic card detailing authorized refund reversal, duplicate refund prevention, and ledger immutability. [Phase 9: Epic DWPG-5]

DWPG-6: Security Defenses & SIEM Auditing

Epic Key: DWPG-6 | Status: DONE | Points: 15 SP

Security Objective:	Pessimistic DB row locking, mandatory Idempotency-Key header, SHA-256 payload binding, and SIEM logging.
Linked Stories:	DWPG-15 (DEF-001), DWPG-16 (Locking), DWPG-17 (Idempotency), DWPG-20 (SIEM Explorer)
Threat Mitigations:	Race conditions (C-03), Replay attacks (C-05), Parameter tampering
Test Verification:	PaymentConcurrencyTest (10 parallel threads serialized), Idempotency replay trap

Figure 47: JIRA-13: Epic DWPG-6 Security Controls Details. Jira Epic card detailing pessimistic DB row locking, mandatory Idempotency-Key headers, and SIEM logging. [Phase 9: Epic DWPG-6]

DWPG-7: DevSecOps Containerization (Docker/K8s)

Epic Key: DWPG-7 | Status: DONE | Points: 3 SP

Security Objective:	Distroless/Alpine multi-stage Docker builds, non-root execution (UID 10001), dropped capabilities, NetworkPolicies.
Linked Stories:	DWPG-21 (Docker & Kubernetes Hardening)
Threat Mitigations:	Container escape, lateral network traversal, secret exposure
Test Verification:	Live Minikube deployment in dwpg namespace, NetworkPolicy isolation

Figure 48: JIRA-14: Epic DWPG-7 DevSecOps Details. Jira Epic card detailing multi-stage Docker builds, non-root user execution, and Kubernetes manifests. [Phase 9: Epic DWPG-7]




Figure 49: JIRA-15: Epic DWPG-8 Testing & QA Details. Jira Epic card detailing automated unit, integration, concurrency fuzzing, and SonarQube quality gates. [Phase 9: Epic DWPG-8]



Figure 50: JIRA-16: Epic DWPG-9 Compliance Details. Jira Epic card detailing academic evidence validation across all 16 Secure Software Engineering phases. [Phase 9: Epic DWPG-9]




Figure 51: JIRA-17: Daily Scrum Standup Meeting Record. Jira Daily Standup log capturing Yesterday, Today, and Blockers across Lead Architect, FullStack Developer, and QA Security Engineer. [Phase 10: Daily Scrum]




Figure 52: JIRA-18: Sprint 2 Retrospective Record. Jira Sprint Retrospective documenting What Went Well, What Could Be Improved, and 2 concrete Action Items for future engineering. [Phase 10: Retrospective]

11. DevSecOps, Testing and Containerized Deployment (Phases 11-15)

11.1 Secure Development and Build Controls (Phase 11)

The development build pipeline incorporates five distinct automated security controls:

- **Control 1:** 1. Maven Dependency Lock & SHA Verification: All external dependencies are pinned to immutable releases in pom.xml to prevent dependency confusion attacks.

- **Control 2:** 2. Automated Code Coverage Enforcement: JaCoCo plugin enforces a mandatory minimum instruction coverage threshold (>60%) across core domain logic.
- **Control 3:** 3. Static Application Security Testing (SAST): Integrated SonarQube quality gate scanner checking for OWASP Top 10 vulnerabilities during the compile phase.
- **Control 4:** 4. Git Secret Scanning: Automated TruffleHog scanner executing on every push to detect accidentally committed tokens, passwords, or private keys.
- **Control 5:** 5. Hardened Compiler Flags: Strict Java 21 compilation with deprecation warnings treated as errors and null-pointer static analysis checks enabled.

11.2 SonarQube SAST Code Quality & Security Review (Phase 11 & 14)

Static Application Security Testing (SAST) was performed using SonarQube 9.9.8 LTS running in Docker against project key `dwpg-simulator`. The Quality Gate passed with an 'OK' rating, achieving zero vulnerabilities, zero security hotspots, zero bugs, and 62.6% code coverage.




Figure 53: SONAR-01: SonarQube Project Overview. Authenticated SonarQube dashboard showing Quality Gate Passed (Green), 0 Bugs, 0 Vulnerabilities, 0 Hotspots, and 62.6% Coverage. [Phase 11: Quality Gate]




Figure 54: SONAR-02: Quality Gate Conditions Status. Detailed Quality Gate evaluation verifying zero blocker/critical issues and maintainability rating A. [Phase 11: Quality Gate Conditions]




Figure 55: SONAR-03: Zero Vulnerabilities SAST Audit. SonarQube vulnerability report confirming 0 security vulnerabilities across all Java classes. [Phase 14: Vulnerability Audit]




Figure 56: SONAR-04: Security Hotspots Review. *Security Hotspots review console showing 0 unreviewed hotspots (100% security review completeness).* [Phase 14: Hotspot Review]




Figure 57: SONAR-05: JaCoCo Code Coverage Breakdown. *JaCoCo coverage analysis verifying 62.6% instruction coverage across core transactional algorithms.* [Phase 11: Code Coverage]




Figure 58: SONAR-06: Code Duplication Analysis. Duplication analysis confirming 0.0% duplicated line density across 2,375 lines of code. [Phase 11: Code Duplication]




Figure 59: SONAR-07: Maintainability and Technical Debt. Measures console confirming Maintainability Rating A with technical debt ratio under 0.1%. [Phase 11: Technical Debt]

11.3 Containerization with Docker (Phase 13)

The backend and frontend are packaged using multi-stage Dockerfiles. The backend build utilizes Eclipse Temurin OpenJDK 21 for compilation and packages the runnable JAR on a minimal Alpine runtime. Execution is strictly constrained to an unprivileged non-root user (UID 10001, GID 10001) with all Linux capabilities dropped (`cap_drop: ALL`).




Figure 60: Multi-Stage Docker Container Architecture. Multi-stage build pipelines isolating Maven compile dependencies from lightweight runtime containers (authored in Draw.io). [Phase 13: Docker Architecture]

```
sathvik@ubuntu:~/sse_project_lab_exam$ docker ps --format 'table {{.Names}}\n{{.Status}}\n{{.Ports}}'
```

NAMES	STATUS	PORTS
sonarqube	Up 4 hours	0.0.0.0:9000->9000/tcp
dwpg-mariadb-local	Up 3 hours	0.0.0.0:3306->3306/tcp
minikube	Up 4 hours	127.0.0.1:49153->22/tcp, 127.0.0.1:49154->8443/tcp

Figure 61: Verified Live Docker Runtime Status. Terminal capture of running containers verifying sonarqube, dwpg-mariadb-local, and Minikube virtualization engine. [Phase 13: Docker Evidence]

11.4 Kubernetes Orchestration and Minikube (Phase 13)

Production deployment is orchestrated via 11 declarative Kubernetes manifests deployed into the dedicated `dwpg` namespace on Minikube. A default-deny NetworkPolicy (`isolate-mariadb`) ensures the MariaDB database pod only accepts ingress TCP connections on port 3306 from pods labeled `app=dwpg-backend`, preventing lateral traversal.




Figure 62: Kubernetes Pod Topology and Network Isolation. Cluster architecture illustrating dwpg namespace, ConfigMap/Secret bindings, and NetworkPolicy firewall barriers (authored in Draw.io). [Phase 13: Kubernetes Architecture]

```
sathvik@ubuntu:~/sse_project_lab_exam$ kubectl get all,networkpolicy -n dwpg
```

NAME	READY	STATUS	RESTARTS	AGE
pod/dwpg-backend-6c9c444b66-9l7l1	1/1	Running	0	45m
pod/dwpg-backend-6c9c444b66-nsm5s	1/1	Running	0	45m
pod/dwpg-frontend-64796679f6-2nf9d	1/1	Running	0	45m
pod/dwpg-mariadb-764985446-q6kqp	1/1	Running	0	45m

NAME	TYPE	CLUSTER-IP	PORT(S)	AGE
service/dwpg-backend-service	ClusterIP	10.110.48.46	8080/TCP	45m
service/dwpg-frontend-service	NodePort	10.111.214.148	3000:30080/TCP	45m
service/dwpg-mariadb-service	ClusterIP	10.96.193.236	3306/TCP	45m

NAME	POD-SELECTOR	AGE
networkpolicy.networking.k8s.io/isolate-mariadb	app=mariadb	45m

Figure 63: Verified Live Kubernetes Workloads in dwpg Namespace. Terminal capture of `kubectl get all,networkpolicy -n dwpg` verifying healthy pods, services, and isolated network policies. [Phase 13: Kubernetes Evidence]

11.5 CI/CD Pipeline and Git Version Control (Phase 14)

The continuous integration and delivery pipeline is configured via GitHub Actions (`.github/workflows/ci.yml`). Every git commit triggers automated compilation, JUnit 5 execution, JaCoCo code coverage analysis, and SonarQube SAST analysis.




Figure 64: DevSecOps CI/CD Pipeline Workflow. Automated pipeline stages: Git Push -> Build -> Unit Test -> SAST Scan -> Quality Gate -> Container Build -> K8s Deploy (authored in Draw.io). [Phase 14: CI/CD Pipeline]




Figure 65: Automated Security Testing Pipeline Architecture. Integration of static code analysis (SonarQube), dynamic concurrency testing, and fuzzing checks (authored in Draw.io). [Phase 14: Security Pipeline]

```

sathvik@ubuntu:~/sse_project_lab_exam$ git log --graph --oneline -n 8

* 33e6295 (HEAD -> main, origin/main) feat(drawio): fulfill step 7 with 24 drawio sources, png/svg exports
* 2c0bfdc feat(capstone): complete 16-phase academic finalization, 62 empirical evidence figures
* e951af1 docs: mirror Phase 13 and 14 documentation to alternate folder names
* 6c45d6d feat(phase16): add master final examination report, traceability matrix, and audit certification
* 7537e3f feat(phase15): add system hardening checklists, secure deployment criteria, and SIEM logging plan
* 41e432e feat(phase14): add GitHub Actions DevSecOps workflow and CI/CD security report
* b1c449f feat(phase13): add hardened containerization with Docker, Kubernetes manifests, and security report
* a145cb5 docs(phase12): add secure coding refactoring evidence and defect remediation report
  
```

Figure 66: Git Commit Audit Trail & Semantic Versioning History. Terminal capture of git log --graph --oneline verifying chronological commits for all 16 academic phases. [Phase 11: Git Audit Trail]

11.6 Automated Test Suite and Security Verification (Phase 14)

Testing encompasses 25 JUnit 5 backend tests, 9 live REST functional integration tests, and 8 adversarial security property probes. All 42 tests passed with a 100% success rate.

Test Suite Domain	Tests Run	Passed	Failed	Key Properties Verified
JUnit 5 AuthServiceTest	3	3	0	BCrypt cost 12 hashing, JWT signature issuance, invalid credentials rejection.
JUnit 5 WalletServiceTest	3	3	0	Atomic provisioning, balance non-negative domain invariant, BOLA tenant isolation.
JUnit 5 PaymentSecurityTest	6	6	0	Idempotency caching, replay detection, duplicate refund rejection, RBAC filters.
JUnit 5 Concurrency Stress Test	1	1	0	10 simultaneous threads racing on \$100 balance: exactly 2 succeed (\$50+\$50), 8 rejected.
JUnit 5 Input Fuzzing Suite	12	12	0	Negative amounts, NaN, integer overflow, SQL injection tokens, XSS script injection probes.
Live REST Functional Suite	9	9	0	End-to-end API verification of auth, wallet, merchant, payment, ledger, and refunds.
Live Security Property Suite	8	8	0	Adversarial probes: BOLA cross-query, replay tampering, overdraft, privilege escalation.
Total Test Execution	42	42	0	100% PASSED (0 FAILURES, 0 ERRORS)

12. Secure Coding and Refactoring (Phase 12)

12.1 Defect DEF-001 Remediation: Pessimistic Row Locking

As detailed in Phase 1 and Phase 10, the discovery of DEF-001 necessitated refactoring the persistence tier to use pessimistic write locks. The code below illustrates the exact before-and-after implementation:

```
// DEF-001 Fix: Repository Method Refactoring
```

```
// BEFORE: Vulnerable optimistic/unlocked query allows race conditions
public interface WalletRepository extends JpaRepository<Wallet, Long> {
    Optional<Wallet> findById(Long userId);
}

// AFTER: Pessimistic Row Locking forces MariaDB SELECT ... FOR UPDATE
public interface WalletRepository extends JpaRepository<Wallet, Long> {
    @Lock(LockModeType.PESSIMISTIC_WRITE)
    @Query("SELECT w FROM Wallet w WHERE w.userId = :userId")
    Optional<Wallet> findByIdWithLock(@Param("userId") Long userId);
}
```

12.2 Replay Attack Remediation: Idempotency Service

The second major refactoring addressed transaction replays. When an incoming payment arrives with an Idempotency-Key, the system calculates a SHA-256 hash of the request body and verifies whether a record already exists:

```
// Replay Fix: Idempotency Service Logic
@Service
public class IdempotencyService {
    @Transactional
    public Optional<IdempotencyRecord> checkReplay(String key, String payloadHash) {
        Optional<IdempotencyRecord> existing = repo.findByIdempotencyKey(key);
        if (existing.isPresent()) {
            if (!existing.get().getPayloadHash().equals(payloadHash)) {
                // Adversary modified parameters under existing key!
                auditService.logEvent(AuditEventType.REPLAY_DETECTED, "TAMPER_DETECTED");
                throw new IdempotencyTamperingException("Payload mismatch for key: " + key);
            }
            // Legitimate retry: return cached response
            return existing;
        }
        return Optional.empty();
    }
}
```

13. Logging, SIEM and System Hardening (Phase 15)

13.1 Twelve Core Security Event Types

The AuditService records twelve distinct security event types defined in the AuditEventType enum:

Event Type Enum	Triggering Condition	Recorded Telemetry Fields	SIEM Threat Severity
LOGIN_SUCCESS	Principal successfully authenticated with valid	Actor, IP, Timestamp, Outcome	Informational

	credentials.		
LOGIN_FAILURE	Authentication failed due to incorrect password or bad username.	Actor, IP, Timestamp, Details	Warning (Brute-Force)
AUTHORIZATION_FAILURE	Authenticated user attempted accessing unprivileged role endpoint.	Actor, Resource ID, IP, Outcome	High (Privilege Escalation)
WALLET_CREATED	New digital wallet provisioned for user account.	Actor, Wallet ID, IP, Outcome	Informational
FUNDS_ADDED	Customer deposited simulated funds into wallet balance.	Actor, Amount, IP, Timestamp	Informational
PAYMENT_INITIATED	Payment checkout transaction received and validated.	Actor, Merchant ID, Amount, Key	Informational
PAYMENT_CONFIRMED	Payment successfully settled via double-entry ledger commit.	Actor, Payment ID, Tamper Hash	Informational (Financial)
PAYMENT_FAILED	Payment rejected due to insufficient balance or domain error.	Actor, Error Message, IP, Key	Low
PAYMENT_REFUNDED	Confirmed payment successfully reversed and restored.	Actor, Payment ID, Reversal Amt	Informational (Financial)
REPLAY_DETECTED	Duplicate Idempotency-Key submitted with mismatched payload.	Actor, Idempotency Key, IP	Critical (Fraud Attempt)
DUPLICATE_PAYMENT	Duplicate transaction intercepted and served from cache.	Actor, Payment ID, Original Timestamp	Notice
SUSPICIOUS_ACTIVITY	Excessive request rate or anomalous parameter patterns.	Actor, IP, Trigger Pattern	High (Adversarial Activity)

13.2 Five Key Security Monitoring Telemetry Metrics

Telemetry Metric	Baseline Normal Range	Alert Threshold	Forensic Investigation Protocol
Failed Login Rate	< 2% of total auth attempts	> 5 failures / min per IP	Temporarily rate-limit IP; verify potential credential stuffing.
Replay Attack Rejection Rate	0 incidents under normal operation	>= 1 incident	Inspect Idempotency-Key and payload diff in SIEM Explorer.
Lock Wait Time (Pessimistic)	< 15 ms average lock acquisition	> 500 ms wait time	Check for thread contention; investigate potential

			concurrency burst.
Payment Rejection Rate	< 5% (legitimate low funds)	> 20% within 10 min window	Audit user balances; check for scripted overdraft probing.
Refund-to-Payment Ratio	< 3% of settled transactions	> 15% ratio per merchant	Flag merchant account for review; assess dispute abuse.

13.3 Twelve-Domain System Hardening Checklist

Hardening Domain	Applied Hardening Configuration	Audit Verification Status
1. Authentication	BCrypt cost factor 12; NIST SP 800-63B password complexity.	VERIFIED
2. Session Management	Stateless HMAC-SHA256 JWT tokens; strict 1-hour expiration.	VERIFIED
3. Authorization (RBAC)	Method-level @PreAuthorize; strict separation of USER, MERCHANT, ADMIN.	VERIFIED
4. Database Concurrency	SELECT ... FOR UPDATE pessimistic row locks; READ_COMMITTED isolation.	VERIFIED
5. Idempotency & Replay	Mandatory Idempotency-Key with SHA-256 payload binding.	VERIFIED
6. Input Validation	Jakarta Validation (@Positive, @NotNull); DB level CHECK constraints.	VERIFIED
7. Sensitive Data Protection	Regex scrubbing of PAN, CVV, passwords; zero plaintext credentials.	VERIFIED
8. Container Hardening	Multi-stage Docker builds; unprivileged user UID 10001; dropped capabilities.	VERIFIED
9. Network Isolation	Kubernetes default-deny NetworkPolicy isolating MariaDB on port 3306.	VERIFIED
10. Secrets Governance	Kubernetes Secrets decoupled from source control; zero hardcoded tokens.	VERIFIED
11. SAST Governance	SonarQube Quality Gate enforced with 0 blocker/critical issues.	VERIFIED
12. Forensic Logging	Append-only immutable audit_logs table; IP address & correlation IDs.	VERIFIED

13.4 Physical and Operational Security Controls

- Physical Isolation: In production, database servers are isolated in secure data center enclaves with biometric multi-factor access control and 24/7 video surveillance. Virtualized containers run in private VPC subnets with zero direct public IP exposure.

- Operational Governance: Administrative access is strictly restricted to designated Site Reliability Engineers (SRE) connecting over mutual-TLS bastion hosts with session recording and mandatory peer approvals.

14. Traceability Matrix and Conclusion (Phase 16)

14.1 End-to-End Requirement-to-Artifact Traceability Matrix

The traceability matrix ensures full bidirectional verification linking initial requirements to UML models, database schemas, code classes, automated test cases, and academic evidence artifacts.

Req ID	Phase / Category	Design & UML Model	Source Implementation	Automated Test Case	Academic Evidence
FR-01	Phase 2 / Auth	UC-01, DFD 1.0 (D-03, D-07)	AuthController, AuthService	TC-AUTH-001, AuthServiceTest	UI-01, JIRA-09
FR-02	Phase 2 / Auth	Sequence Diagram (D-12)	JwtTokenProvider, SecurityConfig	TC-AUTH-002, SEC-TEST-001	UI-02, JIRA-09
FR-03	Phase 2 / Wallet	ERD (D-05), DFD 2.0 (D-07)	WalletController, WalletService	TC-WAL-001, WalletServiceTest	UI-03, JIRA-10
FR-04	Phase 2 / Wallet	Analysis Model (D-04)	WalletService.fund Wallet	TC-WAL-002, SEC-TEST-002	UI-04, UI-05, JIRA-10
FR-05	Phase 2 / Merchant	ERD (D-05)	MerchantController, MerchantService	TC-MER-001	UI-06, UI-07, JIRA-10
FR-06	Phase 2 / Payment	Sequence Diagram (D-14)	PaymentController .initiatePayment	TC-PAY-001, SEC-TEST-003	UI-08, JIRA-11
FR-07	Phase 2 / Payment	Component Model (D-10)	PaymentService.processPayment	TC-PAY-001, PaymentConcurrencyTest	UI-09, UI-10, JIRA-11
FR-08	Phase 2 / Refund	Sequence Diagram (D-15)	RefundController, RefundService	TC-REF-001, SEC-TEST-006	UI-12, UI-13, JIRA-12
FR-09	Phase 2 / Ledger	ERD (D-05), DFD 3.0 (D-07)	TransactionController, TransactionService	TC-LED-001	UI-11, JIRA-12
FR-10	Phase 2 / SIEM	Trust Boundary (D-08)	AdminController, AuditService	TC-ADM-001, SEC-TEST-008	UI-15, JIRA-13
SR-03	Phase 7 / Replay	Attack Tree (D-18), Seq (D-16)	IdempotencyService, IdempotencyRecord	SEC-TEST-003, SEC-TEST-004	UI-14, JIRA-13
SR-04	Phase 7 / Concurrency	Security Arch (D-19)	WalletRepository.findByIdWithLock	PaymentConcurrencyTest (10 th)	JIRA-04, JIRA-13




Figure 67: Requirements-to-Verification Traceability Model. Bidirectional graph mapping functional requirements, threat vectors, security controls, and verification evidence (authored in Draw.io). [Phase 16: Traceability Matrix]

14.2 Academic Evidence Checklist

Phase	Curricular Requirement	Implemented Artifact	Verification Status
Phase 1	Agile Process & Approach	Scrum 2-sprint plan, daily standup logs, retrospective	VERIFIED (Figure 1, Draw.io D-01)
Phase 2	Requirements Engineering	10 Functional, 6 NFR, 8 Security Requirements documented	VERIFIED (Tables 3-5)
Phase 3	Requirements Analysis & UML	Context, Use Case, BCE Analysis, 5 Sequence Diagrams	VERIFIED (Figures 2-9, Draw.io D-02..04, D-12..16)
Phase 4	Data & Information Flow	3NF ERD, DFD Level 0, DFD Level 1, Trust Perimeter	VERIFIED (Figures 10-13, Draw.io D-05..08)
Phase 5	Software Architecture	Layered Architecture, Component, Physical Deployment	VERIFIED (Figures 14-16, Draw.io D-09..11)
Phase 6	User Interface Design	15 High-res real Playwright UI screenshots (UI-01..15)	VERIFIED (Figures 17-31)
Phase 7	Threat Modeling (STRIDE)	8 Assets CIA, 10 STRIDE threats, DREAD scoring, 6 Vulns	VERIFIED (Figure 32, Draw.io D-17)
Phase 8	Attack Tree Analysis	Double spending attack tree & refined security architecture	VERIFIED (Figures 33-34, Draw.io D-18..19)
Phase 9	Product Backlog & Jira	13 Stories in Jira, product-backlog.csv, 8 Epics	VERIFIED (Table 9, Figure 36)
Phase 10	Sprint Metrics & Scrum	18 Authentic Jira figures (JIRA-01..18), burndown curves	VERIFIED (Figures 35-52)
Phase 11	Secure Build Environment	Maven, JaCoCo, SonarQube LTS integration (7 figures)	VERIFIED (Figures 53-59)
Phase 12	Secure Coding & Refactoring	Pessimistic DB row locking,	VERIFIED (Chapter 12 Code

		BCrypt cost 12, Idempotency	Blocks)
Phase 13	Docker & Kubernetes	Multi-stage Dockerfile, 11 K8s YAMLS in dwpg namespace	VERIFIED (Figures 60-63, Draw.io D-20..21)
Phase 14	CI/CD & Security Testing	GitHub Actions ci.yml, 42 automated tests (100% pass)	VERIFIED (Figures 64-66, Draw.io D-22..23, Table 12)
Phase 15	Logging, SIEM & Hardening	Centralized AuditService, 12 event types, NetworkPolicy	VERIFIED (Chapter 13 Tables, Figure 31)
Phase 16	Final Security Review	Traceability matrix, compliance report, zero vulnerabilities	VERIFIED (Figure 67, Draw.io D-24)

14.3 Residual Risks, Limitations, and Future Work

- **Residual Risk 1:** 1. High-Contention Database Lock Latency: Under extreme concurrent load against a single hot wallet (e.g. flash-sale merchant settlement wallet), pessimistic row locking introduces queueing latency. Mitigation: Implement Redis distributed locks with optimistic retry backoff or partition high-traffic merchant balances across sub-accounts.
- **Residual Risk 2:** 2. Idempotency Key Storage Growth: The relational idempotency cache table grows linearly with transaction volume. Mitigation: Configure scheduled MariaDB partition pruning or transition historical idempotency records to a TTL-indexed Redis cluster after 24 hours.
- **Residual Risk 3:** 3. JWT Invalidation Latency: Stateless JWT tokens cannot be revoked before their 1-hour expiration without introducing a shared token blacklist. Mitigation: Shorten JWT access token lifetimes to 15 minutes paired with rotating refresh tokens stored in HTTP-only secure cookies.
- **Limitation 1:** 1. Simulated Financial Rails: The application strictly simulates balances and settlements without integrating with real clearinghouses (Fedwire, ACH, SWIFT) or handling international currency FX conversions.
- **Limitation 2:** 2. In-Cluster Database Architecture: The MariaDB instance runs as a single Kubernetes pod backed by persistent storage rather than a multi-region active-active cluster (e.g. MariaDB Galera or CockroachDB).
- **Future Work 1:** 1. Hardware Security Module (HSM) Integration: Transitioning the HMAC secret and merchant private keys from Kubernetes Secrets to dedicated cloud or physical HSMs (e.g. AWS CloudHSM or HashiCorp Vault with PKCS#11).
- **Future Work 2:** 2. Distributed Idempotency via Redis: Upgrading the relational idempotency cache to a low-latency Redis cluster with atomic SETNX distributed locking to handle horizontal scaling across multi-region gateway clusters.
- **Future Work 3:** 3. Real-Time Fraud ML Inference: Embedding an ONNX-runtime machine learning microservice that calculates behavioral anomaly risk scores on payment initiation prior to locking.

14.4 Closing Summary

The Digital Wallet and Payment Gateway Simulator represents a fully engineered, robustly tested, and empirically validated academic capstone submission. Every single line of production code, database constraint, Kubernetes manifest, and security control was developed to solve real-world financial vulnerabilities: eliminate double-

spending, trap replay attacks, maintain immutable audit ledgers, and guarantee non-negative balance invariants under heavy parallel load. The project achieved a perfect 100% pass rate across 42 automated backend and security tests, satisfied all SonarQube Quality Gate parameters with zero vulnerabilities, and successfully proved the efficacy of embedding security across all 16 phases of the Secure Software Engineering lifecycle.