

A Project Report on

**HYBRID IOT-ML SYSTEM FOR PREDICTIVE FOR
RAILWAY BRIDGE FLOOD RISK DETECTION**

Submitted in partial fulfilment of the requirements for the award of the degree of

BACHELOR OF TECHNOLOGY

IN

ELECTRONICS AND COMMUNICATION ENGINEERING

J N T UNIVERSITY, KAKINADA

Submitted by

**K. GNANA SATHWIKA
(22F01A04C4)**

**G. HARIKA
(22F01A0470)**

**K. KEERTHANA
(22F01A04B9)**

**K. VENKATA NAVYA
(22F01A04A5)**

**K. BHARGAVI
(22F01A04D1)**

Under the Esteemed Guidance of

**N. SYAMALA
Assistant Professor**



DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

ST. ANN'S COLLEGE OF ENGINEERING & TECHNOLOGY, CHIRALA

(Approved by AICTE New Delhi, Permanently Affiliated to JNTUK, Kakinada)

(Accredited by NAAC with 'A' Grade, NBA & IE (I))

2022-2026

**ST. ANN'S COLLEGE OF ENGINEERING & TECHNOLOGY
(AUTONOMOUS)**

CHIRALA

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING



CERTIFICATE

This is to certify that the project report entitled **“HYBRID IOT-ML SYSTEM FOR PREDICTIVE FOR RAILWAY BRIDGE FLOOD RISK DETECTION”**

is submitted by **K. GNANA SATHWIK (22F01A04C4), G. HARIKA (22F01A0470), K. KEERTHANA (22F01A04B9), K. VENKATA NAVYA (22F01A04A5), K. BHARGAVI (22F01A04D1)** who carried out under my guidance and supervision, as a partial fulfilment for the award of **BACHELOR OF TECHNOLOGY in ELECTRONICS AND COMMUNICATION ENGINEERING** of St. Ann's College of Engineering & Technology (Autonomous), Chirala.

Viva Voce Date: _____.

Internal Guide

N. Syamala

Head of the Department

Dr. D. Rajendra Prasad

External Examiner

ACKNOWLEDGEMENT

The successful completion of any work is not possible without proper suggestions, guidance and environment. Combination of these three factors acts like backbone to our project entitled **“HYBRID IOT-ML SYSTEM FOR PREDICTIVE FOR RAILWAY BRIDGE FLOOD RISK DETECTION”**.

We express our sincere thanks to our guide **N. Syamala**, and Head of the department of Electronics and Communication and Engineering, **DR. D Rajendra Prasad, M. Tech ,Ph.D**, for timely help, guidance and providing us with the most essential materials required for the completion of this work. His invaluable moral support and guidance throughout the project helped us to a greater extent. We are thankful to his valuable suggestions and discussions during this project.

We would like to thank our Principal, **Dr K. Jagadeesh Babu, M. Tech., Ph.D.**, for providing support and simulating environment. We would like to express our gratitude to the management of St. Ann’s College of Engineering & Technology for providing us with a pleasant and Excellent Laboratory facilities.

We would be thankful to all the teaching and non-teaching staff of the department of Electronics and Communication Engineering for the co-operation given for the successful completion of project.

Last but not least, we express our heartfelt thanks to all our friends for all help and co-operation extended in bringing out this project successfully in time.

PROJECT ASSOCIATES

K. Gnana Sathwika	(22F01A04C4)
G. Harika	(22F01A0470)
K. Keerthana	(22F01A04B9)
K. Venkata Navya	(22F01A04A5)
K. Bhargavi	(22F01A04D1)

DECLARATION

This is to certify that the thesis titled “**HYBRID IOT-ML SYSTEM FOR PREDICTIVE FOR RAILWAY BRIDGE FLOOD RISK DETECTION**” under the guidance of **N. Syamala** is a Bonafide work done by me, in partial fulfilment of the requirements for the award of the degree of **Bachelor of Technology** and submitted to the Department of Electronics & Communication Engineering, **St. Ann’s College of Engineering & Technology, (Autonomous), Chirala.**

I also declare that this project is a result of my own effort and that has not been copied from anyone and I have taken only citations from the sources which are mentioned in the references.

This work was not submitted earlier at any other University or institute for the award of any degree.

Place: SACET, Chirala.

K. Gnana Sathwika

Date:

(22F01A04C4)

CONTENTS

TOPIC NAME	Page No.
LIST OF FIGURES	i
ABSTRACT	ii
CHAPTER 1: INTRODUCTION	1
1.1 Introduction	1-2
1.2 Literature Survey	2
1.2.1- IoT-Based Flood Monitoring System	2-3
1.2.2- Hybrid Machine Learning Models for Flood Forecasting	3
1.2.3- Machine Learning Techniques for Flood Prediction	3-4
1.2.4- Deep Learning Approach for Flood Prediction	4
1.2.5- IoT and Machine Learning Integrated Flood Warning System	4-5
1.2.6- AI-Based Disaster Management Systems	5
1.2.7- Edge Computing for IoT-Based Flood Monitoring	5-6
1.2.8- Smart Bridge Monitoring System Using IoT	6
1.2.9- Predictive Analytics for Smart Infrastructure	6
CHAPTER 2: EXISTING AND PROPOSED SYSTEM	7-12
2.1 Existing System	7
2.1.1- Manual Flood Monitoring	7-8
2.1.2- IoT-Based Flood Monitoring System	8
2.1.3- Machine Learning-Based Flood Prediction Systems	8-9
2.1.4- Bridge Monitoring Systems	9
2.2 Proposed System	9-11
2.2.1 Advantages	11-12
CHAPTER 3: BLOCK DIAGRAM AND DESCRIPTION	13-14
3.1 Block Diagram	13
3.1.1 Description	13-14
CHAPTER 4: HARDWARE COMPONENTS AND SOFTWARE TOOLS	15-34
4.1 Hardware components	15
4.1.1- Raspberry pi-w	15-18

4.1.2-Water Level Sensor	18-20
4.1.3-Vibration Sensor	20-21
4.1.5-MQ-5 Gas Sensor	21-22
4.1.6-LCD (Liquid crystal Display)	22-24
4.1.7-LED (Light Emitting Diode)	24-26
4.2 Software Tools	26
4.2.1-Python Programming language	26-28
4.2.2-C++ Programming Language	28-29
4.2.3-Machine Learning	29-32
4.2.4-IOT Communication Protocols	32-33
4.2.5-WSN (Wireless Sensor Network)	33-34
CHAPTER 5: SOFTWARE CODE	35-38
CHAPTER 6: ADVANTAGES	39-40
CHAPTER 7: APPLICATIONS	41-42
CHAPTER 8: FUTURE SCOPE	43-44
CHAPTER 9: RESULT	45-47
CHAPTER 10: CONCLUSION	48
REFERENCES	49-50

LIST OF FIGURES

FIGURE NO	NAME OF THE FIGURE	PAGE NO.
Fig.3.1	Block Diagram	13
Fig.4.1.1	Raspberry pi	15
Fig.4.1.1(a)	Raspberry pi-w	16
Fig.4.1.2	Water level Sensor	19
Fig.4.1.3	Vibration Sensor	20
Fig.4.1.4	MQ-5 Sensor	22
Fig.4.1.5	Liquid Crystal Display	23
Fig.4.1.5(a)	LCD Pin Description	23
Fig.4.1.6	Light Emitting Diode	25
Fig.4.2.4	Iot Communication Protocols	32
Fig.4.2.5	Wireless Sensor Network	34
Fig.9.1	Water level Sensor output	45
Fig.9.2	MQ-5 Sensor output	46
Fig.9.3	Vibration Sensor output	47
Fig.9.3(a)	Output in serial monitor	47

ABSTRACT

Flood-induced structural failures of railway bridges pose serious risks to transportation safety, infrastructure integrity, and operational continuity, particularly during extreme weather conditions. Timely detection and accurate prediction of flood situations are essential to prevent accidents, structural damage, and service interruptions. This work proposes a hybrid Internet of Things (IoT) and Machine Learning (ML)–based predictive flood risk detection system tailored for railway bridge environments. The system integrates water-level sensing, vibration monitoring, and environmental gas detection using an MQ-5 sensor, all connected to a Raspberry Pi Zero W–based edge-processing unit. These sensors continuously monitor both environmental and structural parameters affecting flood risk, while real-time data are collected through an IoT-enabled wireless sensor network.

A machine learning model is trained using historical flood data along with real-time sensor inputs to identify complex patterns associated with flood development. Unlike traditional threshold-based methods, the proposed ML approach classifies flood risk into multiple levels such as normal, warning, and danger, enabling early detection and proactive safety measures. This predictive capability supports timely decision-making by railway authorities, including traffic regulation, maintenance planning, and emergency response. The system also provides local alerts through an LCD display and buzzer for immediate on-site warnings, while simultaneously transmitting data to a centralized remote monitoring station via wireless communication. Overall, the proposed hybrid IoT-ML system offers a cost-effective, intelligent, and scalable solution for real-time and predictive flood risk detection, enhancing the safety, reliability, and long-term sustainability of railway bridge infrastructure across diverse conditions.

Keywords:

IoT, Machine Learning, Flood Risk Detection, Railway Bridges, Raspberry Pi, Wireless Sensor Network, Structural Health Monitoring.

CHAPTER-1

1.1 INTRODUCTION

Flooding is one of the most critical and recurring natural hazards affecting railway infrastructure, particularly railway bridges constructed near rivers, canals, floodplains, and other low-lying regions. Climate change, irregular rainfall patterns, and increasing frequency of extreme weather events have further intensified flood occurrences in recent years. Sudden and uncontrolled increases in water level, flow velocity, and debris movement during heavy rainfall can severely impact railway bridges, leading to scour at foundations, erosion of embankments, and progressive structural weakening. In extreme cases, such conditions may result in partial or complete bridge collapse, posing severe threats to passenger safety and causing catastrophic loss of life.

Railway bridge failures due to flooding not only endanger human lives but also cause large-scale disruption of railway services, significant economic losses, and long-term damage to critical transportation infrastructure. Delays in train operations, rerouting of services, and expensive repair or reconstruction activities impose a heavy financial burden on railway authorities. Therefore, ensuring early detection, accurate prediction, and timely warning of flood risks at railway bridge locations is essential for maintaining safe, reliable, and uninterrupted railway operations.

Traditional flood monitoring systems used in railway infrastructure are largely reactive in nature and depend on fixed threshold values of water level or rainfall intensity. These limitations highlight the urgent need for an intelligent, adaptive, and predictive flood monitoring solution.

To address these challenges, the proposed system introduces a hybrid Internet of Things (IoT) and Machine Learning (ML)-based approach for predictive flood risk detection in railway bridge environments. The proposed solution combines real-time sensing, edge computing, and data-driven intelligence to enhance flood risk assessment accuracy and response speed. By integrating multiple sensing parameters and intelligent analysisThe system employs a water-level sensor positioned near the bridge pier to continuously monitor changes in water height caused by rainfall or upstream flooding. Water level is a critical parameter in assessing flood severity and potential submergence risk. Additionally, a vibration sensor is installed on the

bridge structure to detect abnormal vibrations resulting from strong water currents, debris impact, or structural stress. Such vibrations often act as early indicators of structural instability or foundation erosion, providing valuable insight into the health of the bridge during flood conditions.

An MQ-5 gas sensor is incorporated to monitor variations in environmental gas concentration that may arise due to water stagnation, sewage overflow, or the release of hazardous gases during floods. Although gas sensing is not a direct measure of flood level, it contributes to enhanced situational awareness by indicating abnormal environmental conditions around the bridge location, thereby improving overall safety monitoring.

All sensor data are interfaced with a Raspberry Pi Zero W, which serves as the edge-processing unit of the system. The Raspberry Pi collects real-time sensor readings and performs local data processing to minimize communication latency and reduce dependence on cloud infrastructure.

A machine learning model is trained using a combination of historical flood data and real-time sensor inputs to learn complex relationships between water level variations, vibration patterns, and environmental conditions. Based on these learned patterns, the ML algorithm classifies flood risk into multiple levels such as normal, warning, and danger.

1.2 LITERATURE SURVEY

1.2.1. IoT-Based Flood Monitoring System

Authors: S. Kumar, R. Singh, P. Sharma

Published: 2021

Abstract:

This paper presents an IoT-based flood monitoring system that uses water level sensors and wireless communication to track flood conditions in real time. The system sends data to a cloud platform, enabling remote monitoring and early warning alerts..

Introduction:

Flood monitoring is essential for minimizing damage to infrastructure and human life. Traditional monitoring systems rely heavily on manual observation, which can be inefficient and delayed. The integration of Internet of Things (IoT) technology has enabled automated

data collection through sensors that continuously measure environmental parameters such as water levels and flow rates. The proposed system utilizes sensor nodes placed in flood-prone areas to collect real-time data and transmit it via wireless networks to cloud-based platforms.

1.2.2. Hybrid Machine Learning Models for Flood Forecasting

Authors: N. Reddy, V. Kumar

Published: 2023

Abstract:

This paper proposes hybrid machine learning models that combine multiple algorithms to enhance flood prediction accuracy. The approach reduces prediction errors and improves reliability by leveraging the strengths of different models.

Introduction:

Single machine learning models often face limitations in handling complex and uncertain environmental data. Hybrid models address this issue by combining multiple algorithms, such as neural networks and optimization techniques, to achieve better performance. Despite these advantages, the model lacks integration with real-time data acquisition systems like IoT, making it less effective for live monitoring applications.

1.2.3. Machine Learning Techniques for Flood Prediction

Authors: A. Verma, K. Gupta

Published: 2022

Abstract:

This study explores the application of machine learning algorithms such as Artificial Neural Networks (ANN), Support Vector Machines (SVM), and Random Forest for flood prediction. The results show improved accuracy compared to traditional statistical methods, enabling better forecasting of flood events.

Introduction:

Flood prediction has traditionally been performed using statistical and hydrological models, which often fail to capture complex environmental patterns. Machine learning

techniques have emerged as a powerful alternative due to their ability to learn from historical data and identify nonlinear relationships. However, the system relies mainly on past data and does not integrate real-time sensor inputs, which limits its effectiveness in dynamic conditions.

1.2.4. Deep Learning Approach for Flood Prediction

Authors: R. Das, M. Chatterjee

Published: 2024

Abstract:

This paper introduces deep learning models for flood prediction using large-scale environmental datasets. The approach achieves high accuracy by analyzing complex temporal and spatial patterns in flood data.

Introduction:

Deep learning techniques have gained popularity in flood prediction due to their ability to process large and complex datasets. Models such as recurrent neural networks (RNNs) and convolutional neural networks (CNNs) are used to analyze time-series and spatial data. However, it requires high computational resources and large datasets, making it less suitable for real-time embedded systems.

1.2.5. IoT and Machine Learning Integrated Flood Warning System

Authors: K. Patel, D. Shah

Published: 2023

Abstract:

This study presents an integrated system combining IoT and machine learning for flood monitoring and prediction. The system collects real-time data using sensors and applies ML algorithms to forecast flood risks and generate alerts.

Introduction:

The integration of IoT and machine learning provides a comprehensive solution for flood management by combining real-time monitoring with predictive analytics. IoT devices

collect environmental data, which is then processed by ML models to predict future flood conditions.

1.2.6. AI-Based Disaster Management Systems

Authors: S. Nair, P. Menon

Published: 2024

Abstract:

This paper discusses the application of Artificial Intelligence in disaster management, including flood prediction, risk assessment, and emergency response planning. AI models improve decision-making and reduce disaster impact.

Introduction:

Artificial Intelligence has become a key technology in disaster management due to its ability to process large volumes of data and generate accurate predictions. AI-based systems can analyze weather patterns, environmental conditions, and historical data to forecast disasters. These systems support authorities in planning and response activities. However, challenges such as data availability and system integration still exist.

1.2.7. Edge Computing for IoT-Based Flood Monitoring

Authors: K. Lee, J. Park

Published: 2023

Abstract:

This paper introduces an edge computing approach for IoT-based flood monitoring systems. Data processing is performed near the sensor nodes, reducing latency and improving response time.

Introduction:

Traditional IoT systems rely on cloud computing, which can introduce delays in data processing. Edge computing addresses this issue by processing data closer to the source. In flood monitoring systems, this enables faster decision-making and real-time alerts. However,

edge devices have limited computational capacity, which restricts the use of complex machine learning models.

1.2.8. Smart Bridge Monitoring System Using IoT

Authors: R. Patel, V. Joshi

Published: 2023

Abstract:

This study presents an IoT-based smart bridge monitoring system that tracks structural health parameters such as vibration, load, and environmental conditions. The system helps in maintaining bridge safety and preventing failures.

Introduction:

Bridge safety is critical for transportation systems, especially during extreme environmental conditions like floods. IoT-based monitoring systems use sensors to continuously track structural parameters. The collected data helps in identifying potential risks and taking preventive measures..

1.2.9. Predictive Analytics for Smart Infrastructure

Authors: D. Roy, A. Banerjee

Published: 2022

Abstract:

This study focuses on predictive analytics techniques for smart infrastructure systems, including bridges and transportation networks. It highlights the role of data-driven models in risk prediction and maintenance planning.

Introduction:

Smart infrastructure systems rely on predictive analytics to improve efficiency and safety. By analysing sensor data and historical records, predictive models can identify potential risks and failures. This approach is particularly useful for infrastructure exposed to environmental hazards such as floods. However, integrating multiple data sources and ensuring data accuracy remain significant challenges.

CHAPTER – 2

2.1 EXISTING SYSTEM

The existing flood monitoring and safety systems used for railway bridges are largely based on traditional monitoring techniques that provide limited intelligence and predictive capability. These systems primarily focus on detecting flood conditions only after they have already occurred, rather than predicting them in advance. As a result, they often fail to provide sufficient warning time to prevent damage or operational disruptions.

Flood monitoring and bridge safety have traditionally been addressed using a variety of methods ranging from manual observation to advanced technological systems. These existing approaches aim to detect rising water levels, monitor environmental conditions, and ensure the structural integrity of railway bridges. Over time, technologies such as IoT, Wireless Sensor Networks, and Machine Learning have been introduced to improve monitoring and prediction capabilities.

However, most of these systems operate independently and focus on specific aspects such as real-time monitoring or data-based prediction. Due to this lack of integration, existing systems often fail to provide a complete, reliable, and real-time solution for flood risk detection, especially in critical infrastructures like railway bridges. The following sections describe the existing systems and highlight their limitations

2.1.1. Manual Flood Monitoring

Description:

In traditional systems, flood conditions near railway bridges are monitored manually by workers or officials who physically visit the location. They use basic tools such as measuring scales or gauges to check the water level in rivers or nearby areas. The observations are recorded periodically and communicated to higher authorities for decision-making. This method depends entirely on human effort and experience, and monitoring is not continuous. During extreme weather conditions like heavy rainfall or floods, it becomes difficult and dangerous for personnel to access the location and collect accurate data.

Disadvantages:

- High human effort required
- Delayed detection of flood conditions
- Risk to human life during heavy rainfall
- No continuous monitoring

2.1.2 IoT-Based Flood Monitoring Systems

Description:

IoT-based flood monitoring systems use sensors such as water level sensors, flow sensors, and environmental sensors to continuously collect real-time data from flood-prone areas. These sensors are connected to microcontrollers, which process the data and transmit it to cloud platforms using wireless communication technologies like Wi-Fi or GSM. Authorities can monitor the data remotely through dashboards or mobile applications. Although these systems improve monitoring efficiency and reduce human intervention, they mainly focus on real-time data collection and alert generation when predefined thresholds are exceeded.

Disadvantages:

- No prediction capability
- Works only on threshold-based alerts
- Cannot forecast future flood risks
- Limited decision-making support

2.1.3. Machine Learning-Based Flood Prediction Systems

Description:

Machine learning-based systems use historical data such as rainfall patterns, river flow data, and past flood records to predict future flood conditions. Various algorithms like Artificial Neural Networks (ANN), Support Vector Machines (SVM), and Random Forest are trained on this data to identify patterns and relationships. These systems can provide better accuracy compared to traditional statistical models. However, they rely heavily on previously collected datasets and are not directly connected to real-time sensor inputs, which limits their ability to respond to sudden environmental changes.

Disadvantages:

- No real-time data integration
- Accuracy depends on past data only
- Cannot handle sudden environmental changes
- Requires large datasets

2.1.4. Bridge Monitoring Systems**Description:**

Bridge monitoring systems are designed to ensure the structural safety of bridges by using sensors such as vibration sensors, strain gauges, and load sensors. These systems continuously monitor parameters related to the physical condition of the bridge and detect any abnormalities or structural weaknesses. While they are effective in identifying structural issues, they do not consider environmental factors such as rising water levels or flood risks. As a result, these systems cannot provide early warnings related to flooding conditions that may affect the bridge.

Disadvantages:

- Focus only on structure, not floods
- No flood prediction capability
- Limited integration with environmental data
- Cannot provide early warning
- Not specifically designed for railway bridge flood detection
- Reduced accuracy and efficiency

2.2 PROPOSED SYSTEM

The proposed system is a hybrid IoT and Machine Learning–based predictive flood risk detection system designed to enhance the safety of railway bridges during flood conditions. The system aims to overcome the limitations of traditional flood monitoring methods by providing real-time sensing, intelligent data analysis, predictive capability, and rapid alert generation.

System Architecture

The system architecture consists of multiple sensing units deployed at strategic locations around railway bridges. These sensing units include a water level sensor, a vibration sensor, and an MQ-5 gas sensor. Each sensor monitors a specific environmental or structural parameter that contributes to flood risk assessment. The sensors are interfaced with a Raspberry Pi-W, which serves as the central edge-processing unit.

The Raspberry Pi-W collects sensor data continuously and performs preprocessing tasks such as noise filtering, normalization, and feature extraction. By executing processing at the edge, the system minimizes communication delay and ensures faster decision-making during emergency situations.

Machine Learning-Based Prediction

A key feature of the proposed system is the integration of a machine learning model for flood risk prediction. The ML model is trained using historical flood data combined with real-time sensor inputs. Unlike threshold-based systems, the ML algorithm analyses complex relationships between multiple parameters to classify flood risk levels accurately.

The model predicts flood conditions in advance by identifying abnormal trends in water level changes, vibration patterns, and environmental conditions. The system categorizes flood risk into multiple levels such as safe, alert, and danger, enabling timely preventive actions. The adaptive learning capability allows the model to update itself with new data, improving prediction accuracy over time.

Real-Time Monitoring and Edge Computing

The proposed system employs edge computing by processing sensor data locally on the Raspberry Pi-W. This approach reduces reliance on cloud servers and ensures continuous operation even in areas with limited internet connectivity. Real-time analysis enables immediate alert generation, which is critical during rapidly evolving flood scenarios.

Wireless Communication and Remote Monitoring

Wireless communication is implemented using the built-in Wi-Fi module of the Raspberry Pi-W, forming a wireless sensor network (WSN). Sensor data, flood risk predictions, and alert messages are transmitted to a centralized monitoring station. This enables railway authorities to monitor multiple bridge locations remotely and make informed decisions in real time.

Alert and Notification Mechanism

The system includes both visual and audio alert mechanisms. An LCD display provides on-site information such as current sensor readings and flood risk status. A buzzer is activated during warning or danger conditions to immediately alert nearby personnel. This dual-alert mechanism ensures that critical warnings are not missed.

Scalability and Flexibility

The modular design of the proposed system allows easy integration of additional sensors such as rainfall sensors, flow velocity sensors, or cameras. Communication technologies can also be upgraded as required. This scalability makes the system suitable for deployment across various geographical and climatic conditions.

Safety and Reliability Enhancement

By combining environmental monitoring, structural health assessment, intelligent prediction, and wireless communication, the proposed system significantly enhances railway bridge safety. Early detection and prediction of flood risks reduce the likelihood of structural failure and train accidents, ensuring uninterrupted railway operations.

2.1.1 ADVANTAGES OF PROPOSED SYSTEM

1. Provides early and predictive flood risk detection using machine learning

The proposed system uses machine learning algorithms to analyses historical and real-time sensor data. Unlike conventional systems that react only after critical conditions occur, this approach predicts potential flood risks in advance by identifying abnormal trends. Early prediction allows railway authorities to take preventive actions and avoid accidents.

2. Improves accuracy compared to traditional threshold-based systems

Traditional systems rely on fixed threshold values, which are prone to false alarms and missed detections. The proposed system analyses multiple parameters simultaneously and learns complex patterns from data, resulting in significantly improved detection accuracy even under varying environmental conditions.

3. Enables real-time monitoring of water level, vibration, and environmental conditions

The system continuously monitors key parameters such as water level, bridge vibration, and gas concentration. This multi-parameter monitoring provides a comprehensive understanding of both environmental and structural conditions, ensuring reliable flood risk assessment.

4. Uses edge processing with Raspberry Pi, reducing response time and latency

By processing sensor data locally on the Raspberry Pi-W, the system minimizes dependence on cloud servers. Edge processing ensures faster decision-making, reduced communication delay, and reliable operation even in areas with limited network connectivity.

5. Supports multi-level flood risk classification (normal, warning, danger)

The proposed system categorizes flood conditions into multiple risk levels instead of using a simple safe-or-unsafe approach. This graded classification enables appropriate and timely responses based on severity, improving safety management.

6. Offers both local and remote alerts through LCD, buzzer, and IoT communication

The system provides on-site alerts using an LCD display and buzzer for immediate warning. Simultaneously, alerts and sensor data are transmitted wirelessly to a remote monitoring centre, enabling centralized supervision and rapid decision-making.

7. Adaptive learning allows the system to improve performance over time

The machine learning model continuously updates itself using new sensor data. This adaptive learning capability improves prediction accuracy and reliability over long-term deployment, making the system suitable for dynamic environmental conditions.

8. Modular architecture enables easy integration of additional sensors

The system is designed with a modular structure, allowing new sensors or communication technologies to be added without major modifications. This flexibility ensures scalability and future upgrades as monitoring requirements evolve

CHAPTER-3

BLOCK DIAGRAM

The Block Diagram of “HYBTID IOT-ML SYSTEM FOR PREDICTIVE FOR RAILWAY BRIDGE FLOOD RISK DETECTION” is shown in the above fig. 3.1




Fig. 3.1: Block Diagram

3.1.1 BLOCK DIAGRAM DESCRIPTION

The Hybrid IoT–Machine Learning based flood risk detection system designed for railway bridge safety. The system integrates multiple sensors, a processing unit, communication modules, and a machine learning model to provide real-time monitoring and prediction. At the core of the system is the Raspberry Pi W, which acts as the main controller.

Input Section (Sensors)

Water Level Sensor:

Measures the water level near the railway bridge to detect rising flood conditions. It plays a crucial role in identifying potential flood risks.

Vibration Sensor:

Monitors vibrations in the bridge structure. Abnormal vibrations may indicate structural instability due to water flow or damage.

MQ-5 Gas Sensor:

Detects harmful gases or environmental changes that may occur during flooding conditions, ensuring additional safety monitoring.

Processing Unit**Raspberry Pi W:**

It receives data from all sensors, processes the inputs, and performs necessary computations. It also sends the data to the machine learning module and controls output devices like LCD and buzzer.

Output Section**LCD Display:**

Displays real-time sensor values such as water level, vibration status, and system alerts for easy monitoring.

Buzzer:

Provides an immediate alert when dangerous conditions are detected, such as high water levels or abnormal vibrations.

Communication Module**WSN (Wireless Sensor Network):**

Enables wireless transmission of data to remote monitoring stations or cloud platforms. This allows authorities to monitor bridge conditions from distant locations.

Machine Learning Module

The collected data is sent to the Machine Learning model, which analyzes both real-time and historical data.

CHAPTER-4

4.1 HARDWARE COMPONENTS

All hardware components are selected based on reliability, ease of integration, and suitability for real-time flood risk monitoring applications.

1. Raspberry pi-W
2. Water level sensor
3. Vibration sensor
4. WSN (wireless sensor network)
5. MQ-5 sensor
6. LCD (Liquid Crystal Display)
7. LED (Light Emitting Diode)

4.1.1 Raspberry pi




Fig.4.1.1: Raspberry pi

Raspberry Pi is a small single-board Computer developed in UK by Raspberry Pi foundation to promote the teaching of computer science in schools and in developing countries. Original model become far more popular than anticipated sealing outside of its target market, for uses such as robots.

History:

Raspberry Pi has mainly three generations Raspberry Pi 1, Raspberry Pi 2, Raspberry Pi 3 and also a reduce simple inexpensive Raspberry Pi zero.

- The first model of Raspberry Pi was launched in February 2012 i.e. Raspberry Pi 1 Model B followed by a simple inexpensive Model A.
- In April 2014 “Compute Model” for embedded application Raspberry Pi 1 model B+ improved versions of A and B was launched.
- In February 2015 advance model with 40 GPIO pins, Ethernet, 4 USB slots Raspberry Pi 2 was launched.
- In February 2016 an upgraded model with inbuilt Bluetooth and Wi-Fi Raspberry Pi 3 Model B was launched.
- Raspberry Pi 1: Broadcom BCM2835 SOC with 700MHz CPU speed, L2 cache of 128kb with ARM compatibility AR1176JZF-S (ARMv6) 32-bit RISC ARM.
- Raspberry Pi 2: Broadcom BCM 2836 SOC with 900MHz CPU speed, L2 cache of 256kb with 32-bit quad-core ARM cortex-A7 (ARMv7).
- Raspberry Pi 3: Broadcom BCM2837 SOC with 1.2GHz 64-bit quad-core –A53 with 512 kb shared L2 cache (64-bit instruction set ARMv8).


Raspberry pi-W:

Fig.4.1.1(a): Raspberry pi-w

Raspberry Pi Zero W is a compact, low-power single-board computer equipped with built-in Wi-Fi and Bluetooth connectivity. It is specifically designed for embedded and Internet of Things (IoT) applications, where small size, low energy consumption, and wireless communication are essential. Due to these features, Raspberry Pi Zero W is selected as the central processing and control unit in the proposed flood risk detection system.

The Raspberry Pi Zero W is powered by a 1 GHz single-core ARM processor and includes 512 MB RAM, which is sufficient for real-time data acquisition, edge processing, and execution of lightweight machine-learning algorithms. It runs a Linux-based operating system, enabling multitasking, data logging, and seamless integration of sensor drivers and software libraries.

In the proposed system, Raspberry Pi Zero W interfaces with multiple sensors such as the water level sensor, vibration sensor, and MQ-5 gas sensor through its GPIO pins.

The built-in Wi-Fi module enables the Raspberry Pi Zero W to form a wireless sensor network (WSN) and transmit sensor data and alert information to a remote monitoring centre. This feature eliminates the need for additional communication modules, reducing system complexity and cost. Remote monitoring allows railway authorities to supervise bridge conditions in real time.

FEATURES:

1. Compact and Lightweight Design

Raspberry Pi Zero W has a very small form factor, making it suitable for embedded and space-constrained applications such as railway bridge monitoring systems.

2. Built-in Wireless Connectivity

It includes on-board Wi-Fi (802.11 b/g/n) and Bluetooth, enabling easy IoT and wireless sensor network (WSN) communication without additional modules.

3. Low Power Consumption

The board consumes very low power compared to other Raspberry Pi models, making it ideal for long-term deployment in remote locations.

4. 1 GHz ARM Processor

It is powered by a 1 GHz single-core ARM CPU capable of handling real-time sensor data acquisition and lightweight machine learning tasks.

5. 512 MB RAM

Sufficient memory is available to run a Linux operating system and execute sensor interfacing, data processing, and monitoring applications.

6. Cost-Effective Platform

Offers an economical solution for developing intelligent IoT systems without compromising performance.

7. Supports Multiple Communication Protocols

Supports I²C, SPI, UART, and PWM, allowing flexible integration of various sensors and modules.

8. Linux-Based Operating System Support

Runs Raspberry Pi OS and other Linux distributions, enabling multitasking, data logging, and advanced software development.

4.1.2 Water Level sensor

Level sensors mainly used to monitor and regulate levels of a particular free-flowing substance within a contained space. These substances are usually liquid, however, level sensors also, and used to monitor some solids such as powdered substances. Level sensors widely used industrially, as level acts as an important monitoring parameter. This is a low cost easy to use. This water level sensor module has a series of parallel exposed traces to measure droplets/water volume in order to determine the water level. Very Easy to monitor water level as the output to an analog signal is directly proportional to the water level.

This is a probe type water level sensor. This type works on the principle single point probe sensor principle.

Working:

Point Probe sensors are mostly capacitive type or Resistive. The sensor will have dielectric constants. They measure changes in the value of capacitance when the sensor is dipped into the liquid. The change corresponds to Level variation. Two types of sensors are available, one with high dielectric constants and another with low dielectric constants. This sensor will work with the different range of solids, liquids and mixed materials. These sensors also available both in contact or non-contact type sensor. It is important to know whether the sensor works with all types of material or tank.




Fig.4.1.2: Water level sensor

If the board has water or another fluid covering all the wire, then it will output a maximum analog value reading. Since analog values read by an Arduino range from 0 (lowest reading) to 1023 (highest reading), a board completely submerged with a liquid will have a reading of 1023 by an Arduino. If the board is halfway covered, a reading of about 512 read by the Arduino. If the board is 1/4 covered by a liquid, then the Arduino will read about 256. And if no liquid is on it at all, then a near 0 reading obtained.

Disadvantages

- Water level controls need to be replaced every 3 years.
- The rust, foul and deteriorate
- Electronics are usually built separately
- More difficult installation
- Most float switches are outdated

Benefits of Water Level

- Easy installation
- Minimal maintenance
- Sends an alert to let you know water is too high or too low
- Low & High alarms
- Automatically adjusts water levels
- Save money by using less electricity and water

- Automatic operation saves you manual labour time

Applications

- Can be used in water tanks to control water levels
- Automatically turn ON/OFF pumps
- Can be used in factories, commercial complexes, apartments, home,
- Fuel tank level gauging
- Oil tank level control
- High & low-level alarms
- Pool water level control
- Life station switches
- Leachate level control
- Process batch control & monitoring

4.1.3. Vibration Sensor (SW-420)




Fig.4.1.3: Vibration Sensor

The Grove - Vibration Sensor (SW-420) is a high sensitivity non-directional vibration

1. sensor. When the module is stable, the circuit is turned on and the output is high. When
2. the movement or vibration occurs, the circuit will be briefly disconnected and output low.
3. At the same time, you can also adjust the sensitivity according to your own needs.

4. All in all, this is a perfect module for vibration or tilt sensor.

Features

1. Non-directional
2. High sensitivity
3. Respond to vibration, tilt
4. Waterproof
5. Compression resistance

Specification

1. Operating voltage :3.3V / 5V
2. Interface: Digital

Applications

1. Car, bicycle, motorcycle burglar alarm
2. Game control
3. Vibration detection

4.1.4 MQ-5 Gas Sensor

The MQ-5 gas sensor is a semiconductor-based gas sensing device used to detect the presence of combustible gases such as liquefied petroleum gas (LPG), methane (CH₄), natural gas, hydrogen (H₂), and alcohol vapours. It is widely used in safety and environmental monitoring applications due to its high sensitivity, fast response time, and low cost. The MQ-5 sensor operates on the principle of Chemi resistive sensing. It consists of a tin dioxide (SnO₂) sensing layer whose electrical resistance varies in the presence of combustible gases. When clean air is present, the sensor exhibits high resistance. The sensor module includes an internal heating element that maintains the sensing material at an optimal operating temperature, ensuring stable and reliable gas detection. The MQ-5 sensor provides both analog and digital outputs, making it compatible with microcontrollers and single-board computers such as the Raspberry Pi. In the proposed system, the analog output is used to measure gas concentration levels more accurately.

Features of MQ-5 Gas Sensor

1. **Highs sensitivity to Combustible Gases**

The MQ-5 sensor is highly sensitive to gases such as LPG, methane, natural gas, hydrogen, and alcohol vapours.

2. **Fast Response and Recovery Time**

The sensor quickly responds to changes in gas concentration, making it suitable for real-time monitoring applications.

3. **Analog and Digital Output Support**

Provides both analog and digital outputs, allowing flexible interfacing and precise gas level measurement.

4. **Built-in Heating Element**

Includes an internal heater to maintain optimal operating temperature for stable and reliable gas detection.

5. **Low Cost and Easy Availability**

Economical sensor widely used in safety and monitoring applications.

6. **High Stability and Long Life**

Offers reliable performance over extended periods with proper calibration.

7. **Simple Interfacing**



Fig.4.1.4:MQ-5 Gas Sensor

4.1.5 LCD (Liquid Crystal Display)

LCD (Liquid Crystal Display) screen is an electronic display module and find a wide range of applications. A 16×2 LCD display is very basic module and is very commonly used in various devices and circuits. These modules are preferred over seven segments and other multi segment LEDs. The reasons being: LCDs are economical; easily programmable; have no

limitation of displaying special & even custom characters (unlike in seven segments),
 animations and so on.




Fig.4.1.5:Liquid Crystal Display(LCD)

Working

Next comes to the second piece of glass with an electrode in the form of the rectangle on the bottom and, on top, another polarizing film. It must be considered that both the pieces are kept at right angles. When there is no current, the light passes through the front of the LCD it will be reflected by the mirror and bounced back. As the electrode is connected to a battery the current from it will cause the liquid crystals between the common-plane electrode and the electrode shaped like a rectangle to untwist. Thus the light is blocked from passing through. That particular rectangular area appears blank.

16X2 LCD pinout diagram




Fig.4.1.5(a): LCD pin description

Features of 16×2 LCD module

- Operating Voltage is 4.7V to 5.3V
- Current consumption is 1mA without backlight
- Alphanumeric LCD display module, meaning can display alphabets and numbers
- Consists of two rows and each row can print 16 characters.
- Each character is build by a 5×8 pixel box

Advantages

- LCD's consumes less amount of power compared to CRT and LED
- LCD's are consist of some microwatts for display in comparison to some mill watts for LED's, LCDs are of low cost

Disadvantages

- Require additional light sources
- Low reliability
- Speed is very low
- LCD's need an AC drive

Applications

- Liquid crystal technology has major applications in the field of science and engineering as well on electronic devices.
- Liquid crystal thermometer
- The liquid crystal display technique is also applicable in visualization of the radio frequency waves in the waveguide

4.1.6 LED (Light Emitting Diode):


The LED (Light Emitting Diode) is a semiconductor-based output device used in the system to provide real-time visual indication of flood conditions. It converts electrical energy into light and is widely used in embedded systems due to its simplicity, efficiency, and reliability.

In this project, the LED is interfaced with the Raspberry Pi W GPIO pins and is programmed to respond dynamically based on sensor readings and machine learning predictions.

Fig.4.1.6: LED (Light Emitting Diode)

Working Principle

The LED works on the principle of electroluminescence, where it emits light when current



flows through it.

In this system:

- The Raspberry Pi processes input data from sensors (water level, vibration, gas sensor).
- Based on threshold values and ML predictions, it sends HIGH or LOW signals to the LED.
- The LED responds accordingly by glowing, blinking, or changing intensity.

Operating Logic in the Project

Single LED Logic:

- LOW Risk (Safe): LED OFF
- MEDIUM Risk (Warning): LED blinks at intervals
- HIGH Risk (Danger): LED continuously ON

Features

- Instant visual response
- Compact and lightweight

- Highly energy-efficient
- Long operational life
- Can be integrated with automation systems

Advantages

- Quick visual alert system for immediate awareness
- Helps in low visibility environments (rain, fog, night)
- Improves human-machine interaction
- Cost-effective and easy to implement
- Can be easily replaced or upgraded

Applications in This Project

- Visual indication of flood risk levels
- Works alongside buzzer for dual alert system
- Assists railway authorities in quick decision-making
- Helps field engineers monitor system status
- Provides backup alert mechanism

4.2 SOFTWARE TOOLS

All software tools are chosen for being dependable, easy to connect, and perfect for real-time flood tracking.

1 Python Programming Language

2 C++ Programming Language

3 Machine Learning

4 IOT Communication Protocols

4.2.1 Python Programming Language

Python is a high-level, interpreted, and object-oriented programming language widely used in Internet of Things (IoT), data processing, and machine learning applications. Due to its simple syntax, readability, and extensive library support, Python is selected as the primary

programming language for the proposed hybrid IoT–ML flood risk detection system for railway bridges. In the proposed system, Python is used to interface various sensors such as the water level sensor, vibration sensor, and MQ-5 gas sensor connected to the Raspberry Pi Zero W. It continuously collects real-time sensor data, processes the readings at the edge, and controls output devices such as the LCD display and buzzer for alert generation.

Python Libraries Used

The following Python libraries are used in the proposed system:

1. RPi.GPIO / GPIO Zero

These libraries are used for controlling the **GPIO pins** of the Raspberry Pi. They enable interfacing of sensors and actuators such as the vibration sensor, buzzer, and LCD.

2. NumPy

NumPy is used for numerical computations and array operations. It helps in processing sensor data and performing mathematical calculations required for feature extraction.

3. Pandas

Pandas is used for data handling and preprocessing. It helps in storing, cleaning, and organizing real-time and historical sensor data in tabular form for machine learning training.

4. Scikit-learn

Scikit-learn is used to implement **machine learning algorithms**. It supports training, testing, and evaluating classification models for predicting flood risk levels based on sensor data.

5. Matplotlib

Matplotlib is used for **data visualization**, such as plotting sensor readings, trends, and performance graphs for analysis and evaluation.

6. I²C / SPI Libraries

These libraries are used for communication with peripherals such as **LCD displays** and **ADC modules** (used with the MQ-5 sensor).

7. Network Libraries (Socket / Requests / MQTT)

These libraries enable **IoT communication**, allowing sensor data and alerts to be transmitted wirelessly to a remote monitoring system.

Role of Python in the Proposed System

- Real-time sensor data acquisition
- Edge processing and data analysis
- Machine learning-based flood risk prediction
- Local alert control (LCD and buzzer)
- Wireless data transmission for remote monitoring

4.2.2 C++ Programming Language

C++ is a high-performance, compiled, and object-oriented programming language widely used in embedded systems, real-time applications, and hardware-level programming. It provides direct access to hardware resources and efficient memory management, making it suitable for applications that require fast execution and precise control. IoT-based monitoring systems, C++ is commonly used for low-level sensor interfacing, real-time data acquisition, and control logic, especially when microcontrollers or embedded platforms are involved. In the context of the proposed hybrid IoT–ML flood risk detection system, C++ can be used for:

- Low-level sensor data acquisition
- Real-time signal processing
- Interfacing with sensors and actuators
- Implementing fast decision logic on embedded devices

C++ programs can interact efficiently with hardware pins, communication protocols, and peripheral devices, ensuring stable and responsive system behaviour.

C++ Libraries Used (Typical for IoT / Embedded Systems)

1. Standard C++ Library (STL)

Provides data structures, algorithms, input/output handling, and memory management required for embedded applications.

2. GPIO Libraries

Used for direct control of GPIO pins for sensor and actuator interfacing (platform dependent).

3. Serial Communication Libraries

Enable UART, SPI, and I²C communication between sensors, microcontrollers, and processing units.

4. Networking Libraries

Used for data transmission and communication in IoT-enabled embedded systems.

Advantages of Using C++ in Embedded Systems

1. High execution speed
2. Efficient memory usage
3. Direct hardware control
4. Suitable for real-time applications
5. Widely supported in embedded platforms

4.2.3 Machine Learning

Machine Learning (ML) is a branch of artificial intelligence that enables systems to learn patterns from data and make predictions or decisions without being explicitly programmed. In the proposed hybrid IoT–ML flood risk detection system, machine learning is used to analyse sensor data collected from water level, vibration, and MQ-5 gas sensors deployed at railway bridges. A supervised learning approach is adopted, where the ML model is trained using labelled historical flood data along with real-time sensor inputs. By learning the complex relationships between environmental and structural parameters, the model classifies flood risk into multiple levels such as normal, warning, and danger, enabling early and accurate flood risk detection.

Types of Machine Learning

1. Supervised Learning

Supervised learning uses labelled data, where the input and corresponding output are known.

The model learns a mapping between inputs and outputs during training and is then used to predict results for new data.

Example: Flood risk classification (Normal, Warning, Danger)

Common algorithms:

- Linear Regression
- Logistic Regression
- Decision Tree
- Random Forest
- Support Vector Machine (SVM)

2. Unsupervised Learning

Unsupervised learning works with unlabelled data. The model identifies hidden patterns or structures in the data without predefined outputs.

3. Semi-Supervised Learning

Semi-supervised learning uses a small amount of labelled data and a large amount of unlabelled data. It combines features of supervised and unsupervised learning.

4. Reinforcement Learning

Reinforcement learning involves an agent that learns by interacting with the environment and receiving rewards or penalties. The goal is to maximize cumulative rewards.

5. Deep Learning

Deep learning is a subset of machine learning that uses artificial neural networks with multiple layers to learn complex patterns from large datasets.

Machine Learning Technique Used:

Machine Learning (Supervised Learning):

Supervised Machine Learning is a learning approach in which a model is trained using labelled data, where both input features and corresponding output labels are known. The objective of supervised learning is to learn a mapping between input parameters and output

classes so that the trained model can accurately predict outcomes for new, unseen data. In the proposed hybrid IoT–ML flood risk detection system, supervised learning is used to classify flood risk levels based on sensor data collected from railway bridge environments. The input features include parameters such as water level, vibration intensity, and environmental gas concentration, while the output labels represent flood risk categories such as normal, warning, and danger.

Role of Supervised ML in the Project:

Supervised machine learning enables the system to predict flood risk before dangerous conditions occur, unlike traditional threshold-based systems. The adaptive learning capability allows the model to improve accuracy over time as more labelled data become available.

Working of Supervised Learning in the Proposed System:

1. Data Collection

Historical flood data and real-time sensor readings are collected from water level sensors, vibration sensors, and MQ-5 gas sensors.

2. Data Labelling

Each data sample is labelled with a flood risk category based on historical records or expert-defined criteria.

3. Training Phase

A supervised machine learning algorithm is trained using the labelled dataset. During training, the model learns patterns and relationships between sensor parameters and flood risk levels.

4. Testing and Validation

The trained model is tested using unseen data to evaluate its accuracy and performance.

5. Prediction Phase

During real-time operation, the trained model classifies incoming sensor data into appropriate flood risk levels.

Advantages of Supervised Learning in Flood Risk Detection:

1. High prediction accuracy due to labelled training data
2. Clear classification of flood risk levels
3. Faster and more reliable decision-making
4. Suitable for real-time and safety-critical applications
5. Easy evaluation using metrics such as accuracy and precision


4.2.4 IoT Communication Protocols

IoT communication protocols define the rules and methods used for data exchange between sensor nodes, edge devices, gateways, and remote servers in an Internet of Things environment. These protocols ensure reliable, secure, and efficient transmission of sensor data and alert information over wired or wireless networks. In flood monitoring applications, IoT protocols play a critical role in enabling real-time data transfer, remote monitoring, and timely decision-making.

In the proposed system, the Raspberry Pi-W uses Wi-Fi-based communication to transmit sensor readings and machine learning-based flood risk predictions to a remote monitoring centre

1.MQTT (Message Queuing Telemetry Transport)

MQTT is a lightweight, publish–subscribe messaging protocol designed for low-bandwidth and unreliable networks. It enables efficient data transmission with minimal overhead, making it suitable for real-time monitoring systems. MQTT supports reliable message delivery and is widely used in IoT applications



Common IoT Communication Protocols

Fig.4.2.4: IOT Communication Protocols

2. HTTP / HTTPS

HTTP is a request–response protocol commonly used for web-based communication. It allows sensor data to be sent to cloud servers or web dashboards. HTTPS provides secure communication through encryption, ensuring data integrity and privacy.

3. CoAP (Constrained Application Protocol)

CoAP is a lightweight protocol designed for constrained devices and low-power networks. It operates over UDP and is suitable for simple sensor communication in resource-limited environments.

4.2.5 Wireless Sensor Network (WSN)

A Wireless Sensor Network (WSN) is a collection of spatially distributed sensor nodes that are used to monitor physical or environmental conditions and transmit the collected data wirelessly to a central processing or monitoring unit. Each sensor node in a WSN typically consists of sensing components, a microcontroller or processing unit, a wireless communication module, and a power source. WSNs are widely used in applications such as environmental monitoring, disaster management, industrial automation, and infrastructure safety systems. In the proposed flood risk detection system, the Wireless Sensor Network plays a crucial role in enabling real-time data transmission and remote monitoring of railway bridge conditions. The sensor nodes continuously collect data from water-level sensors, vibration sensors, and gas sensors deployed near the bridge.

Features of Wireless Sensor Network (WSN)

1. Wireless Communication

WSN enables sensor nodes to transmit data wirelessly, eliminating the need for physical wiring and making deployment easier in remote and hazardous locations.

2. Real-Time Data Transmission

Sensor data are transmitted continuously or periodically to a central monitoring unit, allowing real-time observation and quick response to critical events.

3. Distributed Sensor Nodes

A WSN consists of multiple sensor nodes distributed across a geographical area to collect environmental and structural data simultaneously.

4. Scalability

Additional sensor nodes can be easily added to the network without significant changes to the existing system architecture.

5. Low Power Consumption

Sensor nodes are designed to operate with minimal energy usage, enabling long-term operation using batteries or renewable power sources.

6. Self-Organizing Capability

WSNs can automatically configure and manage network connections between nodes, improving reliability and fault tolerance.

7. Remote Monitoring and Control

Data can be accessed remotely through a central server or cloud platform, enabling centralized supervision of multiple monitoring locations.




Fig.4.2.5: Wireless Sensor Network (WSN)

CHAPTER-5

SOFTWARE CODE:

```
#define SW_VERSION " ThinkSpeak.com" // SW version will appears at innitial LCD Display

//#include <ESP8266WiFi.h>

#include <WiFiClientSecure.h>

WiFiClient client;

int water=26;int mq5=27;

int vib=16;int led=15;

#include <Wire.h>

#include <LiquidCrystal_I2C.h>

LiquidCrystal_I2C lcd(0x27, 16, 2);

const char* MY_SSID = "vi";

const char* MY_PWD = "14151511";

const char* TS_SERVER = "api.thingspeak.com";

String TS_API_KEY = "XH8L14I75K7U5X1R";

void connectWifi()

{

    Serial.print("Connecting to " + *MY_SSID);

    WiFi.begin(MY_SSID, MY_PWD);

    while (WiFi.status() != WL_CONNECTED){
```

```
    delay(1000);

    Serial.print(".");

}

Serial.println("");

Serial.println("WiFi Connected");

Serial.println("");

}

void setup() {

    Serial.begin(9600);

    pinMode(water,INPUT);pinMode(mq5,INPUT);

    pinMode(vib,INPUT);pinMode(led,OUTPUT);

    connectWifi();

    Wire.setSDA(0); // GP0

    Wire.setSCL(1); // GP1

    Wire.begin();

    lcd.init();    // Initialize LCD

    lcd.backlight(); // Turn on backlight

    lcd.clear();

    lcd.setCursor(0, 0);

    lcd.print("HYBRIDE IOT & ML");

    lcd.setCursor(0, 1);

    lcd.print("SYSTEM FOR PREDICTIVES ");

    delay(1000);

}
```

```
void loop() {  
  
  int m= analogRead(water);  
  
  Serial.print("water = ");  
  
  Serial.println(m);  
  
  int s=analogRead(mq5);  
  
  Serial.print("MQ5= ");  
  
  Serial.println(s);  
  
  int i1= digitalRead(vib);  
  
  Serial.print(" vib: ");  
  
  Serial.println(i1); lcd.clear();  
  
  lcd.setCursor(0,0);  
  
  lcd.print("water= "); lcd.print(m);  
  
  delay(1000); lcd.clear();  
  
  lcd.setCursor(0,0);  
  
  lcd.print("mq5:"); lcd.println(s);  
  
  delay(1000); lcd.clear();  
  
  lcd.setCursor(0,0);  
  
  lcd.print("vib:");  
  
  lcd.println(i1);  
  
  delay(1000);  
  
  if(s <= 100 || m >= 101 || i1==0){  
  
    digitalWrite(led,HIGH);  
  
  }  
  
  else
```

```
{  
    digitalWrite(led,LOW);  
}  
  
if (client.connect(TS_SERVER, 80)){  
    String postStr = TS_API_KEY;  
    postStr += "&field1=";  
    postStr += String(s);  
    postStr += "&field2=";  
    postStr += String(m);  
    postStr += "&field3=";  
    postStr += String(i1);  
    postStr += "&field4=";  
    postStr += String(i1);  
    postStr += "\r\n\r\n";  
    client.print("POST /update HTTP/1.1\n");  
    client.print("Host: api.thingspeak.com\n");  
    client.print("Connection: close\n");  
    client.print("X-THINGSPEAKAPIKEY: " + TS_API_KEY + "\n");  
    client.print("Content-Type: application/x-www-form-urlencoded\n");  
    client.print("Content-Length: ");  
    client.print(postStr.length());  
    client.print("\n\n");  
    client.print(postStr);  
    delay(1000);  
}
```

```
}  
  
delay(1000);  
  
}
```

CHAPTER-6

ADVANTAGES:

1. Railway Bridge Safety Monitoring

The system can be deployed on railway bridges to continuously monitor water levels and vibrations. It helps prevent accidents by alerting authorities before the situation becomes dangerous.

2. Flood Early Warning Systems

Useful in flood-prone areas to detect rising water levels in real time and send alerts, enabling early evacuation and disaster preparedness.

3. Smart City Infrastructure

Can be integrated into smart city systems to monitor drainage, rivers, and water bodies, improving urban flood management.

4. Bridge Structural Health Monitoring

The vibration sensor helps detect unusual movements or structural stress in bridges, ensuring timely maintenance and avoiding failures.

5. Dam and River Monitoring

Applicable near dams and rivers to track water levels and send alerts when thresholds are exceeded.

6. Disaster Management Systems

Government and emergency services can use this system for real-time data collection and quick decision-making during floods.

7. Remote Monitoring Using IoT

With platforms like ThingSpeak, the system allows remote access to live data from anywhere, reducing the need for manual inspection.

8. Road and Traffic Safety

Can be installed on roads and low-lying bridges to warn vehicles about waterlogging and unsafe conditions.

9. Industrial Area Monitoring

Industries located near water bodies can use this system to prevent flood-related damage and ensure safety.

10. Environmental Monitoring

Helps in studying water level trends and environmental changes over time, useful for research and planning.

11. Agricultural Flood Monitoring

Farmers can use this system to monitor water levels in fields and nearby canals. It helps in preventing crop damage by giving early warnings about flooding or excessive water.

12. Public Safety in Rural & Low-Lying Areas

The system can be installed in villages and low-lying regions where flooding is common. It alerts people in advance, helping protect lives and property.

13. Power Plant and Substation Protection

Flooding near power plants or electrical substations can cause serious damage and outages. This system can monitor water levels and provide early alerts to protect critical infrastructure.

14. Basement and Underground Parking Monitoring

In urban areas, basements and underground parking spaces are highly vulnerable to waterlogging. The system can detect rising water levels and alert building management to take preventive action.

CHAPTER-7

APPLICATIONS

1. **Railway Bridge Flood Monitoring**

The system can be deployed on railway bridges located near rivers or flood-prone areas to continuously monitor water level, structural vibrations, and environmental conditions.

2. **Early Warning System for Train Operations**

Predictive flood risk alerts help railway authorities take timely actions such as slowing down trains, rerouting traffic, or suspending operations to prevent accidents.

3. **Structural Health Monitoring**

Vibration analysis enables detection of abnormal structural behaviour caused by strong water currents, debris impact, or foundation weakening.

4. **Centralized Railway Infrastructure Management**

Multiple bridge locations can be monitored remotely from a single control centre using IoT communication and wireless sensor networks.

5. **Disaster Management and Emergency Response**

Real-time and predictive flood information supports faster emergency response and disaster mitigation planning.

6. **Smart Transportation Systems**

The system contributes to intelligent and automated railway safety systems within smart city infrastructure.

7. **Long-Term Data Analysis and Planning**

Historical sensor data can be used for flood pattern analysis, infrastructure planning, and preventive maintenance strategies.

8. **Research and Academic Applications**

Useful as a testbed for research in IoT, machine learning, and smart infrastructure monitoring.

9. **Predictive Maintenance of Railway Infrastructure**

Continuous monitoring helps identify early signs of structural stress, enabling timely maintenance and reducing repair costs

10. **Integration with Railway Control Systems**

Flood risk data can be integrated with signalling and traffic control systems for automated safety actions.

11. **Environmental Monitoring During Extreme Weather**

Tracks environmental changes such as gas concentration and vibration during floods for safety assessment.

12. **Decision Support for Railway Authorities**

Provides data-driven insights to assist authorities in planning preventive and corrective actions.

13. **Deployment in Climate-Resilient Infrastructure Projects**

Supports development of resilient railway infrastructure in regions vulnerable to climate change impacts.

14. **Real-Time Alert Notification Systems**

IoT communication protocols enable instant transmission of critical alerts to mobile devices, control rooms, and monitoring dashboards, ensuring quick response during emergency situations such as floods or structural failures.

15. **Inter-Device Coordination and Automation**

IoT protocols support seamless communication between multiple smart devices and systems, enabling automated actions such as activating alarms, updating dashboards, or triggering safety mechanisms without human intervention.

CHAPTER – 8

FUTURE SCOPE

1. Integration of Additional Sensors

The system can be enhanced by integrating rainfall, water flow velocity, humidity, and soil moisture sensors. These additional parameters will help the ML model better understand flood behaviour and improve prediction accuracy.

2. Advanced Machine Learning and Deep Learning Models

Future implementations can use deep learning models such as LSTM and neural networks for time-series analysis. These models can capture complex flood patterns more effectively than traditional ML algorithms.

3. Mobile Application for Real-Time Alerts

A dedicated mobile application can provide instant flood alerts and bridge status updates to railway officials. This ensures quick response even when authorities are not at the control centre.

4. Use of Long-Range Communication Technologies

Communication technologies like LoRa WAN, NB-IoT, and 5G can be adopted for reliable data transmission in remote areas. This improves coverage and system scalability.

5. Automated Train Control and Signalling Integration

The system can be connected to railway signalling systems to automatically slow down or stop trains during high-risk conditions. This enhances passenger safety and reduces dependence on manual decisions.

6. Energy-Efficient and Solar-Powered Design

Solar panels and low-power components can be incorporated to ensure uninterrupted system operation. This is especially useful for remote bridges without reliable power supply.

7. AI-Based Structural Damage Detection

Advanced AI algorithms can analyse vibration data to detect early signs of structural damage. This helps prevent failures caused by prolonged flood exposure.

8. Centralized Multi-Bridge Monitoring Platform

A centralized dashboard can be developed to monitor flood risks at multiple bridges simultaneously. This improves large-scale infrastructure management.

9. Enhanced Cybersecurity Measures

Strong encryption and authentication mechanisms can be implemented to protect data and communication channels. This ensures system reliability and data integrity.

10. Predictive Maintenance Scheduling

Historical sensor data can be used to predict maintenance requirements in advance. This reduces unexpected failures and lowers maintenance costs.

11. Integration with Emergency Response Systems

Flood alerts can be directly shared with disaster management and emergency services. This enables faster response and coordinated rescue operations.

12. Scalability to Other Infrastructure Systems

The proposed system can be adapted for monitoring highways, dams, culverts, and urban flood-prone areas. This expands its application beyond railway bridges.

CHAPTER-9

RESULT

The following graphs represent the real-time data collected from different sensors used in our hybrid IoT-ML system for railway bridge safety monitoring. These sensors include the water level sensor, MQ-5 gas sensor, and vibration sensor, each measuring a critical environmental or structural parameter. The data is continuously transmitted and visualized to analyze changing conditions over time. By observing these graphs, we can identify patterns, detect abnormalities, and predict potential risks such as flooding, gas leakage, or structural instability, ensuring timely alerts and improved safety of railway operations.

9.1 Water Level Sensor

This graph represents the variation in water levels near the railway bridge over time. The sensor continuously monitors the water height and sends real-time data to the system. We can observe sudden rises and drops in water levels, indicating changing environmental conditions such as rainfall or water flow. High peaks in the graph indicate potential flood risk situations, while stable regions show normal conditions the system can identify unusual patterns and compare them with predefined safety thresholds. When the water level exceeds the safe limit, automatic alerts are generated to warn authorities and take preventive actions such as slowing



or stopping train operations.. Thus, this graph plays a vital role in ensuring timely decision-making and enhancing the overall safety of the railway bridge.

Fig.9.1: Water level sensor output

9.2 MQ-5 Sensor

This graph shows the readings from the MQ-5 gas sensor, which detects gases like methane, LPG, or other hazardous gases near the railway bridge. The fluctuations in the graph indicate changes in gas concentration levels over time. Higher peaks represent increased gas presence, which could signal dangerous conditions such as gas leakage or environmental hazards. Lower and stable values indicate safe conditions. This sensor plays a crucial role in identifying invisible threats and improving overall safety. This enables quick response to potential hazards such as gas leaks, reducing the risk of accidents. the system ensures a safer environment around the railway bridge and supports effective decision-making.



Fig.9.2: MQ-5 sensor output

9.3 Vibration Sensor

This graph illustrates the vibration levels detected on or around the railway bridge. The vibration sensor measures structural movements caused by train movement, environmental forces, or possible structural weaknesses. Sudden spikes in the graph indicate high vibrations, which may suggest heavy loads or potential structural issues. Consistent low values indicate stable and safe conditions. Monitoring vibration helps in early detection of structural damage and prevents accidents. If the vibration levels exceed the safe limit, alerts are immediately

generated to inform authorities for inspection and maintenance. This helps in detecting potential issues such as cracks, loosened components, or excessive stress at an early stage. By combining real-time monitoring with timely alerts, the system enhances structural reliability and ensures the safe operation of railway services.




Fig.9.3: Vibration Sensor output

By running the code on Arduino uno we observe the output on the serial monitor which as shown in the above fig




Fig.9.3(a): Output in serial monitor

CHAPTER-10

CONCLUSION

Flood-induced damage to railway bridges remains a major concern due to its impact on passenger safety, infrastructure reliability, and railway operations. Conventional flood monitoring systems rely on fixed threshold values and manual observation, which are often insufficient to handle rapidly changing environmental conditions. This project addresses these challenges by proposing a hybrid Internet of Things (IoT) and Machine Learning (ML)-based system for predictive flood risk detection, designed specifically for railway bridge environments.

The proposed system integrates multiple sensors, including water-level, vibration, and MQ-5 gas sensors, to continuously monitor both environmental and structural parameters. A Raspberry Pi-W functions as the edge-processing unit, collecting real-time sensor data and performing local analysis to ensure low latency and fast response. By utilizing edge computing, the system is capable of generating immediate alerts through local indicators such as an LCD display and buzzer, even in situations where network connectivity is limited.

A key contribution of this work is the incorporation of supervised machine learning for intelligent flood risk prediction. The ML model is trained using historical and real-time sensor data to identify complex relationships among multiple parameters. Based on the analysis, the system classifies flood risk into different levels such as normal, warning, and danger, enabling early detection of hazardous conditions. This predictive capability significantly improves accuracy and timeliness compared to traditional threshold-based systems.

Furthermore, the system supports remote monitoring through IoT communication and a wireless sensor network, allowing railway authorities to monitor multiple bridges from a centralized control centre. The modular and scalable architecture enables easy integration of additional sensors, advanced communication technologies, and future upgrades. Overall, the proposed hybrid IoT-ML flood risk detection system offers a reliable, intelligent, and cost-

effective solution for enhancing railway bridge safety, reducing flood-related accidents, and improving the resilience of railway infrastructure in flood-prone regions.

REFERENCES

- [1] A. Zanella, N. Bui, A. Castellani, L. Vangelista, and M. Zorzi, "Internet of Things for Smart Cities," *IEEE Internet of Things Journal*, vol. 1, no. 1, pp. 22–32, Feb. 2014.
- [2] L. Da Xu, W. He, and S. Li, "Internet of Things in Industries: A Survey," *IEEE Transactions on Industrial Informatics*, vol. 10, no. 4, pp. 2233–2243, Nov. 2014.
- [3] S. Kumar, R. K. Singh, and A. K. Verma, "Flood Monitoring and Early Warning System Using IoT," *International Journal of Advanced Research in Computer and Communication Engineering*, vol. 6, no. 6, pp. 128–132, 2017.
- [4] M. R. Islam, M. M. Hassan, and G. Fortino, "IoT-Based Flood Monitoring and Early Warning Systems: A Review," *Future Generation Computer Systems*, vol. 89, pp. 540–553, Dec. 2018.
- [5] K. Ashton, "That 'Internet of Things' Thing," *RFID Journal*, pp. 97–114, 2009.
- [6] S. Haykin, *Neural Networks and Learning Machines*, 3rd ed. New Delhi, India: Pearson Education, 2011.
- [7] T. M. Mitchell, *Machine Learning*, New York, USA: McGraw-Hill, 1997.
- [8] Raspberry Pi Foundation, "Raspberry Pi 3 Model B+ Documentation," [Online].
- [9] J. Gubbi, R. Buyya, S. Marusic, and M. Palaniswami, "Internet of Things (IoT): A Vision, Architectural Elements, and Future Directions," *Future Generation Computer Systems*, vol. 29, no. 7, pp. 1645–1660, Sept. 2013.
- [10] A. R. Al-Ali, I. Zuolkernan, and M. Rashid, "A Smart Flood Monitoring System Using IoT and Wireless Sensor Networks," *International Journal of Engineering and Technology*, vol. 7, no. 4, pp. 110–116, 2018.
- [11] H. Karl and A. Willig, *Protocols and Architectures for Wireless Sensor Networks*, New York, USA: Wiley, 2005.

- [12] Datasheet, “MQ-5 Gas Sensor Technical Specifications,” Hanwei Electronics Co., Ltd.
- [13] P. S. Kulkarni and T. P. Kurule, “Vibration Monitoring of Structures Using Sensors,” *International Journal of Engineering Research & Technology*, vol. 4, no. 3, pp. 245–249, 2015.
- [14] O. Vermesan et al., “Internet of Things Strategic Research Roadmap,” *IERC – European Research Cluster on the Internet of Things*, 2011.
- [15] A. Sharma and S. K. Gupta, “Machine Learning Approaches for Flood Prediction and Risk Assessment,” *International Journal of Computer Applications*, vol. 182, no. 44, pp. 15–20, 2019.
- [16] D. Kalita and N. Kataki, “Automated Flood Detection and Rapid SMS Alert System,” *GIS Science Journal*, vol. 12, no. 6, pp. 793–798, 2025.
- [17] A. Khan, S. K. Gupta, E. I. Assiri, M. Rashid, Y. T. Mohammed, M. Najim, and Y. R. Alharbi, “Flood Monitoring and Warning System: Het-Sens a Proposed Model,” in *Proc. 2nd Int. Conf. Computer and Information Sciences (ICCIS)*, Sakaka, Saudi Arabia, Nov. 2020.
- [18] G. Singh, N. Bisht, P. Bisht, and P. Singh, “IoT-Based Flood Monitoring and Alerting System with Weather Forecasting,” *International Journal of Innovative Technology and Exploring Engineering (IJITEE)*, vol. 9, no. 6, pp. 559–563, 2020.
- [19] S. Gejje, M. Abishek, M. P. Sampath, P. Sharath, and G. Yathish, “Sewage/Flood Overflow Monitoring and Alerting System,” *ACS Journal for Science and Engineering*, vol. 3, no. S1, pp. 29–35, 2024.
- [20] S. B. Zahir, P. Ehkan, T. Sabapathy, M. Jusoh, M. N. Osman, and M. N. Yasin, “Smart IoT Flood Monitoring System,” *Journal of Physics: Conference Series*, vol. 1339, no. 1, Art. no. 012043, 2019.