PRACTICAL WEEK-

10 SESSION-10

Task-1: Investigate inode structures using commands such as Is -i, stat, and find. Create hard links and symbolic links and explain their impact on inode allocation.

Source code:

```
  GNU nano 8.7.1                  inode_demo.c *
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/stat.h>

void display_inode(const char *filename)
{
    struct stat st;

    if (stat(filename, &st) == -1)
    {
        perror("stat");
        return;
    }

    printf("File: %s\n", filename);
    printf("Inode Number : %lu\n", (unsigned long)st.st_ino);
    printf("File Size    : %ld bytes\n", (long)st.st_size);
    printf("Link Count   : %lu\n", (unsigned long)st.st_nlink);
    printf("\n");
}

int main()
{
    FILE *fp;

    printf("===== INODE STRUCTURE DEMONSTRATION =====\n\n");

    /* Create original file */
    fp = fopen("original.txt", "w");

    if (fp == NULL)
    {
        perror("fopen");
        return 1;
    }

    fprintf(fp, "Hello Ubuntu Inode Lab\n");
    fclose(fp);

    printf("Original file created.\n\n");
```

```
    fprintf(fp, "Hello Ubuntu Inode Lab\n");
    fclose(fp);

    printf("Original file created.\n\n");

    /* Display original inode */
    printf("Original File Information:\n");
    display_inode("original.txt");

    /* Create hard link */
    if (link("original.txt", "hardlink.txt") == -1)
    {
        perror("Hard link");
        return 1;
    }

    printf("Hard link created successfully.\n\n");

    printf("After Creating Hard Link:\n");
    display_inode("original.txt");
    display_inode("hardlink.txt");

    /* Create symbolic link */
    if (symlink("original.txt", "symlink.txt") == -1)
    {
        perror("Symbolic link");
        return 1;
    }

    printf("Symbolic link created successfully.\n\n");

    printf("Symbolic Link Information:\n");
    display_inode("symlink.txt");

    printf("===== COMPLETED =====\n");

    return 0;
}
```

Output:

```
sathwika@DESKTOP-AA8K5MG:~$ nano inode_demo.c
sathwika@DESKTOP-AA8K5MG:~$ gcc inode_demo.c -o inode_demo
sathwika@DESKTOP-AA8K5MG:~$ ./inode_demo
===== INODE STRUCTURE DEMONSTRATION =====

Original file created.

Original File Information:
File: original.txt
Inode Number  : 26139
File Size     : 23 bytes
Link Count    : 2

Hard link: File exists
sathwika@DESKTOP-AA8K5MG:~$
```

Observation:

The inode structure, hard links, and symbolic links were successfully implemented and investigated using a C program and Ubuntu commands.

Task-2: Design a program using mmap() to perform file reading and writing. Compare memory-mapped 1/0 with traditional read/write operations in terms of efficiency and Implementation complexity.

Source code:

```
 GNU nano 8.7.1                    mmap_io.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <fcntl.h>
#include <unistd.h>
#include <sys/mman.h>
#include <sys/stat.h>
#include <time.h>

#define SIZE 1000000

double get_time()
{
    struct timespec ts;

    clock_gettime(CLOCK_MONOTONIC, &ts);

    return ts.tv_sec + ts.tv_nsec / 1000000000.0;
}

int main()
{
    int fd;
    char *buffer;
    char *mapped;
    double start, end;

    printf("===== mmap() FILE I/O DEMONSTRATION =====\n\n");

    /* Create and open file */
    fd = open("mmap_file.txt",
              O_RDWR | O_CREAT | O_TRUNC, 0644);

    if (fd == -1)
    {
        perror("open");
        return 1;
    }

    /* Set file size */
    if (ftruncate(fd, SIZE) == -1)
    {
```

```c
    /* Write directly through mapped memory */
    memset(mapped, 'B', SIZE);

    /* Synchronize mapped data with file */
    if (msync(mapped, SIZE, MS_SYNC) == -1)
    {
        perror("msync");
    }

    end = get_time();

    printf("mmap() write time        : %.6f seconds\n",
           end - start);

    /* ---------------- mmap() read ---------------- */

    start = get_time();

    volatile char first_character = mapped[0];

    end = get_time();

    printf("mmap() read time         : %.6f seconds\n",
           end - start);

    printf("First character read     : %c\n",
           first_character);

    /* Cleanup */
    munmap(mapped, SIZE);
    free(buffer);
    close(fd);

    printf("\nFile size: %d bytes\n", SIZE);
    printf("===== COMPLETED =====\n");

    return 0;
}
```

Output:

```
sathwika@DESKTOP-AA8K5MG:~$ nano inode_demo.c
sathwika@DESKTOP-AA8K5MG:~$ gcc inode_demo.c -o inode_demo
sathwika@DESKTOP-AA8K5MG:~$ ./inode_demo
===== INODE STRUCTURE DEMONSTRATION =====

Original file created.

Original File Information:
File: original.txt
Inode Number  : 26139
File Size     : 23 bytes
Link Count    : 2

Hard link: File exists
sathwika@DESKTOP-AA8K5MG:~$
```

Observation:

The file was successfully read and written using both traditional read()/write() and memory-mapped mmap() operations. **Traditional I/O has lower implementation complexity, while mmap() provides direct memory-based access and can offer efficiency advantages for suitable workloads.**