

SKILL WEEK-11

SESSION-21

Task-1: To Connect Modules, Validate Interfaces, Test End-to-End Execution, Handle Errors, Improve Reliability, Refactor 4 Components.

Source code:

Nano parser.c:

```
GNU nano 8.7.1 parser.c *
#include <stdio.h>
#include <string.h>
#include "parser.h"

int parse_command(char *input, char *args[])
{
    int count = 0;

    char *token = strtok(input, " \\t\\n");

    while (token != NULL && count < MAX_ARGS - 1)
    {
        args[count++] = token;
        token = strtok(NULL, " \\t\\n");
    }

    args[count] = NULL;

    return count;
}
```

nano executor.c:

```
GNU nano 8.7.1 executor.c *
#include <stdio.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <stdlib.h>

#include "executor.h"

pid_t execute_command(char *args[])
{
    pid_t pid = fork();

    if (pid < 0)
    {
        perror("fork");
        return -1;
    }

    if (pid == 0)
    {
        execvp(args[0], args);

        perror("execvp");
        exit(127);
    }

    return pid;
}
```

Nano job.c:

```
GNU nano 8.7.1 job.c *
#include <stdio.h>
#include <string.h>
#include <sys/wait.h>

#include "job.h"

Job jobs[MAX_JOBS];
int job_count = 0;

void add_job(pid_t pid, const char *command)
{
    if (job_count >= MAX_JOBS)
    {
        printf("Job table is full.\n");
        return;
    }

    jobs[job_count].job_id = job_count + 1;
    jobs[job_count].pid = pid;

    snprintf(jobs[job_count].command,
             sizeof(jobs[job_count].command),
             "%s", command);

    strcpy(jobs[job_count].state, "Running");

    job_count++;
}

void update_job(pid_t pid, int status)
{
    for (int i = 0; i < job_count; i++)
    {
        if (jobs[i].pid == pid)
        {
            if (WIFEXITED(status))
                strcpy(jobs[i].state, "Completed");

            else if (WIFSIGNALED(status))
                strcpy(jobs[i].state, "Terminated");
        }
    }
}
```

nano main.c:

```
GNU nano 8.7.1 main.c *
#include <stdio.h>
#include <string.h>
#include <unistd.h>
#include <sys/wait.h>

#include "parser.h"
#include "executor.h"
#include "job.h"

int main()
{
    char input[100];
    char *args[MAX_ARGS];

    printf("=====\n");
    printf("    Modular Linux Shell\n");
    printf("=====\n");

    while (1)
    {
        printf("myshell> ");
        fflush(stdout);

        if (fgets(input, sizeof(input), stdin) == NULL)
        {
            printf("\nInput error or EOF.\n");
            break;
        }

        if (strcmp(input, "\n") == 0)
            continue;

        int count = parse_command(input, args);

        if (count == 0)
            continue;

        /* Built-in exit command */
        if (strcmp(args[0], "exit") == 0)
        {
            printf("Shell exiting...\n");
            break;
        }
    }
}
```

```

        break;
    }

    /* Built-in jobs command */
    if (strcmp(args[0], "jobs") == 0)
    {
        show_jobs();
        continue;
    }

    /* Execute external command */
    pid_t pid = execute_command(args);

    if (pid < 0)
    {
        printf("Execution failed.\n");
        continue;
    }

    add_job(pid, args[0]);

    printf("Job created: PID=%d\n", pid);

    /* Wait for foreground process */
    int status;

    if (waitpid(pid, &status, 0) < 0)
    {
        perror("waitpid");
    }
    else
    {
        update_job(pid, status);
    }
}

return 0;
}

```

Output:

```

avulasanjana@SanjanaReddy:~$ nano parser.c
avulasanjana@SanjanaReddy:~$ nano executor.c
avulasanjana@SanjanaReddy:~$ nano job.h
avulasanjana@SanjanaReddy:~$ nano job.c
avulasanjana@SanjanaReddy:~$ nano main.c
avulasanjana@SanjanaReddy:~$ gcc main.c parser.c executor.c job.c -o myshell
avulasanjana@SanjanaReddy:~$ ./myshell
=====
Modular Linux Shell
=====
myshell> ls
Job created: PID=932
File1.txt          keyboard_input      session3_task1.c
File2.txt          keyboard_input.c    session3_task2
LICENSE            lowlevel_copy       session3_task2.c
Makefile           lowlevel_copy.c     session4_task1
OSSP               main.c              session4_task1.c
Q1_shell           main_loop            session4_task2
Q2_dispatch         main_loop.c          session4_task2.c
README.md          mmap_compare         session5_task1
append_redirection mmap_compare.c        session5_task1.c
append_redirection.c mmap_file.txt         session5_task2
assets             mmap_io              session5_task2.c
background_jobs     mmap_io.c            session6_task1
background_jobs.c   mmap_test.txt         session6_task1.c
bin                mutex_counter        session6_task2
client              mutex_counter.c       session6_task2.c
client.c            myshell               session7_task1
client_to_server    obj                   session7_task1.c
combined_redirection original.txt           session7_task2
combined_redirection.c ossp_2520090159       session7_task2.c
command_executor    output.txt            session8_task1
command_executor.c  output_redirection    session8_task1.c
complex_commands    output_redirection.c  session8_task2
complex_commands.c  parser.c              session8_task2.c
deadlock            parser.h              sigint_shell
deadlock.c          parser_double_quotes  sigint_shell.c
destination.txt     parser_double_quotes.c signal_demo
docs                parser_escape          signal_demo.c
double_quotes       parser_escape.c        signal_handlers
double_quotes.c     parser_quotes          signal_handlers.c
error.txt           parser_quotes.c        signal_test
executor.c           pipe_exec              signal_test.c
executor.h           pipe_exec.c            sigtstp_jobs
fifo_project        practical_week6_client sigtstp_jobs.c
file_copy            practical_week6_client.c single_quotes

```

Pwd:

```
myshell> pwd
Job created: PID=933
/home/avulasanjana
```

Echo:

```
myshell> echo
Job created: PID=934
```

Jobs:

```
myshell> jobs

----- Job List -----
[1] PID=932 Completed    ls
[2] PID=933 Completed    pwd
[3] PID=934 Completed    echo
-----
```

Error Handling:

```
myshell> abcxyz
Job created: PID=935
execvp: No such file or directory
myshell> exit
Shell exiting...
```

Observation:

The four modules communicate through clearly defined header interfaces. Commands entered through the main shell are parsed, executed by the executor, and recorded by the job manager. Invalid commands generate errors without terminating the shell.

Task-2: TO Detect Runtime Errors, Generate Messages, Log Failures, Handle Invalid Syntax, Recover Gracefully, Test Error Scenarios.

Source code:

```

GNU nano 8.7.1                                error_handling.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <errno.h>
#include <sys/wait.h>

#define MAX_INPUT 100
#define MAX_ARGS 20

/* Log an error message into a file */
void log_error(const char *message)
{
    FILE *file = fopen("shell_errors.log", "a");

    if (file == NULL)
    {
        perror("Unable to open error log");
        return;
    }

    fprintf(file, "%s\n", message);
    fclose(file);
}

/* Display and log an error */
void report_error(const char *message)
{
    fprintf(stderr, "Error: %s\n", message);
    log_error(message);
}

/* Parse command */
int parse_command(char *input, char *args[])
{
    int count = 0;

    char *token = strtok(input, " \\t\\n");

    while (token != NULL)
    {
        if (count >= MAX_ARGS - 1)

```

```

GNU nano 8.7.1                                error_handling.c *
/* Check basic syntax */
int check_syntax(char *input)
{
    if (strchr(input, '|') != NULL)
    {
        char *pipe_position = strchr(input, '|');

        if (pipe_position == input ||
            *(pipe_position + 1) == '\\0' ||
            *(pipe_position + 1) == '\\n')
        {
            report_error("Invalid pipe syntax.");
            return -1;
        }
    }

    return 0;
}

int main()
{
    char input[MAX_INPUT];
    char input_copy[MAX_INPUT];
    char *args[MAX_ARGS];

    printf("=====\n");
    printf("    Shell Error Handling Demo\n");
    printf("=====\n");

    while (1)
    {
        printf("myshell> ");
        fflush(stdout);

        if (fgets(input, sizeof(input), stdin) == NULL)
        {
            report_error("Failed to read input.");
            break;
        }

        /* Empty input */
        if (strcmp(input, "\\n") == 0)

```

```

GNU nano 8.7.1 error_handling.c
/* Parent waits for child */
int status;

if (waitpid(pid, &status, 0) < 0)
{
    report_error("waitpid() failed.");
    continue;
}

/* Check runtime result */
if (WIFEXITED(status))
{
    int exit_status = WEXITSTATUS(status);

    if (exit_status == 127)
    {
        printf("Shell: Command failed, but shell continues.\n");
    }
    else
    {
        printf("Shell: Command completed successfully.\n");
    }
}
else if (WIFSIGNALED(status))
{
    printf("Shell: Process terminated by signal %d.\n",
        WTERMSIG(status));

    char log_message[200];
    snprintf(log_message,
        sizeof(log_message),
        "Process terminated by signal %d",
        WTERMSIG(status));

    log_error(log_message);
}

return 0;

```

Output:

```

avulasanjana@SanjanaReddy:~$ nano error_handling.c
avulasanjana@SanjanaReddy:~$ gcc error_handling.c -o error_handling
avulasanjana@SanjanaReddy:~$ ./error_handling
=====
Shell Error Handling Demo
=====
myshell> echo Hello
Hello
Shell: Command completed successfully.
myshell> abcxyz
Error: Cannot execute 'abcxyz': No such file or directory
Shell: Command failed, but shell continues.
myshell> | ls
Error: Invalid pipe syntax.
myshell> |

```

Observation:

The program detects invalid syntax and runtime failures, displays descriptive error messages, records failures in shell_errors.log, and returns to the shell prompt instead of terminating unexpectedly.

SESSION-22

Task-1: To Run Valgrind, Identify Leaks, Fix Memory Errors, Release Resources, Verify Cleanup, Document Findings.

Source code:

```
GNU nano 8.7.1 memory_test.c *
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

int main()
{
    char *name;
    char *buffer;

    printf("Memory Test Program\n");
    printf("-----\n");

    /* Allocate memory */
    name = malloc(50 * sizeof(char));

    if (name == NULL)
    {
        printf("Memory allocation failed.\n");
        return 1;
    }

    strcpy(name, "Linux Shell");

    printf("Name: %s\n", name);

    /* Another allocation */
    buffer = malloc(100 * sizeof(char));

    if (buffer == NULL)
    {
        printf("Buffer allocation failed.\n");
        free(name);
        return 1;
    }

    return 1;
}

strcpy(buffer, "Testing memory management with Valgrind.");

printf("Buffer: %s\n", buffer);

/* Properly release memory */
free(name);
free(buffer);

printf("Memory released successfully.\n");

return 0;
}
```

Output:

```
avulasanjana@SanjanaReddy:~$ nano memory_test.c
avulasanjana@SanjanaReddy:~$ gcc -g -Wall -Wextra memory_test.c -o memory_test
avulasanjana@SanjanaReddy:~$ ./memory_test
Memory Test Program
-----
Name: Linux Shell
Buffer: Testing memory management with Valgrind.
Memory released successfully.
```

Observation:

Initially, when free(buffer) is removed, Valgrind reports memory still in use at program termination. After adding free(buffer), Valgrind reports that all allocated heap blocks were released and no memory errors remain.

Task-2: To Design Test Cases, Create Test Scripts, Automate Execution, Verify Outputs, Compare Results, Generate reports.

Source code:

Nano test_program.c:

```
GNU nano 8.7.1 test_program.c *
#include <stdio.h>
#include <string.h>

int main(int argc, char *argv[])
{
    if (argc < 2)
    {
        printf("ERROR: No command provided\n");
        return 1;
    }

    if (strcmp(argv[1], "hello") == 0)
    {
        printf("Hello Linux\n");
    }
    else if (strcmp(argv[1], "status") == 0)
    {
        printf("System is running\n");
    }
    else if (strcmp(argv[1], "exit") == 0)
    {
        printf("Program exiting\n");
    }
    else
    {
        printf("ERROR: Unknown command\n");
        return 1;
    }

    return 0;
}
```

Nano test_case.txt:

```
TC01|hello|Hello Linux
TC02|status|System is running
TC03|exit|Program exiting
TC04|unknown|ERROR: Unknown command
TC05||ERROR: No command provided
```

Nano run_tests.sh:

```
GNU nano 8.7.1 run_tests.sh *
#!/bin/bash

PROGRAM="./test_program"
REPORT="test_report.txt"

total=0
passed=0
failed=0

echo "===== > "$REPORT"
echo "      AUTOMATED TEST REPORT" >> "$REPORT"
echo "===== >> "$REPORT"
echo "" >> "$REPORT"

while IFS='|' read -r test_id input expected
do
    total=$((total + 1))

    if [ -z "$input" ]; then
        actual=$($PROGRAM 2>&1)
    else
        actual=$($PROGRAM "$input" 2>&1)
    fi

    echo "Test: $test_id"

    if [ "$actual" = "$expected" ]; then
        echo "Result: PASS"
        passed=$((passed + 1))

        echo "$test_id : PASS" >> "$REPORT"
    else
        echo "Result: FAIL"
        echo "Expected: $expected"
        echo "Actual : $actual"

        failed=$((failed + 1))

        echo "$test_id : FAIL" >> "$REPORT"
        echo "Expected: $expected" >> "$REPORT"
        echo "Actual: $actual" >> "$REPORT"
    fi

    echo "Actual: $actual" >> "$REPORT"
fi

echo "-----"

done < test_cases.txt

echo "" >> "$REPORT"
echo "===== >> "$REPORT"
echo "Total Tests : $total" >> "$REPORT"
echo "Passed Tests : $passed" >> "$REPORT"
echo "Failed Tests : $failed" >> "$REPORT"
echo "===== >> "$REPORT"

echo ""
echo "=====
echo "      TEST SUMMARY"
echo "=====
echo "Total Tests : $total"
echo "Passed Tests : $passed"
echo "Failed Tests : $failed"
echo "=====
echo ""
echo "Report generated: $REPORT"
```

Output:

```
avulasanjana@SanjanaReddy:~$ nano test_program.c
avulasanjana@SanjanaReddy:~$ gcc test_program.c -o test_program
avulasanjana@SanjanaReddy:~$ ./test_program hello
Hello Linux
avulasanjana@SanjanaReddy:~$ nano test_cases.txt
avulasanjana@SanjanaReddy:~$ nano run_tests.sh
avulasanjana@SanjanaReddy:~$ chmod +x run_tests.sh
avulasanjana@SanjanaReddy:~$ ./run_tests.sh
Test: TC01
Result: PASS
-----
Test: TC02
Result: PASS
-----
Test: TC03
Result: PASS
-----
Test: TC04
Result: PASS
-----
Test: TC05
Result: PASS
-----

=====
TEST SUMMARY
=====
Total Tests : 5
Passed Tests : 5
Failed Tests : 0
=====

Report generated: test_report.txt
```

```
avulasanjana@SanjanaReddy:~$ cat test_report.txt
=====
AUTOMATED TEST REPORT
=====

TC01 : PASS
TC02 : PASS
TC03 : PASS
TC04 : PASS
TC05 : PASS

=====
Total Tests : 5
Passed Tests : 5
Failed Tests : 0
=====
avulasanjana@SanjanaReddy:~$ |
```

Observation:

The automated script executes all test cases without requiring manual testing. It compares the actual program output with the expected output and identifies each test as **PASS** or **FAIL**.

