


IKEv1 aggressive mode (edge case)

Analysed 29/09/2026, 02:44:59 · 1 tunnel · model bundle v1 (a88b2a4)
· contract antardrishti.result/1



Antardrishti
SEE INSIDE THE TUNNEL

7d2a8073



0-100, worst tunnel; confident critical findings set a floor of 90

4 checks failed or raised a warning across 1 tunnel.

5 checks could not be decided from this capture (for example, PFS needs a rekey in the capture); they are listed as not determinable, never guessed.

Top findings

High tunnel 0 · IKEv1 aggressive mode

IKEv1 aggressive mode sends the identity in the clear and, with a pre-shared key, a hash an attacker can crack offline

Medium tunnel 0 · IKE version

The tunnel uses IKEv1, which NIST SP 800-77r1 recommends against; use IKEv2

Medium tunnel 0 · Traffic metadata exposure

A passive observer can tell the traffic inside apart: icmp (100% of bytes, presence 99%)

Low tunnel 0 · Peer authentication

IKEv1 authenticates with a pre-shared key; its strength cannot be seen

Traffic overview

Tunnel	Handshake	What it carries (share of bytes)	Risk
#0	full	ICMP 100%	39 Medium

Recommendations

1. IKEv1 aggressive mode: Disable aggressive mode (or move to IKEv2).
2. IKE version: Migrate the tunnel to IKEv2.
3. Traffic metadata exposure: Enable TFC padding (RFC 4303 section 2.7) or dummy traffic where hiding activity matters.
4. Peer authentication: Prefer certificate (RSA-PSS or ECDSA) authentication; if a PSK is used, make it long and random.

Passive analysis of the outer capture only: no traffic was decrypted and no keys were used. Facts marked "inferred" come from models trained on the Antardrishti dataset; their confidence is calibrated, and findings below 80% confidence are worded "likely".