Battery-electric tractors for Värnamo, 2027: order 7

Recommendation. Order 7 tractors under quotation Q-26-1187, for V03, V05, V09, V11, V16, V18, V33. The other seven duties need 460 to 470 kWh on the January design day against a limit of 442 kWh.

Duty	Shipper	Delivery	Round trip km	Planning load t	Design-day kWh	Electric
V03	Gnosjö Stålcenter AB	Helsingborg	294	29.0	430	Yes
V05	Bredaryds Plast AB	Ängelholm	300	7.7	420	Yes
V09	Vaggeryds Glas AB	Göteborg	261	21.0	410	Yes
V11	Hillerstorps Metall AB	Kristianstad	300	26.4	430	Yes
V16	Rydaholms Pall AB	Varberg	298	9.0	410	Yes
V18	Anderstorps Elektronik AB	Alingsås	304	5.4	420	Yes
V33	Hestra Frukt & Grönt AB	Västervik	300	12.6	430	Yes
V02	Kulltorps Cykel AB	Kalmar	339	3.9	460	No
V07	Skillingaryds Ballast AB	Linköping	284	32.0	460	No
V14	Värnamo Isolering AB	Karlskrona	334	4.7	460	No
V21	Reftele Trä AB	Malmö	318	18.4	470	No
V24	Gislaveds Livsmedel AB	Oskarshamn	299	15.1	460	No
V27	Gränna Dryckes AB	Trollhättan	343	13.5	470	No
V30	Bankeryds Mejeri ek. för.	Uddevalla	292	13.4	460	No

Energies to the nearest 10 kWh at -5 C and each duty's planning load. Limit: 85 per cent of the 519 kWh a 540 kWh battery keeps after its first year.

Basis. A model of each pilot duty-day's energy (2334 days) on distance, climb, cold, speed, the combination's weight, the payload and the trailer's fridge unit. (1) The pilot's payloads are shippers' declarations; taken to the loads the Värnamo weighbridge shows they stand for, a tonne costs 2.2 kWh per 100 loaded km (1.3 on the declarations). (2) The tractor and trailer weigh on every leg: the pilot's combinations ran 17.6 to 22.7 t, and V02 and V14's double decks with the 2027 tractor weigh 22.7 and 22.5 t. (3) A multi-drop load comes off along the run: V03's rides 60 per cent of its loaded km, V11's 57. (4) The ePTO fridge units run from the battery, about 4.4 kW for the whole duty: V24 and V30 pull them; the diesel units on V33 draw nothing. (5) Below freezing the draw rises faster (a second rate below 0 C, chosen on Jan-Feb 2026 held out). (6) The batteries lost 3.8 per cent for good in their first year, net of the cold. (7) On a -5 C day the pilot drove at 77 per cent of the routing tool's speed, against 89 over the year.

If one is skipped. Trailer left out: 9 tractors. Loads to the last drop: 5. No fridge term: 9. Every reefer drawing: 7 (V30 in, V33 out). The year's speed ratio: 4; the routing tool's speed: 0; no speed term: 9. Declared weights: 8. One cold rate: 9. No first-year loss: 9. Trailer, drops and fridge units all left out, at the year's speed ratio: 5. The workbook has each route.

Inger Norman, Transport planning