Battery-electric tractors for Värnamo, 2027: order 6

Recommendation. Order 6 tractors under quotation Q-26-1187, for V02, V05, V09, V14, V16, V18. Not 8 or 9: the heavy duties V03, V07, V11 need 450 to 460 kWh on the January design day against a limit of 442 kWh, and V21, V24, V27, V30, V33 are further over.

Duty	Shipper	Delivery	Round trip km	Planning load t	Design-day kWh	Electric
V02	Kulltorps Cykel AB	Kalmar	305	3.9	410	Yes
V05	Bredaryds Plast AB	Ängelholm	299	7.6	420	Yes
V09	Vaggeryds Glas AB	Göteborg	266	20.9	400	Yes
V14	Värnamo Isolering AB	Karlskrona	321	4.7	430	Yes
V16	Rydaholms Pall AB	Varberg	290	9.1	410	Yes
V18	Anderstorps Elektronik AB	Alingsås	304	5.5	420	Yes
V03	Gnosjö Stålcenter AB	Helsingborg	283	29.1	450	No
V07	Skillingaryds Ballast AB	Linköping	279	32.0	460	No
V11	Hillerstorps Metall AB	Kristianstad	288	26.6	450	No
V21	Reftele Trä AB	Malmö	317	18.5	470	No
V24	Vaggeryds Glas AB	Oskarshamn	308	20.9	470	No
V27	Gränna Dryckes AB	Trollhättan	326	13.6	470	No
V30	Bankeryds Mejeri ek. för.	Uddevalla	316	13.4	460	No
V33	Kulltorps Cykel AB	Västervik	355	4.0	480	No

Energies to the nearest 10 kWh at -5 C and each duty's planning load. Limit: 85 per cent of the 520 kWh a 540 kWh battery keeps after its first year.

Basis. A model of each pilot duty-day's energy (2334 days) on distance, climb, cold and payload. Three things move the order. (1) The pilot's payloads are shippers' declarations; at Värnamo, where the same shippers' loads are weighed, the clerks' figures scatter widely around the weighed load, and the dairy declares its planned pallets at a standard weight each. Fitted on the declarations a tonne costs 1.2 kWh per 100 loaded km; taking each declaration to the weighed load it stands for, shipper by shipper, 2.0. (2) Below freezing the draw rises faster: one rate below 16 C fitted without Jan-Feb 2026 under-forecast those sub-zero days by 6.1 per cent, a further rate below 0 C by +0.7. (3) The pilot batteries lost 3.8 per cent of their capacity for good in their first year, once the cold days' temporary loss is taken out.

If any one is skipped. Declared weights: 8 tractors (V03, V07, V11 in, V14 out). One cold rate: 8 (V03, V11 in). No first-year loss: 9. The workbook has each route, the model and the calibration.

Inger Norman, Transport planning