Battery-electric tractors for Värnamo, 2027: order 8

Recommendation. Order 8 tractors under quotation Q-26-1187, for V02, V03, V05, V09, V11, V14, V16, V18. The other 6 duties need 450 to 470 kWh on the January design day against a limit of 438 kWh.

Duty	Shipper	Delivery	Round trip km	Planning load t	Design-day kWh	Electric
V02	Kulltorps Cykel AB	Kalmar	313	3.9	430	Yes
V03	Gnosjö Stålcenter AB	Helsingborg	296	28.9	420	Yes
V05	Bredaryds Plast AB	Ängelholm	300	7.6	420	Yes
V09	Vaggeryds Glas AB	Göteborg	263	20.8	410	Yes
V11	Hillerstorps Metall AB	Kristianstad	300	26.3	420	Yes
V14	Värnamo Isolering AB	Karlskrona	312	4.7	430	Yes
V16	Rydaholms Pall AB	Varberg	302	9.0	420	Yes
V18	Anderstorps Elektronik AB	Alingsås	309	5.4	430	Yes
V07	Skillingaryds Ballast AB	Linköping	284	32.0	450	No
V21	Reftele Trä AB	Malmö	311	18.5	450	No
V24	Gislaveds Livsmedel AB	Oskarshamn	320	15.1	460	No
V27	Gränna Dryckes AB	Trollhättan	342	13.4	470	No
V30	Bankeryds Mejeri ek. för.	Uddevalla	316	13.4	460	No
V33	Hestra Frukt & Grönt AB	Västervik	322	12.6	460	No

Energies to the nearest 10 kWh at -5 C and each duty's planning load. Limit: 85 per cent of the 515 kWh a 540 kWh battery keeps after its first year.

Basis. A model of each pilot duty-day's energy (2334 days) on distance, climb, cold, speed, the combination's weight and the payload. (1) The pilot's payloads are shippers' declarations, and the regional pilot duties carry 75 to 89 per cent of the loads the same shippers declare at Värnamo. The Värnamo weighbridge gives each shipper's declaration error; taking each pilot duty's loads from its own declarations, a tonne costs 1.9 kWh per 100 loaded km. Read through the Värnamo calibration line instead, every pilot duty comes out 0.5 to 4.4 t too heavy and the figure falls to 1.5; Gränna Dryckes' scale-weighed days (J07 11.6 t, J08 10.4 t) bear out the duties' own loads. (2) The batteries lost 4.6 per cent for good in their first year, most of it in the first months; a straight line in age gives 3.1. (3) On a -5 C day the pilot drove at 76 per cent of the routing tool's speed, against 89 over the year. (4) The tractor and trailer weigh on every leg (V02 and V14's double decks 22.6 and 22.5 t with the 2027 tractor), and a multi-drop load comes off along the run (V03's rides 60 per cent of its loaded km). (5) Below freezing the draw rises faster (a second rate below 0 C, chosen on Jan-Feb 2026 held out).

If one is skipped. The Värnamo calibration line, the straight-line loss and the year's speed ratio together: 5 tractors (V03, V05, V09, V11, V16). The same at the design-day speed: 10. The year's speed ratio alone: 1; the routing tool's speed: 0; no speed term: 10. Declared weights: 9. Trailer left out: 6. Loads to the last drop: 6. One cold rate: 9. No first-year loss: 13. The workbook has each route.

Inger Norman, Transport planning