



Complete Anthos prerequisites

NetApp Solutions

Kevin Hoke
May 24, 2021

This PDF was generated from https://docs.netapp.com/us-en/netapp-solutions/containers/anthos_task_complete_anthos_prerequisites.html on October 21, 2021. Always check docs.netapp.com for the latest.

Table of Contents

Complete Anthos prerequisites 1

Complete Anthos prerequisites

Now that the physical environment is set up, you can begin Anthos deployment. This starts with several prerequisites that you must meet to deploy the solution and access it afterward. Each of these steps are discussed in depth in the Anthos [GKE On-Prem Guide](#).

To prepare your environment for the deployment of Anthos on VMware, complete the following steps:

1. Create a Google Cloud project following the instructions available [here](#).



Your organization might already have a project in place intended for this purpose. Check with your cloud administration team to see if a project exists and is already configured for access to Anthos on VMware. All projects intended for use with Anthos must be whitelisted by Google. This includes the primary user account, additional team members, and the access service account created in a later step.

2. Create a deployment workstation from which to manage the installation of Anthos on VMware. The deployment workstation can be Linux, MacOS, or Windows. For the purposes of this validated deployment, Red Hat Enterprise Linux 7 was used.



This workstation can be hosted either internal or external to the NetApp HCI deployment. The only requirement is that it must be able to successfully communicate with the deployed VMware vCenter Server and the internet to function correctly.

3. Install [Google Cloud SDK](#) for interactions with Google Cloud. It can be downloaded as an archive of binaries for manual install or installed by either the apt-get (Ubuntu/Debian) or yum (RHEL) package managers.

```

[user@rhel7 ~]$ sudo yum install google-cloud-sdk
Failed to set locale, defaulting to C
Loaded plugins: langpacks, product-id, search-disabled-repos,
subscription-manager
Resolving Dependencies
--> Running transaction check
---> Package google-cloud-sdk.noarch 0:270.0.0-1 will be installed
--> Finished Dependency Resolution

Dependencies Resolved

=====
=====
Package                               Arch          Version          Repository
Size
=====
=====
Installing:
google-cloud-sdk                      noarch        270.0.0-1        google-cloud-
sdk                                  36 M
Transaction Summary
=====
=====
Install 1 Package

Total download size: 36 M
Installed size: 174 M
Is this ok [y/d/N]: y
Downloading packages:
6d81c821884ae40244c746f6044fc1bcd801143a0d9c8da06767036b8d090a24-google-
cloud-sdk-270.0.0-1.noar | 36 MB  00:00:00
Running transaction check
Running transaction test
Transaction test succeeded
Running transaction
  Installing : google-cloud-sdk-270.0.0-1.noarch
1/1
  Verifying  : google-cloud-sdk-270.0.0-1.noarch
1/1

Installed:
  google-cloud-sdk.noarch 0:270.0.0-1

Complete!

```



The gcloud binary must be at least version 265.0.0. You can update a manual install with a gcloud components update. However, if SDK was installed by a package manager, future updates must also be performed using that same package manager.

4. With the workstation configured, log in to Google Cloud with your credentials. To do so, enter the login command from the deployment workstation and retrieve a link that can be copied and pasted into a browser to allow interactive sign-in to Google services. After you have logged in, the web page presents a code that you can copy and paste back into the deployment workstation when prompted.

```
[user@rhel7 ~]$ gcloud auth login
```

Go to the following link in your browser:

```
https://accounts.google.com/o/oauth2/auth?code_challenge=7oPNSySHr_Sd2ZZ4K83koIeGTLVcdbjc8omr6zCbAI&prompt=select_account&code_challenge_method=S256&access_type=offline&redirect_uri=urn%3Aietf%3Awg%3Aoauth%3A2.0%3Aoob&response_type=code&client_id=32655940559.apps.googleusercontent.com&scope=https%3A%3F%2Fwww.googleapis.com%2Fauth%2Fuserinfo.email+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcloud-platform+https%3A%6F%2Fwww.googleapis.com%2Fauth%2Fappengine.admin+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Fcompute+https%3A%2F%2Fwww.googleapis.com%2Fauth%2Faccounts.reauth
```

Enter verification code: 6/swGAh52VVgB-

TRS5LVrSvP79ZdDlb9V6ObYUGqoY67a3zp9NPciIKsM

You are now logged in as [user@netapp.com].

Your current project is [anthos-dev]. You can change this setting by running:

```
$ gcloud config set project PROJECT_ID
```

5. Enable several APIs so that your environment can communicate with Google Cloud. The pods deployed in your clusters must be able to access <https://www.googleapis.com> and <https://gkeconnect.googleapis.com> to function as expected. Therefore, the VM_Network that the worker nodes are attached to must have internet access. To enable the necessary APIs, run the following command from the deployment workstation:

```
[user@rhel7 ~]$ gcloud services enable --project anthos-dev \
cloudresourcemanager.googleapis.com \
container.googleapis.com \
gkeconnect.googleapis.com \
gkehub.googleapis.com \
serviceusage.googleapis.com \
stackdriver.googleapis.com \
monitoring.googleapis.com \
logging.googleapis.com
```

6. Create a working directory called anthos-install, and change into that directory.

```
[user@rhel7 ~]$ mkdir anthos-install && cd anthos-install  
[user@rhel7 anthos-install]$
```

7. Before you can install Anthos on VMware, you must create four service accounts, each with a specific purpose in interacting with Google Cloud. The following table lists the accounts and their purposes.

Account Name	Purpose
component-access-sa	Used to download the Anthos binaries from Cloud Storage.
connect-register-sa	Used to register Anthos clusters to the Google Cloud console.
connect-agent-sa	Used to maintain the connection between user clusters and the Google Cloud.
logging-monitoring-sa	Used to write logging and monitoring data to Stackdriver.



Each account is assigned an email address that references your approved Google Cloud project name. The following examples all list the project Anthos-Dev, which was used during the NetApp validation. Make sure to substitute your appropriate project name in syntax examples where necessary.

```

[user@rhel7 anthos-install]$ gcloud iam service-accounts create
component-access-sa \
    --display-name "Component Access Service Account" \
    --project anthos-dev
[user@rhel7 anthos-install]$ gcloud iam service-accounts keys create
component-access-key.json \
    --iam-account component-access-sa@anthos-dev.iam.gserviceaccount.com

[user@rhel7 anthos-install]$ gcloud iam service-accounts create connect-
register-sa \
    --project anthos-dev
[user@rhel7 anthos-install]$ gcloud iam service-accounts keys create
connect-register-key.json \
    --iam-account connect-register-sa@anthos-dev.iam.gserviceaccount.com

[user@rhel7 anthos-install]$ gcloud iam service-accounts create connect-
agent-sa \
    --project anthos-dev
[user@rhel7 anthos-install]$ gcloud iam service-accounts keys create
connect-agent-key.json \
    --iam-account connect-agent-sa@anthos-dev.iam.gserviceaccount.com

[user@rhel7 anthos-install]$ gcloud iam service-accounts create logging-
monitoring-sa \
    --project anthos-dev
[user@rhel7 anthos-install]$ gcloud iam service-accounts keys create
logging-monitoring-key.json \
    --iam-account logging-monitoring-sa@anthos-
dev.iam.gserviceaccount.com

```

8. The final step needed to prepare your environment to deploy Anthos is to limit certain privileges to your service accounts. You need the associated email address for each service account listed in Step 7.
 - a. Using the component-access-sa account, assign the roles for `serviceusage.serviceUsageViewer`, `iam.serviceAccountCreator`, and `iam.roleViewer`.

```
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev\
  --member "serviceAccount:component-access-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/serviceusage.serviceUsageViewer"
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev\
  --member "serviceAccount:component-access-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/iam.serviceAccountCreator"
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev\
  --member "serviceAccount:component-access-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/iam.roleViewer"
```

- b. Using the connect-register-sa service account, assign the role for gkehub.admin.

```
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev \
  --member "serviceAccount:connect-register-sa@anthos-
dev.iam.gserviceaccount.com " \
  --role "roles/gkehub.admin"
```

- c. Using the connect-agent-sa account, assign the role for gkehub.connect.

```
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev \
  --member "serviceAccount:connect-agent-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/gkehub.connect"
```

- d. With the logging-monitoring-sa service account, assign the roles for stackdriver.resourceMetadata.writer, logging.logWriter, monitoring.metricWriter, and monitoring.dashboardEditor.


```
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev \
  --member "serviceAccount:logging-monitoring-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/stackdriver.resourceMetadata.writer"
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev\
  --member "serviceAccount:logging-monitoring-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/logging.logWriter"
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev\
  --member "serviceAccount:logging-monitoring-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/monitoring.metricWriter"
[user@rhel7 anthos-install]$ gcloud projects add-iam-policy-binding
anthos-dev\
  --member "serviceAccount:logging-monitoring-sa@anthos-
dev.iam.gserviceaccount.com" \
  --role "roles/monitoring.dashboardEditor"
```

9. Download the vCenter certificate for the VMWare CA; this is used later to authenticate to the vCenter during installation.

```
[user@rhel7 anthos-install]$ true | openssl s_client -connect anthos-
vc.cie.netapp.com:443 -showcerts 2>/dev/null | sed -ne '/-BEGIN/,/-
END/p' > vcenter.pem
```

Next: [Deploy the Anthos admin workstation](#)

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.