



vSphere VMFS Datastore - iSCSI Storage backend with ONTAP

NetApp Solutions

NetApp
September 20, 2021

This PDF was generated from https://docs.netapp.com/us-en/netapp-solutions/virtualization/vsphere_ontap_auto_block_iscsi.html on October 21, 2021. Always check docs.netapp.com for the latest.

Table of Contents

- vSphere VMFS Datastore - iSCSI Storage backend with ONTAP 1
 - About this task 1
 - What you need 1
 - Steps 1
 - ONTAP tasks 1
 - VMware vSphere tasks 2
 - What's next? 2

vSphere VMFS Datastore - iSCSI Storage backend with ONTAP

About this task

This section covers the creation of a VMFS datastore with ONTAP iSCSI storage.

For automated provisioning, use one of these scripts: [\[PowerShell\]](#), [Ansible Playbook](#), or [\[Terraform\]](#).

What you need

- The basic skills necessary to manage a vSphere environment and ONTAP.
- An ONTAP storage system (FAS/AFF/CVO/ONTAP Select/ASA) running ONTAP 9.8 or later
- ONTAP credentials (SVM name, userID, and password)
- ONTAP network port, SVM, and LUN information for iSCSI
- [A completed iSCSI configuration worksheet](#)
- vCenter Server credentials
- vSphere host(s) information
 - vSphere 7.0 or later
- iSCSI VMKernel adapter IP information
- Network switch(es)
 - With ONTAP system network data ports and connected vSphere hosts
 - VLAN(s) configured for iSCSI
 - (Optional) link aggregation configured for ONTAP network data ports
- ONTAP Tool for VMware vSphere deployed, configured, and ready to consume

Steps

1. Check compatibility with the [Interoperability Matrix Tool \(IMT\)](#).
2. [Verify that the iSCSI configuration is supported](#).
3. Complete the following ONTAP and vSphere tasks.

ONTAP tasks

1. [Verify the ONTAP license for iSCSI](#).
 - a. Use the `system license show` command to check if iSCSI is listed.
 - b. Use `license add -license-code <license code>` to add the license.
2. [Verify that the iSCSI protocol is enabled on the SVM](#).
3. Verify that iSCSI network logical interfaces are available on the SVM.



When an SVM is created using the GUI, iSCSI network interfaces are also created.

4. Use the `Network interface` command to view or make changes to the network interface.



Two iSCSI network interfaces per node are recommended.

5. [Create an iSCSI network interface](#). You can use the default-data-blocks service policy.
6. [Verify that the data-iscsi service is included in the service policy](#). You can use `network interface service-policy show` to verify.
7. [Verify that jumbo frames are enabled](#).
8. [Create and map the LUN](#). Skip this step if you are using ONTAP tools for VMware vSphere. Repeat this step for each LUN.

VMware vSphere tasks

1. Verify that at least one NIC is available for the iSCSI VLAN. Two NICs are preferred for better performance and fault tolerance.
2. [Identify the number of physical NICs available on the vSphere host](#).
3. [Configure the iSCSI initiator](#). A typical use case is a software iSCSI initiator.
4. [Verify that the TCP/IP stack for iSCSI is available](#).
5. [Verify that iSCSI portgroups are available](#).
 - We typically use a single virtual switch with multiple uplink ports.
 - Use 1:1 adapter mapping.
6. Verify that iSCSI VMKernel adapters are enabled to match the number of NICs and that IPs are assigned.
7. [Bind the iSCSI software adapter to the iSCSI VMKernel adapter\(s\)](#).
8. [Provision the VMFS datastore with ONTAP Tools](#). Repeat this step for all datastores.
9. [Verify hardware acceleration support](#).

What's next?

After these the tasks are completed, the VMFS datastore is ready to consume for provisioning virtual machines.

Ansible Playbook

```
## Disclaimer: Sample script for reference purpose only.

- hosts: '{{ vsphere_host }}'
  name: Play for vSphere iSCSI Configuration
  connection: local
  gather_facts: false
  tasks:
    # Generate Session ID for vCenter
    - name: Generate a Session ID for vCenter
```

```

uri:
  url: "https://{{ vcenter_hostname }}/rest/com/vmware/cis/session"
  validate_certs: false
  method: POST
  user: "{{ vcenter_username }}"
  password: "{{ vcenter_password }}"
  force_basic_auth: yes
  return_content: yes
register: vclogin

# Generate Session ID for ONTAP tools with vCenter
- name: Generate a Session ID for ONTAP tools with vCenter
  uri:
    url: "https://{{ ontap_tools_ip
}}:8143/api/rest/2.0/security/user/login"
    validate_certs: false
    method: POST
    return_content: yes
    body_format: json
    body:
      vcenterUserName: "{{ vcenter_username }}"
      vcenterPassword: "{{ vcenter_password }}"
  register: login

# Get existing registered ONTAP Cluster info with ONTAP tools
- name: Get ONTAP Cluster info from ONTAP tools
  uri:
    url: "https://{{ ontap_tools_ip
}}:8143/api/rest/2.0/storage/clusters"
    validate_certs: false
    method: Get
    return_content: yes
    headers:
      vmware-api-session-id: "{{ login.json.vmwareApiSessionId }}"
  register: clusterinfo

- name: Get ONTAP Cluster ID
  set_fact:
    ontap_cluster_id: "{{ clusterinfo.json |
json_query(clusteridquery) }}"
  vars:
    clusteridquery: "records[?ipAddress == '{{ netapp_hostname }}' &&
type=='Cluster'].id | [0]"

- name: Get ONTAP SVM ID
  set_fact:

```

```

    ontap_svm_id: "{{ clusterinfo.json | json_query(svmidquery) }}"
vars:
    svmidquery: "records[?ipAddress == '{{ netapp_hostname }}' &&
type=='SVM' && name == '{{ svm_name }}'].id | [0]"

- name: Get Aggregate detail
  uri:
    url: "https://{{ ontap_tools_ip
}}:8143/api/rest/2.0/storage/clusters/{{ ontap_svm_id }}/aggregates"
    validate_certs: false
    method: GET
    return_content: yes
    headers:
      vmware-api-session-id: "{{ login.json.vmwareApiSessionId }}"
      cluster-id: "{{ ontap_svm_id }}"
  when: ontap_svm_id != ''
  register: aggrinfo

- name: Select Aggregate with max free capacity
  set_fact:
    aggr_name: "{{ aggrinfo.json | json_query(aggrquery) }}"
vars:
    aggrquery: "max_by(records, &freeCapacity).name"

- name: Convert datastore size in MB
  set_fact:
    datastoreSizeInMB: "{{ iscsi_datastore_size |
human_to_bytes/1024/1024 | int }}"

- name: Get vSphere Cluster Info
  uri:
    url: "https://{{ vcenter_hostname }}/api/vcenter/cluster?names={{
vsphere_cluster }}"
    validate_certs: false
    method: GET
    return_content: yes
    body_format: json
    headers:
      vmware-api-session-id: "{{ vclogin.json.value }}"
  when: vsphere_cluster != ''
  register: vcenterclusterid

- name: Create iSCSI VMFS-6 Datastore with ONTAP tools
  uri:
    url: "https://{{ ontap_tools_ip
}}:8143/api/rest/3.0/admin/datastore"

```

```

    validate_certs: false
    method: POST
    return_content: yes
    status_code: [200]
    body_format: json
    body:
      traditionalDatastoreRequest:
        name: "{{ iscsi_datastore_name }}"
        datastoreType: VMFS
        protocol: ISCSI
        spaceReserve: Thin
        clusterID:  "{{ ontap_cluster_id }}"
        svmID:  "{{ ontap_svm_id }}"
        targetMoref: ClusterComputeResource:{{
vcenterclusterid.json[0].cluster }}
        datastoreSizeInMB:  "{{ datastoreSizeInMB | int }}"
        vmfsFileSystem: VMFS6
        aggrName:  "{{ aggr_name }}"
        existingFlexVolName: ""
        volumeStyle: FLEXVOL
        datastoreClusterMoref: ""
      headers:
        vmware-api-session-id:  "{{ login.json.vmwareApiSessionId }}"
    when: ontap_cluster_id != '' and ontap_svm_id != '' and aggr_name !=
''

    register: result
    changed_when: result.status == 200

```

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.