Status	Finished
Started	Monday, 3 November 2025, 4:22 PM
Completed	Monday, 3 November 2025, 4:44 PM
Duration	21 mins 46 secs

Question **1**

Correct

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.
The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

2
3
5

Output:

WBW
BWB
WBW
WBWBW
BWBWB
WBWBW
BWBWB
WBWBW

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main ()
{
int s,i,j;
int t;
scanf("%d",&t);
while(t--)
{
scanf("%d",&s);
for(i=0;i<s;i++)
{
```

```
for(j=0;j<s;j++)
{
if((i+j)%2==0)
{
printf("W");
}
else
{
printf("B");
}
}
printf("\n");
}
}
return 0;
}
```

	Input	Expected	Got	
✓	2 3 5	WBW BWB WBW WBWBW BWBWB WBWBW BWBWB WBWBW	WBW BWB WBW WBWBW BWBWB WBWBW BWBWB WBWBW	✓

Passed all tests! ✓

Question **2**

Correct

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

2
2 W
3 B

Output:

WB
BW
BWB
WBW
BWB

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main ()
{
    int t,n,i,j;
    char s;
    scanf("%d",&t);
    while(t--)
    {
        scanf("%d %c",&n,&s);
        char ch=(s=='W')?'B':'W';
        for(i=0;i<n;i++)
        {
            for(j=0;j<n;j++)
```

```
            {
                if((i+j)%2==0)
                {
                    printf("%c",s);
                }
                else
                {
                    printf("%c",ch);
                }
            }
            printf("\n");
        }
    }
    return 0;
}
```

	Input	Expected	Got	
✓	2 2 W 3 B	WB BW BWB WBW BWB	WB BW BWB WBW BWB	✓

Passed all tests! ✓

Question **3**

Correct

Problem Statement:

In a small coding competition, participants are to be grouped into teams of three members, each member represented by a number — 1, 2, and 3.
The rule of the competition states that no member can repeat within the same team.

Write a program to display all possible unique team combinations that can be formed using the members 1, 2, and 3 without repetition.

Sample Output:

1 2 3

1 3 2

2 1 3

2 3 1

3 1 2

3 2 1

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main ()
{
    int i,j,k;
    for (i=1;i<=3;i++)
    {
        for(j=1;j<=3;j++)
        {
            for(k=1;k<=3;k++)
            {
                if(i!=j&&j!=k&&i!=k)
                {
                    printf("%d %d %d\n",i,j,k);
                }
            }
        }
    }
    return 0;

}
```

	Expected	Got	
✓	1 2 3 1 3 2 2 1 3 2 3 1 3 1 2 3 2 1	1 2 3 1 3 2 2 1 3 2 3 1 3 1 2 3 2 1	✓

Passed all tests! ✓