

SATHYASEELAN - 241001235

Program:

```
#include <string.h>
#include <stdio.h>

int main() {
    char msg[50];
    int w,i,j,n;

    printf("window size: ");
    scanf("%d",&w);

    printf("Text message");
    scanf("%s",msg);
    n=strlen(msg);

    for(i=0;i<n;i+=w){
        printf("\nSender Buffer:\n");
        for(j=i;j<i+w&& j<n;j++) printf("Frame %d: %c\n",j+1,msg[j]);
        printf("Receiver: ");
        for(j=i;j<i+w&& j<n;j++) printf("ACK %d ",j+1);
        printf("\n");
    }
    printf("\n message transmitted successfully");
    return 0;
}
```

Output:

Online Python Compiler | Online C Compiler (Editor) | computer_network_exp | Computer_networks/cc | mail.google.com | + | Ask Gemini

programiz.com/c-programming/online-compiler/



C Online Compiler

Programiz PRO

main.c

Run

```
10 printf("window size: ");
11 scanf("%d",&w);
12
13 printf("Text message");
14 scanf("%s",msg);
15 n=strlen(msg);
16
17 for(i=0;i<n;i+=w){
18     printf("\nSender Buffer:\n");
19     for(j=i;j<i+w&&j<n;j++) printf("Frame %d: %c\n",j+1,msg[j]);
20     printf("Receiver: ");
21     for(j=i;j<i+w&&j<n;j++) printf("ACK %d ",j+1);
22     printf("\n");
23 }
24 printf("\n message transmitted successfully");
25 return 0;
26
27 }
```

Output

```
window size: 3
hello
Text message
Sender Buffer:
Frame 1: h
Frame 2: e
Frame 3: l
Receiver: ACK 1 ACK 2 ACK 3

Sender Buffer:
Frame 4: l
Frame 5: o
Receiver: ACK 4 ACK 5

message transmitted successfully
```

Type here to search

30°C Mostly cloudy

16:33 24-09-2026