Agent Ricochet

Version 1.0.0 · SatisVizion · Unity 6000.0.62f1 · URP 17.0.4

Drag to aim the agent arm, then release to shoot. Knock out every henchman with ricochets and chain reactions. Protect the scientist and avoid hitting the agent; ammunition is limited.

First run

1. Install Unity **6000.0.62f1** in Unity Hub. For Android add matching Android Build Support, SDK, NDK and OpenJDK; for browser builds add WebGL Build Support.
2. Open the supplied standalone project, or create a Unity 6 **URP** project before importing the buyer package. Required packages: URP **17.0.4**, uGUI **2.0.0**, Input System **1.14.2**, the standard Unity modules, **ScreenCapture** and **AndroidJNI**. The standalone project includes its manifest and lock file.
3. Import the complete product folder. Keep its required subfolders together: **Assets/SatisVizionAgentRicochet/Games/AgentRicochet**, **Assets/SatisVizionAgentRicochet/HyperCasualLiveOpsKit** and **Assets/SatisVizionAgentRicochet/TextMesh Pro**. Keep every `.meta` file and the game's private **Kit** folder; it is required runtime code.
4. Set Edit → Project Settings → Player → Other Settings → **Active Input Handling = Both** and restart Unity if prompted. Run **Tools → Agent Ricochet → Setup** after package import to select the supplied URP settings.
5. Open `Assets/SatisVizionAgentRicochet/Games/AgentRicochet/Scenes/AgentRicochet_Mobile.unity` and press Play. This is the portrait scene. A landscape WebGL scene is also included; use the scene appropriate for your build. Much of the game UI and world are created at runtime.

Gameplay and content

Drag to aim the agent arm, then release to shoot. Knock out every henchman with ricochets and chain reactions. Protect the scientist and avoid hitting the agent; ammunition is limited.

Deterministic bullet physics, three ricochets, mirrors, glass, ropes, hanging safes, pillars, barrels, armored guards, hostages and final-shot slow motion.

The source includes **25 authored levels** and seeded procedural continuation. Progress, settings and charges are stored locally with PlayerPrefs. Browser storage depends on the browser profile. The template includes source and editable level data; generated continuation is not advertised as hundreds of individually authored levels.

Boosters

- **Spy Scope** unlocks at level **3**.
- **Extra Mag** unlocks at level **6**.

- **Boom Round** unlocks at level **10**.
- **Agent Intel** unlocks at level **14**.

First-use guidance introduces each booster. Availability depends on the level, current state and remaining charges. Rewarded placements are simulated by default; only a completed reward callback should grant a refill. Use the DEV panel to unlock boosters for authoring, not as a substitute for real progression testing.

Manual editor and generation

Open **Tools → Agent Ricochet → Level Editor**. Duplicate a level before changing the original tutorial. The authoring file is `Assets/SatisVizionAgentRicochet/Games/AgentRicochet/Resources/agentricochet/Levels/levels.json`.

The visual editor supports placing and selecting steel, stone, wood, glass, mirrors, agents, henchmen, armored guards, scientists, ropes and physics props. Select a piece to adjust position, dimensions and angle. Name, First-time hint, Theme, Bullets and Breather are level settings. The physics bot used by Validate and Validate All is the same simulation used at runtime. For a safe first edit: select level 3, press Dup, give the copy a new Name and increase Bullets by one. Keep the first two tutorial boards intact. Press Validate, inspect its result, Save, then Play this level. For geometry edits, drag one selected piece a short distance and validate again; moving a hostage, mirror or rope can change the solving shot. Generation uses a seed and difficulty-curve controls; it accepts scenes only after the bot finds a legal solution. Generated scenes are not individually authored campaign levels.

The included editor supports saving, duplication and ordering, and provides generation and validation controls appropriate for this game. Read the actual validation result; a difficulty target is not a guarantee of player success. Use a repeatable seed when comparing generated variants. Test changed boards in Play mode.

First authored level schema

```
{
  "levels": [
    {
      "name": "First Contact",
      "hint": "Drag to aim at the henchman, then let go to shoot!",
      "theme": 0,
      "shots": 3,
      "par": 1,
      "diff": 29,
      "breather": false,
      "heroX": 1.2,
      "heroY": 1,
      "heroDir": 1,
      "boxes": [
        {
          "k": 0,
          "x": 5,
          "y": 0.65,
          "w": 9.4,
          "h": 0.7,
          "a": 0
        },
```

```
          {
            "k": 0,
            "x": 4.8,
            "y": 1.3,
            "w": 0.8,
            "h": 0.6,
            "a": 0
          }
        ],
        "ents": [
          {
            "k": 0,
            "x": 7.6,
            "y": 1,
            "dir": -1,
            "w": 0,
            "h": 0,
            "len": 0,
            "ang": 0,
            "bx": 0,
            "by": 0
          }
        ]
      }
    ]
}
```

Customisation

Game logic is under `Scripts`; presentation and UI are in the game's Game partial classes. Artwork, sound effects, music and levels are under `Resources/agentricochet`. Shared UI, audio, ad and haptic helpers live in `Kit/Runtime`; font files and placements are under `Kit/Resources/agentricochet/kit`. Keep resource paths unless you update every matching code reference.

Change Company Name, Product Name, Version and the Android application identifier in Player Settings to values you control. Do not publish under `com.satisvizion.agentricochet.demo`. Assign your own launcher/adaptive icon layers and review the splash screen, in-game title and other branding. Increase Android Bundle Version Code for each released update. Test UI fit, text and touch targets on an actual phone.

LiveOps, ads and haptics

The publisher-owned **HyperCasual LiveOps Kit** is included. Read its complete kit manual (HTML is also included offline).

Settings: `Assets/SatisVizionAgentRicochet/HyperCasualLiveOpsKit/Resources/HLK/HLKSettings.asset`. Shipping defaults are **Ads Mode Dummy (0)** and **IAP Mode Disabled (3)**. Banner, interstitial and rewarded placements are simulations. **No Google Mobile Ads, billing or other vendor SDK is included.** Automatic vendor-SDK installers are disabled. The game's own Kit is required code, not an advertising SDK.

To enable a real provider, separately install its official SDK, follow the kit manual, configure your own

identifiers, consent and privacy policy, then test the selected platform and all cancellation/failure cases. Do not enable SDK symbols without the corresponding dependency. Optional kit modules are capabilities, not production services already configured for this game. Native vibration needs a supported device; browser haptics and other native services have platform limits.

Development controls

Open DEV, press F2/backquote, or use the kit's top-left multi-tap shortcut. The global panel supports level jumps, booster access, ads and haptics controls. Add `HZ_RELEASE` to scripting defines when you want these development controls excluded from a consumer build. This does not configure real ads or certify store readiness.

Android release

Use the Mobile scene, portrait orientation and ARM64/IL2CPP with matching Unity tools. The provided APK is a **debug-signed development demo**, not a production store release. For release turn off Development Build and debugging, choose your own application identifier and review current store API requirements.

In Player → Publishing Settings create or select **your own keystore and alias**. Securely retain the keystore, alias and passwords for future updates; never redistribute signing secrets. Enable Build App Bundle for a Google Play AAB. Install a release candidate on a physical Android device and check touch, audio, haptics, pause/resume, saves and any enabled provider flows. Complete destination-store ads/data declarations and your privacy policy for the services actually enabled.

WebGL

Build the Mobile scene for a portrait-only demo with the built-in Default template and Brotli decompression fallback. Use **Tools → Agent Ricochet → Create Responsive WebGL Page** after building and select the output folder. This generates an original responsive page around the complete Build folder. Serve every loader, framework, data and WASM file over HTTP(S); `file://` is unsupported. Audio normally starts after a first click/tap.

The two-scene landscape-first route supports `?mobile=1` to switch to the following Mobile scene. The included WebGL build menu uses HLK's non-development **local showcase** scope. It supports simulated demos; configure your production providers and resolve the kit build-doctor checks for a real service release.

Troubleshooting

- Missing types: install the required packages and import all three roots, preserving `.meta` files.
- Pointer input exception: select Active Input Handling Both and restart Unity.
- Pink materials: use URP 17.0.4 and run the game's Setup command.
- Sparse scene in edit mode: world/UI objects are built at runtime; press Play.
- No real ad revenue: Dummy mode is simulated and no provider SDK is bundled.

- IAP is unavailable: it is deliberately Disabled by default; configure an official billing integration separately if you need it.
- Progress persists: use the development reset controls or deliberately clear this product's PlayerPrefs.
- WebGL does not load from a local file: serve the complete output over HTTP(S).

Licences and support

Retain the font, icon, TextMesh Pro and HLK licences and Third-Party Notices. See the game's `Third-Party Notices.txt` and `AI-DISCLOSURE.txt`. Marketing artwork is distinct from authentic gameplay captures. For product support use the marketplace item support channel or contact SatisVizion at satisvizion@gmail.com.