





Practical SAT Solving

Lecture 4 – Elementary SAT Solving Heuristics, Conflict-Driven Clause Learning

Markus Iser, Dominik Schreiber | May 12, 2025



SAtRes
Scalable Automated Reasoning

Overview

Recap. Lecture 3: Elementary SAT Solving Algorithms

- Local Search
- Resolution
- DP Algorithm
- DPLL Algorithm

Overview

Recap. Lecture 3: Elementary SAT Solving Algorithms

- Local Search
- Resolution
- DP Algorithm
- DPLL Algorithm

Today's Topics

- Elementary SAT Solving Heuristics
 - Branching Order
 - Branching Polarity
 - Restart Strategies
- Conflict-Driven Clause Learning

DPLL Algorithm: Iterative Variant

Decision Heuristics:

- Branching Order:
Which variable to choose?
- Branching Polarity:
Which value to assign?

Algorithm: iterativeDPLL(CNF Formula F)

Data: Trail (Stack of Literals)

```
1 while not all variables assigned by Trail do
2   if unitPropagation( $F$ , Trail) has CONFLICT then
3      $L \leftarrow$  last literal not tried both True and False
4     if no such  $L$  then return UNSAT
5     pop all literals after and including  $L$  from Trail
6     push  $\{L = 0\}$  on Trail
7   else
8      $L \leftarrow$  pick an unassigned literal
9     push  $\{L = 1\}$  on Trail
10 return SAT
```

Properties of Decision Heuristics

Desired properties

- Fast to compute
- Gives easy sub-problems

Properties of Decision Heuristics

Desired properties

- Fast to compute
- Gives easy sub-problems
 - Satisfy many clauses
 - Maximize unit propagation

Properties of Decision Heuristics

Desired properties

- Fast to compute
- Gives easy sub-problems
 - Satisfy many clauses
 - Maximize unit propagation

Types of heuristics

Properties of Decision Heuristics

Desired properties

- Fast to compute
- Gives easy sub-problems
 - Satisfy many clauses
 - Maximize unit propagation

Types of heuristics

- Static vs. Dynamic
 - Static: Based on formula statistics
 - Dynamic: Based on formula and current state
- Separate vs. Joint
 - Separate: Choose variable and value independently
 - Joint: Choose variable and value together

Decision Heuristics: Böhm's Heuristic

- $h_i(x)$: number of clauses of size i containing literal x which are not yet satisfied
- $H_i(x) := \alpha \max(h_i(x), h_i(\bar{x})) + \beta \min(h_i(x), h_i(\bar{x}))$ (let $\alpha := 1$ and $\beta := 2$, for example)
- Select literal x with the maximal vector $(H_1(x), H_2(x), \dots)$ under lexicographic order

Properties of Böhm's Heuristic

Goal: satisfy or reduce size of many and preferably short clauses

- Separate polarity heuristic (note that $H_i(x) = H_i(\bar{x})$)
→ select x if $\sum_i h_i(x) \geq \sum_i h_i(\bar{x})$
- depends on literal occurrence counts over the not yet satisfied clauses
- SAT Competition 1992: best heuristic for random instances

Decision Heuristics: Mom's Heuristic

Maximum Occurrences in clauses of Minimum Size

- $f^*(x)$: how often x occurs in the **smallest not yet satisfied** clauses
- Select variable x with a maximum $S(x) = (f^*(x) + f^*(\bar{x})) \cdot 2^k + f^*(x) \cdot f^*(\bar{x})$ (let $k := 10$, for example)

Properties of Mom's Heuristic

Goal: assign variables with **high occurrence** in short clauses

- Separate polarity heuristic
→ for example, select x if $f^*(\bar{x}) \geq f^*(x)$
- depends on literal occurrence counts over the not yet satisfied clauses
- Popular in the mid 90s (Find some variants in [Freeman 1995, pages 39f.](#))

Decision Heuristics: Jeroslow-Wang Heuristic

- Choose the literal x with a maximum $J(x) = \sum_{x \in c, c \in F} 2^{-|c|}$

Properties of Jeroslow-Wang Heuristic

Goal: assign variables with high occurrence in short clauses

- Considers all clauses, but shorter clauses are more important
- Separate polarity heuristic
→ for example, use conflict-seeking polarity heuristic
- Two-sided variant: choose variable x with maximum $J(x) + J(\bar{x})$
→ one-sided version works better
- Much better experimental results than Böhm and MOMS

(R)DLCS and (R)DLIS Heuristics

(Randomized) Dynamic Largest (Combined | Individual) Sum

- based on positive $C_P(x)$ and negative occurrences $C_N(x)$ of variable x
- used in the famous SAT solver **GRASP** in 2000

Properties of (R)DLCS and (R)DLIS Heuristics

- **Dynamic:** Take the current partial assignment into account
- **Combined:** select x with maximal $C_P(x) + C_N(x)$
- **Individual:** select x with maximal $\max(C_P(x), C_N(x))$
- **Randomized:** randomly select variable among the best

Recap

Decision Heuristics


- Böhm's Heuristic
- Mom's Heuristic
- Jeroslow-Wang Heuristic
- (R)DLCS and (R)DLIS Heuristics

Next up


Restart Strategies

Restarts Strategies: Motivation

Given n runs of randomized DPLL search, what is the average number of backtracks per run?



Heavy-tailed distribution




Standard distribution


[Gomes et al. 2000]

Restarts Strategies: Motivation

Given n runs of randomized DPLL search, what is the average number of backtracks per run?



Heavy-tailed distribution



Standard distribution

[Gomes et al. 2000]

Restart Strategies

Clear the partial assignment and backtrack to the root of the search tree.

- Recover from bad branching decisions
- Solve more instances on average
- Might decrease performance on easy instances

When to Restart?

- After some number of conflicts / backtracks
- The intervals between restarts should increase to guarantee completeness
 - Linear increase: too slow
 - Exponential increase: ok, with small exponent
 - MiniSat: k -th restart happens after 100×1.1^k conflicts


Restart Strategies: Inner / Outer Pattern (MiniSat)

Algorithm: Inner / Outer

Data: int inner = 100, outer = 100

```
1 while true do
2   run DPLL() with conflict-limit inner
3   restarts++
4   if inner  $\geq$  outer then
5     outer *= 1.1
6     inner = 100
7   else
8     inner *= 1.1
```

Restart Strategies: Inner / Outer Pattern (MiniSat)



Algorithm: Inner / Outer

Data: int inner = 100, outer = 100

```
1 while true do
2   run DPLL() with conflict-limit inner
3   restarts++
4   if inner ≥ outer then
5     outer *= 1.1
6     inner = 100
7   else
8     inner *= 1.1
```

Restart Strategies: Luby Sequence


Theorem [Luby et al, 1993]

Consider a **Las Vegas** algorithm A (i.e., correct but with **random run time**) and a restart strategy $S = \langle t_1, t_2, \dots \rangle$ (i.e., run A for time t_1 , then for time t_2 , etc.). Up to a constant factor, the Luby sequence is the **best possible universal strategy** to minimize the **expected run time** until a run is successful.

$$Luby = u \cdot (t_i)_{i \in \mathbb{N}} \quad \text{with} \quad t_i = \begin{cases} 2^{k-1} & \text{if } i = 2^k - 1 \\ t_{i-2^{k-1}+1} & \text{if } 2^{k-1} \leq i \leq 2^k - 1 \end{cases}$$

Example: 1, 1, 2, 1, 1, 2, 4, 1, 1, 2, 1, 1, 2, 4, 8, ...

Restart Strategies: Luby Sequence



Algorithm: Luby Sequence

Input: int i

```
1 for  $k = 1$  to 32 do
2   if  $i == (1 \ll k) - 1$  then
3     return  $1 \ll (k - 1)$ 

4 for  $k = 1$  to  $\infty$  do
5   if  $(1 \ll (k - 1)) \leq i \leq (1 \ll k) - 1$  then
6     return Luby( $i - (1 \ll (k - 1)) + 1$ )
```

run DPLL() with conflict-limit 512 · Luby(++restarts)

Restart Strategies: Luby Sequence

Luby Sequence: Reluctant Doubling

A more efficient implementation of the Luby sequence invented by Donald Knuth

Use the v_n of the following pairs (u_n, v_n) :

$$(u_1, v_1) = (1, 1);$$

$$(u_{n+1}, v_{n+1}) = u_n \ \& \ -u_n == v_n \ ? \ (u_n+1, 1) : (u_n, 2v_n);$$

Example: $(1, 1), (2, 1), (2, 2), (3, 1), (4, 1), (4, 2), (4, 4), (5, 1), \dots$


Branching Polarity: Phase Saving

Observation: Frequent restarts decrease performance on some satisfiable instances

Phase Saving / Assignment Caching

Idea: Remember **last assignment of each variable** and use it first in branching

- First implemented in **RSAT (2006)**
- Result: Phase saving stabilizes positive effect of restarts
- Best results in combination with non-chronological backtracking (follows)



Example: *A* and *B* are satisfied,
searching in component *C*

Recap

Decision Heuristics

Restart Strategies

- Inner / Outer Pattern
- Luby Sequence / Reluctant Doubling
- Phase Saving / Assignment Caching

Next up

Clause Learning

DPLL: Chronological Backtracking

$\{\{A, B\}, \{B, C\}, \{\neg A, \neg X, Y\},$
 $\{\neg A, X, Z\}, \{\neg A, X, \neg Z\},$
 $\{\neg A, \neg Y, Z\}, \{\neg A, \neg Y, \neg Z\}\}$


(Formula)

A, B, C, X, Y, Z

(Trail)

$\{\neg A, \neg Y, \neg Z\}$

(Conflicting Clause)



DPLL: Chronological Backtracking

$\{\{A, B\}, \{B, C\}, \{\neg A, \neg X, Y\},$
 $\{\neg A, X, Z\}, \{\neg A, X, \neg Z\},$
 $\{\neg A, \neg Y, Z\}, \{\neg A, \neg Y, \neg Z\}\}$


(Formula)

$A, B, C, \neg X, Z$

(Trail)

$\{\neg A, X, \neg Z\}$

(Conflicting Clause)




DPLL: Chronological Backtracking

$\{\{A, B\}, \{B, C\}, \{\neg A, \neg X, Y\},$
 $\{\neg A, X, Z\}, \{\neg A, X, \neg Z\},$
 $\{\neg A, \neg Y, Z\}, \{\neg A, \neg Y, \neg Z\}\}$ (Formula)

Observation: Conflicting clauses $\{\neg A, \neg Y, \neg Z\}$,
 $\{\neg A, X, \neg Z\}$ constrain only a fraction of the trail (B
and C irrelevant)

How to find out which assignments on the trail are
relevant for the actual conflict and immediately
backtrack to A ?



Implication Graph

Definition: Implication Graph

Given a formula F , assignment trail T , and conflicting clause C , the implication graph is a DAG $G = (V \cup \{\bot\}, E)$ of

- vertices $[\ell_i, d_i]$ for each literal ℓ_i with decision level d_i on the trail
- vertex $\bot$ representing the conflicting assignment

Note: all literals of C have edges to $\bot$

- edges $([\ell_i, d_i], [u_{i,j}, d_i])$ for each propagated literal $u_{i,j}$ at decision level d_i

The sink is always the **conflicting assignment**, and the sources are the **decision literals** involved in the conflict.


We can use this to determine the **reasons for the conflict**.

Example: Implication Graph

Implication graph for the conflicting state under the trail A, B, C, X, Y, Z .

The edge labels denote **clauses**, node labels indicate a variable assignment and its **decision level**.

- Consider inferring the clause $\{\neg A, \neg X\}$ by the following resolution steps: $(7 \circ_Z 5) \circ_Y 3$.
- Learning of $\{\neg A, \neg X\}$ prevents the solver choosing the same partial assignment again.



- $\{A, B\},$ (1)
- $\{B, C\},$ (2)
- $\{\neg A, \neg X, Y\},$ (3)
- $\{\neg A, X, Z\},$ (4)
- $\{\neg A, \neg Y, Z\},$ (5)
- $\{\neg A, X, \neg Z\},$ (6)
- $\{\neg A, \neg Y, \neg Z\}$ (7)

Conflict Analysis: Implementation

Implement trail as **stack of literals** together with a pointer to the **reason clause** (*null* for decisions) and the **decision level**. On each conflict, use the trail to trace back the implications to the conflict sources.

Example: Trail with conflicting clause $\{\neg A, \neg Y, \neg Z\}$

Var. Lvl. Reason

⚡	4	$\{\neg A, \neg Y, \neg Z\}$
Z	4	$\{\neg A, \neg Y, Z\}$
Y	4	$\{\neg A, \neg X, Y\}$
X	4	null
C	3	null
B	2	null
A	1	null


Trail Resolution:

- $\{\neg A, \neg Y, \neg Z\} \otimes_Z \{\neg A, \neg Y, Z\} = \{\neg A, \neg Y\}$
- $\{\neg A, \neg Y\} \otimes_Y \{\neg A, \neg X, Y\} = \{\neg A, \neg X\}$
- Conflict Clause $C = \{\neg A, \neg X\}$

Conflict Analysis: Unit Implication Points (UIP)

Several possibilities to learn a clause from an implication graph exist.

- UIP is a dominator in the implication graph (restricted to variables assigned at the current decision level)
- A node v is a dominator for $\downarrow$, if all paths to $\downarrow$ contain v
- FirstUIP: “first” dominator (seen from conflict side)



[Beame et al, 2003]

Conflict Analysis: 1-UIP Learning

- FirstUIP Clause:

Resolve the conflicting clause and reason clauses until only a single literal of the current decision level remains.


- Advantage:

- Stopping at a UIP always leads to an asserting clause.
- A clause is asserting if all literals are false except one, which is unassigned.
- Algorithm becomes simpler: backtrack until clause becomes asserting.

- In 1-UIP learning, the backtrack level is always the second highest level in a conflict clause.

Non-chronological Backtracking

1-UIP learning changes the decision tree in our example like this:



$$F = \{\{A, B\}, \{B, C\}, \{\neg A, \neg X, Y\}, \{\neg A, X, Z\}, \{\neg A, \neg Y, Z\}, \{\neg A, X, \neg Z\}, \{\neg A, \neg Y, \neg Z\}\}$$


Trail: A, B, C, X, Y, Z

Conflicting Clause: $\{\neg A, \neg Y, \neg Z\}$

Conflict Clause (1UIP): $\{\neg A, \neg Y\}$

Non-chronological Backtracking

1-UIP learning changes the decision tree in our example like this:



$$F = \{\{A, B\}, \{B, C\}, \\ \{\neg A, \neg X, Y\}, \\ \{\neg A, X, Z\}, \\ \{\neg A, \neg Y, Z\}, \\ \{\neg A, X, \neg Z\}, \\ \{\neg A, \neg Y, \neg Z\} \\ \{\neg A, \neg Y\}\}$$

Trail: $A, \neg Y, \neg X, Z$

Conflicting Clause: $\{\neg A, X, \neg Z\}$

Clause Learning: Further Reading

- Clause Size Reduction with all-UIP Learning (Feng and Bacchus, 2020)
- Efficient All-UIP Learned Clause Minimization (Fleury and Biere, 2021)

Resolution Proof

Properties of conflict clause C

- $F \models C$
- $F \cup \neg C \vdash_{UP} \perp$
- $\forall D \subseteq C, D \notin F$

Certificates for Unsatisfiability

- sequence of learned clauses serves as a **proof of unsatisfiability**
- can be used to validate the correctness of the SAT result in **high risk applications**

The End.

Recap

- Decision Heuristics
 - Böhm's Heuristic
 - Mom's Heuristic
 - Jeroslow-Wang Heuristic
 - (R)DLCS and (R)DLIS Heuristics
- Restart Strategies
 - Inner / Outer Pattern
 - Luby Sequence / Reluctant Doubling
 - Branching Heuristic: Phase Saving
- Conflict Analysis, Clause Learning