



Performance



Accessibility



Best Practices



SEO



Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)




0-49



50-89



90-100



METRICS

[Expand view](#)

First Contentful Paint

1.2 s

Largest Contentful Paint

1.3 s

■ Total Blocking Time

300 ms

● Cumulative Layout Shift

0.003

■ Speed Index

2.2 s



Show audits relevant to:

[All](#)

[FCP](#)

[LCP](#)

[TBT](#)

[CLS](#)

INSIGHTS

▲ Render-blocking requests — Est savings of 510 ms

^

Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. FCP LCP Unscored


☒ Show 3rd-party resources (1)




URL	Transfer Size	Duration
pricely.space 1st Party	33.9 KiB	120 ms
...assets/app-Wly2Tonl.css (pricely.space)	31.1 KiB	120 ms
...assets/app-CLLIcC51.css (pricely.space)	2.8 KiB	
Google Fonts Cdn	1.1 KiB	320 ms
/css2?family=... (fonts.googleapis.com)	1.1 KiB	320 ms



▲ Improve image delivery — Est savings of 538 KiB

^

Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimizing image size](#) FCP LCP Unscored

	URL	Resource Size	Est Savings
	pricely.space 1st Party	558.7 KiB	538.0 KiB
	Shop Detail /images/price_map2.webp (pricely.space)	128.7 KiB	123.6 KiB

	URL	Resource Size	Est Savings
	<pre></pre>		
	This image file is larger than it needs to be (1200x2712) for its displayed dimensions (240x533). Use responsive images to reduce the image download size.		123.6 KiB
	Market Trends <pre></pre>	/images/price_forecast1.webp (pricely.space)	128.5 KiB
	This image file is larger than it needs to be (1200x2712) for its displayed dimensions (240x533). Use responsive images to reduce the image download size.		123.4 KiB
	Interactive Map <pre></pre>	/images/price_map1.webp (pricely.space)	90.5 KiB
	This image file is larger than it needs to be (1200x2712) for its displayed dimensions (240x533). Use responsive images to reduce the image download size.		87.0 KiB
	SMS Alerts <pre><img src="https://pricely.space/images/sms_feature.webp"</pre>	/images/sms_feature.webp (pricely.space)	79.0 KiB
			75.4 KiB

	URL	Resource Size	Est Savings
alt="SMS Alerts" style="display: block; width: 100%;" loading="lazy">			
	This image file is larger than it needs to be (1201x2712) for its displayed dimensions (258x574). Use responsive images to reduce the image download size.		75.4 KiB
Forecast Chart	https://pricely.space/images/price_forecast2.webp (pricely.space)	78.3 KiB	75.3 KiB
	This image file is larger than it needs to be (1200x2712) for its displayed dimensions (240x533). Use responsive images to reduce the image download size.		75.3 KiB
San Mateo Logo	/san-mateo-logo.webp (pricely.space)	53.8 KiB	53.3 KiB
	Increasing the image compression factor could improve this image's download size.		13.1 KiB
	This image file is larger than it needs to be (612x408) for its displayed dimensions (64x43). Use responsive images to reduce the image download size.		53.2 KiB

▲ Forced reflow

^

A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn

more about [forced reflows](#) and possible mitigations. Unscored


Source	Total reflow time
[unattributed]	92 ms

▲ LCP breakdown

^

Each [subpart has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. LCP Unscored

Subpart	Duration
Time to first byte	200 ms
Resource load delay	40 ms
Resource load duration	2,830 ms
Element render delay	50 ms




SMS Alerts
``

▲ LCP request discovery

^

[Optimize LCP](#) by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading LCP Unscored

- ❌ fetchpriority=high should be applied
- ✅ Request is discoverable in initial document
- ❌ LCP resources should not use loading=lazy



SMS Alerts
``


▲ Network dependency tree

^

[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. LCP Unscored

Maximum critical path latency: **2,154 ms**

Initial Navigation



Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

Origin	Source
https://fonts.googleapis.com/	head > link <link rel="preconnect" href="https://fonts.googleapis.com">
https://fonts.gstatic.com/	head > link <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin="">

Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.

No additional origins are good candidates for preconnecting

Use efficient cache lifetimes — Est savings of 55 KiB

A long cache lifetime can speed up repeat visits to your page. [Learn more about caching.](#) FCP LCP Unscored


☒ Show 3rd-party resources (1)

Request	Cache TTL	Transfer Size
JSDelivr CDN Cdn		256 KiB
/npm/apexcharts (cdn.jsdelivr.net)	7d	256 KiB
pricely.space 1st Party		295 KiB
...assets/app-DmhQQQdD.js (pricely.space)	7d	240 KiB
/san-mateo-logo.webp (pricely.space)	7d	54 KiB
...assets/_commonjs....js (pricely.space)	7d	1 KiB

○ Layout shift culprits

Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed, or their fonts changing as the page loads. CLS

Unscored

Element	Layout shift score
Total	0.003
 Patas na Presyo, Sapat na Kita. <h1 class="gsap-hero-title reveal-stagger-item text-4xl sm:text-5xl md:text-6xl lg:te...">	0.003
...v12/LDIoaomQN....woff2 (fonts.gstatic.com)	Web font
...v24/tDbv2o-fl....woff2 (fonts.gstatic.com)	Web font

○ Optimize DOM size

A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. [Learn how to avoid an excessive DOM size](#). Unscored

Statistic	Element	Value
Total elements		392
DOM depth	div > div > div > div <div style="width: 11px; height: 11px; border-radius: 50%;">	15
Most children	 body.bg-base-100 > div.fixed <div class="fixed inset-0 overflow-hidden pointer-events-none z-0">	7

○ 3rd parties

3rd party code can significantly impact load performance. [Reduce and defer loading of 3rd party code](#) to prioritize your page's content. Unscored

3rd party	Transfer size	Main thread time
JSDelivr CDN Cdn	256 KiB	23 ms
/npm/apexcharts (cdn.jsdelivr.net)	256 KiB	23 ms
Unpkg Cdn	98 KiB	17 ms

3rd party	Transfer size	Main thread time
/lucide@latest (unpkg.com)	0 KiB	17 ms
...umd/lucide.min.js (unpkg.com)	98 KiB	0 ms
Google Fonts Cdn	58 KiB	0 ms
...v24/tDbv2o-fl....woff2 (fonts.gstatic.com)	31 KiB	0 ms
...v12/LDloaomQN....woff2 (fonts.gstatic.com)	27 KiB	0 ms
/css2?family=... (fonts.googleapis.com)	1 KiB	0 ms

These insights are also available in the Chrome DevTools Performance Panel - [record a trace](#) to view more detailed information.

DIAGNOSTICS

Reduce unused JavaScript — Est savings of 460 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript](#). FCP LCP Unscored

☒ Show 3rd-party resources (1)

URL	Transfer Size	Est Savings
JSDelivr CDN Cdn	255.6 KiB	251.8 KiB
/npm/apexcharts (cdn.jsdelivr.net)	255.6 KiB	251.8 KiB
pricely.space 1st Party	239.7 KiB	208.3 KiB
...assets/app-DmhQQQdD.js (pricely.space)	239.7 KiB	208.3 KiB

Avoid long main-thread tasks — 2 long tasks found





Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#). TBT Unscored

URL	Start Time	Duration
Unattributable	1,187 ms	408 ms
Unattributable	778 ms	377 ms

○ Avoid non-composited animations — 4 animated elements found



Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) CLS Unscored

Element	Name
	Shop Detail <pre><div class="absolute left-0 top-0" :style="`transition: all 0.55s cubic-bezier(0.34,1.56,0.64,1); ` + (swapped ..."</pre> <pre>style="transition: 0.55s cubic-bezier(0.34, 1.56, 0.64, 1); z-index: 1;"></pre>
Filter-related property may move pixels	filter
	Market Trends <pre><div class="absolute left-0 top-0" :style="`transition: all 0.55s cubic-bezier(0.34,1.56,0.64,1); ` + (swapped ..."</pre> <pre>style="transition: 0.55s cubic-bezier(0.34, 1.56, 0.64, 1); z-index: 2;"></pre>
Filter-related property may move pixels	filter
	Interactive Map <pre><div class="absolute left-0 top-0" :style="`transition: all 0.55s cubic-bezier(0.34,1.56,0.64,1); ` + (swapped ..."</pre> <pre>style="transition: 0.55s cubic-bezier(0.34, 1.56, 0.64, 1); z-index: 2;"></pre>
Filter-related property may move pixels	filter
	Forecast Chart <pre><div class="absolute left-0 top-0" :style="`transition: all 0.55s cubic-bezier(0.34,1.56,0.64,1); ` + (swapped ..."</pre> <pre>style="transition: 0.55s cubic-bezier(0.34, 1.56, 0.64, 1); z-index: 1;"></pre>
Filter-related property may move pixels	filter

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (16)

Hide

● Document request latency



Your first network request is the most important. [Reduce its latency](#) by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP Unscored



- ✓ Avoids redirects
- ✓ Server responds quickly (observed 192 ms)
- ✓ Applies text compression

● Duplicated JavaScript

Remove large, [duplicate JavaScript modules](#) from bundles to reduce unnecessary bytes consumed by network activity. FCP LCP Unscored

● Font display

Consider setting [font-display](#) to swap or optional to ensure text is consistently visible. swap can be further optimized to mitigate layout shifts with [font metric overrides](#). Unscored

○ INP breakdown

Start investigating [how to improve INP](#) by looking at the longest subpart. Unscored

● Legacy JavaScript

Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile [Baseline](#) features, unless you know you must support older browsers. [Learn why most sites can deploy ES6+ code without transpiling](#) FCP LCP Unscored

● Modern HTTP

HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. [Learn more about using modern HTTP](#). FCP LCP Unscored

● Optimize viewport for mobile

Tap interactions may be [delayed by up to 300 ms](#) if the viewport is not optimized for mobile. Unscored

head > meta

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

● Minify CSS

^

Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS.](#) FCP LCP Unscored

● Minify JavaScript

^

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript.](#) FCP LCP Unscored

● Reduce unused CSS

^

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS.](#) FCP LCP Unscored

● Avoids enormous network payloads — Total size was 1,824 KiB

^

Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes.](#) Unscored

☒ Show 3rd-party resources (2)

URL	Transfer Size
pricely.space 1st Party	1,016.8 KiB
...assets/app-DmhQQQdD.js (pricely.space)	240.0 KiB
/images/price_map2.webp (pricely.space)	129.0 KiB
/images/price_map2.webp?v=3 (pricely.space)	129.0 KiB
/images/price_forecast1.webp?v=3 (pricely.space)	128.8 KiB
/images/price_forecast1.webp (pricely.space)	128.8 KiB
/images/price_map1.webp (pricely.space)	90.9 KiB
/images/price_map1.webp?v=3 (pricely.space)	90.9 KiB
/images/sms_feature.webp (pricely.space)	79.3 KiB
JSDelivr CDN Cdn	255.9 KiB
/npm/apexcharts (cdn.jsdelivr.net)	255.9 KiB

URL	Transfer Size
Unpkg Cdn	97.9 KiB
...umd/lucide.min.js (unpkg.com)	97.9 KiB

 User Timing marks and measures

^

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks.](#) Unscored

 JavaScript execution time — 0.1 s

^

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time.](#) TBT Unscored

URL	Total CPU Time	Script Evaluation	Script Parse
Unattributable	1,112 ms	2 ms	0 ms
Unattributable	1,112 ms	2 ms	0 ms
pricely.space 1st Party	369 ms	92 ms	4 ms
https://pricely.space	298 ms	55 ms	3 ms
...assets/app-DmhQQQdD.js (pricely.space)	70 ms	37 ms	1 ms

 Minimizes main-thread work — 1.5 s

^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) TBT Unscored

Category	Time Spent
Other	1,241 ms
Style & Layout	113 ms
Script Evaluation	109 ms
Script Parsing & Compilation	31 ms
Rendering	21 ms

Category	Time Spent
Parse HTML & CSS	9 ms
Garbage Collection	7 ms

● Image elements have explicit [width](#) and [height](#) ^

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) CLS Unscored

● Page didn't prevent back/forward cache restoration ^

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#)

Unscored



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio. ^

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast](#).

Failing Elements




Tignan ang Map

```
<a href="https://pricely.space/map" class="btn-pricely-primary flex items-center justify-center gap-2 w-full sm:w-auto">
```



Market index forecasts represent predictive trends derived from agricultural mo...

```
<p class="max-w-md mx-auto text-slate-400 text-2xs leading-relaxed text-[10px]">
```



Pricely Agricultural Indexing Systems Market index forecasts represent predict...

```
<footer class="w-full border-t border-slate-100 bg-white py-12 text-slate-500 text-xs tex...">
```

These are opportunities to improve the legibility of your content.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

☐ Interactive controls are keyboard focusable

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable](#). Unscored

☐ Interactive elements indicate their purpose and state

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints](#). Unscored

☐ The page has a logical tab order

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering](#). Unscored

☐ Visual order on the page follows DOM order

DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering](#). Unscored

☐ User focus is not accidentally trapped in a region

A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#) Unscored

- ☐ The user's focus is directed to new content added to the page ^

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content.](#) Unscored

- ☐ HTML5 landmark elements are used to improve navigation ^

Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements.](#) Unscored

- ☐ Offscreen content is hidden from assistive technology ^

Offscreen content is hidden with display: none or aria-hidden=true. [Learn how to properly hide offscreen content.](#) Unscored

- ☐ Custom controls have associated labels ^

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more about custom controls and labels.](#) Unscored

- ☐ Custom controls have ARIA roles ^

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls.](#) Unscored

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (12)

Hide

- ☒ [aria-hidden="true"] is not present on the document <body> ^

Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. [Learn how aria-hidden affects the document body.](#)

- ☒ Buttons have an accessible name ^

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

● Image elements have `[alt]` attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

● `[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5. ^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

● `[aria-hidden="true"]` elements do not contain focusable descendents ^

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how aria-hidden affects focusable elements.](#)

● Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

● `<html>` element has a `[lang]` attribute ^

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

● `<html>` element has a valid value for its `[lang]` attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn how to use the lang attribute.](#)

 Links have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#)

 Touch targets have sufficient size and spacing.

Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. [Learn more about touch targets.](#)

 Heading elements appear in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

 Document has a main landmark.

One main landmark helps screen reader users navigate a web page. [Learn more about landmarks.](#)

NOT APPLICABLE (50)

Hide

 `[accesskey]` values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#) Unscored

 `[aria-*) attributes match their roles `

Each ARIA role supports a specific subset of `aria-*) attributes. Mismatching these invalidates the aria-*) attributes. Learn how to match ARIA attributes to their roles. Unscored`

☐ [button](#), [link](#), and [menuitem](#) elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#) Unscored

☐ ARIA attributes are used as specified for the element's role ^

Some ARIA attributes are only allowed on an element under certain conditions. [Learn more about conditional ARIA attributes.](#) Unscored

☐ Deprecated ARIA roles were not used ^

Deprecated ARIA roles may not be processed correctly by assistive technology. [Learn more about deprecated ARIA roles.](#) Unscored

☐ Elements with `role="dialog"` or `role="alertdialog"` have accessible names. ^

ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#) Unscored

☐ ARIA input fields have accessible names ^

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#) Unscored

☐ ARIA [meter](#) elements have accessible names ^

When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#) Unscored

☐ ARIA [progressbar](#) elements have accessible names ^

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#) Unscored

☐ Elements use only permitted ARIA attributes ^

Using ARIA attributes in roles where they are prohibited can mean that important information is not

communicated to users of assistive technologies. [Learn more about prohibited ARIA roles.](#) Unscored

☐ `[role]`s have all required `[aria-*)` attributes ^

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#) Unscored

☐ Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children. ^

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#) Unscored

☐ `[role]`s are contained by their required parent element ^

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#) Unscored

☐ `[role]` values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#) Unscored

☐ Elements with the `role=text` attribute do not have focusable descendents. ^

Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the `role=text` attribute.](#) Unscored

☐ ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#) Unscored

☐ ARIA `tooltip` elements have accessible names ^

When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#) Unscored

☐ ARIA `treeitem` elements have accessible names ^

When a `treeitem` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labeling `treeitem` elements.](#) Unscored

☐ `[aria-*)` attributes have valid values ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more about valid values for ARIA attributes.](#) Unscored

☐ `[aria-*)` attributes are valid and not misspelled ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#) Unscored

☐ The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#) Unscored

☐ `<d1>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#) Unscored

☐ Definition list items are wrapped in `<d1>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<d1>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#) Unscored

☐ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#) Unscored

☐ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#) Unscored

☐ `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#) Unscored

- `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#) Unscored

- Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#) Unscored

- `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#) Unscored

- Form elements have associated labels ^

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#) Unscored

- Links are distinguishable without relying on color. ^

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#) Unscored

- Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#) Unscored

- List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements ^

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#) Unscored

- The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta](#)

[tag](#). Unscored

☐ `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements](#). Unscored

☐ Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element](#). Unscored

☐ Skip links are focusable. ^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links](#). Unscored

☐ No element has a `[tabindex]` value greater than 0 ^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the tabindex attribute](#). Unscored

☐ Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute](#). Unscored

☐ `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers](#). Unscored

☐ `[lang]` attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute](#). Unscored

☐ `<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#) Unscored

☐ [autocomplete](#) attributes are used correctly ^

The autocomplete attribute values must be valid and correctly applied for screen readers to function correctly. [Learn more about valid autocomplete values.](#) Unscored

☐ Elements with `role="none"` or `role="presentation"` do not have conflicts ^

There are certain cases where the semantic role of an element with `role="none"` or `role="presentation"` does not resolve to none or presentation. To ensure the element remains removed from the accessibility tree, you should not add any global ARIA attributes to the element or make it focusable. [Learn more about presentation role conflict.](#) Unscored

☐ SVG elements with an `img` role have an accessible text alternative ^

Ensures SVG elements with an `img`, `graphics-document` or `graphics-symbol` role have an accessible text alternative. [Learn more about SVG alt text.](#) Unscored

☐ Tables have different content in the summary attribute and `<caption>`. ^

The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#) Unscored

☐ All heading elements contain content. ^

A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. [Learn more about headings.](#) Unscored

☐ Uses ARIA roles only on compatible elements ^

Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#) Unscored

☐ Image elements do not have `[alt]` attributes that are redundant text. ^

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#) Unscored

○ Identical links have the same purpose. ^

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#) Unscored



Best Practices

TRUST AND SAFETY

○ Ensure CSP is effective against XSS attacks ^

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#) Unscored

Description	Directive	Severity
`script-src` directive is missing. This can allow the execution of unsafe scripts.	script-src	High
Missing `object-src` allows the injection of plugins that execute unsafe scripts. Consider setting `object-src` to `none` if you can.	object-src	High

○ Use a strong HSTS policy ^

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy.](#) Unscored

Description	Directive	Severity
No HSTS header found		High

○ Ensure proper origin isolation with COOP

^

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header.](#) Unscored

Description	Directive	Severity
No COOP header found		High

○ Mitigate clickjacking with XFO or CSP

^

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. [Learn more about mitigating clickjacking.](#) Unscored

Description	Severity
No frame control policy found	High

○ Mitigate DOM-based XSS with Trusted Types

^

The require-trusted-types-for directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with Trusted Types.](#) Unscored

Description	Severity
No `Content-Security-Policy` header with Trusted Types directive found	High

BROWSER COMPATIBILITY

○ Baseline Features

^

Lists web features used on the page and their Baseline status as of 2026-07-15. [Learn more about Baseline.](#) Unscored

Web-features	Baseline Status	Source
pricely.space	1st Party	

Web-features	Baseline Status	Source
page-visibility-state	⚠ Limited Availability	https://pricely.space:2:18421
long-animation-frames	⚠ Limited Availability	https://pricely.space:2:2509
layout-instability	⚠ Limited Availability	https://pricely.space:2:17083
requestidlecallback	⚠ Limited Availability	https://pricely.space:1:10990
if	⚠ Limited Availability	https://pricely.space:-1:-2
background-clip-text	⚠ Limited Availability	https://pricely.space:-1:-2
interpolate-size	⚠ Limited Availability	https://pricely.space:-1:-2
box-decoration-break	⚠ Limited Availability	https://pricely.space:-1:-2
with	⚠ Limited Availability	...assets/app-DmhQQQdD.js:13:748 (pricely.space)
scrollbar-color	✅ Newly Available (2025-12-12)	https://pricely.space:-1:-2
details-content	✅ Newly Available (2025-09-16)	https://pricely.space:-1:-2
content-visibility	✅ Newly Available (2025-09-15)	https://pricely.space:-1:-2
print-color-adjust	✅ Newly Available (2025-05-01)	https://pricely.space:-1:-2
scrollbar-gutter	✅ Newly Available (2024-12-11)	https://pricely.space:-1:-2
scrollbar-width	✅ Newly Available (2024-12-11)	https://pricely.space:-1:-2
text-wrap	✅ Newly Available (2024-10-17)	https://pricely.space:-1:-2
relative-color	✅ Newly Available (2024-09-16)	https://pricely.space:-1:-2
backdrop-filter	✅ Newly Available (2024-09-16)	https://pricely.space:-1:-2
starting-style	✅ Newly Available (2024-08-06)	https://pricely.space:-1:-2

Web-features	Baseline Status	Source
transition-behavior	 Newly Available (2024-08-06)	https://pricely.space:-1:-2
registered-custom-properties	 Newly Available (2024-07-09)	https://pricely.space:-1:-2
gradient-interpolation	 Newly Available (2024-06-11)	https://pricely.space:-1:-2
has	 Widely Available (2023-12-19)	https://pricely.space:-1:-2
masks	 Widely Available (2023-12-07)	https://pricely.space:-1:-2
dir-pseudo	 Widely Available (2023-12-07)	https://pricely.space:-1:-2
user-pseudos	 Widely Available (2023-11-02)	https://pricely.space:-1:-2
contain-intrinsic-size	 Widely Available (2023-09-18)	https://pricely.space:-1:-2
color-mix	 Widely Available (2023-05-09)	https://pricely.space:-1:-2
oklab	 Widely Available (2023-05-09)	https://pricely.space:-1:-2
constructed-stylesheets	 Widely Available (2023-03-27)	https://pricely.space:24:24
outline	 Widely Available (2023-03-27)	https://pricely.space:-1:-2
overflow-clip	 Widely Available (2022-09-12)	https://pricely.space:-1:-2
forced-colors	 Widely Available (2022-09-12)	https://pricely.space:-1:-2
individual-transforms	 Widely Available (2022-08-05)	https://pricely.space:-1:-2
cascade-layers	 Widely Available (2022-03-14)	https://pricely.space:-1:-2

Web-features	Baseline Status	Source
focus-visible	✓ Widely Available (2022-03-14)	https://pricely.space:-1:-2
appearance	✓ Widely Available (2022-03-14)	https://pricely.space:-1:-2
color-scheme	✓ Widely Available (2022-02-03)	https://pricely.space:-1:-2
aspect-ratio	✓ Widely Available (2021-09-20)	https://pricely.space:-1:-2
logical-properties	✓ Widely Available (2021-09-20)	https://pricely.space:-1:-2
file-selector-button	✓ Widely Available (2021-04-26)	https://pricely.space:-1:-2
weak-references	✓ Widely Available (2021-04-26)	https://pricely.space:2:17785
not	✓ Widely Available (2021-01-21)	https://pricely.space:11:59
where	✓ Widely Available (2021-01-21)	https://pricely.space:-1:-2
is	✓ Widely Available (2021-01-21)	https://pricely.space:-1:-2
clip-path	✓ Widely Available (2021-01-21)	https://pricely.space:-1:-2
nullish-coalescing	✓ Widely Available (2020-09-16)	https://pricely.space:1:0
webp	✓ Widely Available (2020-09-16)	https://pricely.space:-1:-2
overflow-shorthand	✓ Widely Available (2020-03-24)	https://pricely.space:-1:-2
will-change	✓ Widely Available (2020-01-15)	https://pricely.space:-1:-2
scroll-snap	✓ Widely Available (2020-01-15)	https://pricely.space:-1:-2

Web-features	Baseline Status	Source
aborting	✔ Widely Available (2019-03-25)	https://pricely.space:2:17253
js-modules	✔ Widely Available (2018-05-09)	https://pricely.space:-1:-2
template	✔ Widely Available (2015-11-12)	https://pricely.space:-1:-2
flexbox	✔ Widely Available (2015-09-30)	https://pricely.space:-1:-2
text-indent	✔ Widely Available (2015-07-29)	https://pricely.space:-1:-2
request-animation-frame	✔ Widely Available (2015-07-29)	...assets/app-DmhQQQdD.js:9:20841 (pricely.space)
canvas	✔ Widely Available (2015-07-29)	...assets/app-DmhQQQdD.js:13:57578 (pricely.space)

GENERAL

Detected JavaScript libraries

^

All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit.](#)

Unscored

Name	Version
Leaflet	1.9.4

Missing source maps for large first-party JavaScript

^

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#)

Unscored

☒ Show 3rd-party resources (1)

URL	Map URL
pricely.space 1st Party	
...assets/app-DmhQQQdD.js (pricely.space)	
Large JavaScript file is missing a source map	
Unpkg Cdn	
/lucide@latest (unpkg.com)	/lucide.min.js.map (unpkg.com)
Error: Failed fetching source map (404)	

PASSED AUDITS (12)

Hide

 Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS.](#)

 Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs.](#)

 Avoids third-party cookies

Third-party cookies may be blocked in some contexts. [Learn more about preparing for third-party cookie restrictions.](#)

 Allows users to paste into input fields

Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. [Learn more about user-friendly input fields.](#)

● Avoids requesting the geolocation permission on page load ^

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more about the geolocation permission](#). Also consider using the [<geolocation> element](#).

● Avoids requesting the notification permission on page load ^

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more about responsibly getting permission for notifications](#).

● Displays images with correct aspect ratio ^

Image display dimensions should match natural aspect ratio. [Learn more about image aspect ratio](#).

● Serves images with appropriate resolution ^

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn how to provide responsive images](#).

● Page has the HTML doctype ^

Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more about the doctype declaration](#).

● Properly defines charset ^

A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding](#).

● No browser errors logged to the console ^

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

● No issues in the [Issues](#) panel in Chrome Devtools



Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

NOT APPLICABLE (1)

Hide

○ Redirects HTTP traffic to HTTPS



Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. [Learn more.](#) Unscored



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials](#).

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

○ Structured data is valid



Run the [Structured Data Testing Tool](#) to validate structured data. [Learn more about Structured Data](#).

Unscored

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (9)

Hide

 Page isn't blocked from indexing ^

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives.](#)

 Document has a <title> element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

 Document has a meta description ^

Meta descriptions may be included in search results to concisely summarize page content. [Learn more about the meta description.](#)

 Page has successful HTTP status code ^

Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes.](#)

 Links have descriptive text ^

Descriptive link text helps search engines understand your content. [Learn how to make links more accessible.](#)

 Links are crawlable ^

Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn how to make links crawlable](#)

 robots.txt is valid ^

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more about robots.txt.](#)

 Image elements have `[alt]` attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

 Document has a valid `hreflang`

hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more about hreflang.](#)

NOT APPLICABLE (1)

Hide

 Document has a valid `rel=canonical`

Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#)

Unscored

 Captured at Sep 3, 2026, 6:53 PM
GMT+8 Emulated Desktop with Lighthouse
13.4.1 Single page session Initial page load Custom throttling Using Chromium 152.0.0.0 with
devtoolsGenerated by **Lighthouse** 13.4.1 | [File an issue](#)