Programming Language (5) Basics of Programming Language Implementation

田浦

Contents

1 Introduction

2 CPU and machine code: An overview

3 A glance at x86 machine (assembly) code

Contents

Introduction

2 CPU and machine code: An overview

3 A glance at x86 machine (assembly) code

Two basic forms of language implementation

- interpreter: interprets and executes programs (takes a program and an input; and computes the output)
- compiler: translates programs into a machine (assembly) code, that can directly execute by the processor
 - ▶ ahead-of-time (AOT): the entire program is compiled before execution
 - ▶ just-in-time (JIT): programs are incrementally compiled as they get executed (e.g., a function at a time)

regardless of details, the central issue is how to translate a source $program \rightarrow machine\ code$

Why do you want to build a language, today?

- new hardware
 - ► GPUs (CUDA, OpenACC, OpenMP), AI chips, Quantum, ...
- ▶ new instruction set (e.g., SIMD, matrix, ...) of the processor
- new general purpose languages
 - ► Scala, Julia, Go, Rust, etc.
- special purpose (domain specific) languages
 - ▶ statistics (R, MatLab, etc.)
 - ▶ data processing (SQL, NoSQL, SPARQL, etc.)
 - deep learning
 - constraint solving, proof assistance (Coq, Isabelle, etc.)
 - macro (Visual Basic (MS Office), Emacs Lisp (Emacs),
 Javascript (web browser), etc.)

Contents

Introduction

2 CPU and machine code: An overview

3 A glance at x86 machine (assembly) code

What a machine (assembly) code looks like

• it is just another programming language


• it has many features present in programming languages

source	machine code
expressions	arithmetic instructions
if statement	compare / conditional jump instructions
variables	registers and memory
structs and arrays	memory and load/store instructions

compilation is nothing like a magic; it's more like translating English to French


What a CPU (core) looks like

- a small number (typically < 100) of registers
 - each register can hold a small amount of (e.g., 64 bit) data
- majority of data are stored in memory (a few to ~ 1000 GB)



Memory

- where majority of data your program processes are stored
- memory is essentially a large flat array indexed by integers, often called *addresses*
- an address is just an integer




What a CPU (core) does

- a special register, called *program counter* or *instruction pointer* specifies the address to fetch the next instruction at
- a CPU core is essentially a machine that does the following

```
1     repeat:
2     inst = memory[program counter]
3     execute inst
```

- an instriction
 - performs some computation of values on a few registers or a memory location, and
 - changes the program counter (typically to the next instruction on memory)



Exercise objectives

- pl06_how_it_gets_compiled
- learn how a compiler does the job,
- by inspecting assembly code generated from functions of the source language

Contents

Introduction

2 CPU and machine code: An overview

3 A glance at x86 machine (assembly) code

The first glance

```
1
             .globl go_OplO6.Many__args
 2
                      go_OplO6.Many__args, @function
             .type
 3
     go_OplO6.Many__args:
 4
     .LFB0:
 5
             .cfi_startproc
 6
                      %fs:112, %rsp
             cmpq
 7
             jb
                      .L3
 8
     .L2:
 9
                      48(%rsp), %rax
             movq
10
                      40(%rsp), %rax
             adda
11
             addq
                      32(%rsp), %rax
12
             addq
                      24(%rsp), %rax
13
                      16(%rsp), %rax
             adda
14
             addq
                      8(%rsp), %rax
15
             addq
                      %r9, %rax
16
                     %r8, %rax
             adda
17
             adda
                      %rcx, %rax
18
             addq
                      %rdx, %rax
19
             addq
                      %rsi, %rax
20
             adda
                      %rdi, %rax
21
             ret
22
     . L.3:
23
                      $0, %r10d
             movl
24
                      $48, %r11d
             movl
25
             call.
                      __morestack
26
              ret
27
             jmp
                      .L2
28
             .cfi_endproc
29
     .LFEO:
30
              .size
                      go_OplO6.Many_args, .-go_OplO6.Many_args
31
              .globl
                      go.pl06..types
```

Unimportant lines

```
.globl go_OplO6.Many__args
          .tvpe go_OplO6.Manv_args. ...
     go_OplO6.Many__args:
      . LFBO:
          .cfi_startproc
          cmpq
                  %fs:112, %rsp
                  .1.3
          jb
      .L2:
          movq
                  48(%rsp), %rax
10
                  40(%rsp), %rax
          addq
11
          addq
                  32(%rsp), %rax
12
          adda
                  24(%rsp), %rax
13
          adda
                  16(%rsp), %rax
1%
                  8(%rsp), %rax
          addq
15
          adda
                  %r9, %rax
16
          addq
                  %r8, %rax
17
          addq
                  %rcx, %rax
18
          addq
                  %rdx, %rax
19
          adda
                  %rsi, %rax
20
                  %rdi, %rax
          addq
21
          ret
22
      1.3:
23
          mov1
                  $0, %r10d
                  $48, %r11d
          movl
25
          call
                  morestack
26
          ret.
27
                  .1.2
          qmp
28
          .cfi_endproc
29
     .LFE0:
30
          .size go_OplO6.Many__args, ...
31
          .globl go.pl06..types
```

- indented lines beginning with a dot (e.g., .file, .section, .ascii, .text, .globl, ...) are not instructions and largely not interesting or import
- lines with a symbol followed by a colon (e.g., .L2:, .LFE0:, go_0pl06.Many_args:, ...) are labels and used for the target of jump instructions or call instructions

Where to look

```
.globl go_OplO6.Many__args
 23
          .tvpe go_OplO6.Manv__args. ...
     go_OplO6.Many__args:
      . LFBO:
          .cfi_startproc
 6
                  %fs:112, %rsp
          cmpq
 7
8
                  . I.3
          jb
      .L2:
                  48(%rsp), %rax
          movq
10
                  40(%rsp), %rax
          addq
11
          addq
                  32(%rsp), %rax
                  24(%rsp), %rax
12
          adda
13
          adda
                  16(%rsp), %rax
14
                  8(%rsp), %rax
          addq
15
          adda
                  %r9, %rax
16
          addq
                  %r8, %rax
17
          addq
                  %rcx, %rax
18
          addq
                  %rdx, %rax
19
          adda
                  %rsi, %rax
20
                  %rdi, %rax
          addq
21
          ret
22
      1.3:
23
                  $0, %r10d
          mow1
24
                  $48, %r11d
          movl
25
          call
                  morestack
26
          ret.
27
                  .1.2
          jmp
28
          .cfi_endproc
29
      .LFE0:
30
          .size go_OplO6.Many__args, ...
31
          .globl go.pl06..types
```

- focus on lines having *instructins*
- instructions for a function start with a label *similar to* the function name, but it may not be exactly the same (name mangling)

Registers

- general-purpose 64 bit integer registers: r{a,b,c,d}x, rdi, rsi, r[8-15], rbp
- general-purpose floating point number registers: xmm [0-15]
- stack pointer register: rsp
- a compare flag register: **eflags**, not directly used by instructions
 - implicitly set by compare instructions
 - ▶ implicitly used by conditional jump instructions
- an instruction pointer register: rip, not directly used by instructions
 - set by every instruction
- https://wiki.cdot.senecapolytechnic.ca/wiki/X86_64_ Register_and_Instruction_Quick_Start

Frequently used instructions

learn details and other instructions from the exercise

- addq (+), leaq (+), subq (-), imulq (×), idivq (/)
- movq: move values between registers or between register and memory (load/store)
- \bullet cmpq : compare two values and set the result into the <code>eflags</code> register
- j1 (<), jle (\leq), jg (>), jge (\geq), je (=), jne (\neq) : jump if a condition (indicated by eflags) is met
- call, ret: call or return from a function

How to read instructions and operands (GNU assembler)

• e.g., addq instructios takes two operands

```
addq x, y
and its effect is
y += x
```

many two operand instructions behave similarly

```
1 \left[ opq \ x, y \equiv y = y \ op \ x \right]
```

• especially confusing is subq

```
subq x, y \equiv y = y - x
```

• syntax and operand order actually depend on the assembler

Syntax of operands

• n: immediate value of n• R: register named R • (...): address operand (details in the next slide) where • n: a constant (4, 8, etc.) • R: regiser name (rax, rbx, rdi, etc.) ex. • addg \$1, %rax : add 1 to %rax register

• subq \$1, %rax : subtract 1 from %rax register

Address operands

- an address operand (...) specifies an address, and can be
 - (%R) : R
 - n(%R) : R + n
 - $n(\/\/R, s, R') : R + sR' + n$
- where
 - \triangleright n, s: integer constants
 - ightharpoonup R, R': register names
- ex.
 - mulq (%rdi), %rax : reads address specified by %rdi and multiply %rax by it
 - movq %rax,(%rdi): writes the value of %rax to the address specified by %rdi
 - ▶ leaq 4(%rdi), %rax : %rax = %rdi + 4; this instruction looks like reading/writing memory, but it is actually just a peculiar arithmetic (common in address calculation)

Things to watch in the exercise

- calling convention or ABI: function's incoming parameters and the return value are put in places (typically registers) predetermined by convention
- observe where incoming parameters are by compiling simple functions like

```
f(\text{int } x, \text{ int } y) = x + y
```

- change parameter types and function body to know
 - ▶ how data are represented (integers, floating point numbers, arrays, structs, etc.)
 - ▶ how various expressions are implemented (arithmatic, array access, structure access, etc.)