

# example

s.haithem

February 2024

```
\begin{lstlisting}[language=Python]
conference_sessions = 40
slots = 7
papers_range = np.arange(3, 7)
max_parallel_sessions = 11
working_groups = 20
npMax = {1: 4, 2: 6, 3: 6, 4: 4, 5: 4, 6: 5, 7: 3}

# list of groups session groups
session_groups = [
    [1], [2], [3], [], [], [], [6], [7], [7, 8], [10], [8], [8, 11], [5, 8],
    [3, 8], [7], [13], [13], [14], [], [13], [16], [16], [20], [17], [13],
    [], [9], [11], [11, 12], [9], [6, 19], [], [], [18], [10], [5], [16],
    [4, 5], [8, 12], [7, 15]
]
\end{lstlisting}

\begin{lstlisting}[language=Python]
def var_x(s, c, l):
    s_index = conference_sessions * slots * len(papers_range)
    c_index = slots * len(papers_range)
    l_index = len(papers_range)
    return s_index - (conference_sessions - s) * c_index - (slots - c) * l_index - (len(papers_range) - 1)

max_var_x = var_x(conference_sessions, slots, papers_range[-1])

def var_z(s, c):
    z_offset = max_var_x + 1 % Start after the last x variable
    return z_offset + (s - 1) * slots + c

max_var_z = var_z(conference_sessions, slots)

def var_y(s1, s2, c, g):
    y_offset = max_var_z + 1
```

```

% Calculate the unique identifier for y variables
unique_index = ((s1 - 1) * conference_sessions + (s2 - 1)) * slots * working_groups + (
return y_offset + unique_index
\end{lstlisting}

```

1. At most one amount of papers chosen for a (session, slot) pair:

$$\sum_{l \in L} x_{(s,c,l)} \leq 1 \quad \forall (s,c) \in S \times C$$

```

\begin{lstlisting}[language=Python]
for s in range(1, conference_sessions + 1):
    for c in range(1, slots + 1):
        vars_for_s_c = [var_x(s, c, l) for l in papers_range]
        % en peut le modifier
        amo_clause = CardEnc.atmost(lits=vars_for_s_c, bound=1, encoding=EncType.pairwise)
        constraints.extend(amo_clause.clauses)
\end{lstlisting}

```

- 2 - The subdivision of a session into slots covers all the papers in the session:

$$\sum_{c \in C, l \in L} x_{(s,c,l)} * l = np(s) \quad \forall s \in S$$

```

\begin{lstlisting}[language=Python]
for s in range(1, conference_sessions + 1):
    aux_vars = []
    weights = []

    for c in range(1, slots + 1):
        for l in papers_range:
            aux_vars.append(var_x(s, c, l))
            weights.append(l)

    equals_clause = PBEnc.equals(lits=aux_vars, weights=weights, bound=session_papers[s])
    constraints.extend(equals_clause.clauses)
\end{lstlisting}

```

- 3 - The subdivision respects the maximum length of each slot:

$$x_{(s,c,l)} * l \leq npMax(c) \quad \forall (s,c,l) \in S \times C \times L$$

```

\begin{lstlisting}[language=Python]
% 3 eme constraint

for s in range(1, conference_sessions + 1):

```

```

for c in range(1, slots + 1):
    for l in papers_range:
        if l > npMax[c]:
            % j'ai travailler avec la conjonction des negation de x if l>npMax(c)
            constraints.append([-var_x(s, c, l)])
\end{lstlisting}

```

$$\begin{aligned}
 & \left( z_{(s,c)} \implies \bigwedge_{l \in L} \overline{x_{(s,c,l)}} \right) \wedge \left( \bigwedge_{l \in L} \overline{x_{(s,c,l)}} \implies z_{(s,c)} \right) \quad \forall (s,c) \in S \times C \\
 & \left( \overline{z_{(s,c)}} \vee \left( \bigwedge_{l \in L} \overline{x_{(s,c,l)}} \right) \right) \wedge \left( \overline{\left( \bigwedge_{l \in L} \overline{x_{(s,c,l)}} \right)} \vee z_{(s,c)} \right)
 \end{aligned}$$

The final CNF formula

$$\left( \overline{z_{(s,c)}} \vee \overline{x_{(s,c,l)}} \right) \wedge \left( \overline{z_{(s,c)}} \vee \overline{x_{(s,c,l)}} \right) \wedge \dots \wedge \left( \bigvee_{l \in L} x_{(s,c,l)} \vee z_{(s,c)} \right)$$

```

\begin{lstlisting}[language=Python]
for s in range(1, conference_sessions + 1):
    for c in range(1, slots + 1):
        z_var = var_z(s, c)
        x_vars = [var_x(s, c, l) for l in papers_range]

        for x in x_vars:
            constraints.append([-z_var, -x])

        or_clause = [-x for x in x_vars] + [z_var]
        constraints.append(or_clause)
\end{lstlisting}

```

4 - The number of parallel sessions is not exceeded (or is equal ?) for each slot:

$$\sum_{s \in S, l \in L} x_{(s,c,l)} \leq n \quad \forall c \in C$$

but in our code we implement it with z

This Rewriting can enable us to reduce the size of constraint 4 as follows :

$$\sum_{s \in S} \overline{z_{(s,c)}} \leq n \quad \forall c \in C$$

```

\begin{lstlisting}[language=Python]
or c in range(1, slots + 1):
    neg_z_vars = [-var_z(s, c) for s in range(1, conference_sessions + 1)]
    atmost_clause = CardEnc.atmost(lits=neg_z_vars, bound=max_parallel_sessions)
    constraints.extend(atmost_clause.clauses)
\end{lstlisting}

```

We want to minimize the number of working-group conflicts in the schedule:

$$\max_{(s_1, s_2, c, g) \in S \times S \times C \times G, s_1 < s_2, g \in WG(s_1) \cap WG(s_2)} \overline{y_{(s_1, s_2, c, g)}}$$

implementation

```

\begin{lstlisting}[language=Python]
for s1 in range(1, conference_sessions + 1):
    for s2 in range(s1 + 1, conference_sessions + 1): % Ensure s1 < s2
        for c in range(1, slots + 1):
            common_groups = set(session_groups[s1 - 1]).intersection(session_groups[s2 - 1])
            for g in common_groups:
                y_var = var_y(s1, s2, c, g)
                constraints.append([-y_var], weight=1)
\end{lstlisting}

```