

Team Notebook

Metropolitan University

December 6, 2024

Contents

1 Array	3	6 DP	9	10.5 Dijkstra K shortest	13
1.1 Kadane in circular array	3	6.1 Coin Changing	9	10.6 Distance of Leaf from root	13
1.2 Kadane	3	6.2 Digit DP	9	10.7 Euler Tour	14
2 Bitmasks	3	6.3 Knapsack	10	10.8 Floyed Warshal	14
2.1 Change Bit for a given position	3	6.4 LIS	10	10.9 Krushkal;s + DSU	14
2.2 Know every Bit of an Integer	3	6.5 LNDS	10	10.10Longest Path in dag	15
3 Boilerplate	3	6.6 SOS DP	10	10.11Lowest Common Ancestor	15
4 Combitatorics	3	7 DSU	10	10.12Topological Sort	15
4.1 Formula	3	8 Formulas	10	11 Math	16
5 Data Structure	3	8.1 Formula	10	11.1 String and int multiply	16
5.1 BIT with Lazy	3	8.2 Physics	11	11.2 Sum of Absolute Diff of All Pairs	16
5.2 BIT	4	8.3 Trigonometry	11	12 Miscellaneous	16
5.3 LCA	4	9 Geometry	11	12.1 repeat	16
5.4 Maximum Subarray Sum	4	9.1 Circle	11	13 Number Theory	16
5.5 Monotonic Stack	5	9.2 Convex Hull	11	13.1 Big Mul	16
5.6 MOs	5	9.3 Parallelogram	11	13.2 Bigmod , Inverse MOD, ncr	16
5.7 Ordered Set	6	9.4 Polygon	11	13.3 Bigmod with Loop	16
5.8 Segement Tree	6	9.5 Right Circular Cone	12	13.4 Check if a subset sum exists	16
5.9 Segment Tree with Lazy	6	9.6 Trapezium	12	13.5 Euler Phi Sieve	16
5.10 Sliding Window Maximum	7	9.7 Triangle	12	13.6 Factorial	17
5.11 Sparse Table	8	9.8 Truncated Cone	12	13.6.1 Digit Count	17
5.12 Sqrt Decomposition	8	10 Graph	12	13.6.2 Divisor Count	17
		10.1 Articulation Point	12	13.6.3 Tailing Zeros	17
		10.2 Detect Cycle in Tree	12	13.7 Generate Number of Divisor 1 to N	17
		10.3 DFS on Tree	13	13.8 Get Prime	17
		10.4 Dijkstra	13	13.9 Is Prime	17
				13.10MOD Jog Gun	17

13.11	Number of Divisor	17	13.18	Sum of Divisor	19	14.6	String Matching with Bitset	21
13.12	Number of Prime Divisor	18				14.7	Suffix Array	21
13.13	Pascal Tree	18	14 String		19			
13.14	Phi 4 large number	18	14.1	Hashing	19	15 templates		22
13.15	Phi for a large number	18	14.2	KMP	20			
13.16	Pollard Rho	18	14.3	KthLexiSmallestSubstring	20	16 Trie		24
13.17	SOD	18	14.4	lcs	21			
			14.5	Mancher	21	17 Z Function		25

1 Array

1.1 Kadane in circular array

```
int maxSubarraySumCircular(vector<int> &nums)
{
    int mxsf = -30000, mnsf = 30000, sum = 0, csum = 0;
    for (int x : nums)
    {
        csum += x; sum += x;
        mxsf = max(mxsf, csum);
        csum = max(csum, 0);
    }
    csum = 0;
    for (int x : nums)
    {
        csum += x;
        mnsf = min(mnsf, csum);
        if (csum > 0) csum = 0;
    }
    if (mnsf == sum) mnsf = 0;
    return max(mxsf, sum - mnsf);
}
```

1.2 Kadane

```
int maxSubArraySum(int a[], int size)
{
    int max_so_far = INT_MIN, max_ending_here = 0;

    for (int i = 0; i < size; i++) {
        max_ending_here = max_ending_here + a[i];
        if (max_so_far < max_ending_here)
            max_so_far = max_ending_here;

        if (max_ending_here < 0)
            max_ending_here = 0;
    }
    return max_so_far;
}
```

2 Bitmasks

2.1 Change Bit for a given position

```
int changeBit(int n, int x){
    n ^= 1<<(x-1); // flip xth bit
    n |= 1<<(x-1); // on xth bit
    if(n&(1<<(x-1))) n ^= 1<<(x-1); // off xth bit

    return n;
}
```

2.2 Know every Bit of an Integer

```
void keepBit(vector<int> &b, int n, int h = 1)
{
    int i = 25;
    for (i = 25; i >= 0; i--)
    {
        if (n >= (2 << i))
        {
            n -= (2 << i);
            b[i + 1] = b[i + 1] + h;
        }
    }
    if (n)
        b[i + 1] = b[i + 1] + h;
}
```

```
// for array b
//for 12 it keeps 0 0 1 1 0 0 0 0 0 0 0 0 0
//for 13 it keeps 1 0 1 1 0 0 0 0 0 0 0 0 0
```

3 Boilerplate

```
#define pi acos(-1)
#define MOD 1000000007
#define dpos(n) fixed << setprecision(n)
#define clear1(a) memset(a, -1, sizeof(a))
#define clear0(a) memset(a, 0, sizeof(a))
#define unik(a) unique(a.begin(), a.end()) - a.begin()
#define iotav(s, x) iota(s.begin(), s.end(), x)
#define lowerbound(v,x) lower_bound(v.begin(), v.end(), x)-v.begin()
#define upperbound(v,x) upper_bound(v.begin(), v.end(), x)-v.begin()
#define print(x) cout << #x << " = " << x << endl
long long dx[] = {1, -1, 0, 0, 1, 1, -1, -1};
long long dy[] = {0, 0, 1, -1, 1, -1, 1, -1};
int main() {
```

```
ios_base::sync_with_stdio(false); cin.tie(0),cout.tie(0);
#ifdef ONLINE_JUDGE
    freopen("input.txt", "r", stdin);
    freopen("output.txt", "w", stdout);
#endif
}
```

4 Combitatorics

4.1 Formula

Summation of squares of n natural numbers: $(n*(n+1)*(2n+1))/6$

$C(n,r): n! / (r! * (n-r)!)$
 $C(n,r): (n*(n-1)*...*(n-r+1)) / r!$

$P(n,k): n! / (n-k)!$
 $\rightarrow nCk = nCn-k$
 \rightarrow Ways to go from (0,0) to (r,c): $(r+c)Cr$ or $(r+c)Cc$
 \rightarrow Ways to go from (0,0,0) to (x,y,z): $(x+y+z)Cx * (y+z)Cy$

$\rightarrow a1+a2+...+an = k, ai \geq 0: C(k+n-1, n-1)$

\rightarrow Catalan Numbers: $C(n) = (2n)! / ((n+1)! * n!)$

5 Data Structure

5.1 BIT with Lazy

```
template <class T>
struct Fenwick {
    int n;
    vector<T> t;
    Fenwick() {}
    Fenwick(int _n) {
        n = _n;
        t.assign(n + 1, 0); // 1-indexed, so size is n + 1
    }
    void upd(int i, T val) {
        if (i <= 0) return;
        for (; i <= n; i += (i & -i))
            t[i] += val;
    }
    void upd(int l, int r, T val) {
```

```

        upd(l, val);
        upd(r + 1, -val);
    }
    T query(int i) {
        T sum = 0;
        for (; i >= 1; i -= (i & -i))
            sum += t[i];
        return sum;
    }
    T query(int l, int r) {
        return query(r) - query(l - 1);
    }
};

int main() {
    long long t = 1;
    while (t--) {
        long long n, q;
        cin >> n >> q;
        vector<long long> a(n + 1); // 1-indexed
        Fenwick<long long> tree(n);
        for (long long i = 1; i <= n; i++) {
            cin >> a[i];
        }
        for (long long i = 1; i <= n; i++) {
            tree.upd(i, i, a[i]);
        }
        while (q--) {
            int type;
            cin >> type;
            if (type == 1) {
                long long l, r, val;
                cin >> l >> r >> val;
                tree.upd(l, r, val);
            } else {
                long long l;
                cin >> l;
                cout << tree.query(l) << endl;
            }
        }
    }
}

```

5.2 BIT

```

void update(int i, int val, int n, int *tree)
{
    while (i <= n)
    {

```

```

        tree[i] += val;
        i += (i & -i);
    }
}
//sum from 1 to i
int getSum(int i, int *tree)
{
    int sum = 0;
    while (i > 0)
    {
        sum += tree[i];
        i ^= (i & -i);
    }
    return sum;
}

```

5.3 LCA

```

const int N = 1e5 + 10;
int tin[N], tout[N];
int up[N][32];
vector<int> adj[N];
int n, lg, timer;
void dfs(int src, int par)
{
    tin[src] = ++timer;
    up[src][0] = par;
    for(int i = 1; i <= lg; i++)
    {
        up[src][i] = up[up[src][i - 1]][i - 1];
    }
    for(auto child : adj[src])
    {
        if(child != par)
            dfs(child, src);
    }
    tout[src] = ++timer;
}
bool is_ancestor(int u, int v)
{
    return tin[u] <= tin[v] && tout[u] >= tout[v];
}
int lca(int u, int v)
{
    if(is_ancestor(u, v)) return u;
    if(is_ancestor(v, u)) return v;
    for(int i = lg; i >= 0; i--)
    {
        if(!is_ancestor(up[u][i], v))

```

```

        u = up[u][i];
    }
    return up[u][0];
}
void pre_process(int root)
{
    timer = 0;
    lg = ceil(log2(n));
    dfs(root, root);
}

```

5.4 Maximum Subarray Sum

```

const ll M = 2e5 + 10;
const ll inf = 1e9 + 10;
ll arr[M];
struct Node
{
    ll sum, pref, suf, ans;
} seg[4 * M];
Node ck(Node l, Node r)
{
    Node res;
    if (l.ans == inf)
        return r;
    if (r.ans == inf)
        return l;
    res.sum = l.sum + r.sum;
    res.pref = max(l.pref, r.pref + l.sum);
    res.suf = max(r.suf, l.suf + r.sum);
    res.ans = max({l.ans, r.ans, l.suf + r.pref});
    return res;
}
Node make(ll val)
{
    Node tmp;
    tmp.sum = val;
    tmp.pref = tmp.suf = tmp.ans = val;
    return tmp;
}
void build(ll node, ll l, ll r)
{
    if (l == r)
    {
        seg[node] = make(arr[l]);
        return;
    }
    ll mid = (l + r) >> 1;
    build(node * 2, l, mid);

```

```

    build(node * 2 + 1, mid + 1, r);
    seg[node] = ck(seg[node * 2], seg[node * 2 + 1]);
}
void update(ll node, ll l, ll r, ll idx, ll val)
{
    if (l == r)
    {
        seg[node] = make(val);
        return;
    }
    ll mid = (l + r) >> 1;

    if (idx <= mid)
        update(node * 2, l, mid, idx, val);
    else
        update(node * 2 + 1, mid + 1, r, idx, val);

    seg[node] = ck(seg[node * 2], seg[node * 2 + 1]);
}
Node query(ll node, ll l, ll r, ll L, ll R)
{
    if (l > R || r < L)
        return make(inf);
    if (L <= l && R >= r)
        return seg[node];

    ll mid = (l + r) >> 1;
    return ck(query(node * 2, l, mid, L, R), query(node * 2 + 1, mid + 1, r, L, R));
}
int main()
{
    ll n, q;
    cin >> n;
    for (ll i = 1; i <= n; i++)
        cin >> arr[i];
    build(1, 1, n);
    cin >> q;
    while (q--)
    {
        ll ty, id, val, i, j;
        cin >> ty;
        if (ty == 0)
        {
            cin >> id >> val;
            update(1, 1, n, id, val);
        }
        else
        {
            cin >> i >> j;

```

```

        cout << query(1, 1, n, i, j).ans << endl;
    }
}
}

5.5 Monotonic Stack

void printNGE(int arr[], int n)
{
    stack<int> s;
    s.push(arr[0]);
    for (int i = 1; i < n; i++) {
        if (s.empty()) {
            s.push(arr[i]);
            continue;
        }
        while (s.empty() == false && s.top() < arr[i]) {
            cout << s.top() << " --> " << arr[i] << endl;
            s.pop();
        }
        s.push(arr[i]);
    }
    while (s.empty() == false) {
        cout << s.top() << " --> " << -1 << endl;
        s.pop();
    }
}
}

```

5.6 MOs

```

#include <bits/stdc++.h>
using namespace std;

struct Query {
    int l, r, idx;
};

bool compare(const Query &q1, const Query &q2) {
    int block_size = sqrt(q1.l);
    if (q1.l / block_size != q2.l / block_size)
        return q1.l < q2.l;
    return q1.r < q2.r;
}

class MosAlgorithm {
public:
    vector<int> arr, answers, freq;

```

```

    vector<Query> queries;
    int current_answer = 0;

    MosAlgorithm(int n, int q) {
        arr.resize(n);
        answers.resize(q);
        freq.resize(n + 1, 0);
    }

    void add(int idx) {
        freq[arr[idx]]++;
        if (freq[arr[idx]] == 1)
            current_answer++;
    }

    void remove(int idx) {
        if (freq[arr[idx]] == 1)
            current_answer--;
        freq[arr[idx]]--;
    }

    vector<int> processQueries(int n) {
        int block_size = sqrt(n);
        sort(queries.begin(), queries.end(), compare);
        int curr_l = 0, curr_r = -1;
        for (const Query &q : queries) {
            int l = q.l, r = q.r;
            while (curr_r < r) add(++curr_r);
            while (curr_r > r) remove(curr_r--);
            while (curr_l < l) remove(curr_l++);
            while (curr_l > l) add(--curr_l);
            answers[q.idx] = current_answer;
        }
        return answers;
    }

    void addQuery(int l, int r, int idx) {
        queries.push_back({l, r, idx});
    }

    void setArray(const vector<int> &input) {
        arr = input;
    }
};

int main() {
    int n, q;
    cin >> n >> q;
    MosAlgorithm mos(n, q);
    vector<int> arr(n);

```

```

for (int i = 0; i < n; i++) cin >> arr[i];
mos.setArray(arr);
for (int i = 0; i < q; i++) {
    int l, r;
    cin >> l >> r;
    l--, r--;
    mos.addQuery(l, r, i);
}
vector<int> results = mos.processQueries(n);
for (int i = 0; i < q; i++) {
    cout << results[i] << endl;
}
return 0;
}

```

5.7 Ordered Set

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace std;
typedef __gnu_pbds::tree<int, __gnu_pbds::null_type, less<
    int>, __gnu_pbds::rb_tree_tag, __gnu_pbds::
    tree_order_statistics_node_update> ordered_set;

int main()
{
    ios_base::sync_with_stdio(false);
    cin.tie(0), cout.tie(0);

    ordered_set s;
    long long cnt = 0;

    for (long long i = 1; i <= n; i++)
    {
        long long x;
        cin >> x;
        s.insert(x);

        long long index = s.order_of_key(x); //index of this
            number in a set
        cout << index << endl;
    }
}

```

5.8 Segement Tree

```

#include <bits/stdc++.h>
using namespace std;

void build(long long *tree, long long *a, long long node,
    long long l, long long r)
{
    if (l == r)
    {
        tree[node] = a[l];
        return;
    }

    long long left = 2 * node, right = left + 1;
    long long mid = 1 + (r-l)/2;

    build(tree, a, left, l, mid);
    build(tree, a, right, mid + 1, r);

    tree[node] = tree[left] + tree[right];
}

long long query(long long *tree, long long *a, long long
    node, long long l, long long r, long long begin, long
    long end)
{
    if (r < begin || end < l)
        return 0;

    if (begin <= l && r <= end)
    {
        return tree[node];
    }

    long long left = 2 * node, right = left + 1;
    long long mid = 1 + (r-l)/2;

    long long left_value = query(tree, a, left, l, mid, begin
        , end);
    long long right_value = query(tree, a, right, mid + 1, r,
        begin, end);

    return left_value + right_value;
}

void update(long long *tree, long long *a, long long node,
    long long l, long long r, long long index, long long
    value)
{
    if (l == r)
    {

```

```

        a[l] = value;
        tree[node] = a[l];
        return;
    }

    long long left = 2 * node, right = left + 1;
    long long mid = 1 + (r-l)/2;

    if (index <= mid)
        update(tree, a, left, l, mid, index, value);
    else
        update(tree, a, right, mid + 1, r, index, value);

    tree[node] = tree[left] + tree[right];
}

int main()
{
    long long n;
    cin >> n;
    long long q;
    cin >> q;

    long long a[n + 2], tree[4 * n];
    for (long long i = 1; i <= n; i++)
        cin >> a[i];

    build(tree, a, 1, 1, n);

    while (q--)
    {
        long long tt, x, y;
        cin >> tt >> x >> y;
        if (tt == 1) {
            update(tree, a, 1, 1, n, x, y);
        }
        long long desire_value = query(tree, a, 1, 1, n, x, y
            );
        cout << desire_value << endl;
    }
}

```

5.9 Segment Tree with Lazy

```

template <class T>
struct SegmentTree
{
    vector<T> tree, lazy, a;

```

```

int n;

SegmentTree(int size)
{
    n = size;
    tree.resize(4 * n);
    lazy.resize(4 * n);
    a.resize(n + 1);
}

void build_tree(int node, int l, int r)
{
    lazy[node] = 0;
    if (l == r)
    {
        tree[node] = a[l];
        return;
    }
    int left = 2 * node, right = left + 1, mid = l + (r - 1) / 2;
    build_tree(left, l, mid);
    build_tree(right, mid + 1, r);
    tree[node] = tree[left] + tree[right];
}

void propagate(int node, int l, int r)
{
    if (lazy[node])
    {
        tree[node] += (r - l + 1) * lazy[node];
        if (l != r)
        {
            lazy[2 * node] += lazy[node];
            lazy[2 * node + 1] += lazy[node];
        }
        lazy[node] = 0;
    }
}

T query(int node, int l, int r, int b, int e)
{
    propagate(node, l, r);
    if (r < b || e < l)
        return 0;
    if (b <= l && r <= e)
        return tree[node];
    int mid = l + (r - l) / 2;
    return query(2 * node, l, mid, b, e) + query(2 * node + 1, mid + 1, r, b, e);
}

```

```

void update(int node, int l, int r, int b, int e, T val)
{
    propagate(node, l, r);
    if (r < b || e < l)
        return;
    if (b <= l && r <= e)
    {
        tree[node] += (r - l + 1) * val;
        if (l != r)
        {
            lazy[2 * node] += val;
            lazy[2 * node + 1] += val;
        }
        return;
    }
    int mid = l + (r - l) / 2;
    update(2 * node, l, mid, b, e, val);
    update(2 * node + 1, mid + 1, r, b, e, val);
    tree[node] = tree[2 * node] + tree[2 * node + 1];
}

void update_range(int l, int r, T val)
{
    update(1, 1, n, l, r, val);
}

T range_query(int l)
{
    return query(1, 1, n, l, l);
}

T range_query(int l, int r)
{
    return query(1, 1, n, l, r);
}

void set_array(const vector<T>& input)
{
    for (int i = 1; i <= n; i++)
        a[i] = input[i - 1];
    build_tree(1, 1, n);
}

};

int main()
{
    int n, q;
    cin >> n >> q;
    SegmentTree<long long> st(n);

```

```

vector<long long> arr(n);
for (int i = 0; i < n; i++) cin >> arr[i];
st.set_array(arr);
while (q--)
{
    int type;
    cin >> type;
    if (type == 1)
    {
        int l, r;
        long long val;
        cin >> l >> r >> val;
        st.update_range(l, r, val);
    }
    else
    {
        int l;
        cin >> l;
        cout << st.range_query(l) << endl;
    }
}
}

```

5.10 Sliding Window Maximum

```

vector<int> maxSlidingWindow(vector<int> &nums, int k)
{
    int n = nums.size();
    deque<int> dq;
    vector<int> ans;
    for (int i = 0; i < n; i++)
    {
        while (dq.size() > 0 && nums[dq.back()] < nums[i])
            dq.pop_back();
        dq.push_back(i);
        if (i >= k - 1)
        {
            ans.push_back(nums[dq.front()]);
            if (dq.front() < i - k + 2)
                dq.pop_front();
        }
    }
    for (int i = 0; i < ans.size(); i++)
    {
        ans[i] = nums[ans[i]];
    }
    return ans;
}

```

5.11 Sparse Table

```
const int N = 2e5 + 5, K = 20;

struct SparseTable {
    long long a[N], sparseAll[N][K][8];

    long long lcm(long long x, long long y) {
        return (x / __gcd(x, y)) * y;
    }

    void build(int n) {
        for (int i = 1; i <= n; i++)
            for (int j = 0; j < 8; j++)
                sparseAll[i][0][j] = a[i];
        for (int j = 1; j < K; j++)
            for (int i = 1; i + (1 << j) - 1 <= n; i++) {
                sparseAll[i][j][0] = min(sparseAll[i][j - 1][0], sparseAll[i + (1 << (j - 1))][j - 1][0]);
                sparseAll[i][j][1] = max(sparseAll[i][j - 1][1], sparseAll[i + (1 << (j - 1))][j - 1][1]);
                sparseAll[i][j][2] = sparseAll[i][j - 1][2] + sparseAll[i + (1 << (j - 1))][j - 1][2];
                sparseAll[i][j][3] = __gcd(sparseAll[i][j - 1][3], sparseAll[i + (1 << (j - 1))][j - 1][3]);
                sparseAll[i][j][4] = lcm(sparseAll[i][j - 1][4], sparseAll[i + (1 << (j - 1))][j - 1][4]);
                sparseAll[i][j][5] = sparseAll[i][j - 1][5] ^ sparseAll[i + (1 << (j - 1))][j - 1][5];
                sparseAll[i][j][6] = sparseAll[i][j - 1][6] & sparseAll[i + (1 << (j - 1))][j - 1][6];
                sparseAll[i][j][7] = sparseAll[i][j - 1][7] | sparseAll[i + (1 << (j - 1))][j - 1][7];
            }
    }

    long long qMin(int l, int r) {
        int k = __lg(r - l + 1);
        return min(sparseAll[l][k][0], sparseAll[r - (1 << k) + 1][k][0]);
    }

    long long qMax(int l, int r) {
        int k = __lg(r - l + 1);
        return max(sparseAll[l][k][1], sparseAll[r - (1 << k) + 1][k][1]);
    }
};
```

```
    }

    long long qSum(int l, int r) {
        int k = __lg(r - l + 1);
        return sparseAll[l][k][2] + sparseAll[r - (1 << k) + 1][k][2];
    }

    long long qGcd(int l, int r) {
        int k = __lg(r - l + 1);
        return __gcd(sparseAll[l][k][3], sparseAll[r - (1 << k) + 1][k][3]);
    }

    long long qLcm(int l, int r) {
        int k = __lg(r - l + 1);
        return lcm(sparseAll[l][k][4], sparseAll[r - (1 << k) + 1][k][4]);
    }

    long long qXor(int l, int r) {
        int k = __lg(r - l + 1);
        return sparseAll[l][k][5] ^ sparseAll[r - (1 << k) + 1][k][5];
    }

    long long qAnd(int l, int r) {
        int k = __lg(r - l + 1);
        return sparseAll[l][k][6] & sparseAll[r - (1 << k) + 1][k][6];
    }

    long long qOr(int l, int r) {
        int k = __lg(r - l + 1);
        return sparseAll[l][k][7] | sparseAll[r - (1 << k) + 1][k][7];
    }
};

int main() {
    int n, q;
    cin >> n >> q;
    SparseTable st;
    for (int i = 1; i <= n; i++) cin >> st.a[i];
    st.build(n);
    while (q--) {
        int l, r, type;
        cin >> l >> r >> type;
        //print what u want
    }
}
```

5.12 Sqrt Decomposition

```
#include <bits/stdc++.h>
using namespace std;

struct SqrtDecomposition {
    int n, block_size;
    vector<int> arr, blocks;

    SqrtDecomposition(const vector<int> &input) {
        n = input.size();
        block_size = sqrt(n); // Calculate the size of each block
        arr = input;
        blocks.resize((n + block_size - 1) / block_size, 0);
        // Adjust for the number of blocks

        // Build the initial blocks by summing over ranges
        for (int i = 0; i < n; i++) {
            blocks[i / block_size] += arr[i];
        }
    }

    // Query the sum in range [l, r]
    int query(int l, int r) {
        l--, r--; // Adjust for 0 indexing
        int sum = 0;

        int start_block = l / block_size;
        int end_block = r / block_size;

        if (start_block == end_block) {
            // When l and r are in the same block, sum directly
            for (int i = l; i <= r; i++) sum += arr[i];
        } else {
            // Sum the partial block from l to the end of its block
            for (int i = l; i < (start_block + 1) * block_size; i++) sum += arr[i];
        }
    }
};
```



```

        // Sum the full blocks in between
        for (int i = start_block + 1; i < end_block; i++)
            sum += blocks[i];

        // Sum the partial block from the start of r's
        // block to r
        for (int i = end_block * block_size; i <= r; i++)
            sum += arr[i];
    }

    return sum;
}

// Update the value at index idx to val
void update(int idx, int val)
{
    idx--; //Adjust for 0 indexing
    int block_idx = idx / block_size;

    // Adjust the block's sum by the difference in values
    blocks[block_idx] += (val - arr[idx]);

    // Update the original array
    arr[idx] = val;
}

};

int main()
{
    int n, q;
    cin >> n >> q;

    vector<int> a(n);
    for (int i = 0; i < n; i++)
        cin >> a[i];

    // Initialize sqrt decomposition
    SqrtDecomposition sqrtDecomp(a);

    while (q--)
    {
        int type;
        cin >> type;

        if (type == 1)
        {
            int l, r;
            cin >> l >> r;

```

```

        cout << sqrtDecomp.query(l, r) << endl; // 1
            indexing
        }
        else
        {
            int x, val;
            cin >> x >> val;

            sqrtDecomp.update(x, val); //indexing
        }
    }
    return 0;
}

```

6 DP

6.1 Coin Changing

```

long long minNumberOfCoin(vector<long long> &v, long long
    val, long long n, vector<long long> &dp)
{
    cnt++;
    if (val == 0)
        return 0;
    if (val < 0)
        return LLONG_MAX;
    if (dp[val] != LLONG_MAX)
        return dp[val];

    long long ans = LLONG_MAX;

    for (long long i = 0; i < n; i++)
    {
        long long res = minNumberOfCoin(v, val - v[i], n, dp)
            ;
        if (res != LLONG_MAX)
            ans = min(ans, res + 1);
    }

    return dp[val] = ans;
}

int numberOfWays(int coins[], int n, int sum)
{
    int dp[sum + 1];
    memset(dp, 0, sizeof(dp));

```

```

dp[0] = 1;
for (int i = 0; i < n; i++)
    for (int j = coins[i]; j <= sum; j++)
        dp[j] += dp[j - coins[i]];
return dp[sum];
}

```

6.2 Digit DP

```

vector<int> num;
int sz, k, n, m;
int dp[10][2][100][100];
int digitdp(int pos, int issmall, int sum, int val)
{
    if (pos == sz)
    {
        if (!sum && !val)
            return 1;
        return 0;
    }
    if (dp[pos][issmall][sum][val] != -1)
        return dp[pos][issmall][sum][val];
    int lim;
    if (issmall == 0)
        lim = num[pos];
    else
        lim = 9;
    int ans = 0;
    for (int digit = 0; digit <= lim; digit++)
    {
        int cur_issmall = issmall;
        if (issmall == 0 && digit < lim)
            cur_issmall = 1;
        int cur_sum = (sum + digit) % k;
        int cur_val = ((val * 10) + digit) % k;
        ans += digitdp(pos + 1, cur_issmall, cur_sum, cur_val
            );
    }
    return dp[pos][issmall][sum][val] = ans;
}

int solve(int n)
{
    num.clear();
    while (n > 0)
    {
        num.push_back(n % 10);
        n /= 10;
    }
}

```

```

    sz = num.size();
    reverse(num.begin(), num.end());
    memset(dp, -1, sizeof(dp));
    return digitdp(0, 0, 0, 0);
}

```

6.3 Knapsack

```

long long knapSack(long long w, long long i, long long *
    marks, long long *cap, vector<vector<long long>> &dp)
{
    if (i < 0)
        return 0;
    if (dp[i][w] != -1)
        return dp[i][w];

    if (cap[i] > w) dp[i][w] = knapSack(w, i - 1, marks, cap,
        dp);
    else dp[i][w] = max(marks[i] + knapSack(w - cap[i], i -
        1, marks, cap, dp), knapSack(w, i - 1, marks, cap,
        dp));

    return dp[i][w];
}

```

6.4 LIS

```

int LIS(vector<int>&v){
    int l = v.size(), dp[l];
    for(int i=0; i<l;i++){
        dp[i]=1;
        for(int j=0; j<i; j++){
            if(v[j]<v[i] and dp[i]<dp[j]+1) dp[i] = dp[j] +
                1;
        }
    }
    return *max_element(dp, dp+l);
}

```

6.5 LNDS

```

int lnds[MAX];
int LNDS(int n) {
    lnds[1]=arr[1]; //1 base index
    int len = 1 ;

```

```

for(int i = 2; i<=n;i++) {
    if(arr[i]>=lnds[len])
        lnds[++len] = arr[i];
    else{
        int j=upper_bound(lnds+1,lnds+len+ 1,arr[i])-lnds;
        lnds[j] = arr[i]; } }
    return len; }

```

6.6 SOS DP

```

for(int i = 0; i < (1 << N); ++i) {
    F[i] = A[i]; }
for(int i = 0; i < N; ++i) {
    for(int mask=0;mask<(1<<N); ++mask) {
        if(mask & (1 << i)) {
            F[mask] += F[mask ^ (1 << i)]; } }}

```

7 DSU

```

struct DSU
{
    int connected;
    vector<int> par, sz;
    void init(int n)
    {
        par = sz = vector<int> (n + 1, 0);
        for(int i = 1; i <= n; i++)
            par[i] = i, sz[i] = 1;
        connected = n;
    }
    int getPar(int u)
    {
        while(u != par[u])
        {
            par[u] = par[par[u]];
            u = par[u];
        }
        return u;
    }
    int getSize(int u)
    {
        return sz[getPar(u)];
    }
    void unite(int u, int v)
    {
        int par1 = getPar(u), par2 = getPar(v);

```

```

    if(par1 == par2)
        return;

    connected--;
    if(sz[par1] > sz[par2])
        swap(par1, par2);

    sz[par2] += sz[par1];
    sz[par1] = 0;
    par[par1] = par[par2];
}
}

```

8 Formulas

8.1 Formula

Others:
 Decider for a point located left or right of a line:
 $d = (x_3 - x_2) * (y_2 - y_1) - (y_3 - y_2) * (x_2 - x_1)$
 Number of digits: $\log_{10}(n) + 1$
 Depth of road water: $(s^2 - h^2) / 2h$

```

//sum of series n/1+n/2+n/3+....n/n
ll root=sqrt(n);
for(int i=1; i<=root; i++)
    sum+=n/i;
sum=(2*sum)-(root*root);

```

count the numbers that are
 divisible by given number in a
 certain range: $a=2, b=3, c=7$;
 $low = (a+b-1)/a$;
 $high = c/a$;
 $total = high - low + 1$;

Euler Constant: 0 .5772156649

#Number of squares in a $n*n$ grid:
 $S = (n*(n+1)*(2*n+1))/6$;

#Number of rectangle in a $n*n$ grid:
 $R = (n+1)*n/2*(n+1)*n/2 - S$;

#Total number of rectangle and square in a $n*n$ grid:
 $ans = [(n^2 + n)^2] / 4$

```
#Number of squares in a n*m grid
exp:6*4
S=6*4+5*3+4*2+3*1=50

#Number of rectangles in n*m grid
R=m(m+1)n(n+1)/4

#Number of cubes in a n*n*n grid
formula:n^k-(n-2)^k
C=n*(n+1)/2*n*(n+1)/2;

#Number of boxes in a n*n*n grid:
B=(n+1)*n/2*(n+1)*n/2*(n+1)*n/2-C;

#Number of hypercube in a n^4grid:
start a loop from 1 to <=n;
HC=0;
for(i=1;i<=n;i++)
HC+=i*i*i*i;

#Number of hyper box in a n^4 grid:
HB=(n+1)*n/2*(n+1)*n/2*(n+1)*n/2*(n+1)*n/2 - HC;
```

8.2 Physics

```
Physics Formuas
Projectile motion
x = utcos
y = utsin      (1/2) gt*t
y = x tan      g*x*x/( 2u*u*cos*cos )
T = 2u sin/g
R = u*u*sin2/g
H = u*u*sin*sin /2g
```

8.3 Trigonometry

```
//Trigonometry
sin2 =2 sincos
cos2 = cos * cos - sin * sin
sin3 =3 sin -4* sin * sin * sin
cos3 =4* cos * cos * cos -3 cos

//For triangle:
a=bcosC+ccosB
b=acosC+ccosA
c=bcosA+acosB
```

```
sin(A+ B )=sinAcosB + cosAsinB
cos(A+ B )=cosAcosB + sinAsinB
```

9 Geometry

9.1 Circle

```
Distance: sqrt((x2-x1)^2 + (y2-y1)^2)

Check if 3 points are in same line:
x1*(y2-y3)-x2(y1-y3)+x3(y1-y2) = 0

Find a circle that covers 2 given:
x3 = (x1+x2)/2 , y3 = (y1+y2)/2
r = dist(x1,y1,x2,y2)

Lattice Points:1+gcd(|x1-x2|,|y1-y2|)
Slope formed by 2 points:(y2-y1)/(x2-x1)
Area of sector of circle: r^2*
Arc Length: r*theta
```

9.2 Convex Hull

```
vector<PT> convex_hull(vector<PT> &p) {
    if (p.size() <= 1) return p;
    vector<PT> v = p;
    sort(v.begin(), v.end());
    vector<PT> up, dn;
    for (auto& p : v) {
        while (up.size() > 1 && orientation(up[up.size() - 2],
            up.back(), p) >= 0) {
            up.pop_back();
        }
        while (dn.size() > 1 && orientation(dn[dn.size() - 2],
            dn.back(), p) <= 0) {
            dn.pop_back();
        }
        up.push_back(p);
        dn.push_back(p);
    }
    v = dn;
    if (v.size() > 1) v.pop_back();
    reverse(up.begin(), up.end());
    up.pop_back();
    for (auto& p : up) {
        v.push_back(p);
    }
}
```

```
}
if (v.size() == 2 && v[0] == v[1]) v.pop_back();
return v;
}
bool is_convex(vector<PT> &p) {
    bool s[3]; s[0] = s[1] = s[2] = 0;
    int n = p.size();
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n;
        int k = (j + 1) % n;
        s[sign(cross(p[j] - p[i], p[k] - p[i])) + 1] = 1;
        if (s[0] && s[2]) return 0;
    }
    return 1;
}
int is_point_in_convex(vector<PT> &p, const PT& x) {
    int n = p.size(); assert(n >= 3);
    int a = orientation(p[0], p[1], x), b = orientation(p[0],
        p[n - 1], x);
    if (a < 0 || b > 0) return 1;
    int l = 1, r = n - 1;
    while (l + 1 < r) {
        int mid = l + r >> 1;
        if (orientation(p[0], p[mid], x) >= 0) l = mid;
        else r = mid;
    }
    int k = orientation(p[l], p[r], x);
    if (k <= 0) return -k;
    if (l == 1 && a == 0) return 0;
    if (r == n - 1 && b == 0) return 0;
    return -1;
}
```

9.3 Parallelogram

```
Given 3 points find 4th point:
Dx = Ax + (Cx-Bx)
Dy = Ay + (Cy-By)

Area: | ((Ax*By+Bx*Cy+Cx*Dy+Dx*Ay)
-(Ay*Bx + By*Cx + Cx*Dx + Dy*Ax))|
```

9.4 Polygon

```
The sum of the interior angles: (2n - 4) * 90
*Area of the largest square inside
a pentagon->
```

$s * (\sin(108) / (\sin(18) + \sin(36)))$
$\text{Area: } (s^2 * n) / 4 * \tan(180 / 4)$ $\text{Area: } (r^2 * n * \sin(360 / n)) / 2$ $\text{Area: } \text{Apo}^2 * n * \tan(180 / n)$ $\text{Area: } * \text{sq}(5 * (5 + 2 * \text{sq}(5))) * s^2$ $\text{Area: } (\text{Apo} * s) / 2$ $\text{Area: } \text{pr} / 2$ $\text{Area: } * n * \sin(360 / n) * s^2$ $\text{Area: } n * \text{apo}^2 * \tan(180 / n)$ $\text{Area: } (n * r * \sin(2 * (180 / n))) / 2$ $\text{Area: } (* n * s^2) / \tan(180 / n)$ $\text{Perimeter: } 5 * s$ $\text{Diagonal: } (s * (1 + \text{sq}(5))) / 2$ $\text{Height: } (s * \text{sq}(5 + 2 * \text{sq}(5))) / 2$
$\text{an: } 2 * R * \sin(180 / n)$..here:an=side of regular inscribed polygon,R=radius of circumscribed circle.
Sum of interior angles of a Convex polygon: $180(n-2)$
Exterior taken one at each vertex:360
measurement of Exterior Ang: $360/n$ Measure Interior An: $((n-2)*180)/n$ No. Of Dia: $(n*(n-3))/2$ No. Of Tri: $N-2$ Side: $2 * R * \sin(180/n)$ Apo: $R * \cos(180/n)$ Side: $2 * \text{apo} * \tan(180/n)$
Area of smallest tri: $\text{apo} * (s/2)$ $= * \text{Apo}^2 * \tan(180/n)$
Intersection points of diagonals of n(odd) sided regular polygon = $nC4$

9.5 Right Circular Cone

$\text{Volume: } (\text{pie} * h / 3) * (R^2 + R * r + r^2)$ $\text{Lateral surface Area: } \text{pie} * (r + R) * S$ $\text{Area of the base: } \text{pie} * r^2$ $\text{Lateral area: } \text{pie} * r * L$ $\text{Total Surface A: } \text{pie} * r^2 + \text{pie} * r * s$ $\text{Volume: } * \text{pie} * r^2 * h$ $s = \text{sq}(r^2 + h^2)$
--

9.6 Trapezium

$\text{Area: } (a+b) / (a-b) * \text{sqrt}((s-a)(s-b)(s-b-c)(s-b-d))$ $\rightarrow s = (a+b+c+d) / 2$ $\rightarrow a = \text{long parallel side}$ $\rightarrow b = \text{short parallel side}$ $\rightarrow c, d = \text{non-parallel side}$
$\text{Area: } h * ((b1+b2) / 2)$ $H: \text{sq}(b^2 - (b^2 - d^2 + (a-c)^2) / 2(a-c))^{.5}$

9.7 Triangle

To form: $a+b>c, b+c>a, c+a>b$ Check if 3 points form triangle: $ (x2-x1)(y3-y1)-(y2-y1)(x3-x1) > 0$ Perimeter: $p = a+b+c$ Area: 1) $(a*b) / 2$ 2) $(ab \sin C) / 2$ 3) $\text{sqrt}(s(s-a)(s-b)(s-c)); //s=(p/2)$ 4) $(\text{sqrt}(3)/4) * a * a; //\text{equi triangle}$ 5) $(b * \text{sqrt}(4 * a * a - b * b)) / 4; //\text{isosceles}$
Pythagoras: $a^2 + b^2 = c^2$ SineRule: $a / \sin A = b / \sin B = c / \sin C$ CosineRule: $\cos A = (b^2 + c^2 - a^2) / 2bc$ Centre: $x = (x1 + x2 + x3) / 3, y = (y1 + y2 + y3) / 3$ Median: $AD = \text{sqrt}((2 * b^2 + 2 * c^2 - a^2) / 4)$ Centroid: $AG = \text{sqrt}(2 * b^2 - 2 * c^2 - a^2) / 3$ Inradius: A / s Circumradius: $a / (2 * \sin A)$ $r = abc / \text{sq}((a+b+c)(a+b-c)(a+c-b)(b+c-a))$

9.8 Truncated Cone

$z = (H * r2^2) / (r1^2 - r2^2)$ $R = (* r1^2(z+h)) / (H+z)$ $\text{Volume: } * \text{pie} * h * (R^2 + (R * r2) + r2^2)$ $\text{Volume of a cylinder: } \text{pi} * r * r * h$ $\text{Volume of a triangular prism: } 0.5 * b * h * H$
--

10 Graph

10.1 Articulation Point

<pre>void dfs(int v, int p = -1) { visited[v] = true; tin[v] = low[v] = timer++; int children=0; for (int to : adj[v]) { if (to == p) continue; if (visited[to]) { low[v] = min(low[v], tin[to]); } else { dfs(to, v); low[v] = min(low[v], low[to]); if (low[to] >= tin[v] && p!=-1) IS_CUTPOINT(v); ++children; } } if(p == -1 && children > 1) IS_CUTPOINT(v); //v is the point print it }</pre>
<pre>void find_cutpoints() { timer = 0; visited.assign(n, false); tin.assign(n, -1); low.assign(n, -1); for (int i = 0; i < n; ++i) { if (!visited[i]) dfs (i); } }</pre>

10.2 Detect Cycle in Tree

<pre>void dfs(int u, vector<bool> &vis, vector<vector<int>>&p, int prev) { if(vis[u]){ cycle = true; return; } vis[u] = true; for (int i = 0; i < p[u].size(); i++) { int v = p[u][i]; if(prev!=v){ dfs(v, vis, p, u); } } }</pre>

```

    }
}

```

10.3 DFS on Tree

```

vector<vector<int>> p;
vector<long long> depth;
vector<long long> reverse_depth;
void dfs(int u, int par)
{
    if (p[u].size() == 1 && p[u][0] == par){
        depth[u] = depth[par]+1;
        reverse_depth[u] = 1;
    }
    else
    {
        for (auto v : p[u])
        {
            if (v != par)
            {
                depth[v] = 1 + depth[u];
                dfs(v, u);
                reverse_depth[u] = 1 + reverse_depth[v];
            }
        }
    }
}
void solve(int n)
{
    p.assign(n + 2, vector<int>());
    depth.assign(n + 2, 0);
    reverse_depth.assign(n + 2, 0);
    for (int i = 1; i < n; i++)
    {
        int x, y;
        cin >> x >> y;
        p[x].push_back(y);
        p[y].push_back(x);
    }
    depth[1]=1;
    dfs(1, -1);
    int x = 2;
    cout<<depth[x]<<" "<<reverse_depth[x]<<endl;
}

```

10.4 Dijkstra

```

#include <bits/stdc++.h>
using namespace std;

const long long N = 2e5 + 3;
const long long inf = 1e18;

vector<pair<long long, long long>> edges[N];
vector<long long> dist(N, inf);

int main()
{
    long long n, m;
    cin >> n >> m;

    while (m--)
    {
        long long x, y, w;
        cin >> x >> y >> w;
        edges[x].push_back({y, w});
    }

    dist[1] = 0;

    priority_queue<pair<long long, long long>, vector<pair<
        long long, long long>>, greater<pair<long long, long
        long>>> pq;

    pq.push({0, 1});

    while (!pq.empty())
    {
        long long u = pq.top().second, d = pq.top().first;
        pq.pop();
        if (dist[u] < d)
            continue;
        for (auto e : edges[u])
        {
            long long w = e.second, v = e.first;
            if (dist[v] > dist[u] + w)
            {
                dist[v] = dist[u] + w;
                pq.push({dist[v], v});
            }
        }
    }

    for (long long i = 1; i <= n; i++)
        cout << dist[i] << " ";
}

```

10.5 Dijkstra K shortest

```

const ll mx = 1e6;
ll n, m, k;
map<pair<ll, ll>, ll> mp;
void dijkstra(ll src, vector<pair<ll, ll>> adj[])
{
    vector<vector<ll>> dist(n + 10, vector<ll>(k,
        LONG_LONG_MAX));
    priority_queue<pair<ll, ll>, vector<pair<ll, ll>>,
        greater<pair<ll, ll>>> pq;
    pq.push({0, src});
    while (pq.size() > 0)
    {
        pair<ll, ll> cur = pq.top();
        pq.pop();
        ll u = cur.second;
        ll d = cur.first;

        if (d > dist[u][k - 1])
        {
            continue;
        }
        for (ll i = 0; i < adj[u].size(); i++)
        {
            ll v = adj[u][i].first;
            ll d1 = adj[u][i].second;
            if (d + d1 < dist[v][k - 1])
            {
                dist[v][k - 1] = d + d1;
                pq.push({dist[v][k - 1], v});
                srt(dist[v]);
            }
        }
    }
    for (ll i = 0; i < k; i++)
    {
        cout << dist[n][i] << " ";
    }
    cout << endl;
}

```

10.6 Distance of Leaf from root

```

#include<bits/stdc++.h>
using namespace std;
//K= root, n=node
void find(vector<long long>a[], long long n, long long k)
{

```

```

queue<long long>q;
long long vis[n+2]={};
long long dis[n+2]={},maxx=0ll;
vis[k]=0;
dis[k]=1;
q.push(k);
while(!q.empty())
{
    long long x=q.front();
    q.pop();
    long long l=a[x].size();
    for(long long i=0;i<l;i++)
    {
        long long y=a[x][i];
        if(!vis[y])
        {
            q.push(y);
            vis[y]=1;
            dis[y]=dis[x]+1;
            maxx=max(maxx,dis[y]);
        }
    }
}
cout<<maxx<<endl;
}

```

10.7 Euler Tour

```

void dfs_euler(int src, int par)
{
    euler_path.push_back(src);
    int f = 0;
    for (auto i : graph[src])
    {
        if (i == par)
            continue;
        f = 1;
        dfs_euler(i, src);
    }
    if (f)
        euler_path.push_back(src);
}

void init_euler_path()
{
    dfs_euler(1, 0);
    int idx = 1;
    for (auto i : euler_path)
    {

```

```

        if (st[i] == 0)
            st[i] = idx;
        en[i] = idx;
        idx++;
    }
}

```

10.8 Floyd Warshal

```

const int INF = 1e9; // Replace with a suitable large value
for infinity

void floydWarshall(vector<vector<int>>& graph, int nodes) {
    for (int k = 1; k <= nodes; k++) {
        for (int i = 1; i <= nodes; i++) {
            for (int j = 1; j <= nodes; j++) {
                if (graph[i][k] != INF && graph[k][j] != INF)
                {
                    graph[i][j] = min(graph[i][j], graph[i][k]
                    + graph[k][j]);
                }
            }
        }
    }
}

void addEdge(vector<vector<int>>& dist, int u, int v, int c,
int N) {
    for (int x = 0; x < N; ++x) {
        for (int y = 0; y < N; ++y) {
            if (dist[x][u] != INF && dist[v][y] != INF) {
                dist[x][y] = min(dist[x][y], dist[x][u] + c +
                dist[v][y]);
            }
            if (dist[x][v] != INF && dist[u][y] != INF) {
                dist[x][y] = min(dist[x][y], dist[x][v] + c +
                dist[u][y]);
            }
        }
    }
}

int main() {
    int nodes = 4; // Example: Number of nodes
    vector<vector<int>> graph(nodes + 1, vector<int>(nodes +
    1, INF));

    // Initialize graph distances
    for (int i = 1; i <= nodes; i++) {

```

```

        graph[i][i] = 0; // Distance to self is 0
    }

    // Add some edges (example)
    graph[1][2] = 4;
    graph[2][3] = 5;
    graph[3][4] = 6;

    floydWarshall(graph, nodes);

    int N = nodes; // Example: Graph size for 'dist'
    vector<vector<int>> dist = graph; // Copy 'graph' to '
    dist'
    int u = 1, v = 4, c = 3; // Example edge
    addEdge(dist, u, v, c, N);

    // Output the result
    for (int i = 1; i <= nodes; i++) {
        for (int j = 1; j <= nodes; j++) {
            cout << (dist[i][j] == INF ? "INF" : to_string(
            dist[i][j])) << " ";
        }
        cout << endl;
    }

    return 0;
}

```

10.9 Krushkal;s + DSU

```

int par[N];
int sz[N];
void make_set(int v){
    par[v] = v;
}

int find_set(int v){
    if(v == par[v]) return v;
    return par[v] = find_set(par[v]);
}

void union_sets(int a, int b){
    a = find_set(a);
    b = find_set(b);
    if(a != b){
        if(sz[a] > sz[b]) swap(a, b);
        par[a] = b;
        sz[b] += sz[a];
    }
}

void reset(int n){

```

```

    for(int i = 0; i <= n; i++){
        make_set(i);
    }
    for(int i = 0; i <= n; i++){
        sz[i] = 0;
    }
}
int mst(vector<pair<int, pair<int, int>>> &edge){
    int ret = 0;
    for(int i = 0; i < edge.size(); i++){
        int w = edge[i].first;
        int v1 = edge[i].second.first;
        int v2 = edge[i].second.second;
        if(find_set(v1) == find_set(v2)) continue;
        ret += w;
        union_sets(v1, v2);
    }
    return ret;
}

```

10.10 Longest Path in dag

```

const int N = 1e5;
vector<pair<int, int>> adj[N];
int dp[N];
bool visited[N];

void topologicalSort(int v, stack<int>& Stack) {
    visited[v] = true;
    for (auto& neighbor : adj[v]) {
        int next = neighbor.first;
        if (!visited[next]) {
            topologicalSort(next, Stack);
        }
    }
    Stack.push(v);
}

void longestPath(int src, int n) {
    fill(dp, dp + n, INT_MIN);
    dp[src] = 0;
    stack<int> Stack;
    for (int i = 1; i <= n; i++) {
        if (!visited[i]) {
            topologicalSort(i, Stack);
        }
    }
    while (!Stack.empty()) {
        int u = Stack.top();
        Stack.pop();
    }
}

```

```

    if (dp[u] != INT_MIN) {
        for (auto& neighbor : adj[u]) {
            int v = neighbor.first;
            int weight = neighbor.second;
            if (dp[v] < dp[u] + weight) {
                dp[v] = dp[u] + weight;
            }
        }
    }
}
//now dp[i] = longest path
//INT_MIN mane impossible
}

```

10.11 Lowest Common Ancestor

```

const int N = 1e5 + 10;
vector<int> adj[N];
int timer, l;
int tin[N], tout[N];
int up[N][18];
int dist[N];

void dfs(int src, int par){
    tin[src] = ++timer;
    up[src][0] = par;
    for (int i = 1; i <= 17; ++i)
        up[src][i] = up[up[src][i-1]][i-1];
    for (int child : adj[src]) {
        if(child != par){
            dist[child] = dist[src] + 1;
            dfs(child, src);
        }
    }
    tout[src] = ++timer;
}

bool is_ancestor(int u, int v){
    return tin[u] <= tin[v] && tout[u] >= tout[v];
}

int lca(int u, int v){
    if (is_ancestor(u, v))
        return u;
    if (is_ancestor(v, u))
        return v;
    for (int i = 17; i >= 0; --i) {
        if (!is_ancestor(up[u][i], v))
            u = up[u][i];
    }
    return up[u][0];
}

```

```

}
void preprocess(int root, int n) {
    timer = 0;
    l = ceil(log2(n));
    dfs(root, root);
}

int getKthAncestor(int node, int k) {
    for(int i = 0; i < l; i++){
        if(k & (1 << i)){
            node = up[node][i];
            if(node == -1) return -1;
        }
    }
    return node;
}

```

10.12 Topological Sort

```

void topologicalSortUtil(
    int v,
    vector<vector<int>> &adj,
    vector<bool> &visited,
    stack<int> &Stack)
{
    visited[v] = true;
    for (int i : adj[v])
    {
        if (!visited[i])
            topologicalSortUtil(i, adj, visited, Stack);
    }
    Stack.push(v);
}

void topologicalSort(vector<vector<int>> &adj, int N)
{
    stack<int> Stack;
    vector<bool> visited(N, false);
    for (int i = 0; i < N; i++)
    {
        if (!visited[i])
            topologicalSortUtil(i, adj, visited, Stack);
    }
    while (!Stack.empty())
    {
        cout << Stack.top() << " ";
        Stack.pop();
    }
}

```

11 Math

11.1 String and int multiply

```
string multiply(string a, int b)
{
    int carry = 0, l = a.size();

    string ans = "";

    for (int i = l - 1; i >= 0; i--)
    {
        carry = ((a[i] - '0') * b + carry);
        ans += carry % 10 + '0';
        carry /= 10;
    }
    while (carry != 0)
    {
        ans += carry % 10 + '0';
        carry /= 10;
    }
    reverse(ans.begin(), ans.end());
    return ans;
}
```

11.2 Sum of Absolute Diff of All Pairs

```
int sum_of_absolute_differences_of_all_pairs_in_a_given_array(
    int a[], int n)
{
    int ans = 0;
    sort(a, a + n);
    for (long long i = 0; i < n; i++)
        ans += a[i] * (2 * i - n + 1);
    return ans;
}
```

12 Miscellaneous

12.1 repeat

```
long long doRepeat(int cur, int plus, int n, bool clockwise=
    true){
    long long pos;
```

```
    if(clockWise) pos = (cur+plus)%n;
    else pos = (cur-plus+n)%n;
    return pos?pos:n;
}
```

13 Number Theory

13.1 Big Mul

```
long long bigMul(long long n, long long m, long long p)
{
    if(m<=0) return 0;
    long long res = bigMul(n, m/2, p);
    long long ans = (2*res)%p;
    if(m%2) ans = (ans+n)%p;
    return ans;
}
```

13.2 Bigmod , Inverse MOD, ncr

```
#define MOD 1000000007
long long bigMod(long long a, long long b)
{
    a %= MOD;
    if (!b)
        return 1;
    long long res = bigMod(a, b / 2);
    long long ans = (res * res) % MOD;
    if (b % 2)
        ans = (ans * a) % MOD;
    return ans;
}

long long inverseMod(long long a)
{
    return bigMod(a, MOD - 2);
}

long long fact[MOD];
void factorial()
{
    fact[0] = 1;
    for (long long i = 1; i < MOD; i++)
        fact[i] = (((i % MOD) * (fact[i - 1] % MOD)) % MOD);
}
```

```
long long nCr(long long n, long long r)
{
    return ((fact[n] % MOD) * (inverseMod((fact[r] * fact[n -
        r]) % MOD) % MOD)) % MOD;
}
```

13.3 Bigmod with Loop

```
#define MOD 1000000007
long long Big(long long x, long long n)
{
    long long ans=1;
    while(n>0){
        x%=MOD;
        if(n&1) ans*=x;
        ans%=MOD;
        x*=x;
        n>>=1;
    }
    return ans;
}
```

13.4 Check if a subset sum exists

```
bitset<MAX>bs;
bool check(int sum) { bs.reset(); bs[0]=1;
for(int i=1;i<=n;i++) bs |= bs << arr[i]; return bs[sum]; }
```

13.5 Euler Phi Sieve

```
// P1k1 1(P1 1).P2k2 1(P2 1)...Prkr - 1(Pr - 1)
void computeTotient(int n)
{
    for (int i = 1; i <= n; i++) phi[i] = i;
    for (int j = 2; j <= n; j++)
    {
        if (phi[j] == j)
        {
            phi[j] = j - 1;
            for (int i = 2 * j; i <= n; i += j)
            {
                phi[i] = (phi[i] / j) * (j - 1);
            }
        }
    }
}
```



```

    }
}

```

13.6 Factorial

13.6.1 Digit Count

```

int factDigitCnt(int n)
{
    if (n <= 1)
        return n;
    double digits = 0;
    for (int i = 2; i <= n; i++)
    {
        digits += log10(i);
    }
    return floor(digits) + 1;
}

```

13.6.2 Divisor Count

```

long long factDivisorsCnt(long long n)
{
    long long res = 1;
    for (int i = 0; primes[i] <= n; i++)
    {
        long long exp = 0;
        long long p = primes[i];
        while (p <= n)
        {
            exp += (n / p);
            p *= primes[i];
        }
        res *= (exp + 1);
    }
    return res;
}

```

13.6.3 Tailing Zeros

```

int trailingZeroes(int n)
{
    int c = 0, f = 5;
    while (f <= n)
    {
        c += n / f;
    }
}

```

```

        f *= 5;
    }
    return c;
}

```

13.7 Generate Number of Divisor 1 to N

```

vector<int>generateNumberOfDivisor(int n= 1e6){
    vector<int>divisor(n+1, 1);
    for(int i=2;i<=n;i++){
        if(divisor[i]==1){
            for(int j=i;j<=n;j+=i){
                int num = j, primeFactor = 0;
                while(num%i==0){
                    num/=i;
                    primeFactor++;
                }
                divisor[j] *= (primeFactor+1);
            }
        }
    }
    return divisor;
}

```

13.8 Get Prime

```

#define INF 1000005
int prime[INF];
bool vis[INF];

void getPrime()
{
    int k = 1;
    prime[k++] = 2;
    for (long long i = 3; i < INF; i += 2)
    {
        if (!vis[i] && i % 2)
            prime[k++] = i;
        for (long long j = i * i; j < INF; j += i)
        {
            vis[j] = true;
        }
    }
}

```

13.9 Is Prime

```

vector<bool> isPrime(long long n = 1e6)
{
    vector<bool> vis(n + 5);
    vis[1] = true;
    for (long long i = 3; i <= n; i+=2)
    {
        if (!vis[i])
            for (long long j = i * i; j <= n; j += i)
                vis[j] = true;
    }
    return vis;
}

```

13.10 MOD Jog Gun

```

#define MOD 1000000007

long long modGunKoro(long long a, long long b){
    return ((a%MOD)*(b%MOD))%MOD;
}

long long modJogKoro(long long a, long long b){
    return ((a%MOD)+(b%MOD))%MOD;
}

```

13.11 Number of Divisor

```

#define nn 1000010115.
long long int notprime[nn] = {}, prime[nn];
long long numberOfDivisor(long long n)
{
    long long int c = 1, i, j, ans = 1;
    for (i = 3; i * i <= nn; i += 2)
    {
        if (!notprime[i])
        {
            for (j = i * i; j <= nn; j += i)
                notprime[j] = 1;
        }
        prime[c++] = i;
    }
    for (i = 3; i <= nn; i += 2)
    {
        if (!notprime[i])

```

```

    {
        prime[c++] = i;
    }
}

for (i = 1; i <= nn && prime[i] * prime[i] <= n; i++)
{
    if (n % prime[i] == 0)
    {
        int cnt = 1;
        while (n > 1 && n % prime[i] == 0)
        {
            n /= prime[i];
            cnt++;
        }
        ans *= cnt;
    }
}
if (n != 1)
    ans *= 2;
}

```

13.12 Number of Prime Divisor

```

vector<int>generateNumberOfPrimeDivisor(int n = 1e6){
    vector<int>primeDivisor(n+1, 0);
    for(int i=2;i<=n;i++){
        if(primeDivisor[i]==0){
            for(int j=i;j<=n;j+=i){
                primeDivisor[j] ++;
            }
        }
    }
    return primeDivisor;
}

```

13.13 Pascal Tree

```

void generatePascalsTriangle(int maxN)
{
    for (int n = 0; n <= maxN; n++)
    {
        pascalTriangle[n][0] = 1;
        for (int r = 1; r <= n; r++)
        {
            pascalTriangle[n][r] =

```

```

        pascalTriangle[n - 1][r - 1] +
        pascalTriangle[n - 1][r];
    }
}
}
ll nCr(int n, int r) { return pascalTriangle[n][r]; }

```

13.14 Phi 4 large number

```

int phi(int n)
{
    double res = n;
    for (int i = 2; i * i <= n; i++)
    {
        if (n % i == 0)
        {
            while (n % i == 0)
                n /= i;
            res *= (1.0 - (1.0 / i))
        }
    }
    if (n > 1)
        res *= (1.0 - (1.0 / n));
    return (int)(res);
}

```

13.15 Phi for a large number

```

int phi(int n)
{
    double res = n;
    for (int i = 2; i * i <= n; i++)
    {
        if (n % i == 0)
        {
            while (n % i == 0)
                n /= i;
            res *= (1.0 - (1.0 / i))
        }
    }
    if (n > 1)
        res *= (1.0 - (1.0 / n));
    return (int)(res);
}

```

13.16 Pollard Rho

```

ll modular_pow(ll base, int exponent, ll modulus)
{
    ll result = 1;
    while (exponent > 0)
    {
        if (exponent & 1)
            result = (result * base) % modulus;
        exponent = exponent >> 1;
        base = (base * base) % modulus;
    }
    return result;
}

ll PollardRho(ll n)
{
    srand(time(NULL));
    if (n == 1)
        return n;
    if (n % 2 == 0)
        return 2;
    ll x = (rand() % (n - 2)) + 2;
    ll y = x;
    ll c = (rand() % (n - 1)) + 1;
    ll d = 1;
    while (d == 1)
    {
        x = (modular_pow(x, 2, n) + c + n) % n;
        y = (modular_pow(y, 2, n) + c + n) % n;
        y = (modular_pow(y, 2, n) + c + n) % n;
        d = __gcd(abs(x - y), n);
        if (d == n)
            return PollardRho(n);
    }
    return d;
}

```

13.17 SOD

```

// SOD of n^m:
//((P1e1 +1 1 / P1 1). (P2e2 +1 1 / P2 1)..... (
    Prer +1 1 / Pr 1)
ll primeFact(ll n, int m)
{
    ll sum = 1;
    for (int i = 0; i < primes.size() && primes[i] <= n; i++)
    {
        ll cnt = 0, p = primes[i];
        if (n % p == 0)

```

```

{
    while (n % p == 0)
        cnt++, n /= p;
    cnt = cnt * m + 1;
    ll calc = (bigMod(p, cnt, MOD) + MOD - 1) % MOD;
    calc *= bigMod(p - 1, MOD - 2, MOD);
    calc %= MOD;
    sum = (sum * calc) % MOD;
}
}
if (n > 1)
{
    ll calc = (bigMod(n, 1 + m, MOD) + MOD - 1) % MOD;
    calc *= bigMod(n - 1, MOD - 2, MOD);
    calc %= MOD;
    sum = (sum * calc) % MOD;
}
return sum;
}

// Sod
sod(n) = (p1 ^ (e1 + 1) - 1) / (p1 - 1)

```

13.18 Sum of Divisor

```

vector<int> generateSumOfDivisor(int n = 2e6)
{
    vector<int> divSum(n + 5, 1);
    divSum[1] = 0;
    for (int i = 2; i <= n; i++)
    {
        for (int j = i; j <= n; j += i)
            divSum[j] += i;
    }
    return divSum;
}

```

14 String

14.1 Hashing

```

#include <bits/stdc++.h>
using namespace std;

const int N = 1e6 + 9;

```

```

const int MOD1 = 127657753, MOD2 = 987654319;
const int p1 = 137, p2 = 277;
pair<int, int> pw[N], ipw[N];
int ip1, ip2;

int power(long long n, long long k, int mod)
{
    int ans = 1 % mod;
    n %= mod;
    if (n < 0)
        n + mod;
    while (k)
    {
        if (k & 1)
            ans = (long long)ans * n % mod;
        n = (long long)n * n % mod;
        k >>= 1;
    }
    return ans;
}

void prec()
{
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++)
    {
        pw[i].first = 1LL * pw[i - 1].first * p1 % MOD1;
        pw[i].second = 1LL * pw[i - 1].second * p2 % MOD2;
    }
    ip1 = power(p1, MOD1 - 2, MOD1);
    ip2 = power(p2, MOD2 - 2, MOD2);
    ipw[0] = {
        1,
        1,
    };
    for (int i = 1; i < N; i++)
    {
        ipw[i].first = 1LL * ipw[i - 1].first * ip1 % MOD1;
        ipw[i].second = 1LL * ipw[i - 1].second * ip2 % MOD2;
    }
}

struct Hashing
{
    int n;
    string s;
    vector<pair<int, int>> hs;
    Hashing() {}
    Hashing(string _s)
    {

```

```

        n = _s.size();
        s = _s;
        hs.emplace_back(0, 0);
        for (int i = 0; i < n; i++)
        {
            pair<int, int> p;
            p.first = (hs[i].first + 1ll * pw[i].first * s[i]
                % MOD1) % MOD1;
            p.second = (hs[i].second + 1ll * pw[i].second * s
                [i] % MOD2) % MOD2;
            hs.push_back(p);
        }
    }

    pair<int, int> get_hash(int l, int r)
    {
        pair<int, int> ans;
        ans.first = (hs[r].first - hs[l - 1].first + MOD1) *
            1ll * ipw[l - 1].first % MOD1;
        ans.second = (hs[r].second - hs[l - 1].second + MOD2) *
            1ll * ipw[l - 1].second % MOD2;
        return ans;
    }
};

int main()
{
    ios_base::sync_with_stdio(false);
    cin.tie(0);
    cout.tie(0);

    prec();

    string s;
    cin >> s;
    int n = s.size();

    Hashing h(s);

    int ans = -1;
    for (int i = 1; i < n; i++)
    {
        auto p1 = h.get_hash(1, i), p2 = h.get_hash(n - i +
            1, n);
        if (p1 == p2) ans = i;
    }

    if (ans == -1) cout << "Not found!" << endl;
    else
    {

```

```

        for (int i = 0; i < ans; i++)
            cout << s[i];
    }

    //abxaxbxab
    //pre: ab
    //suff: ab
}

```

14.2 KMP

```

vector<int> lps(string pattern)
{
    int n = pattern.size();
    vector<int> v(n);
    int index = 0;

    for (int i = 1; i < n;)
    {
        if (pattern[i] == pattern[index])
        {
            v[i] = index + 1;
            i++;
            index++;
        }
        else
        {
            if (index)
                index = v[index - 1];
            else
            {
                v[i] = 0;
                i++;
            }
        }
    }
    return v;
}

int kmp(string s, string pattern)
{
    int n = s.size(), m = pattern.size();
    int i = 0, j = 0;
    int ans = 0;

    vector<int> v = lps(pattern);

    while (i < n)
    {

```

```

        if (s[i] == pattern[j])
        {
            i++;
            j++;
        }
        else
        {
            if (j)
                j = v[j - 1];
            else
                i++;
        }

        if (j == m) //to count how many pattern match
        {
            ans++;
            j = v[j - 1];
        }
    }

    return ans;
}

```

14.3 KthLexiSmallestSubstring

```

const int N = 1e5 + 5;
struct state {
    int len, link, next[26];
    ll cnt = 0, cnt2 = -1;
};
string s; state st[2 * N];
int n, k, sz, last;
vector<pair<int, int>> order;

void st_init() {
    st[0].len = 0;
    st[0].link = -1;
    sz++; last = 0; }

void dfs(int u) {
    if (st[u].cnt2 != -1) return;
    st[u].cnt2 = st[u].cnt;
    for (int i = 0; i < 26; ++i) {
        if (st[u].next[i]) {
            dfs(st[u].next[i]);
            st[u].cnt += st[st[u].next[i]].cnt; } } }

void st_extend(int c) {
    int cur = sz++;

```

```

    st[cur].len = st[last].len + 1;
    st[cur].cnt = 1;
    order.emplace_back(st[cur].len, cur);
    int p = last;
    while (p != -1 && !st[p].next[c]) {
        st[p].next[c] = cur;
        p = st[p].link; }
    if (p == -1) st[cur].link = 0;
    else {
        int q = st[p].next[c];
        if (st[p].len + 1 == st[q].len) {
            st[cur].link = q; }
        else {
            int clone = sz++;
            st[clone].len = st[p].len + 1;
            st[clone].link = st[q].link;
            memcpy(st[clone].next, st[q].next, sizeof(st[q].next));
            order.emplace_back(st[clone].len, clone);
            while (p != -1 && st[p].next[c] == q) {
                st[p].next[c] = clone;
                p = st[p].link; }
            st[cur].link = st[q].link = clone; } }
    last = cur; }

```

```

int main() {
    cin >> s >> k;
    n = s.length(); k += n;
    st_init();
    for (int i = 0; i < n; ++i) st_extend(s[i] - 'a');
    sort(order.begin(), order.end());
    reverse(order.begin(), order.end());
    for (auto &p: order) {
        st[st[p.second].link].cnt += st[p.second].cnt; }

    dfs(0);
    if (st[0].cnt < k) {
        cout << "No such line.";
        return 0; }

    int cur = 0;
    while (k > st[cur].cnt2) {
        k -= st[cur].cnt2;
        for (int i = 0; i < 26; ++i) {
            if (st[cur].next[i]) {
                int j = st[cur].next[i];
                if (st[j].cnt < k) k -= st[j].cnt;
                else {
                    cout << (char)(i + 'a');
                    cur = j;
                    break; } } } }
}

```

14.4 lcs

```
int lcs(string X, string Y, int m, int n, vector<vector<int>>> &dp)
{
    if (m == 0 || n == 0)
        return 0;
    if (X[m - 1] == Y[n - 1])
        return dp[m][n] = 1 + lcs(X, Y, m - 1, n - 1, dp);

    if (dp[m][n] != -1)
    {
        return dp[m][n];
    }
    return dp[m][n] = max(lcs(X, Y, m, n - 1, dp), lcs(X, Y,
        m - 1, n, dp));
}
```

14.5 Manacher

```
struct Manacher {
    vector<int> p[2];
    p[0][2] = 2
    Manacher(string s) {
        int n = s.size();
        p[0].resize(n + 1);
        p[1].resize(n);
        for (int z = 0; z < 2; z++) {
            for (int i = 0, l = 0, r = 0; i < n; i++) {
                int t = r - i + !z;
                if (i < r) p[z][i] = min(t, p[z][l + t]);
                int L = i - p[z][i], R = i + p[z][i] - !z;
                while (L >= 1 && R + 1 < n && s[L - 1] == s[R + 1])
                    p[z][i]++, L--, R++;
                if (R > r) l = L, r = R;
            }
        }
    }
    bool is_palindrome(int l, int r) {
        int mid = (l + r + 1) / 2, len = r - l + 1;
        return 2 * p[len % 2][mid] + len % 2 >= len;
    }
};

string s; cin >> s;
Manacher M(s);
int n = s.size();
for (int i = 0; i < n; i++) {
    cout << 2 * M.p[1][i] + 1 << ' ';
    if (i + 1 < n) cout << 2 * M.p[0][i + 1] << ' ';
```

```
}
```

14.6 String Matching with Bitset

```
const int N = 1e5 + 9;
vector<int> v;
bitset<N> bs[26], oc;
int i, j, k, n, q, l, r;
string s, p;
cin >> s;
for(i = 0; s[i]; i++) bs[s[i] - 'a'][i] = 1;
cin >> q;
while(q--) {
    cin >> p;
    oc.set();
    for(i = 0; p[i]; i++) oc &= (bs[p[i] - 'a'] >> i);
    cout << oc.count() << endl; // number of occurrences
    int ans = N, sz = p.size();
    int pos = oc._Find_first();
    v.push_back(pos);
    pos = oc._Find_next(pos);
    while(pos < N) {
        v.push_back(pos);
        pos = oc._Find_next(pos);
    }
    for(auto x : v) cout << x << ' '; // position of
        occurrences
    cout << endl;
    v.clear();
    cin >> l >> r; // number of occurrences from l to r, where l
        and r is 1-indexed
    if(sz > r - l + 1) cout << 0 << endl;
    else cout << (oc >> (l - 1)).count() - (oc >> (r - sz + 1))
        .count() << endl;
}
```

14.7 Suffix Array

```
const int mxN = 1e5, K = 20;
int sa[mxN], pos[mxN], tmp[mxN], st[mxN][K+1], lcp[mxN], pre[
    mxN], gap, N;

bool comp(int x, int y) {
    if(pos[x] != pos[y]) return pos[x] < pos[y];
    x += gap;
    y += gap;
    return (x < N && y < N) ? pos[x] < pos[y] : x > y; }
```

```
void suffix(string &s) {
    for (int i = 0; i < N; i++) sa[i] = i, pos[i] = s[i];
    for (gap = 1;; gap <= 1) {
        sort(sa, sa+N, comp);
        for (int i = 0; i < N-1; i++)
            tmp[i+1] = tmp[i] + comp(sa[i], sa[i+1]);
        for (int i = 0; i < N; i++)
            pos[sa[i]] = tmp[i];
        if (tmp[N - 1] == N - 1) break; } }
```

```
int check(int m, string &s, string &x) {
    int f = -1, k = x.size(), j = sa[m];
    if (N - j >= k) f = 0;
    for (int i = 0; i < min(N - j, k); i++) {
        if (s[j+i] < x[i]) return -1;
        if (s[j+i] > x[i]) return 1; }
    return f; }
```

```
int patternExistsLB(int l, int r, string &s, string &x) {
    int ans=-1;
    while (l <= r) {
        int m = l + (r-l)/2;
        int v = check(m, s, x);
        if (v == 0) {
            ans = m; r = m - 1; }
        else if (v == 1) r = m - 1;
        else l = m + 1; }
    return ans; }

int patternExistsRB(int l, int r, string &s, string &x) {
    int ans=-1;
    while (l <= r) {
        int m = l + (r-l)/2;
        int v = check(m, s, x);
        if (v == 0) {
            ans = m; l = m + 1; }
        else if (v == -1) l = m + 1;
        else r = m - 1; }
    return ans; }
```

```
int patternCount(int l, int r, string s, string &x) {
    int L=patternExistsLB(l, r, s, x);
    if (L==-1) return 0;
    int R=patternExistsRB(L, r, s, x);
    return (R-L)+1; }
```

```
int query(int l, int r) {
    int j = log2(r-l+1);
    return min(st[l][j], st[r-(1<<j)+1][j]) + 1; }
```

```

void buildIdx() {
for (int i = 0; i < N; i++)
st[i][0] = sa[i];

for (int j = 1; j <= K; j++) {
for (int i = 0; i + (1<<j) <= N; i++) {
st[i][j] = min(st[i][j-1], st[i + (1<<j-1)][j-1]); } } }

int findFirstIdx(int l,int r, string s,string &x) {
int L=patternExistsLB(l,r,s,x);
if(L==-1)return -1;
int R=patternExistsRB(L,r,s,x);
return query(L,R); }

void build_lcp(string &s){
for (int i = 0, k = 0; i < N; i++) if (pos[i] != N-1) {
int j = sa[pos[i] + 1];
while (s[i + k] == s[j + k]) k++;
lcp[pos[i]] = k;
if (k) k--; } }

long long int getUniqueSubCnt() {
long long int sm = accumulate(lcp, lcp+N, 0LL);
long long int tot = ((long long)1*(N)*(N+1))/2;
tot-=sm;
return tot; }

void printEveryUnqiueSubStirngCnt() {
int prev = 0;
for (int i = 0; i < N; i++) {
pre[prev + 1]++;
pre[N - sa[i] + 1]--;
prev = lcp[i]; }
for (int i = 1; i <= N; i++) {
cout << pre[i] << ' ' ;
pre[i+1] += pre[i]; } }

string kthDistinctSubstring(string s,long long k){
long long prev = 0;
long long cur = 0;
for (int i = 0; i < N; i++){
if (cur + (N-sa[i]) - prev >= k) {
long long j = prev;
string ans = s.substr(sa[i], j);
while (cur < k){
ans += s[sa[i]+j];
cur++; j++; }
return ans; }
cur += (N-sa[i]) - prev;
prev = lcp[i]; }

```

```
return ""; }
```

15 templates

```

struct Point
{
double x, y;
Point() {}
Point(double x, double y) : x(x), y(y) {}
Point(const Point &p) : x(p.x), y(p.y) {}
void input()
{
scanf("%lf%lf", &x, &y);
}
Point operator+(const Point &p)
const
{
return Point(x + p.x, y + p.y);
}
Point operator-(const Point &p)
const
{
return Point(x - p.x, y - p.y);
}
Point operator*(double c) const
{
return Point(x * c, y * c);
}
Point operator/(double c) const
{
return Point(x / c, y / c);
}
};
vector<Point> polygon;
double getClockwiseAngle(Point p)
{
return -1 * atan2(p.x, -1 * p.y);
}
// compare function to compare clockwise
bool comparePoints(Point p1, Point p2)
{
return getClockwiseAngle(p1) < getClockwiseAngle(p2);
}
// rotate 90 degree counter clockwise
Point RotateCCW90(Point p)
{
return Point(-p.y, p.x);
}

```

```

// rotate 90 degree clockwise
Point RotateCW90(Point p)
{
return Point(p.y, -p.x);
}

Point RotateCCW(Point p, double t)
{
return Point(p.x * cos(t) - p.y * sin(t),
p.x * sin(t) + p.y * cos(t));
}
Point RotateCW(Point p, double t)
{
return Point(p.x * cos(t) + p.y * sin(t),
-p.x * sin(t) + p.y * cos(t));
}
double dot(Point A, Point B)
{
return A.x * B.x + A.y * B.y;
}
double cross(Point A, Point B)
{
return A.x * B.y - A.y * B.x;
}
double dist2(Point A, Point B)
{
return dot(A - B, A - B);
}
// returns distance between two point
double dist(Point A, Point B)
{
return sqrt(dot(A - B, A - B));
}
// Distance between point A and B
double distBetweenPoint(Point A, Point B)
{
return sqrt(dot(A - B, A - B));
}
// project point c onto line AB (A != B)
Point ProjectPointLine(Point A, Point B, Point C)
{
return A + (B - A) *
dot(C - A, B - A) / dot(B - A, B - A);
}
// Determine if Line AB and CD are parallel or collinear
bool LinesParallel(Point A, Point B, Point C, Point D)
{
return fabs(cross(B - A, C - D)) < EPS;
}
// Determine if Line AB and CD are collinear

```

```

bool LinesCollinear(Point A, Point B, Point C, Point D)
{
    return LinesParallel(A, B, C, D) && fabs(cross(A - B, A -
        C)) < EPS && fabs(cross(C - D, C - A)) < EPS;
}

// checks if AB intersect with CD
bool SegmentIntersect(Point A, Point B, Point C, Point D)
{
    if (LinesCollinear(A, B, C, D))
    {
        if (dist2(A, C) < EPS || dist2(A, D) < EPS || dist2(B,
            C) < EPS || dist2(B, D) < EPS)
            return true;
        if (dot(C - A, C - B) > 0 && dot(D - A, D - B) > 0 &&
            dot(C - B, D - B) > 0)
            return false;
        return true;
    }
    if (cross(D - A, B - A) * cross(C - A, B - A) > 0)
        return false;
    if (cross(A - C, D - C) * cross(B - C, D - C) > 0)
        return false;
    return true;
}

// Compute the coordinates where AB and CD intersect
Point ComputeLineIntersection(Point A, Point B, Point C,
    Point D)
{
    double a1, b1, c1, a2, b2, c2;
    a1 = A.y - B.y;
    b1 = B.x - A.x;
    c1 = cross(A, B);
    a2 = C.y - D.y;
    b2 = D.x - C.x;
    c2 = cross(C, D);
    double Dist = a1 * b2 - a2 * b1;
    return Point((b1 * c2 - b2 * c1) / Dist, (c1 * a2 - c2 *
        a1) / Dist);
}

// Project point C onto line segment AB -- return the Point
// from AB which is the closest to C --
Point ProjectPointSegment(Point A, Point B, Point C)
{
    double r = dot(B - A, B - A);
    if (fabs(r) < EPS)
        return A;
    r = dot(C - A, B - A) / r;
    if (r < 0)
        return A;

```

```

        if (r > 1)
            return B;
        return A + (B - A) * r;
    }
    // return the minimum distance from a point C to a line AB
    double DistancePointSegment(Point A, Point B, Point C)
    {
        return distBetweenPoint(C, ProjectPointSegment(A, B, C));
    }
    // return distance between P and a
    // point where p is perpendicular on
    // AB. AB er upore p jei point e lombo
    // shei point theke p er distance
    double distToLine(Point p, Point a, Point b)
    {
        pair<double, double> c;
        double scale = (double)(dot(p - a, b - a)) / (dot(b - a,
            b - a));
        c.first = a.x + scale * (b.x - a.x);
        c.second = a.y + scale * (b.y - a.y);
        double dx = (double)p.x - c.first;
        double dy = (double)p.y - c.second;
        return sqrt(dx * dx + dy * dy);
    }
    long long orientation(Point p, Point q, Point r)
    {
        long long val = (q.y - p.y) * (r.x - q.x) - (q.x - p.x) *
            (r.y - q.y);
        if (val > 0)
            return 1;
        if (val < 0)
            return 2;
        else
            return val;
    }
    // Given three colinear points p,
    // q, r, the function checks if
    // point q lies on line segment
    // 'pr'
    bool onSegment(Point p, Point q, Point r)
    {
        if (q.x <= max(p.x, r.x) && q.x >= min(p.x, r.x) && q.y
            <= max(p.y, r.y) && q.y >= min(p.y, r.y))
            return true;
        return false;
    }
}

```

```

// checks if Point P is inside of
// polygon or not
bool isInside(int n, Point p)
{
    if (n < 3)
        return false;
    Point extreme = Point(INF, p.y); // here INF=1e4
    int count = 0, i = 0;
    do
    {
        int next = (i + 1) % n;
        if (SegmentIntersect(polygon[i], polygon[next], p,
            extreme))
        {
            if (orientation(polygon[i], p, polygon[next]) ==
                0)
                return onSegment(polygon[i], p, polygon[next]);
            count++;
        }
        i = next;
    } while (i != 0);
    return count & 1;
}

// returns the perimeter of a
// polygon
double polygonPerimeter(int n)
{
    double perimeter = 0.0;
    for (int i = 0; i < n - 1; i++) // polygon vector holds
        the corner points of the given polygon
        perimeter += dist(polygon[i], polygon[i + 1]);
    perimeter += dist(polygon[0], polygon[n - 1]);
    return perimeter;
}

// returns the area of a polygon
double polygonArea(int n)
{
    double area = 0.0;
    int j = n - 1;
    for (int i = 0; i < n; i++)
    {
        area += (polygon[j].x + polygon[i].x) * (polygon[j].y
            - polygon[i].y);
        j = i;
    }
    return fabs(area) * 0.5;
}

double getTriangleArea(Point a, Point b, Point c)
{

```

```

    return fabs(cross(b - a, c - a));
}
bool compareConvex(Point X, Point Y)
{
    long long ret =
        orientation(points[0], X, Y);
    if (ret == 0)
    {
        ll dist11 = dist2(points[0], X);
        ll dist22 = dist2(points[0], Y);
        return dist11 < dist22;
    }
    else if (ret == 2)
        return true;
    else
        return false;
}
Point nextToTop(stack<Point> &S)
{
    Point p = S.top();
    S.pop();
    Point res = S.top();
    S.push(p);
    return res;
}

// make a minimum area polygon
stack<Point> convexHull(int N)
{
    int ymin = points[0].y, index = 0;
    for (int i = 1; i < N; i++)
    {
        if (points[i].y < ymin || (points[i].y == ymin &&
            points[i].x < points[index].x))
        {
            ymin = points[i].y;
            index = i;
        }
    }
    stack<Point> S;
    swap(points[0], points[index]);
    sort(&points[1], &points[N], compareConvex);
    S.push(points[0]);
    for (int i = 1; i < N; i++)
    {
        while (S.size() > 1 && orientation(nextToTop(S), S.
            top(), points[i]) != 2)
        {
            S.pop();
        }
    }
}

```

```

    S.push(points[i]);
}
return S;
}
// Angle between Line AB and AC in degree
double angle(Point B, Point A, Point C)
{
    double c = dist(A, B);
    double a = dist(B, C);
    double b = dist(A, C);
    double ans = acos((b * b + c * c - a * a) / (2 * b * c));
    return (ans * 180) / acos(-1);
}
// returns number of vertices on boundary of a polygon
ll picks_theorem_boundary_count()
{
    int sz = polygon.size(), i;
    long long res = __gcd((long long)abs(polygon[0].x -
        polygon[sz - 1].x), (long long)abs(polygon[0].y -
        polygon[sz - 1].y));
    for (i = 0; i < sz - 1; i++)
    {
        res += __gcd((long long)abs(polygon[i].x - polygon[i
            + 1].x), (long long)abs(polygon[i].y - polygon[i
            + 1].y));
    }
    return res;
}

// picks theorem
// Polygon area= inside points + boundary points/2 -1
// return inside points counts
ll lattice_points_inside_polygon()
{
    ll ar = polygonArea(n);
    ll b =
        picks_theorem_boundary_count();
    long long tot = ar + 1 - b / 2;
    return tot;
}

// Physics Formuas
// motion
v = u + at
s = ut + (1/2) at*t ,
v*v    u*u = 2*a*s

// Projectile motion
x = utcos
y = utsin    (1/2) gt*t

```

```

y = x tan    g*x*x/( 2u*u*cos*cos )
T = 2u sin/g
R = u*u*sin2/g
H = u*u*sin*sin /2g

// others:
p=mv
v*v/r*g = tan(Banking angle)
W = F S cos
K = ( )mv*v = p*p/ 2m
T = 2* *sqrt(l/g)

// Trigonometry
sin2 =2 sincos
cos2 = cos * cos - sin * sin
sin3 =3 sin -4* sin * sin * sin
cos3 =4* cos * cos * cos -3 cos
For triangle:
a=bcosC+ccosB
b=acosC+ccosA
c=bcosA+acosB
sin(A+ B )=sinAcosB + cosAsinB
cos(A+ B )=cosAcosB + sinAsinB

// Circle Line intersection
double r, a, b, c; // given as input //ax+by+c=0//EPS=1e-9
double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
if (c*c > r*r*(a*a+b*b)+EPS)
    puts ("no points");
else if (abs (c*c - r*r*(a*a+b*b)) < EPS){
    puts ("1 point");
    cout << x0 << ' ' << y0 << '\n';
}
else {
    double d = r*r - c*c/(a*a+b*b);
    double mult = sqrt (d / (a*a+b*b));
    double ax, ay, bx, by;
    ax = x0 + b * mult;
    bx = x0 - b * mult;
    ay = y0 - a * mult;
    by = y0 + a * mult;
    puts ("2 points");
    cout << ax << ' ' << ay << '\n' << bx << ' ' << by << '\n';
}

```

16 Trie

```

struct Trie
{
    bool lastLetter;

```



```

Trie *children[10];

Trie()
{
    for (int i = 0; i < 10; i++)
    {
        lastLetter = false;
        children[i] = nullptr;
    }
};

void insert(string &s, Trie *root)
{
    int n = s.size();

    for (char c : s)
    {
        int index = c - '0';
        if (root->children[index] == nullptr)
            root->children[index] = new Trie();
        root = root->children[index];
    }
    root->lastLetter = true;
}

bool isPrefix(Trie *node)
{
    for (int i = 0; i < 10; i++)
    {
        if (node->children[i] != nullptr)
        {
            if (node->lastLetter)
                return true;
            if (isPrefix(node->children[i]))
                return true;
        }
    }
}

```

```

    }
    return false;
}

void clear(Trie *node)
{
    for (int i = 0; i < 10; i++)
    {
        if (node->children[i] != nullptr)
        {
            clear(node->children[i]);
            node->children[i] = nullptr;
        }
    }
    delete (node);
}

int main()
{
    long long t, k = 0;
    cin >> t;
    while (t--)
    {
        long long n;
        cin >> n;

        Trie *root = new Trie();

        while (n--)
        {
            string s;
            cin >> s;
            insert(s, root);
        }

        bool f = !isPrefix(root);
        cout << loj(++k, con) << endl;
    }
}

```

```

        clear(root);
    }
}

```

17 Z Function

```

#include <bits/stdc++.h>
using namespace std;
#define endl \n
vector<int> z_function(string s)
{
    int n = (int)s.size();
    vector<int> z(n);
    z[0] = n;
    for (int i = 1, l = 0, r = 0; i < n; ++i)
    {
        if (i <= r)
            z[i] = min(r - i + 1, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            ++z[i];
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1;
    }
    return z;
}

int main()
{
    // Simple is BEAST
    int n;
    cin >> n;
    cout << n * n << endl;
    return 0;
}

```