

Module 5: CPU Scheduling

- Basic Concepts
- Scheduling Criteria
- Scheduling Algorithms
- Multiple-Processor Scheduling
- Real-Time Scheduling
- Algorithm Evaluation




Basic Concepts

- Maximum CPU utilization obtained with multiprogramming
- CPU-I/O Burst Cycle Process execution consists of a cycle of CPU execution and I/O wait.
- CPU burst distribution




Alternating Sequence of CPU And I/O Bursts





Histogram of CPU-burst Times





CPU Scheduler

- Selects from among the processes in memory that are ready to execute, and allocates the CPU to one of them.
- CPU scheduling decisions may take place when a process:
 - 1. Switches from running to waiting state.
 - 2. Switches from running to ready state.
 - 3. Switches from waiting to ready.
 - 4. Terminates.
- Scheduling under 1 and 4 is nonpreemptive.
- All other scheduling is preemptive.



Dispatcher

- Dispatcher module gives control of the CPU to the process selected by the short-term scheduler; this involves:
 - switching context
 - switching to user mode
 - jumping to the proper location in the user program to restart that program
- *Dispatch latency* time it takes for the dispatcher to stop one process and start another running.



Scheduling Criteria

- CPU utilization keep the CPU as busy as possible
- Throughput # of processes that complete their execution per time unit
- Turnaround time amount of time to execute a particular process
- Waiting time amount of time a process has been waiting in the ready queue
- Response time amount of time it takes from when a request was submitted until the first response is produced, **not** output (for time-sharing environment)




Optimization Criteria

- Max CPU utilization
- Max throughput
- Min turnaround time
- Min waiting time
- Min response time



First-Come, First-Served (FCFS) Scheduling

- Exampl Process Burst e: Time P_1 24 P_2 3 P_3 3
- Suppose that the processes arrive in the order: P_1 , P_2 , P_3 The Gantt Chart for the schedule is:



- Waiting time for $P_1 = 0$; $P_2 = 24$; $P_3 = 27$
- Average waiting time: (0 + 24 + 27)/3 = 17




FCFS Scheduling (Cont.)

Suppose that the processes arrive in the order

$$P_2$$
, P_3 , P_1 .

• The Gantt chart for the schedule is:



- Waiting time for $P_1 = 6$; $P_2 = 0$; $P_3 = 3$
- Average waiting time: (6 + 0 + 3)/3 = 3
- Much better than previous case.
- Convoy effect short process behind long process



Shortest-Job-First (SJR) Scheduling


- Associate with each process the length of its next CPU burst.
 Use these lengths to schedule the process with the shortest time.
- Two schemes:
 - nonpreemptive once CPU given to the process it cannot be preempted until completes its CPU burst.
 - Preemptive if a new process arrives with CPU burst length less than remaining time of current executing process, preempt. This scheme is know as the Shortest-Remaining-Time-First (SRTF).
- SJF is optimal gives minimum average waiting time for a given set of processes.



Example of Non-Preemptive SJF

Proces Arrival Time Burst
$$\underline{s}$$
 Time P_1 7 0. P_2 4

• SJF (non-preemptive)




• Average waiting time = (0 + 6 + 3 + 7)/4 - 4



Example of Preemptive SJF

$$\begin{array}{ccc} \underline{Proces} & \underline{Arrival Time} & \underline{Burst} \\ \underline{s} & \underline{Time} \\ P_1 & 7 & \\ 0. & \\ 0 & \\ P_2 & 4 & \\ \end{array}$$

• SJF (preemptive)



• Average waiting time = (9 + 1 + 0 + 2)/4 - 3



Determining Length of Next CPU Burst

- Can only estimate the length.
- Can be done by using the length of previous CPU bursts, using exponential averaging.
 - 1. t_n = actual length of n^{th} CPU burst
 - 2. τ_{n+1} = predicted value for the next CPU burst
 - 3. $a, 0 \le a \le 1$
 - 4. Define:

$$\tau_{n=1} = a \ t_n + (1-a)\tau_n$$



Examples of Exponential Averaging

- a =0
 - $T_{n+1} = T_n$
 - Recent history does not count.
- a =1
 - $\mathsf{T}_{\mathsf{n+1}} = \mathsf{t}_{\mathsf{n}}$
 - Only the actual last CPU burst counts.
- If we expand the formula, we get:

$$\tau_{n+1} = a t_n + (1 - a) a t_n - 1 + ...$$

$$+ (1 - a)^n a t_n - 1 + ...$$

$$+ (1 - a)^{n-1} t_n \tau_0$$

 Since both a and (1 - a) are less than or equal to 1, each successive term has less weight than its predecessor.



Priority Scheduling

- A priority number (integer) is associated with each process
- The CPU is allocated to the process with the highest priority (smallest integer ≡ highest priority).
 - Preemptive
 - nonpreemptive
- SJF is a priority scheduling where priority is the predicted next CPU burst time.
- Problem = Starvation low priority processes may never execute.



Round Robin (RR)

- Each process gets a small unit of CPU time (time quantum), usually 10-100 milliseconds. After this time has elapsed, the process is preempted and added to the end of the ready queue.
- If there are *n* processes in the ready queue and the time quantum is *q*, then each process gets 1/*n* of the CPU time in chunks of at most *q* time units at once. No process waits more than (*n*-1)*q* time units.
- Performance
 - q large ⇒ FIFO
 - q small $\Rightarrow q$ must be large with respect to context switch, otherwise overhead is too high.



Example: RR with Time Quantum = 20

Process Burst Time


 P_1 53

*P*₂ 17

 P_3 68

 P_4 24


The Gantt chart is:



• Typically, higher average turnaround than SJF, but better response.




How a Smaller Time Quantum Increases Context Switches





Turnaround Time Varies With The Time Quantum



process	time
P ₁	6
P ₂	3
P ₃	1
P ₄	7




Multilevel Queue

- Ready queue is partitioned into separate queues: foreground (interactive) background (batch)
- Each queue has its own scheduling algorithm, foreground – RR background – FCFS
- Scheduling must be done between the queues.
 - Fixed priority scheduling; i.e., serve all from foreground then from background. Possibility of starvation.
 - Time slice each queue gets a certain amount of CPU time which it can schedule amongst its processes; i.e., 80% to foreground in RR
 - 20% to background in FCFS



Multilevel Queue Scheduling






Multilevel Feedback Queue

- A process can move between the various queues; aging can be implemented this way.
- Multilevel-feedback-queue scheduler defined by the following parameters:
 - number of queues
 - scheduling algorithms for each queue
 - method used to determine when to upgrade a process
 - method used to determine when to demote a process
 - method used to determine which queue a process will enter when that process needs service



Multilevel Feedback Queues





Example of Multilevel Feedback Queue

Three queues:

- Q_0 time quantum 8 milliseconds
- Q_1 time quantum 16 milliseconds
- $-Q_2 FCFS$

Scheduling

- A new job enters queue Q_0 which is served FCFS. When it gains CPU, job receives 8 milliseconds. If it does not finish in 8 milliseconds, job is moved to queue Q_1 .
- At Q_1 job is again served FCFS and receives 16 additional milliseconds. If it still does not complete, it is preempted and moved to queue Q_2 .



Multiple-Processor Scheduling

- CPU scheduling more complex when multiple CPUs are available.
- Homogeneous processors within a multiprocessor.
- Load sharing
- Asymmetric multiprocessing only one processor accesses the system data structures, alleviating the need for data sharing.




Real-Time Scheduling

- *Hard real-time* systems required to complete a critical task within a guaranteed amount of time.
- Soft real-time computing requires that critical processes receive priority over less fortunate ones.



Dispatch Latency





Algorithm Evaluation

- Deterministic modeling takes a particular predetermined workload and defines the performance of each algorithm for that workload.
- Queuing models
- Implementation



Evaluation of CPU Schedulers by Simulation

