

# Arrays

## Arrays

Arrays are lists of ordered, stored data. They can hold items that are of any data type. Arrays are created by using square brackets, with individual elements separated by commas.

## Index

Array elements are arranged by *index* values, starting at 0 as the first element index. Elements can be accessed by their index using the array name, and the index surrounded by square brackets.

## Property .length

The `.length` property of a JavaScript array indicates the number of elements the array contains.

## Method .push()

The `.push()` method of JavaScript arrays can be used to add one or more elements to the end of an array.

`.push()` mutates the original array returns the new length of the array.

```
// An array containing numbers
const numberArray = [0, 1, 2, 3];

// An array containing different data
types
const mixedArray = [1, 'chicken', false];
```

```
// Accessing an array element
const myArray = [100, 200, 300];

console.log(myArray[0]); // 100
console.log(myArray[1]); // 200
console.log(myArray[2]); // 300
```

```
const numbers = [1, 2, 3, 4];

numbers.length // 4
```

```
// Adding a single element:
const cart = ['apple', 'orange'];
cart.push('pear');

// Adding multiple elements:
const numbers = [1, 2];
numbers.push(3, 4, 5);
```

## Method `.pop()`

The `.pop()` method removes the last element from an array and returns that element.

```
const ingredients = ['eggs', 'flour',  
  'chocolate'];  
  
const poppedIngredient =  
  ingredients.pop(); // 'chocolate'  
console.log(ingredients); // ['eggs',  
  'flour']
```

## Mutable

JavaScript arrays are *mutable*, meaning that the values they contain can be changed.

Even if they are declared using `const`, the contents can be manipulated by reassigning internal values or using methods like `.push()` and `.pop()`.

```
const names = ['Alice', 'Bob'];  
  
names.push('Carl');  
// ['Alice', 'Bob', 'Carl']
```