Lecture 02

22 August 2026 13:23

Variables & let, const, var

Variable - Container

=> A variable is a name given to a value so that we can use that value later in our program.

variable

let $\boxed{\text{name}}$ = "Satyam"

डब्बा सत्यम

firstname

a = 5

b = 10

c = "satyam"

let a = 5

let b = 5

c = a+b

@ = 5 → memory

= "Satyam"

Naming rule -

- Don't start with a number. ✓

let 1name = "Satyam" X

_name ✓

1name X

4

- Don't use space

  let first name = "satyam" - X

  space X

- Don't use JS reserved words

  keywords

  reserved

  let let = 1 X

  let if = 10 X

- use camelcase →

  let firstName = "satyam"

Var, let, const

→ JS provides three keywords for creating variables.

let name = "satyam"
let a = 5

key	value can change	scope	hoisting
oldest var	yes	function	yes (undefined)
let	yes	Block	yes (TDZ)
const	Not	Block	

let, const → modern → ES6

Scope

→ It decides who can see and use your variables

① Global scope → public park

→ variables made outside of any brackets { } are global

(II) function scope - Inside a house

→ variable made inside a function belong only to that function.

(III) Block scope → inside a bedroom

(iii) Block scope → inside a bedroom

→ A block is code wrapped in curly braces {}

hoisting → JS → Two steps -

```
console.log("hello")
var a = 10;
var b = 20;
cons— (a+3)
```

var a;

code compile → code run

variable declaration Top

a →
b →

undefined

a = 10
b = 20

cons— a
var a = 10
c— a

1st compile . run

(1) a = undefined → undefined, a = 10, 10

let a

let const a → access ×

TDZ con + assign → TDZ

Data types ~ "Satyam" string (10) Numbe

string

Primitive → 7

non-primitive (Reference)

- object, Array, function

String → "Satyam" or 'Satyam' `@hi $ {}`

Number → 0, 1, 2, -4, 5, 1.5

Boolean → True or, false

Undefined → JS default

null → Assigned by you

a = null, a;

a = undefined

BigInt → 459348 7 8 ....

Symbol → unique

a = 10

const

const a = 10

a = 13

const user = {
name : "Ram"
}

user 0123

0123

{ name : Ram }